



Spare parts for the professional sector: Cooking equipment



Suitable for:

ATA



This catalogue is automatically generated.
Therefore, the sequence of the items might
not be always shown at best.
Updates will be issued in case of additions
and/or amendments.

Suitable universal spare parts may not be included





Suitable for:

ATA



Suitable for:

Bearings

1063901 BEARING 6204 DDU NSK
external \varnothing 47mm - internal \varnothing 20mm - thickness 14mm



ATA 6638

Circlips


1250223 RADIAL SEEGER RING \varnothing 6 mm
stainless steel - external \varnothing 12.3 - thickness 0.7
UNI 7434 - DIN 6799



ATA 52061

Contact thermostats

3444607 CONTACT THERMOSTAT 110°C
with manual reset



ATA 4280

Contactors

3446557 CONTACTOR LOVATO BG0901A
coil 9A 230V 50/60Hz 4Kw
3 normally open contacts
1 normally closed auxiliary contact



ATA 4204

ATA 9800

5024564 THERMAL RELAY LOVATO 0,9-1,5 A
RF9.1V5
1 contact NO
1 contact NC



ATA 14149



Drain taps and accessories

3526671 BALL VALVE \varnothing 1/2"FF



ATA K20029

Electric hot plates

3311062 ELECTRIC HOT PLATE 3000W 230V
 dimensions 300x300 mm
 terminal block electric connections
 with STAINLESS steel edge
 for electric cooking top



ATA K24011

Electrical gas valves and accessories

3526176 VALVE 820 NOVA \varnothing 1/2"FF
 inlet \varnothing 1/2" F - outlet \varnothing 1/2" F
 thermocouple connection M9x1
 maximum gas inlet pressure 60 mbar
 outlet pressure adjustment range
 3÷30 mbar
 ambient temperature 0÷70°C
 power supply 230V 50Hz



ATA K00055

3526098 COIL 220V
 for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA



2100054 COIL 220V 60Hz
 for VALVE 820 NOVA-822 NOVA-828 NOVA



3526099 COIL 24V
 for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA





Suitable for:


3526077 ELBOW FLANGE \varnothing 1/2" F
with screws and OR
for valves SIT 820-Honeywell V4400-V4600-VR4605P



3526102 ELECTRIC COUPLING WITH CABLE
cable length 1000 mm - 3 wires
for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA



3020083 FITTING AND OLIVE \varnothing 4 mm



3526075 FLANGE STRAIGHT \varnothing 1/2"
with screws and OR
for valves SIT 820-Honeywell V4400-V4600-VR4605P



3526124 KNOB EXTENSION LENGTH 67 mm
for VALVE 820 NOVA-824 NOVASIT



3348041 OLIVE FOR PIPE \varnothing 16 mm
for model PEL 23



ATA



Suitable for:


3526078 ELBOW FLANGE \varnothing 3/4" F
with screws and OR
for valves SIT 820-Honeywell V4400-V4600-VR4605P



5047586 EXTENSION FOR VALVE 820 NOVA
D-shaped pin \varnothing 10x8 mm




3020084 FITTING AND OLIVE \varnothing 6 mm



3526076 FLANGE STRAIGHT \varnothing 3/4"
with screws and OR
for valves SIT 820-Honeywell V4400-V4600-VR4605P



3182008 MAGNETIC UNIT SIT
head \varnothing 35 mm - end piece \varnothing 20 mm - length 47 mm
for valve SIT NOVASIT 820



3348036 OLIVE FOR PIPE \varnothing 4 mm
for model PEL 21-22-24-25






Suitable for:


3001008 PIEZO IGNITER
a \varnothing 14 mm hole is required for the assembly
faston M \varnothing 2.4 mm



3020077 PIPE FITTING \varnothing 4 mm
thread M10x1



5053766 PROTECTION RUBBER VALVE 820 NOVA
 \varnothing external 46 mm - \varnothing internal 20 mm
depth 5,5 mm



3526096 VALVE MICROSWITCH
maximum load 0.2 A
for VALVE ELETTROSIT-820 NOVA-824 NOVASIT



ATA

Suitable for:

3348034 PIPE FITTING \varnothing 16 mm
thread M24x1.5
for model PEL 23



3526103 PROTECTING COVER
for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA



5012595 VALVE EXTENSION 820 NOVA
D-shaped pin \varnothing 6x4.6 mm




Gas taps and accessories

3348016 GAS TAP 21/S
with pilot flame
fittings \varnothing M16x1.5mm
with flow regulator
thermocouple connection M9x1
D-shaped pin \varnothing 8x6.5 mm



7102841 BODY FITTING TAP
 \varnothing pipe 10 mm
thread \varnothing 3/8" F - M16x1 mm
for taps PEL 20S-21S






Suitable for:

3348085 BUSH FOR TAP



3348220 CAP WITH PIN \varnothing 6x4.6 mm
pin length 30/23 mm upper/lower
for model PEL 21



3348021 CAP WITH PIN \varnothing 8x6.5 mm
pin length 22 mm
for model PEL 21S



3348243 CAP WITH PIN \varnothing 8x6.5 mm
pin length 22/15 mm right/lef
for model PEL 21S




3348058 MAGNET PROTECTION NUT M8x1
thread M18x1 mm
for model PEL 20-21-22



ATA

Suitable for:

3348219 CAP WITH PIN \varnothing 6x4.6 mm
pin length 45/20 mm upper/lower
for model PEL 21



3348221 CAP WITH PIN \varnothing 6x4.6 mm
pin length 30/17,5 mm upper/lower
for model PEL 21



3348238 CAP WITH PIN \varnothing 8x6.5 mm
pin 35/15 mm upper/lower
for model PEL 21S



3348236 FLANGIA WITH PRESSURE FITTING \varnothing 16/10 mm
thread M16x1,5 mm - M10x1,25 mm
for model PEL 21S



3348059 MAGNET PROTECTION NUT M9x1
thread M18x1mm
for model PEL 20-21-22





Suitable for:

3182022 MAGNETIC GROUP PEL SMALL HEAD
head \varnothing 15.5 mm - end piece \varnothing 11.5 mm - length 44mm



3348044 OLIVE FOR PIPE \varnothing 10 mm
for model PEL 20-21-24-25



ATA K22002

3348037 OLIVE FOR PIPE \varnothing 6 mm
for model PEL 21-22-24-25



3348029 PIPE FITTING \varnothing 4 mm
thread M10x1 mm
for model PEL 21-22-24-25



ATA K22005


5014757 PIPE FITTING \varnothing 6 mm
thread M10x1 mm



ATA

Suitable for:

3182011 MAGNETIC UNIT PEL SMALL HEAD
head \varnothing 15 mm - end piece \varnothing 11 mm - length 44 mm
for PEL tap models 20-21
for EGA tap model 25213
for JUNKERS tap model CH110



3348036 OLIVE FOR PIPE \varnothing 4 mm
for model PEL 21-22-24-25



ATA K22003

3348043 PIPE FITTING \varnothing 10 mm
thread M16x1.5 mm
for model PEL 20-21-24-25



ATA K22004

3020078 PIPE FITTING \varnothing 6 mm
thread M10x1





Suitable for:

ATA



Suitable for:

3348002 GAS TAP 22S/O
 with pilot flame
 with horizontal flange
 fittings \varnothing M20x1.5mm
 with flow regulator
 thermocouple connection M9x1
 D-shaped pin \varnothing 10x8 mm



3348229 CAP WITH PIN \varnothing 10 mm
 pin length 31 mm
 for model PEL 22S/O



ATA K22011


3348017 CAP WITH PIN \varnothing 10x8 mm
 pin length 26 mm
 for model PEL 22



3348245 CAP WITH PIN \varnothing 10x8 mm
 pin length 34/26 mm upper/lower
 for model PEL 22S




3348019 CAP WITH PIN \varnothing 10x9 mm
 pin length 26 mm
 for model PEL 22




3348231 CAP WITH PIN \varnothing 6x4.6 mm
 pin length 35/21 mm upper/lower
 for model PEL 22



3348232 CAP WITH PIN \varnothing 8x6.5 mm
 pin length 39/7 mm upper/lower
 for model PEL 22



3348213 FLANGE \varnothing 12/10 mm
 without adjustment
 thread M20x1.5 mm
 for model PEL 22S



3348023 FLANGE HORIZONTAL \varnothing 12/10 mm
 thread M20x1.5
 for model PEL 22



3348025 FLANGE HORIZONTAL CONICAL \varnothing 12/10 mm
 thread M20x1.5
 for model PEL 22





Suitable for:


3348024 FLANGE VERTICAL \varnothing 12/10 mm
thread M20x1.5
for model PEL 22



3348058 MAGNET PROTECTION NUT M8x1
thread M18x1 mm
for model PEL 20-21-22



3182009 MAGNETIC UNIT PEL BIG HEAD
head \varnothing 15.5 mm - end piece \varnothing 14 mm - length 44 mm
for PEL tap model 22-24



3348038 OLIVE FOR PIPE \varnothing 10 mm
for model PEL 22-24-25



ATA K22013

3348036 OLIVE FOR PIPE \varnothing 4 mm
for model PEL 21-22-24-25



ATA K22003

3348230 PIN FOT GAS TAP \varnothing 6x4.6 mm
pin length 45/20 mm rh/lh
for model PEL 22




ATA

Suitable for:

3348214 FLANGIA WITH PRESSURE FITTING \varnothing 12/10 mm
thread M20x1.5 mm
for model PEL 22S



3348059 MAGNET PROTECTION NUT M9x1
thread M18x1mm
for model PEL 20-21-22



3182021 MAGNETIC UNIT PEL LARGE HEAD
head \varnothing 15.5 mm - end piece \varnothing 14 mm - length 44 mm



3020082 OLIVE FOR PIPE \varnothing 12 mm
for model PEL 22-24-25



ATA K22012

3348037 OLIVE FOR PIPE \varnothing 6 mm
for model PEL 21-22-24-25



3348031 PIPE FITTING \varnothing 10 mm
thread M20x1.5 mm
for model PEL 22-24-25





Suitable for:

3348032 PIPE FITTING \varnothing 12 mm
thread M20x1.5 mm
for model PEL 22-24-25



ATA K22014

3020078 PIPE FITTING \varnothing 6 mm
thread M10x1



3348038 OLIVE FOR PIPE \varnothing 10 mm
for model PEL 22-24-25



ATA K22013

3348040 OLIVE FOR PIPE \varnothing 12 mm
for model PEL 23



ATA K22037

3348036 OLIVE FOR PIPE \varnothing 4 mm
for model PEL 21-22-24-25



ATA K22003

ATA



Suitable for:

3348029 PIPE FITTING \varnothing 4 mm
thread M10x1 mm
for model PEL 21-22-24-25



ATA K22005

5014757 PIPE FITTING \varnothing 6 mm
thread M10x1 mm



3348044 OLIVE FOR PIPE \varnothing 10 mm
for model PEL 20-21-24-25



ATA K22002

3348042 OLIVE FOR PIPE \varnothing 20 mm
for model PEL 23



ATA K22038

3348043 PIPE FITTING \varnothing 10 mm
thread M16x1.5 mm
for model PEL 20-21-24-25



ATA K22004

3348032 PIPE FITTING \varnothing 12 mm
thread M20x1.5 mm
for model PEL 22-24-25



ATA K22014

Suitable for:

3348033 PIPE FITTING \varnothing 12 mm
thread M24x1.5
for model PEL 23



ATA K22040

3348035 PIPE FITTING \varnothing 20 mm
thread M28x1.5
for model PEL 23



ATA K22039

3348029 PIPE FITTING \varnothing 4 mm
thread M10x1 mm
for model PEL 21-22-24-25



ATA K22005

Heating elements

3355046 HEATING ELEMENT 6000W 220/380V
immersed length 490 mm
flange \varnothing external 63 mm - with probe receptacle
complete with O-ring \varnothing 58 mm (3186013)



ATA 6205

3186013 O-RING 06187 EPDM \varnothing 58 mm
ring thickness 5.34 mm - internal \varnothing 47.00 mm



ATA 4207

Hydraulic piping

3450152 HOSE RUBBER REINFORCED \varnothing 13/19 mm
internal \varnothing 13 mm - external \varnothing 19 mm
temperature -40+100°C
sold per meter



ATA 7237

ATA 9702

ATA 9700

ATA 9701



Suitable for:

ATA



Suitable for:

Ignitors

3001020 **PIEZO IGNITER**
a \varnothing 18 mm hole is required for the assembly
faston M \varnothing 2.4 mm



ATA K24003

5071589 **WATERTIGHT PIEZO CAP**
made of silicone rubber



5035512 **WATERTIGHT PIEZO CAP**
of silicone rubber



Indicator lights

3221097 **INDICATOR LIGHT NEUTRAL 220V**
head \varnothing 8 mm - 120°C



ATA 7215

3221163 **ORANGE LAMP RECEPTACLE**
head \varnothing 15 mm - hole \varnothing 10 mm



ATA 7953

Interference suppression filters

3160479 **INTERFERENCE SUP. FILTER D.E.M.FC701Y2FL**
0.47 μ F



ATA 1500

Ironmongery (screws,nuts,washers)

3053132 **CLASP \varnothing 3x22 mm**
UNI 6873 - DIN 1481 - ISO 8752



ATA 7167

3242041 **CLASP \varnothing 3x25 mm**
stainless steel C70 - UNI 6873 - DIN 1481 - ISO 87



ATA 4185

Suitable for:

3528164 FINNED NUT M6
stainless steel - UNI 5448 - DIN 315



ATA 1013

Suitable for:

1348041 HEXAGONAL SELF-LOCKING NUT M8
stainless steel - with built in nylon ring
UNI 7473 - DIN 982 - ISO 7040



ATA 52050


Microswitches, magnetic

3240179 MAGNETIC MICROSWITCH E5301C
0.4A 250V - contact NO - head 65x20x9 mm
with cable length 500 mm



ATA 13105

3240181 PROTECTED MAGNET 62x18x10 mm




ATA 13642

3240204 MAGNETIC MICROSWITCH E5301C
0.4A 250V - contact NO - head 65x20x9 mm
with magnet 63x19x11 mm
with cable length 1900 mm



ATA 13122

3240181 PROTECTED MAGNET 62x18x10 mm



ATA 13642

O-Ring and ORM gaskets

3786454 O-RING GASKET 0153 EPDM
ring thickness 3.53 mm - internal \varnothing 49.21 mm



ATA 1033

1186255 O-RING 0109 EPDM
ring thickness 2.62 mm - internal \varnothing 9.13 mm



ATA 7623

1186805 O-RING 0115 EPDM
ring thickness 2.62 mm - internal \varnothing 11.91 mm



ATA 7130

3186287 O-RING 0123 EPDM
ring thickness 2.62 mm - internal \varnothing 17.86 mm



ATA 7134



Suitable for:

ATA



3186606 O-RING 0144 EPDM
ring thickness 3.53 mm - internal \varnothing 39.69 mm



ATA 4616

1186611 O-RING 02025 RED SILICONE
ring thickness 1.78 mm - internal \varnothing 6.07 mm



ATA 4692

1186223 O-RING 02056 EPDM
ring thickness 1.78 mm - internal \varnothing 14.00 mm



ATA 7601

1186833 O-RING 03100 EPDM
ring thickness 2.62 mm - internal \varnothing 25.07 mm



ATA 4615

1186237 O-RING 03300 EPDM
ring thickness 2.62 mm - internal \varnothing 75.87 mm



ATA 0042R

1186238 O-RING 04081 EPDM
ring thickness 3.53 mm - internal \varnothing 20.22 mm



ATA 1037

1186506 O-RING 04125 EPDM
ring thickness 3.53 mm - internal \varnothing 31.34 mm



ATA 13761

3786459 O-RING 04200 VITON
ring thickness 3.53 mm - internal \varnothing 50.39 mm



ATA K20007

3186235 O-RING 04425 EPDM
ring thickness 3.53 mm - internal \varnothing 107.50 mm



ATA 7683

3186013 O-RING 06187 EPDM \varnothing 58 mm
ring thickness 5.34 mm - internal \varnothing 47.00 mm



ATA 4207

3186014 O-RING 06225 EPDM \varnothing 67 mm
ring thickness 5.34 mm - internal \varnothing 56.52 mm



ATA



Pilot burners and accessories

3020085 FITTING FOR SPARKING PLUG FIXING M10x1mm




ATA K22024

3020082 OLIVE FOR PIPE \varnothing 12 mm
for model PEL 22-24-25



ATA K22012

3020025 ONE-FLAME PILOT BURNER SIT
multigas type with nozzle \varnothing 0.25 mm
with 2 positions bracket



ATA K22015


3020101 BRACKET CLAMP 2 POSITIONS



3020092 BRACKET PILOT BURNER SUPP. LH 92x55x45mm
for mounting of pilot assembly



3020292 BRACKET PILOT BURNER SUPPORT 47x40x15 mm
for burner \varnothing 90 mm



3020293 BRACKET PILOT BURNER SUPPORT 65x50x45 mm
for burner \varnothing 115 mm



3020291 BRACKET PILOT BURNER SUPPORT 85x45x55 mm
for burner \varnothing 135 mm




3020100 BRACKET 2 POSITIONS




3020108 DEFLECTOR 1 FLAME



3020083 FITTING AND OLIVE \varnothing 4 mm



3020084 FITTING AND OLIVE \varnothing 6 mm





Suitable for:

3020102 HEXAGON HEAD SCREW 3/16"x18 mm



3020060 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M 4x1 mm
overall length 82 mm
model CB505/021 Junkers
for model P502F



3020294 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M4x1 mm
overall length 67 mm



3020082 OLIVE FOR PIPE \varnothing 12 mm
for model PEL 22-24-25



ATA K22012

5027953 OLIVE FOR PIPE \varnothing 4 mm
for COPRECI CAL3200



3020115 PILOT CAP 1 FLAME



ATA

Suitable for:

3001003 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M4x1 mm
overall length 65 mm



3020124 IGNITION PLUG ROUND \varnothing 7x44 mm
connection \varnothing 2.4 mm
overall length 58 mm



3020365 IGNITION PLUG ROUND \varnothing 7x44 mm
connection \varnothing 2.4 mm
overall length 52 mm



3348036 OLIVE FOR PIPE \varnothing 4 mm
for model PEL 21-22-24-25



ATA K22003

3020081 OLIVE FOR PIPE \varnothing 6 mm



3020119 PILOT CAP 1 FLAME
for multigas burner





Suitable for:

3020054 PILOT JET \varnothing 0.20 mm



ATA K22025

4058525 PILOT JET \varnothing 0.30 mm



5015516 PILOT JET \varnothing 0.40 mm




5075989 PILOT JET \varnothing 0.70 mm



3020105 PILOT WITH 0.20 mm \varnothing JET



3020107 PILOT WITH 0.35 mm \varnothing JET



ATA

Suitable for:

3020156 PILOT JET \varnothing 0.25 mm



3020055 PILOT JET \varnothing 0.35 mm



ATA K22026

3500269 PILOT JET \varnothing 0.45 mm



3020308 PILOT WITH NOZZLE \varnothing 0.40 mm



3020106 PILOT WITH 0.25 mm \varnothing JET




3020079 PIPE FITTING \varnothing 12 mm
thread \varnothing 3/8" M





Suitable for:

3020077 PIPE FITTING \varnothing 4 mm
thread M10x1



3020078 PIPE FITTING \varnothing 6 mm
thread M10x1



3020054 PILOT JET \varnothing 0.20 mm




ATA K22025

3020055 PILOT JET \varnothing 0.35 mm




ATA K22026

3020011 THREE-FLAME PILOT BURNER
without sparking plug, gas jet
with pipe fitting and pilot pipe olive
with thermocouple connection
with sparking plug fitting



ATA K22029

3020200 FITTING FOR THERMOCOUPLE \varnothing 6.5 mm
thread M10x1



ATA



Suitable for:

5033138 PIPE FITTING \varnothing 4 mm
thread \varnothing 1/8" M



5014757 PIPE FITTING \varnothing 6 mm
thread M10x1 mm



3020040 PILOT JET \varnothing 0.30 mm



ATA K22022

4053669 PILOT JET \varnothing 0.75 mm



ATA K22021

3020085 FITTING FOR SPARKING PLUG FIXING M10x1 mm



ATA K22024

3001003 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M4x1 mm
overall length 65 mm





Suitable for:

3020060 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M 4x1 mm
overall length 82 mm
model CB505/021 Junkers
for model P502F



3020294 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M4x1 mm
overall length 67 mm



3020111 OLIVE FOR PIPE \varnothing 4 mm



3020044 PILOT JET \varnothing 0.20 mm



3020452 PILOT JET \varnothing 0.32 mm



3020449 PILOT JET \varnothing 0.54 mm



ATA

Suitable for:

3020124 IGNITION PLUG ROUND \varnothing 7x44 mm
connection \varnothing 2.4 mm
overall length 58 mm



3020365 IGNITION PLUG ROUND \varnothing 7x44 mm
connection \varnothing 2.4 mm
overall length 52 mm



3020112 OLIVE FOR PIPE \varnothing 6 mm



5071220 PILOT JET \varnothing 0.22 mm



3020045 PILOT JET \varnothing 0.50 mm




3020464 PILOT JET \varnothing 0.64 mm





Suitable for:

3020077 PIPE FITTING \varnothing 4 mm
thread M10x1



5014757 PIPE FITTING \varnothing 6 mm
thread M10x1 mm



ATA



Suitable for:

3020078 PIPE FITTING \varnothing 6 mm
thread M10x1




3020038 THREE-FLAME PRINTED PILOT BURNER SIT
without sparking plug, gas nozzle and gasket
thermocouple fitting included



ATA K22019

3020200 FITTING FOR THERMOCOUPLE \varnothing 6.5 mm
thread M10x1



3020085 FITTING FOR SPARKING PLUG FIXING M10x1m m



ATA K22024

3001003 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M4x1 mm
overall length 65 mm



3020060 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M 4x1 mm
overall length 82 mm
model CB505/021 Junkers
for model P502F



3020124 IGNITION PLUG ROUND \varnothing 7x44 mm
connection \varnothing 2.4 mm
overall length 58 mm





Suitable for:

3020294 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M4x1 mm
overall length 67 mm



3020111 OLIVE FOR PIPE \varnothing 4 mm



3020112 OLIVE FOR PIPE \varnothing 6 mm



5035324 PILOT JET \varnothing 0.18 mm



3020157 PILOT JET \varnothing 0.25 mm



3020541 PILOT JET \varnothing 0.35 mm



ATA

Suitable for:

3020365 IGNITION PLUG ROUND \varnothing 7x44 mm
connection \varnothing 2.4 mm
overall length 52 mm



3348036 OLIVE FOR PIPE \varnothing 4 mm
for model PEL 21-22-24-25



ATA K22003

3020086 PILOT GASKET



3020557 PILOT JET \varnothing 0.20 mm



3020040 PILOT JET \varnothing 0.30 mm



ATA K22022

3020041 PILOT JET \varnothing 0.41 mm





Suitable for:

2106308 PILOT JET \varnothing 0.45 mm



4053669 PILOT JET \varnothing 0.75 mm



ATA K22021

**3348029 PIPE FITTING \varnothing 4 mm
thread M10x1 mm
for model PEL 21-22-24-25**



ATA K22005

**5014757 PIPE FITTING \varnothing 6 mm
thread M10x1 mm**



ATA

Suitable for:

3020187 PILOT JET \varnothing 0.51 mm



**3020077 PIPE FITTING \varnothing 4 mm
thread M10x1**



**3020078 PIPE FITTING \varnothing 6 mm
thread M10x1**



Probes

3445107 PTC PVC PROBE 3000 mm
2-wire probe temperature range -30+80°C
bulb \varnothing 6x40 mm



ATA 7710

ATA 7723



Relays

3351029 POWER RELAY FINDER 62.82.8.230.0300
230V 50/60Hz
2 contacts NO 16A



ATA 4271

3351031 RELAY IMPULSE FINDER 26.01.8.230.0000
230V 50/60Hz - 1 contact NO 10A



ATA 7711


Selector switches

3057026 SELECTOR SWITCH 0-1 POSITIONS
contact capacity 16A 250V - max 150°C
D shaft \varnothing 6x4.6 mm



ATA K24034

3057023 SELECTOR SWITCH 0-6 POSITIONS
contact capacity 32A 250V - max 150°C
D shaft \varnothing 6x4.6 mm



ATA K24014

Solenoid valves

3120016 ADJUSTER FOR OUTLET ELBI NEUTRAL
flow rate 1.2 L/min - tolerance +/- 25%



ATA 7269

3120004 SOLEN. VALVE ELBI TYPE 319 1 WAY 90°
220/240V 50/60Hz - max. temperature 90°C
inlet 3/4" - outlet \varnothing 10.5 mm



ATA 2504

3120019 ADJUSTER FOR INLET ELBI BLACK
flow rate 5.5 L/min - tolerance +/- 15%



3120021 ADJUSTER FOR INLET ELBI BLACK
flow rate 12 L/min - tolerance +/- 15%



3120022 ADJUSTER FOR INLET ELBI BLACK
flow rate 16 L/min - tolerance +/- 15%





Suitable for:

3120037 ADJUSTER FOR OUTLET ELBI GREEN
flow rate 0.25 L/min - tolerance +/- 25%



3120016 ADJUSTER FOR OUTLET ELBI NEUTRAL
flow rate 1.2 L/min - tolerance +/- 25%



ATA 7269
3120015 ADJUSTER FOR OUTLET ELBI RED
flow rate 0.5 L/min - tolerance +/- 25%



3120202 ADJUSTER FOR OUTLET ELBI YELLOW
flow rate 0.35 L/min / tolerance +/- 25%



3120204 OUTLET ADJUSTER ELBI BLACK
flow rate 5.5 L/min - tolerance +/- 25%



3120504 SOLEN. VALVE ELBI TYPE 319 1 WAY 90°
24V 50/60Hz - max. temperature 90°C
inlet 3/4" - outlet ø 10.5 mm



ATA 13103

ATA



Suitable for:
3120201 ADJUSTER FOR OUTLET ELBI GREY
flow rate 4.7 L/min - tolerance +/- 25%



3120017 ADJUSTER FOR OUTLET ELBI ORANGE
flow rate 2.5 L/min - tolerance +/- 25%



3120203 ADJUSTER FOR OUTLET ELBI WHITE
flow rate 2 L/min - tolerance +/- 25%



3120000 FILTER FOR INLET SOLENOID VALVE ELBI



3120019 ADJUSTER FOR INLET ELBI BLACK
flow rate 5.5 L/min - tolerance +/- 15%





Suitable for:

3120021 ADJUSTER FOR INLET ELBI BLACK
flow rate 12 L/min - tolerance +/- 15%



3120037 ADJUSTER FOR OUTLET ELBI GREEN
flow rate 0.25 L/min - tolerance +/- 25%



3120016 ADJUSTER FOR OUTLET ELBI NEUTRAL
flow rate 1.2 L/min - tolerance +/- 25%



ATA 7269

3120015 ADJUSTER FOR OUTLET ELBI RED
flow rate 0.5 L/min - tolerance +/- 25%



3120202 ADJUSTER FOR OUTLET ELBI YELLOW
flow rate 0.35 L/min / tolerance +/- 25%



3120204 OUTLET ADJUSTER ELBI BLACK
flow rate 5.5 L/min - tolerance +/- 25%



ATA

Suitable for:

3120022 ADJUSTER FOR INLET ELBI BLACK
flow rate 16 L/min - tolerance +/- 15%



3120201 ADJUSTER FOR OUTLET ELBI GREY
flow rate 4.7 L/min - tolerance +/- 25%



3120017 ADJUSTER FOR OUTLET ELBI ORANGE
flow rate 2.5 L/min - tolerance +/- 25%



3120203 ADJUSTER FOR OUTLET ELBI WHITE
flow rate 2 L/min - tolerance +/- 25%



3120000 FILTER FOR INLET SOLENOID VALVE ELBI





Suitable for:

ATA



3120006 SOLEN. VALVE ELBI TYPE 339 2 WAY 90°
220/240V 50/60Hz - max. temperature 90°C
inlet 3/4" - two outlets ø 10.5 mm



ATA 1066

3120021 ADJUSTER FOR INLET ELBI BLACK
flow rate 12 L/min - tolerance +/- 15%



Suitable for:

3120019 ADJUSTER FOR INLET ELBI BLACK
flow rate 5.5 L/min - tolerance +/- 15%



3120022 ADJUSTER FOR INLET ELBI BLACK
flow rate 16 L/min - tolerance +/- 15%



3120037 ADJUSTER FOR OUTLET ELBI GREEN
flow rate 0.25 L/min - tolerance +/- 25%



3120201 ADJUSTER FOR OUTLET ELBI GREY
flow rate 4.7 L/min - tolerance +/- 25%



3120016 ADJUSTER FOR OUTLET ELBI NEUTRAL
flow rate 1.2 L/min - tolerance +/- 25%



3120017 ADJUSTER FOR OUTLET ELBI ORANGE
flow rate 2.5 L/min - tolerance +/- 25%



ATA 7269

3120015 ADJUSTER FOR OUTLET ELBI RED
flow rate 0.5 L/min - tolerance +/- 25%



3120203 ADJUSTER FOR OUTLET ELBI WHITE
flow rate 2 L/min - tolerance +/- 25%



3120202 ADJUSTER FOR OUTLET ELBI YELLOW
flow rate 0.35 L/min / tolerance +/- 25%



3120000 FILTER FOR INLET SOLENOID VALVE ELBI





Suitable for:

3120204 **OUTLET ADJUSTER ELBI BLACK**
flow rate 5.5 L/min - tolerance +/- 25%



ATA



Suitable for:

3120506 **SOLENOID VALVE ELBI TYPE 339 2 WAY 90°**
24V 50/60Hz - max. temperature 90°C
inlet 3/4" - two outlets ø 10.5 mm



3120019 **ADJUSTER FOR INLET ELBI BLACK**
flow rate 5.5 L/min - tolerance +/- 15%



ATA 14131

3120021 **ADJUSTER FOR INLET ELBI BLACK**
flow rate 12 L/min - tolerance +/- 15%



3120022 **ADJUSTER FOR INLET ELBI BLACK**
flow rate 16 L/min - tolerance +/- 15%



3120037 **ADJUSTER FOR OUTLET ELBI GREEN**
flow rate 0.25 L/min - tolerance +/- 25%



3120201 **ADJUSTER FOR OUTLET ELBI GREY**
flow rate 4.7 L/min - tolerance +/- 25%



3120016 **ADJUSTER FOR OUTLET ELBI NEUTRAL**
flow rate 1.2 L/min - tolerance +/- 25%



3120017 **ADJUSTER FOR OUTLET ELBI ORANGE**
flow rate 2.5 L/min - tolerance +/- 25%



ATA 7269

3120015 **ADJUSTER FOR OUTLET ELBI RED**
flow rate 0.5 L/min - tolerance +/- 25%



3120203 **ADJUSTER FOR OUTLET ELBI WHITE**
flow rate 2 L/min - tolerance +/- 25%





Suitable for:

3120202 ADJUSTER FOR OUTLET ELBI YELLOW
flow rate 0.35 L/min / tolerance +/- 25%



3120204 OUTLET ADJUSTER ELBI BLACK
flow rate 5.5 L/min - tolerance +/- 25%



ATA

Suitable for:

3120000 FILTER FOR INLET SOLENOID VALVE ELBI



3120008 SOLEN. VALVE ELBI TYPE 350 1 WAY 90°
220/240V 50/60Hz - max. temperature 90°C
inlet 3/4" - outlet ø 13.5 mm



3120019 ADJUSTER FOR INLET ELBI BLACK
flow rate 5.5 L/min - tolerance +/- 15%



ATA 7604

3120021 ADJUSTER FOR INLET ELBI BLACK
flow rate 12 L/min - tolerance +/- 15%



3120022 ADJUSTER FOR INLET ELBI BLACK
flow rate 16 L/min - tolerance +/- 15%



3120037 ADJUSTER FOR OUTLET ELBI GREEN
flow rate 0.25 L/min - tolerance +/- 25%



3120201 ADJUSTER FOR OUTLET ELBI GREY
flow rate 4.7 L/min - tolerance +/- 25%



3120016 ADJUSTER FOR OUTLET ELBI NEUTRAL
flow rate 1.2 L/min - tolerance +/- 25%



3120017 ADJUSTER FOR OUTLET ELBI ORANGE
flow rate 2.5 L/min - tolerance +/- 25%



ATA 7269



Suitable for:

3120015 ADJUSTER FOR OUTLET ELBI RED
flow rate 0.5 L/min - tolerance +/- 25%



3120202 ADJUSTER FOR OUTLET ELBI YELLOW
flow rate 0.35 L/min / tolerance +/- 25%



3120204 OUTLET ADJUSTER ELBI BLACK
flow rate 5.5 L/min - tolerance +/- 25%



3120511 SOLEN. VALVE ELBI TYPE 350 1 WAY 90°
24V 50Hz - max. temperature 90°C
inlet 3/4" - outlet ø 13.5 mm



3120021 ADJUSTER FOR INLET ELBI BLACK
flow rate 12 L/min - tolerance +/- 15%



3120037 ADJUSTER FOR OUTLET ELBI GREEN
flow rate 0.25 L/min - tolerance +/- 25%



ATA



Suitable for:

3120203 ADJUSTER FOR OUTLET ELBI WHITE
flow rate 2 L/min - tolerance +/- 25%



3120000 FILTER FOR INLET SOLENOID VALVE ELBI



3120019 ADJUSTER FOR INLET ELBI BLACK
flow rate 5.5 L/min - tolerance +/- 15%



3120022 ADJUSTER FOR INLET ELBI BLACK
flow rate 16 L/min - tolerance +/- 15%



3120201 ADJUSTER FOR OUTLET ELBI GREY
flow rate 4.7 L/min - tolerance +/- 25%





Suitable for:

3120016 ADJUSTER FOR OUTLET ELBI NEUTRAL
flow rate 1.2 L/min - tolerance +/- 25%



ATA 7269

3120015 ADJUSTER FOR OUTLET ELBI RED
flow rate 0.5 L/min - tolerance +/- 25%



3120202 ADJUSTER FOR OUTLET ELBI YELLOW
flow rate 0.35 L/min / tolerance +/- 25%



3120204 OUTLET ADJUSTER ELBI BLACK
flow rate 5.5 L/min - tolerance +/- 25%



ATA

Suitable for:

3120017 ADJUSTER FOR OUTLET ELBI ORANGE
flow rate 2.5 L/min - tolerance +/- 25%



3120203 ADJUSTER FOR OUTLET ELBI WHITE
flow rate 2 L/min - tolerance +/- 25%



3120000 FILTER FOR INLET SOLENOID VALVE ELBI



3120408 SOLEN. VALVE T&P 1 WAY 90°
230V 50/60Hz - max. temperature 90°C
inlet 3/4" - outlet ø 13.5 mm



ATA

3120608 ADJUSTER FOR OUTLET T&P DARK BROWN
flow rate 1.2 L/min - tolerance +/- 25%



3120421 ADJUSTER FOR OUTLET T&P BLACK
flow rate 5 L/min - tolerance +/- 20%



3120568 ADJUSTER FOR OUTLET T&P GREEN
flow rate 3 L/min - tolerance +/- 25%





Suitable for:

3120391 ADJUSTER FOR OUTLET T&P LIGHT BLUE
flow rate 1 L/min - tolerance +/- 25%



3120423 ADJUSTER FOR OUTLET T&P ORANGE
flow rate 0.5 L/min - tolerance +/- 25%



3120386 ADJUSTER FOR OUTLET T&P WHITE
flow rate 0.8 L/min - tolerance +/- 25%



D120056 ADJUSTER INLET T&P BRONZE
flowrate 12 L/min



D120057 ADJUSTER INLET T&P LIGHT BROWN
flowrate 16 L/min



D120052 ADJUSTER INLET T&P RED
flowrate 3 L/min



ATA

Suitable for:

3120387 ADJUSTER FOR OUTLET T&P LIGHT BROWN
flow rate 1.5 L/min - tolerance +/- 25%



3120424 ADJUSTER FOR OUTLET T&P RED
flow rate 0.25 L/min - tolerance +/- 25%



3120422 ADJUSTER FOR OUTLET T&P YELLOW
flow rate 2.5 L/min - tolerance +/- 25%



D120054 ADJUSTER INLET T&P GREY
flowrate 6 L/min



D120058 ADJUSTER INLET T&P ORANGE
flowrate 20 L/min



D120055 ADJUSTER INLET T&P WHITE
flowrate 10 L/min





Suitable for:

D120053 ADJUSTER INLET T&P YELLOW
flowrate 5.5 L/min



3120431 COIL T&P 12Vac 50/60Hz
for solenoid valves T&P



D120090 COIL T&P 120V 60Hz 8VA
for solenoid valves T&P



3120432 COIL T&P 24Vac 50/60Hz
for solenoid valves T&P



3120013 SOLENOID VALVE ELBI TYPE 359 3-WAY 90°
220/240V 50/60Hz - max. temperature 90°C
inlet 3/4" - three outlets ø 10.5 mm



ATA 7209

3120021 ADJUSTER FOR INLET ELBI BLACK
flow rate 12 L/min - tolerance +/- 15%



ATA



Suitable for:

D120059 ADJUSTER OUTLET T&P BLUE
flow rate 8 L/min - tolerance +/- 25%



D120092 COIL T&P 12Vdc
for solenoid valves T&P




3120433 COIL T&P 220V 50/60Hz
for solenoid valves T&P



D120093 COIL T&P 24Vdc
for solenoid valves T&P



3120019 ADJUSTER FOR INLET ELBI BLACK
flow rate 5.5 L/min - tolerance +/- 15%



3120022 ADJUSTER FOR INLET ELBI BLACK
flow rate 16 L/min - tolerance +/- 15%





Suitable for:

3120037 ADJUSTER FOR OUTLET ELBI GREEN
flow rate 0.25 L/min - tolerance +/- 25%



3120016 ADJUSTER FOR OUTLET ELBI NEUTRAL
flow rate 1.2 L/min - tolerance +/- 25%



ATA 7269

3120015 ADJUSTER FOR OUTLET ELBI RED
flow rate 0.5 L/min - tolerance +/- 25%



3120202 ADJUSTER FOR OUTLET ELBI YELLOW
flow rate 0.35 L/min / tolerance +/- 25%



3120204 OUTLET ADJUSTER ELBI BLACK
flow rate 5.5 L/min - tolerance +/- 25%



3120400 SOLENOID VALVE INVENSYS 1-WAY 90°
12Vac/dc 50/60Hz - max. temperature 90°C
inlet 3/4" - outlet ø 13.5 mm
operating pressure from 0.2 to 10 bar
flow rate 1.2 m3/h



ATA

ATA

Suitable for:

3120201 ADJUSTER FOR OUTLET ELBI GREY
flow rate 4.7 L/min - tolerance +/- 25%



3120017 ADJUSTER FOR OUTLET ELBI ORANGE
flow rate 2.5 L/min - tolerance +/- 25%




3120203 ADJUSTER FOR OUTLET ELBI WHITE
flow rate 2 L/min - tolerance +/- 25%



3120000 FILTER FOR INLET SOLENOID VALVE ELBI



3120473 ADJUSTER FOR INLET ROBERTSHAW BROWN
flow rate 5 L/min - tolerance +/- 15%





Suitable for:

3120474 ADJUSTER FOR INLET ROBERTSHAW DARK BLUE
flow rate 6 L/min - tolerance +/- 15%



3120479 ADJUSTER FOR INLET ROBERTSHAW GREY
flow rate 12 L/min - tolerance +/- 15%



3120475 ADJUSTER FOR INLET ROBERTSHAW ORANGE
flow rate 8 L/min - tolerance +/- 15%



3120477 ADJUSTER FOR INLET ROBERTSHAW WHITE
flow rate 10 L/min - tolerance +/- 15%



3120499 ADJUSTER FOR OUTLET ROBERTSHAW BLU
flow rate 1.2 L/min - tolerance +/- 25%



3120488 ADJUSTER FOR OUTLET ROBERTSHAW PINK
flow rate 3.3 L/min - tolerance +/- 20%



ATA

Suitable for:

3120478 ADJUSTER FOR INLET ROBERTSHAW GREEN
flow rate 11 L/min - tolerance +/- 15%



3120476 ADJUSTER FOR INLET ROBERTSHAW LIGHT BLUE
flow rate 9 L/min - tolerance +/- 15%



3120472 ADJUSTER FOR INLET ROBERTSHAW PURPLE
flow rate 4 L/min - tolerance +/- 15%



3120481 ADJUSTER FOR INLET ROBERTSHAW YELLOW
flow rate 14.5 L/min - tolerance +/- 15%



3120484 ADJUSTER FOR OUTLET ROBERTSHAW GREEN
flow rate 0.8 L/min - tolerance +/- 25%



3120482 ADJUSTER FOR OUTLET ROBERTSHAW WHITE
flow rate 0.25 L/min - tolerance +/- 10%





Suitable for:

3120483 ADJUSTER FOR OUTLET ROBERTSHAW YELLOW
flow rate 0.5 L/min - tolerance +/- 15%



3120485 OUTLET ADJUSTER ROBERTSHAW LIGHT BROWN
flow rate 1.3 L/min - tolerance +/- 25%



3120625 OUTLET REDUCER ROBERTSHAW GRIGIO
flow rate 0.35 L/min - tolerance +/- 10%



ATA

Suitable for:

3120487 OUTLET ADJUSTER ROBERTSHAW DARK BROWN
flow rate 2.5 L/min - tolerance +/- 20%



3120486 OUTLET ADJUSTER ROBERTSHAW LIGHT GREEN
flow rate 2 L/min - tolerance +/- 25%



Switches

3319016 BIPOLAR SWITCH RED 16A 250V
16(4)A 250V - max. temperature 120°C
with indicator light - silk screen printing 0 - I
mounting hole 22x30 mm



3319780 BLOCK CONNECTION WHITE 22x30 mm



ATA 1089

3319779 BLOCK CONNECTIONS BLACK 22x30 mm



3319782 FRAME SAFETY 2 SIDES BLACK 22x30 mm



3319783 FRAME SAFETY 4 SIDES BLACK 22x30 mm



3319501 PUSH-BUTTON PROTECTION CAP
external dimensions 29x36 mm
for switches with mounting hole 22x30 mm






Suitable for:

ATA



3319018 CHANGEOVER SWITCH 2 POLE RED 16A 250V
16(4)A 250V - max. temperature 120°C
with indicator light - mounting hole 22x30 mm



ATA 1087

3319779 BLOCK CONNECTIONS BLACK 22x30 mm



3319783 FRAME SAFETY 4 SIDES BLACK 22x30 mm



3319015 PUSH-BUTTON BIPOLAR RED 16A 250V
16(4)A 250V - max. temperature 120°C
with indicator light - silk screen printing 0 - I
mounting hole 22x30 mm



ATA 1085

3319779 BLOCK CONNECTIONS BLACK 22x30 mm



3319783 FRAME SAFETY 4 SIDES BLACK 22x30 mm



3319780 BLOCK CONNECTION WHITE 22x30 mm



3319782 FRAME SAFETY 2 SIDES BLACK 22x30 mm



3319501 PUSH-BUTTON PROTECTION CAP
external dimensions 29x36 mm
for switches with mounting hole 22x30 mm



3319780 BLOCK CONNECTION WHITE 22x30 mm



3319782 FRAME SAFETY 2 SIDES BLACK 22x30 mm




3319501 PUSH-BUTTON PROTECTION CAP
external dimensions 29x36 mm
for switches with mounting hole 22x30 mm





Terminal blocks

- 3247037** **TERMINAL BLOCK 4-POLES FV173 40A 600V**
for cable max 6 mm²
operating temperature 150°C
nominal voltage 450 V



ATA 13162

Thermocouples and accessories

- 3440836** **THERMOCOUPLE SIT M9x1 85 cm - 10 PCS**



ATA K22176

- 3440036** **THERMOCOUPLE SIT M9x1 85 cm.**



ATA K22176

- 3440049** **THERMOCOUPLE SIT M9x1 75 cm**



ATA K22176

- 3440836** **THERMOCOUPLE SIT M9x1 85 cm - 10 PCS**



ATA K22176

- 3440849** **THERMOCOUPLE SIT M9x1 75 cm - 10 PCS**





Suitable for:


ATA



Suitable for:

Thermostatic gas valves

3345018 THERMOSTATIC TAP 25ST
 operating temperature 100-300°C
 connections M16x1.5 mm
 thermocouple connection M9x1
 bulb \varnothing 6x75 mm
 capillary length 1200 mm
 D-shaped pin \varnothing 8x6.5 mm



ATA K22131

3348044 OLIVE FOR PIPE \varnothing 10 mm
 for model PEL 20-21-24-25




ATA K22002

3348036 OLIVE FOR PIPE \varnothing 4 mm
 for model PEL 21-22-24-25



ATA K22003

3348031 PIPE FITTING \varnothing 10 mm
 thread M20x1.5 mm
 for model PEL 22-24-25



3348032 PIPE FITTING \varnothing 12 mm
 thread M20x1.5 mm
 for model PEL 22-24-25



ATA K22014

3348038 OLIVE FOR PIPE \varnothing 10 mm
 for model PEL 22-24-25



ATA K22013

3020082 OLIVE FOR PIPE \varnothing 12 mm
 for model PEL 22-24-25




ATA K22012

3348037 OLIVE FOR PIPE \varnothing 6 mm
 for model PEL 21-22-24-25



3348043 PIPE FITTING \varnothing 10 mm
 thread M16x1.5 mm
 for model PEL 20-21-24-25



ATA K22004

3020077 PIPE FITTING \varnothing 4 mm
 thread M10x1





Suitable for:

3348029 PIPE FITTING \varnothing 4 mm
thread M10x1 mm
for model PEL 21-22-24-25



ATA K22005

5014757 PIPE FITTING \varnothing 6 mm
thread M10x1 mm



ATA


Suitable for:

3020078 PIPE FITTING \varnothing 6 mm
thread M10x1




Thermostats

3444312 SINGLE-PHASE THERMOSTAT 360°C
with manual reset
capillary length covered 1500 mm - 16A 250V
bulb \varnothing 4x110 mm



ATA K24041

3444004 THERMOSTAT SINGLE-PHASE TR2 0-90°C
D-shaped pin \varnothing 6x4.6 mm
capillary length 1500 mm - 15A 250V
bulb \varnothing 6.5x95 mm



ATA 1080

ATA 2080

ATA 7280

3444031 SINGLE-PHASE THERMOSTAT 90-185°C
complete with auxiliary selector switch
D-shaped pin \varnothing 6x4.6 mm
covered capillary length 2500 mm - 16A 250V
bulb \varnothing 4x230 mm



ATA K24048

3444052 THREE-PHASE THERMOSTAT 50-320°C
D-shaped pin \varnothing 6x4.6 mm
capillary length 900 mm - 10A 400V
bulb \varnothing 3x230 mm



ATA K24015

The data herewith contained may change without notice and LF SpA cannot be held responsible for possible errors stated or resulting by the use of this document. All rights reserved. No part of this publication may be reproduced without written permission by LF SpA.



Distributing Components, Spare Parts & Accessories in original quality worldwide

-
- LF SpA HEADQUARTERS**
via Voltri, 80 - 47522 Cesena (FC) ITALY
Tel. +39 0547 34 11 11 - Fax +39 0547 34 11 10
www.lfircambi724.it - info@lfircambi.it
Export Dept. Tel. +39 0547 34 11 50 - Fax +39 0547 34 11 55
www.lfspareparts724.com - export@lfspareparts.com
- LF SpA HOUSEHOLD COMPONENTS DIVISION**
Via Padriciano, 99 - AREA Science Park - 34149 Trieste (TS) ITALY
Tel. +39 0547 34 12 42 - Fax +39 0547 34 12 48
www.lfspareparts724.com - info@lfspareparts.com
- EPGC Sas FRANCE**
13, Rue des Forts - 59960 Neuville en Ferrain
Tel. +33 (0)3 20 25 06 21 - Fax +33 (0)3 20 25 34 12
www.epgc.com - epgc@epgc.com
- LF GmbH GERMANY**
Junkersstrasse, 3 - D-82178 Puchheim - München
Tel. +49 89 89 45 78 66 - Fax +49 89 89 45 78 88
www.lfersatzteile724.de - info@lfersatzteile.de
- LF China REPUBLIC OF CHINA**
Room 403, No.2, Huadu Mansion, Lane 422, Huanghua Rd.
Minhang Dist. - 201103 Shanghai
Tel. +86 (0)21 33 53 66 31 - Fax +86 (0)21 33 53 66 32
www.lfspareparts724.com - china@lfspareparts.com
- OOO LF RUSSIAN FEDERATION**
Ul. Anatoliya Zhivova, 8 - office 1 - 123100 Moscow
Tel./Fax +7 495 725 26 53
www.lfspareparts724.ru - info@lfspareparts.ru
- LF Repuestos Horeca S.L.U. SPAIN**
Poligono Industrial Carpetania - C/Miguel Faraday, 8 - 28906 Getafe
Tel. +34 91 477 91 00 - Fax +34 91 477 90 81
www.lfrepuestos-horeca724.es - info@lfrepuestos.es
- LF Scandinavia Aps - LF Spareparts S.p.A. DENMARK**
Nupark, 51 - 7500 Holstebro
Tel. +45 70 70 77 33
www.lfspareparts724.dk - denmark@lfspareparts.dk
- LF SpA Cesena (IT) Swiss Branch Steinhausen SWITZERLAND**
Sennweidstrasse, 45 - CH-6312 Steinhausen
Tel. +41 (0)41 760 15 80/1 - Fax +41 (0)41 760 15 85
www.lfersatzteile724.ch - info@lfersatzteile.ch
- LF Spare Parts Ltd. UNITED KINGDOM**
A10a Lakeside Business Park, Broadway Lane
South Cerney, Gloucestershire GL7 5XL
Tel. +44 (0)1285 86 16 25 - Fax +44 (0)1285 86 39 49
www.lfspareparts724.co.uk - info@lfspareparts.co.uk
- LF Central Est Europe S.r.o. CZECH REPUBLIC**
Antala Staska 1859/34
14000 Praha 4 - KRC
Tel. +420 730 156 910
www.lfspareparts724.cz - info@lfspareparts.cz
- LF SPARE PARTS INC. USA**
Legal address:
155 Office Plaza Dr - Suite A - Tallahassee, FL 32301
Business/Mailing address:
1100 South Tower, 225 Peachtree St., N.E. - Atlanta, GA 30303, USA
Tel. +1-404-525-2600 - Fax +1-404-586-3528
www.lfspareparts724.us - info@lfspareparts.us
Tel. West Coast and Midwest: 206-349-1525 Sauro
Tel. East Coast and the Caribbean: 786-817-1764 Luis
-
- AUSTRALIA AND NEW ZEALAND**
www.lfspareparts724.com
andrea.calvio@lfspareparts.com
- AUSTRIA**
www.lfersatzteile724.at
info@lfersatzteile.at
- BALKAN COUNTRIES**
www.lfspareparts724.com
matija.ramov@lfspareparts.com
- BALTIC COUNTRIES**
www.lfspareparts724.com
inara.silina@lfspareparts.com
- LATIN AMERICA AND THE CARRIBEANS**
www.lfrepuestos-horeca724.es
export@lfrepuestos.es
- POLAND**
www.lfspareparts724.pl
info@lfspareparts.pl
- SOUTH KOREA**
www.lfspareparts724.com
fabio.doni@lfspareparts.com
- TURKEY**
www.lfyedekparca724.com
export@lfspareparts.com