



Spare parts for the professional sector: Cooking equipment



Suitable for:

CAPIC



This catalogue is automatically generated.
Therefore, the sequence of the items might
not be always shown at best.
Updates will be issued in case of additions
and/or amendments.

*Suitable **universal spare parts** may not be included*





Suitable for:

CAPIC



Suitable for:

Axial motor fans

3240519 AXIAL FAN EBM 4656N
230V 50Hz 19W 2650rpm
119x119x38 mm
ball bearing



CAPIC E050571


3805037 CABLE FOR AXIAL MOTOR FAN
cable length 2000 mm



3805036 CABLE FOR AXIAL MOTOR FAN
cable length 1500 mm



3240600 FAN GRID 119x119 mm
distance between mounting holes 145 mm



Burners, flame spreaders and accessories

3025598 BURNER ø 106 mm



CAPIC G204011

3025629 BURNER ø 119 mm



CAPIC G204069

CAPIC

3025633 BURNER ø 135 mm



CAPIC

3025634 BURNER ø 143 mm



CAPIC

3025595 BURNER ø 83 mm



CAPIC G204006



Suitable for:

Suitable for:

3025797 BURNER ASSEMBLY MOUNTING DISTANCE 110 mm
with vertical flame
4000-7000 Kcal/h
height 90 mm - \varnothing 80 mm - pipe \varnothing 27 mm

3025595 BURNER \varnothing 83 mm



CAPIC

CAPIC G204006

3025596 FLAME SPREADER \varnothing 80 mm

3025679 GAS BURNER SUPPORT GR5 \varnothing 27 mm



CAPIC

CAPIC

3500185 GAS JET CONICAL M17x1 \varnothing 1.20 mm

3500193 GAS JET CONICAL M17x1 \varnothing 2.00 mm




CAPIC G206512

CAPIC G206536

3025772 BURNER ASSEMBLY MOUNTING DISTANCE 120 mm
vertical flame outlet
6000-9000 Kcal/h
height 60 mm - \varnothing 120 mm - pipe \varnothing 27 mm

3025605 FLAME SPREADER \varnothing 115 mm



CAPIC

CAPIC G204037

3025606 FLAME SPREADER \varnothing 120 mm

3025679 GAS BURNER SUPPORT GR5 \varnothing 27 mm



CAPIC G204035

CAPIC

3500186 GAS JET CONICAL M17x1 \varnothing 1.30 mm

3500196 GAS JET CONICAL M17x1 \varnothing 2.30 mm



CAPIC G206516

CAPIC G206542



CAPIC



Suitable for:

Suitable for:

3025752 BURNER ASSEMBLY MOUNTING DISTANCE 125 mm
with central flame
5000-6000 Kcal/h
height 63 mm - \varnothing 90 mm - pipe \varnothing 27 mm

3500192 CONICAL GAS JET M17x1 \varnothing 1.90 mm



CAPIC G201018

CAPIC G206534

3025587 FLAME SPREADER \varnothing 81 mm

3025588 FLAME SPREADER \varnothing 90 mm



CAPIC

CAPIC

3025679 GAS BURNER SUPPORT GR5 \varnothing 27 mm

3500185 GAS JET CONICAL M17x1 \varnothing 1.20 mm



CAPIC

CAPIC G206512

3025756 BURNER ASSEMBLY MOUNTING DISTANCE 165 mm
with vertical flame
4000-7000 Kcal/h
height 90 mm - \varnothing 80 mm - pipe \varnothing 27 mm

3025595 BURNER \varnothing 83 mm



CAPIC

CAPIC G204006

3025596 FLAME SPREADER \varnothing 80 mm

3025679 GAS BURNER SUPPORT GR5 \varnothing 27 mm



CAPIC

CAPIC

3500185 GAS JET CONICAL M17x1 \varnothing 1.20 mm

3500193 GAS JET CONICAL M17x1 \varnothing 2.00 mm



CAPIC G206512

CAPIC G206536

Suitable for:

Suitable for:

3025762 BURNER ASSEMBLY MOUNTING DISTANCE 175 mm
vertical flame outlet
6000-9000 Kcal/h
height 60 mm - \varnothing 120 mm - pipe \varnothing 27 mm

3025605 FLAME SPREADER \varnothing 115 mm



CAPIC G200520

CAPIC G204037

3025606 FLAME SPREADER \varnothing 120 mm

3025679 GAS BURNER SUPPORT GR5 \varnothing 27 mm



CAPIC G204035

CAPIC

3500186 GAS JET CONICAL M17x1 \varnothing 1.30 mm

3500196 GAS JET CONICAL M17x1 \varnothing 2.30 mm



CAPIC G206516

CAPIC G206542

3025753 BURNER ASSEMBLY MOUNTING DISTANCE 180 mm
with central flame
5000-6000 Kcal/h
height 63 mm - \varnothing 90 mm - pipe \varnothing 27 mm

3500192 CONICAL GAS JET M17x1 \varnothing 1.90 mm



CAPIC

CAPIC G206534

3025587 FLAME SPREADER \varnothing 81 mm

3025588 FLAME SPREADER \varnothing 90 mm



CAPIC

CAPIC

3025679 GAS BURNER SUPPORT GR5 \varnothing 27 mm

3500185 GAS JET CONICAL M17x1 \varnothing 1.20 mm



CAPIC

CAPIC G206512



CAPIC



Suitable for:

Suitable for:

3025769 BURNER ASSEMBLY MOUNTING DISTANCE 185 mm
with vertical flame
7000-9000 Kcal/h
height 100 mm - \varnothing 100 mm - pipe \varnothing 34 mm
for Kitchen (CAPIC) 405 B1

3025598 BURNER \varnothing 106 mm



CAPIC G205020

CAPIC G205515

CAPIC G204011

3500187 CONICAL GAS JET M17x1 \varnothing 1.40 mm

3025627 FLAME SPREADER \varnothing 100 mm



CAPIC G206520

CAPIC G204012

CAPIC G204027

3025680 GAS BURNER SUPPORT GR6 \varnothing 34 mm

3500195 GAS JET CONICAL M17x1 \varnothing 2.20 mm



CAPIC

CAPIC G206540

3025750 BURNER ASSEMBLY MOUNTING DISTANCE 215 mm
with central flame
7000-9000 Kcal/h
height 60 mm - \varnothing 120 mm - pipe \varnothing 34 mm
for Hot plate gas (CAPIC)

3500188 CONICAL GAS JET M17x1 \varnothing 1.50 mm



CAPIC G201025

CAPIC G206524

3025611 FLAME SPREADER \varnothing 120 mm

3025680 GAS BURNER SUPPORT GR6 \varnothing 34 mm



CAPIC G204055

CAPIC



Suitable for:

3500196 GAS JET CONICAL M17x1 ø 2.30 mm



CAPIC G206542

CAPIC



Suitable for:

3025698 BURNER ASSEMBLY MOUNTING DISTANCE 225 mm
with central flame
7000-9000 Kcal/h
height 80 mm - ø 120 mm - pipe ø 34 mm



CAPIC

3025680 GAS BURNER SUPPORT GR6 ø 34 mm



CAPIC

3025699 BURNER ASSEMBLY MOUNTING DISTANCE 235 mm
with central flame
9000-12000 Kcal/h
height 80 mm - ø 140 mm - pipe ø 34 mm



CAPIC

3500198 CONICAL GAS JET M17x1 ø 2.50 mm



CAPIC G206546

3500187 CONICAL GAS JET M17x1 ø 1.40 mm



CAPIC G206520

3500195 GAS JET CONICAL M17x1 ø 2.20 mm



CAPIC G206540

3500189 CONICAL GAS JET M17x1 ø 1.60 mm



CAPIC G206526

3025680 GAS BURNER SUPPORT GR6 ø 34 mm



CAPIC



Suitable for:

CAPIC



3025799 BURNER ASSEMBLY MOUNTING DISTANCE 240 mm
with vertical flame
4000-7000 Kcal/h
height 90 mm - \varnothing 80 mm - pipe \varnothing 27 mm



CAPIC

3025596 FLAME SPREADER \varnothing 80 mm



CAPIC

3500185 GAS JET CONICAL M17x1 \varnothing 1.20 mm



CAPIC G206512

3025768 BURNER ASSEMBLY MOUNTING DISTANCE 245 mm
with vertical flame
5000-7000 kcal/h
height 100 mm - \varnothing 80 mm - pipe \varnothing 34 mm



CAPIC

3025624 FLAME SPREADER \varnothing 80 mm
for Kitchen (CAPIC) W070109 G0402



CAPIC G204007

CAPIC G204060

Suitable for:

3025595 BURNER \varnothing 83 mm



CAPIC G204006

3025679 GAS BURNER SUPPORT GR5 \varnothing 27 mm



CAPIC

3500193 GAS JET CONICAL M17x1 \varnothing 2.00 mm



CAPIC G206536

3025595 BURNER \varnothing 83 mm



CAPIC G204006

3025680 GAS BURNER SUPPORT GR6 \varnothing 34 mm



CAPIC



Suitable for:

3500185 GAS JET CONICAL M17x1 ϕ 1.20 mm



CAPIC G206512

CAPIC



Suitable for:

3500193 GAS JET CONICAL M17x1 ϕ 2.00 mm



CAPIC G206536

3025770 BURNER ASSEMBLY MOUNTING DISTANCE 245 mm
with vertical flame
7000-9000 Kcal/h
height 100 mm - ϕ 100 mm - pipe ϕ 34 mm



CAPIC

3500187 CONICAL GAS JET M17x1 ϕ 1.40 mm



CAPIC G206520

3025680 GAS BURNER SUPPORT GR6 ϕ 34 mm



CAPIC

3025707 BURNER ASSEMBLY MOUNTING DISTANCE 265 mm
with central flame
15000-20000 Kcal/h
height 80 mm - ϕ 200 mm - pipe ϕ 34 mm
for Boiling pan gas (CAPIC)



CAPIC G201032

3025598 BURNER ϕ 106 mm



CAPIC G204011

3025627 FLAME SPREADER ϕ 100 mm



CAPIC G204012

CAPIC G204027

3500195 GAS JET CONICAL M17x1 ϕ 2.20 mm



CAPIC G206540

3025680 GAS BURNER SUPPORT GR6 ϕ 34 mm



CAPIC



CAPIC



Suitable for:

Suitable for:

3025764 BURNER ASSEMBLY MOUNTING DISTANCE 275 mm
with central flame
7000-9000 Kcal/h
height 60 mm - \varnothing 120 mm - pipe \varnothing 34 mm

3500188 CONICAL GAS JET M17x1 \varnothing 1.50 mm



CAPIC

CAPIC G206524

3025611 FLAME SPREADER \varnothing 120 mm

3025680 GAS BURNER SUPPORT GR6 \varnothing 34 mm



CAPIC G204055

CAPIC

3500196 GAS JET CONICAL M17x1 \varnothing 2.30 mm



CAPIC G206542

3025709 BURNER ASSEMBLY MOUNTING DISTANCE 295 mm
with central flame
9000-12000 Kcal/h
height 80 mm - \varnothing 140 mm - pipe \varnothing 34 mm

3500198 CONICAL GAS JET M17x1 \varnothing 2.50 mm



CAPIC

CAPIC G206546

3500199 CONICAL GAS JET M17x1 \varnothing 2.60 mm

3025680 GAS BURNER SUPPORT GR6 \varnothing 34 mm



CAPIC

Suitable for:

Suitable for:

3025713 BURNER ASSEMBLY MOUNTING DISTANCE 325 mm
with central flame
15000-20000 Kcal/h
height 80 mm - \varnothing 200 mm - pipe \varnothing 34 mm

3025680 GAS BURNER SUPPORT GR6 \varnothing 34 mm



CAPIC

CAPIC

3025714 COMPLETE BURNER MOUNTING DISTANCE 120 mm
vertical flame outlet
4000-7000 Kcal/h
height 54 mm - \varnothing 80 mm - pipe \varnothing 27 mm

3025653 FLAME SPREADER \varnothing 80 mm



CAPIC

CAPIC

3025679 GAS BURNER SUPPORT GR5 \varnothing 27 mm

3500185 GAS JET CONICAL M17x1 \varnothing 1.20 mm



CAPIC

CAPIC G206512

3500193 GAS JET CONICAL M17x1 \varnothing 2.00 mm

3025688 NOZZLE HOLDER WITH BRACKET



CAPIC G206536

CAPIC G204062

CAPIC G205514

3025715 COMPLETE BURNER MOUNTING DISTANCE 175 mm
vertical flame outlet
4000-7000 Kcal/h
height 54 mm - \varnothing 80 mm - pipe \varnothing 27 mm

3025653 FLAME SPREADER \varnothing 80 mm



CAPIC

CAPIC



Suitable for:

3025679 GAS BURNER SUPPORT GR5 ø 27 mm



CAPIC

3500193 GAS JET CONICAL M17x1 ø 2.00 mm



CAPIC G206536

3025754 COMPLETE BURNER MOUNTING DISTANCE 175 mm
5000-7000 Kcal/h
height 40 mm - ø 80 mm - pipe ø 27 mm



CAPIC

3025591 FLAME SPREADER ø 80 mm



CAPIC G204040

3500185 GAS JET CONICAL M17x1 ø 1.20 mm



CAPIC G206512

3025774 COMPLETE BURNER MOUNTING DISTANCE 175 mm
4000-7000 Kcal/h
height 48 mm - ø 80 mm - pipe ø 27 mm



CAPIC

CAPIC

Suitable for:

3500185 GAS JET CONICAL M17x1 ø 1.20 mm



CAPIC G206512

3025688 NOZZLE HOLDER WITH BRACKET



CAPIC G204062

CAPIC G205514

3025590 FLAME SPREADER ø 73 mm



CAPIC G204032

3025679 GAS BURNER SUPPORT GR5 ø 27 mm



CAPIC

3500193 GAS JET CONICAL M17x1 ø 2.00 mm



CAPIC G206536

3500192 CONICAL GAS JET M17x1 ø 1.90 mm



CAPIC G206534





Suitable for:

3025590 FLAME SPREADER \varnothing 73 mm



CAPIC G204032

3025679 GAS BURNER SUPPORT GR5 \varnothing 27 mm



CAPIC

3025767 COMPLETE BURNER MOUNTING DISTANCE 275 mm
7000-14000 Kcal/h
height 65 mm - \varnothing 120 mm - pipe \varnothing 34 mm



CAPIC

3500200 CONICAL GAS JET M17x1 \varnothing 2.70 mm



3025606 FLAME SPREADER \varnothing 120 mm



CAPIC G204035

3025599 FLAME SPREADER \varnothing 100 mm



CAPIC

CAPIC

Suitable for:

3025615 FLAME SPREADER \varnothing 80 mm



CAPIC G204030

3500184 GAS JET CONICAL M17x1 \varnothing 1.15 mm



CAPIC G206510

3500187 CONICAL GAS JET M17x1 \varnothing 1.40 mm



CAPIC G206520

3025605 FLAME SPREADER \varnothing 115 mm



CAPIC G204037

3025680 GAS BURNER SUPPORT GR6 \varnothing 34 mm



CAPIC

3025627 FLAME SPREADER \varnothing 100 mm



CAPIC G204012

CAPIC G204027





Suitable for:

CAPIC



3025605 FLAME SPREADER \varnothing 115 mm



CAPIC G204037

Suitable for:

3025606 FLAME SPREADER \varnothing 120 mm



CAPIC G204035

3025611 FLAME SPREADER \varnothing 120 mm



CAPIC G204055

3025590 FLAME SPREADER \varnothing 73 mm



CAPIC G204032

3025591 FLAME SPREADER \varnothing 80 mm



CAPIC G204040

3025596 FLAME SPREADER \varnothing 80 mm



CAPIC

3025615 FLAME SPREADER \varnothing 80 mm



CAPIC G204030

**3025624 FLAME SPREADER \varnothing 80 mm
for Kitchen (CAPIC) W070109 G0402**



CAPIC G204007

CAPIC G204060

3025653 FLAME SPREADER \varnothing 80 mm



CAPIC

3025587 FLAME SPREADER \varnothing 81 mm



CAPIC

3025588 FLAME SPREADER \varnothing 90 mm



CAPIC

3025679 GAS BURNER SUPPORT GR5 \varnothing 27 mm



CAPIC

Suitable for:

3025680 GAS BURNER SUPPORT GR6 ø 34 mm



CAPIC

Suitable for:

3025688 NOZZLE HOLDER WITH BRACKET



CAPIC G204062

CAPIC G205514

Buzzers

3446191 BUZZER FOR TIMER
230 V - 50 Hz
for Bratt pan (CAPIC) W295125



CAPIC E204042

Cables for piezo igniters

3001215 IGNITION LEAD LF - 10 mt
thickness ø 1 mm
temperature -60°+200°C



CAPIC E351610

3001115 IGNITION LEAD LF - 100 mt
thickness ø 1 mm
temperature -60°+200°C



CAPIC E351610

3001002 IGNITION LEAD 1000 mm
with faston 6.35x0.8 mm for ignition
with faston ø 4 mm for ignition plug



CAPIC


Contact thermostats

3444609 CONTACT THERMOSTAT KSD301-R 95°C
manual reset - 10A 250V



CAPIC L455110

3444607 CONTACT THERMOSTAT 110°C
with manual reset



CAPIC L455105



Suitable for:

CAPIC



3444341 CONTACT THERMOSTAT 215°C 16A 250V
with manual reset - pin M4



CAPIC L455107

Suitable for:

3444608 CONTACT THERMOSTAT 60°C
automatic reset - for wash tank



CAPIC L455115

3444606 CONTACT THERMOSTAT 80°C
safety thermostat - for boiler



CAPIC L455112

Contactors

3454060 CONTACTOR SCHNEIDER LC1D09B7
9A 400V 4Kw - coil 24V 50/60Hz
3 normally open contacts
1 normally open auxiliary contact
1 normally closed auxiliary contact



CAPIC E050901

3454013 CONTACTOR SCHNEIDER LC1D09P7
9A 400V 4Kw - coil 230V 50/60Hz
3 normally open contacts
1 normally open auxiliary contact
1 normally closed auxiliary contact
for Bratt pan electric (CAPIC)



CAPIC E050903

3454017 CONTACTOR SCHNEIDER LC1D09V7
9A 400V 4Kw - coil 400V 50/60Hz
3 normally open contacts
1 normally open auxiliary contact
1 normally closed auxiliary contact
for Fry top electric (CAPIC) C15



CAPIC E050904

3454015 CONTACTOR SCHNEIDER LC1D18P7
18A 400V 7.5Kw - coil 230V 50/60Hz
3 normally open contacts
1 normally open auxiliary contact
1 normally closed auxiliary contact



CAPIC E050932

Suitable for:

Suitable for:

3454059 CONTACTOR SCHNEIDER LC1D40AV7
 40A 400V 18.5Kw - coil 400V 50/60Hz
 3 normally open contacts
 1 normally open auxiliary contact
 1 normally closed auxiliary contact
 for Fryer gas (CAPIC) 2045 - 3085



CAPIC E050869

CAPIC E050969


Drain taps and accessories

3356092 DRAIN OFF TAP DIA 3/4 F.
 TECO BLOCK safety handle
 tap body in brass CW617N UNI 12165
 chrome plated superficial finish
 Hostaform handle with metal core
 operating temperature 120°C max
 operating pressure 4 bar max



CAPIC Q451110

3356109 DRAIN TAP Ø 1" F
 fixed connection Ø 1" F - fixed handle
 for Boiling pan (CAPIC)



CAPIC

3179010 FITTINGS SEALING TAPE LOCTITE 55 - 50 m
 length 50 mt
 suitable to hot and cold drinking water, gas
 replaces pastes, hemp and sealing tapes
 it allows the repositioning of couplings
 in compliance with the latest regulations
 Drinking water (Italian certification by C.S.A.,
 according to standard KTW and WRC approved)
 gas - water IMQ-UNICIG.
 compliant with UNI EN 51-2 class Arp
 approved by DVGW and DIN 30660





Suitable for:

1180001 GREASE KLUBERSYNTH UH1 14-151 45 g

food safe grease for lubrication
of all friction points
ideal for water and steam taps
operating temperature -45°/+120°
beige color - NSF H1 certified
hot and cold water resistant
high anti-corrosion power
can replace vaseline



3180039 VASELINE WUERTH 750 g

for lubrication of food processing machines
it protects chromed and rubber parts from
weather factors, moisture resistant,
operating temperature from -10°C up to +120°C
from +50°C to +120 °C the grease becomes oily



3356112 DRAIN TAP ø 1"1/2F
fixed connection ø 1"1/2"F - fixed handle
for Boiling pan (CAPIC)



CAPIC

CAPIC



Suitable for:

3180061 TAPE F. COUPLING SEALING LOCTITE 55-150m

length 150 metri
suitable for hot / cold drinking water. gas
replaces pastes, hemp and sealing tapes
it allows the correct replacement of fittings
compliant with the latest regulatory requirements
Drinking water (C.S.A. italian certified.
in line with KTW standard and WRC approved)
IMQ-UNICIG gas-water,
compliant with UNI EN 51-2 class Arp
DVGW and DIN 30660 approved



3179010 FITTINGS SEALING TAPE LOCTITE 55 - 50 m

length 50 mt
suitable to hot and cold drinking water, gas
replaces pastes, hemp and sealing tapes
it allows the repositioning of couplings
in compliance with the latest regulations
Drinking water (Italian certification by C.S.A.,
according to standard KTW and WRC approved)
gas - water IMQ-UNICIG.
compliant with UNI EN 51-2 class Arp
approved by DVGW and DIN 30660





Suitable for:

1180001 GREASE KLUBERSYNTH UH1 14-151 45 g

food safe grease for lubrication
of all friction points
ideal for water and steam taps
operating temperature -45°/+120°
beige color - NSF H1 certified
hot and cold water resistant
high anti-corrosion power
can replace vaseline



3180039 VASELINE WUERTH 750 g

for lubrication of food processing machines
it protects chromed and rubber parts from
weather factors, moisture resistant,
operating temperature from -10°C up to +120°C
from +50°C to +120 °C the grease becomes oily



3356116 DRAIN TAP ø 1"1/2F

fixed connection ø 1"1/2" F - folding handle
for Boiling pan (CAPIC)
for Boiling pan (CAPIC) W071201 G0701 MDC150E/RF
for Fryer gas (CAPIC) 3085



CAPIC Q451015

CAPIC



Suitable for:

3180061 TAPE F. COUPLING SEALING LOCTITE 55-150m

length 150 metri
suitable for hot / cold drinking water. gas
replaces pastes, hemp and sealing tapes
it allows the correct replacement of fittings
compliant with the latest regulatory requirements
Drinking water (C.S.A. italian certified.
in line with KTW standard and WRC approved)
IMQ-UNICIG gas-water,
compliant with UNI EN 51-2 class Arp
DVGW and DIN 30660 approved



3179010 FITTINGS SEALING TAPE LOCTITE 55 - 50 m

length 50 mt
suitable to hot and cold drinking water, gas
replaces pastes, hemp and sealing tapes
it allows the repositioning of couplings
in compliance with the latest regulations
Drinking water (Italian certification by C.S.A.,
according to standard KTW and WRC approved)
gas - water IMQ-UNICIG.
compliant with UNI EN 51-2 class Arp
approved by DVGW and DIN 30660





Suitable for:

1180001 GREASE KLUBERSYNTH UH1 14-151 45 g

food safe grease for lubrication
of all friction points
ideal for water and steam taps
operating temperature -45°/+120°
beige color - NSF H1 certified
hot and cold water resistant
high anti-corrosion power
can replace vaseline



3180039 VASELINE WUERTH 750 g

for lubrication of food processing machines
it protects chromed and rubber parts from
weather factors, moisture resistant,
operating temperature from -10°C up to +120°C
from +50°C to +120 °C the grease becomes oily



3356007 DRAIN TAP ø 1"1/2F TECNO

TAPERED SEAL - swivel nut ø 1"1/2F
with gasket
for BOILING PAN



CAPIC Q451030

3179010 FITTINGS SEALING TAPE LOCTITE 55 - 50 m

length 50 mt
suitable to hot and cold drinking water, gas
replaces pastes, hemp and sealing tapes
it allows the repositioning of couplings
in compliance with the latest regulations
Drinking water (Italian certification by C.S.A.,
according to standard KTW and WRC approved)
gas - water IMQ-UNICIG.
compliant with UNI EN 51-2 class Arp
approved by DVGW and DIN 30660



CAPIC



Suitable for:

3180061 TAPE F. COUPLING SEALING LOCTITE 55-150m

length 150 metri
suitable for hot / cold drinking water. gas
replaces pastes, hemp and sealing tapes
it allows the correct replacement of fittings
compliant with the latest regulatory requirements
Drinking water (C.S.A. italian certified.
in line with KTW standard and WRC approved)
IMQ-UNICIG gas-water,
compliant with UNI EN 51-2 class Arp
DVGW and DIN 30660 approved



3186240 ASBESTOS FREE FLAT GASKET ø 46x38x2 m m

for drain tap ø 1"1/2



3186199 GASKET INTERNAL EPDM FOR TAPS

NSF certified
for DRAIN TAP ø 1"1/4 and 1"1/2





Suitable for:

- 1180001 GREASE KLUBERSYNTH UH1 14-151 45 g**
food safe grease for lubrication
of all friction points
ideal for water and steam taps
operating temperature $-45^{\circ}/+120^{\circ}$
beige color - NSF H1 certified
hot and cold water resistant
high anti-corrosion power
can replace vaseline



- 3356128 PIN \varnothing 5x30 mm**
complete with blind nut



- 3180039 VASELINE WUERTH 750 g**
for lubrication of food processing machines
it protects chromed and rubber parts from
weather factors, moisture resistant,
operating temperature from -10°C up to $+120^{\circ}\text{C}$
from $+50^{\circ}\text{C}$ to $+120^{\circ}\text{C}$ the grease becomes oily



CAPIC

Suitable for:

- 3242189 HANDGRIP FOR DRAIN TAP**
for DRAIN TAP \varnothing 1"1/2F e 1"1/4F



- 3180061 TAPE F. COUPLING SEALING LOCTITE 55-150m**
length 150 metri
suitable for hot / cold drinking water. gas
replaces pastes, hemp and sealing tapes
it allows the correct replacement of fittings
compliant with the latest regulatory requirements
Drinking water (C.S.A. italian certified.
in line with KTW standard and WRC approved)
IMQ-UNICIG gas-water,
compliant with UNI EN 51-2 class Arp
DVGW and DIN 30660 approved





Suitable for:

CAPIC



3356121 DRAIN TAP \varnothing 1"1/2M
 fixed connection \varnothing 1"1/2"M - fixed handle
 for Boiling pan (CAPIC)
 for Fryer (CAPIC)



CAPIC

1180001 GREASE KLUBERSYNTH UH1 14-151 45 g
 food safe grease for lubrication
 of all friction points
 ideal for water and steam taps
 operating temperature $-45^{\circ}/+120^{\circ}$
 beige color - NSF H1 certified
 hot and cold water resistant
 high anti-corrosion power
 can replace vaseline



3180039 VASELINE WUERTH 750 g
 for lubrication of food processing machines
 it protects chromed and rubber parts from
 weather factors, moisture resistant,
 operating temperature from -10°C up to $+120^{\circ}\text{C}$
 from $+50^{\circ}\text{C}$ to $+120^{\circ}\text{C}$ the grease becomes oily



Suitable for:

3179010 FITTINGS SEALING TAPE LOCTITE 55 - 50 m
 length 50 mt
 suitable to hot and cold drinking water, gas
 replaces pastes, hemp and sealing tapes
 it allows the repositioning of couplings
 in compliance with the latest regulations
 Drinking water (Italian certification by C.S.A.,
 according to standard KTW and WRC approved)
 gas - water IMQ-UNICIG.
 compliant with UNI EN 51-2 class Arp
 approved by DVGW and DIN 30660



3180061 TAPE F. COUPLING SEALING LOCTITE 55-150m
 length 150 metri
 suitable for hot / cold drinking water. gas
 replaces pastes, hemp and sealing tapes
 it allows the correct replacement of fittings
 compliant with the latest regulatory requirements
 Drinking water (C.S.A. italian certified.
 in line with KTW standard and WRC approved)
 IMQ-UNICIG gas-water,
 compliant with UNI EN 51-2 class Arp
 DVGW and DIN 30660 approved



3356110 DRAIN TAP ø 1"1/4F
fixed connection ø 1"1/4"F - fixed handle
for Boiling pan (CAPIC)



CAPIC

1180001 GREASE KLUBERSYNTH UH1 14-151 45 g
food safe grease for lubrication
of all friction points
ideal for water and steam taps
operating temperature -45°/+120°
beige color - NSF H1 certified
hot and cold water resistant
high anti-corrosion power
can replace vaseline



3180039 VASELINE WUERTH 750 g
for lubrication of food processing machines
it protects chromed and rubber parts from
weather factors, moisture resistant,
operating temperature from -10°C up to +120°C
from +50°C to +120 °C the grease becomes oily



Suitable for:

3179010 FITTINGS SEALING TAPE LOCTITE 55 - 50 m
length 50 mt
suitable to hot and cold drinking water, gas
replaces pastes, hemp and sealing tapes
it allows the repositioning of couplings
in compliance with the latest regulations
Drinking water (Italian certification by C.S.A.,
according to standard KTW and WRC approved)
gas - water IMQ-UNICIG.
compliant with UNI EN 51-2 class Arp
approved by DVGW and DIN 30660



3180061 TAPE F. COUPLING SEALING LOCTITE 55-150m
length 150 metri
suitable for hot / cold drinking water. gas
replaces pastes, hemp and sealing tapes
it allows the correct replacement of fittings
compliant with the latest regulatory requirements
Drinking water (C.S.A. italian certified.
in line with KTW standard and WRC approved)
IMQ-UNICIG gas-water,
compliant with UNI EN 51-2 class Arp
DVGW and DIN 30660 approved





Suitable for:

CAPIC



3356115 DRAIN TAP ø 1"1/4F
fixed connection ø 1"1/4"F - folding handle
for Boiling pan (CAPIC)



CAPIC Q451011

1180001 GREASE KLUBERSYNTH UH1 14-151 45 g
food safe grease for lubrication
of all friction points
ideal for water and steam taps
operating temperature -45°/+120°
beige color - NSF H1 certified
hot and cold water resistant
high anti-corrosion power
can replace vaseline



3180039 VASELINE WUERTH 750 g
for lubrication of food processing machines
it protects chromed and rubber parts from
weather factors, moisture resistant,
operating temperature from -10°C up to +120°C
from +50°C to +120 °C the grease becomes oily



Suitable for:

3179010 FITTINGS SEALING TAPE LOCTITE 55 - 50 m
length 50 mt
suitable to hot and cold drinking water, gas
replaces pastes, hemp and sealing tapes
it allows the repositioning of couplings
in compliance with the latest regulations
Drinking water (Italian certification by C.S.A.,
according to standard KTW and WRC approved)
gas - water IMQ-UNICIG.
compliant with UNI EN 51-2 class Arp
approved by DVGW and DIN 30660



3180061 TAPE F. COUPLING SEALING LOCTITE 55-150m
length 150 metri
suitable for hot / cold drinking water. gas
replaces pastes, hemp and sealing tapes
it allows the correct replacement of fittings
compliant with the latest regulatory requirements
Drinking water (C.S.A. italian certified.
in line with KTW standard and WRC approved)
IMQ-UNICIG gas-water,
compliant with UNI EN 51-2 class Arp
DVGW and DIN 30660 approved





- 3356120 DRAIN TAP \varnothing 1"1/4M**
fixed connection \varnothing 1"1/4" M - fixed handle
for Boiling pan (CAPIC)
for Fryer (CAPIC)



CAPIC

- 1180001 GREASE KLUBERSYNTH UH1 14-151 45 g**
food safe grease for lubrication
of all friction points
ideal for water and steam taps
operating temperature $-45^{\circ}/+120^{\circ}$
beige color - NSF H1 certified
hot and cold water resistant
high anti-corrosion power
can replace vaseline



- 3180039 VASELINE WUERTH 750 g**
for lubrication of food processing machines
it protects chromed and rubber parts from
weather factors, moisture resistant,
operating temperature from -10°C up to $+120^{\circ}\text{C}$
from $+50^{\circ}\text{C}$ to $+120^{\circ}\text{C}$ the grease becomes oily



Suitable for:

- 3179010 FITTINGS SEALING TAPE LOCTITE 55 - 50 m**
length 50 mt
suitable to hot and cold drinking water, gas
replaces pastes, hemp and sealing tapes
it allows the repositioning of couplings
in compliance with the latest regulations
Drinking water (Italian certification by C.S.A.,
according to standard KTW and WRC approved)
gas - water IMQ-UNICIG.
compliant with UNI EN 51-2 class Arp
approved by DVGW and DIN 30660



- 3180061 TAPE F. COUPLING SEALING LOCTITE 55-150m**
length 150 metri
suitable for hot / cold drinking water. gas
replaces pastes, hemp and sealing tapes
it allows the correct replacement of fittings
compliant with the latest regulatory requirements
Drinking water (C.S.A. italian certified.
in line with KTW standard and WRC approved)
IMQ-UNICIG gas-water,
compliant with UNI EN 51-2 class Arp
DVGW and DIN 30660 approved





Suitable for:

CAPIC



3356113 DRAIN TAP Ø 2" F
fixed connection Ø 2" F - fixed handle
for Boiling pan (CAPIC)



CAPIC

1180001 GREASE KLUBERSYNTH UH1 14-151 45 g
food safe grease for lubrication
of all friction points
ideal for water and steam taps
operating temperature -45°/+120°
beige color - NSF H1 certified
hot and cold water resistant
high anti-corrosion power
can replace vaseline



3180039 VASELINE WUERTH 750 g
for lubrication of food processing machines
it protects chromed and rubber parts from
weather factors, moisture resistant,
operating temperature from -10°C up to +120°C
from +50°C to +120 °C the grease becomes oily



Suitable for:


3179010 FITTINGS SEALING TAPE LOCTITE 55 - 50 m
length 50 mt
suitable to hot and cold drinking water, gas
replaces pastes, hemp and sealing tapes
it allows the repositioning of couplings
in compliance with the latest regulations
Drinking water (Italian certification by C.S.A.,
according to standard KTW and WRC approved)
gas - water IMQ-UNICIG.
compliant with UNI EN 51-2 class Arp
approved by DVGW and DIN 30660



3180061 TAPE F. COUPLING SEALING LOCTITE 55-150m
length 150 metri
suitable for hot / cold drinking water. gas
replaces pastes, hemp and sealing tapes
it allows the correct replacement of fittings
compliant with the latest regulatory requirements
Drinking water (C.S.A. italian certified.
in line with KTW standard and WRC approved)
IMQ-UNICIG gas-water,
compliant with UNI EN 51-2 class Arp
DVGW and DIN 30660 approved



3356108 DRAIN TAP \varnothing 3/4" F
fixed connection \varnothing 3/4" F - fixed handle
for Boiling pan (CAPIC)



CAPIC Q451006

1180001 GREASE KLUBERSYNTH UH1 14-151 45 g
food safe grease for lubrication
of all friction points
ideal for water and steam taps
operating temperature $-45^{\circ}/+120^{\circ}$
beige color - NSF H1 certified
hot and cold water resistant
high anti-corrosion power
can replace vaseline



3180039 VASELINE WUERTH 750 g
for lubrication of food processing machines
it protects chromed and rubber parts from
weather factors, moisture resistant,
operating temperature from -10°C up to $+120^{\circ}\text{C}$
from $+50^{\circ}\text{C}$ to $+120^{\circ}\text{C}$ the grease becomes oily



3356140 DRAIN TAP \varnothing 3/4" FF
for Fryer (CAPIC)



CAPIC Q401005

Suitable for:

3179010 FITTINGS SEALING TAPE LOCTITE 55 - 50 m
length 50 mt
suitable to hot and cold drinking water, gas
replaces pastes, hemp and sealing tapes
it allows the repositioning of couplings
in compliance with the latest regulations
Drinking water (Italian certification by C.S.A.,
according to standard KTW and WRC approved)
gas - water IMQ-UNICIG.
compliant with UNI EN 51-2 class Arp
approved by DVGW and DIN 30660



3180061 TAPE F. COUPLING SEALING LOCTITE 55-150m
length 150 metri
suitable for hot / cold drinking water. gas
replaces pastes, hemp and sealing tapes
it allows the correct replacement of fittings
compliant with the latest regulatory requirements
Drinking water (C.S.A. italian certified.
in line with KTW standard and WRC approved)
IMQ-UNICIG gas-water,
compliant with UNI EN 51-2 class Arp
DVGW and DIN 30660 approved





Suitable for:

CAPIC



3526673 GAS/WATER VALVE \varnothing 1"FF
 ball valve
 heavy series with PN 40 total passage
 aluminium lever
 for Fryer gas (CAPIC) CTI - CTIB - TI - TIB



CAPIC Q401016


5023594 CAST IRON FITTING \varnothing 1"MF



3356138 DRAIN TAP FITTING \varnothing 1"MM
 \varnothing side outlet 28 mm - bracket 68x40x19 mm
 fitting height 100 mm




3242049 DRAIN TAP HANDLE 140 mm
 square hole 6x6 mm



5036175 DRAIN TAP MANIFOLD
 2 top connections \varnothing 1"MM - 2 top connections \varnothing 33
 1 bottom connection \varnothing 1"MM
 width 295 mm - overall length 114 mm
 distance between holes 275 mm



3356078 BUSHING \varnothing 11x20 mm



5031496 DRAIN PIPE \varnothing 1"MM
 length 195 mm




5028002 DRAIN TAP FITTING \varnothing 1"MM
 side exit \varnothing 30 mm - bracket 80x30 mm
 distance between holes 60 mm - coupling height 100



3242280 DRAIN TAP KNOB BLACK 79 mm
 square hole 6x6 mm



5033656 FITTING OF BRASS \varnothing 1"MF





Suitable for:

7100207 HEADLESS SCREW HEXAGONAL M5x8
stainless steel - conical top
UNI 5927 - DIN 914 - ISO 4027




CAPIC



Suitable for:

5011612 LEVER DRAIN TAP 250 mm
square pin 6x6 mm



3359328 3 WAY TAP \varnothing 1/2"FF
nickel plated brass - 90° perforation
operating pressure 20 bar
with 1/2" reduction piece
for Bratt pan (CAPIC)



CAPIC Q402506

3359327 3 WAY TAP \varnothing 3/8"FF
nickel plated brass - 90° perforation
operating pressure 20 bar
with 1/2" reduction piece
for Bratt pan (CAPIC)



CAPIC Q402505

Electric hot plates

3311089 ELECTRIC HOT PLATE \varnothing 300 mm 3500W 230V
screw electric connections
with STAINLESS steel edge
for electric cooking top



CAPIC E154020

3311078 ELECTRIC HOT PLATE \varnothing 300 mm 3500W 400V
terminal block electric connections
with STAINLESS steel edge
for electric cooking top




CAPIC E154021

3311174 ELECTRIC HOT PLATE 3000W 400V
dimensions 300x300 mm
terminal block electric connections
for electric cooking top



CAPIC E154016

3311075 ELECTRIC HOT PLATE 4000W 400V
dimensions 300x300 mm
tilting plate
terminal block electric connections
for electric cooking top



CAPIC E154011



Suitable for:

CAPIC



Suitable for:

Electrical capacitors

3068027 CAPACITOR DUCATI ENERGIA 20µF
450V 50/60Hz
operating temperature -25 +85°C
lead connector 6.35x0.8 mm
ø 40xh70 mm



CAPIC L452027

3068008 CAPACITOR DUCATI ENERGIA 5µF
450V 50/60Hz
operating temperature -25 +85°C
lead connection 6.35x0.8 mm
ø 28xh55 mm



CAPIC L452005

3068084 CAPACITOR ELECTRICAL 20µF
450V 50/60Hz - ø 40xh71 mm



CAPIC L452027

3068096 CAPACITOR ELECTRICAL 5µF
450V 50/60Hz - ø 30xh51 mm



CAPIC L452005

Electrical gas valves and accessories

3526077 ELBOW FLANGE ø 1/2" F
with screws and OR
for valves SIT 820-Honeywell V4400-V4600-VR4605P



CAPIC G652031

3526078 ELBOW FLANGE ø 3/4" F
with screws and OR
for valves SIT 820-Honeywell V4400-V4600-VR4605P



CAPIC G653032

3526075 FLANGE STRAIGHT ø 1/2"
with screws and OR
for valves SIT 820-Honeywell V4400-V4600-VR4605P



CAPIC G653033

3526124 KNOB EXTENSION LENGTH 67 mm
for VALVE 820 NOVA-824 NOVASIT



CAPIC G653037

3526085 VALVE 810 ELETTROSIT \varnothing 3/4"FF
 inlet \varnothing 3/4"F - outlet \varnothing 3/4"F
 thermocouple connection M9x1
 maximum gas inlet pressure 50 mbar
 pressure adjustment range
 3÷18 mbar
 ambient temperature 0÷60°C
 power supply 230V 50Hz
 pilot connection and LATERAL thermocouple



CAPIC G652401

3526108 ELBOW FLANGE \varnothing 1/2"
 with screws and OR
 for ELETTROSIT VALVE



3526106 FLANGE STRAIGHT \varnothing 1/2"
 with screws and OR
 for ELETTROSIT VALVE



3526107 FLANGE STRAIGHT \varnothing 3/4"
 with screws and OR
 for ELETTROSIT VALVE



3001008 PIEZO IGNITER
 a \varnothing 14 mm hole is required for the assembly
 faston M \varnothing 2.4 mm



3526096 VALVE MICROSWITCH
 maximum load 0.2 A
 for VALVE ELETTROSIT-820 NOVA-824 NOVASIT





Suitable for:

CAPIC



3526090 VALVE 810 Elettrosit \varnothing 3/4"FF
 inlet \varnothing 3/4" F - outlet \varnothing 3/4" F
 thermocouple connection M9x1
 maximum gas inlet pressure 50 mbar
 pressure adjustment range
 3 ÷ 18 mbar
 ambient temperature 0 ÷ 60°C
 power supply 230V 50Hz
 long buttons
 pilot connection and LATERAL thermocouple



CAPIC G652405

3526100 COIL 220V
 for VALVE Elettrosit



3526137 BUTTON FOR Elettrosit VALVE 46 mm



3526093 EXTENSION FOR Elettrosit BUTTON 34 mm
 for switching on/off buttons



3526108 ELBOW FLANGE \varnothing 1/2" F
 with screws and OR
 for Elettrosit VALVE



3526106 FLANGE STRAIGHT \varnothing 1/2" F
 with screws and OR
 for Elettrosit VALVE



3526107 FLANGE STRAIGHT \varnothing 3/4" F
 with screws and OR
 for Elettrosit VALVE



3001008 PIEZO IGNITER
 a \varnothing 14 mm hole is required for the assembly
 faston M \varnothing 2.4 mm



3526136 SPRING FOR PUSH-BUTTON



3526096 VALVE MICROSWITCH
 maximum load 0.2 A
 for VALVE Elettrosit-820 NOVA-824 NOVASIT



3526079 VALVE 820 NOVA \varnothing 1/2"FF
 inlet \varnothing 1/2" F - outlet \varnothing 1/2" F
 thermocouple fitting M9x1
 maximum gas inlet pressure 60 mbar
 outlet pressure setting range
 3÷30 mbar
 room temperature 0÷70°C
 power supply 230V 50Hz
 for Fryer gas (CAPIC)



CAPIC G653030

3526098 COIL 220V
 for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA



3526099 COIL 24V
 for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA



3526078 ELBOW FLANGE \varnothing 3/4" F
 with screws and OR
 for valves SIT 820-Honeywell V4400-V4600-VR4605P



CAPIC G653032

5047586 EXTENSION FOR VALVE 820 NOVA
 D-shaped pin \varnothing 10x8 mm



Suitable for:
3526270 VALVE 820 NOVA EXTENSION
 D shaft \varnothing 10x8 mm



2100054 COIL 220V 60Hz
 for VALVE 820 NOVA-822 NOVA-828 NOVA



3526077 ELBOW FLANGE \varnothing 1/2" F
 with screws and OR
 for valves SIT 820-Honeywell V4400-V4600-VR4605P



CAPIC G652031

3526102 ELECTRIC COUPLING WITH CABLE
 cable length 1000 mm - 3 wires
 for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA




3241141 EXTENSION FOR 820 NOVA VALVE
 D-shaped pin 10x8 mm





Suitable for:

3020083 FITTING AND OLIVE \varnothing 4 mm



3526075 FLANGE STRAIGHT \varnothing 1/2"
with screws and OR
for valves SIT 820-Honeywell V4400-V4600-VR4605P




CAPIC G653033

3526124 KNOB EXTENSION LENGTH 67 mm
for VALVE 820 NOVA-824 NOVASIT



CAPIC G653037

3182008 MAGNETIC UNIT SIT
head \varnothing 35 mm - end piece \varnothing 20 mm - length 47 mm
for valve SIT NOVASIT 820



3526103 PROTECTING COVER
for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA




5012595 VALVE EXTENSION 820 NOVA
D-shaped pin \varnothing 6x4.6 mm



CAPIC

Suitable for:

3020084 FITTING AND OLIVE \varnothing 6 mm



3526076 FLANGE STRAIGHT \varnothing 3/4"
with screws and OR
for valves SIT 820-Honeywell V4400-V4600-VR4605P




3241142 KNOB GASKET \varnothing 44 mm



3001008 PIEZO IGNITER
a \varnothing 14 mm hole is required for the assembly
faston M \varnothing 2.4 mm



5017951 PROTECTION RUBBER VALVE 820-824 NOVA
 \varnothing external 50 mm - \varnothing internal 20 mm
depth 1 mm



3526096 VALVE MICROSWITCH
maximum load 0.2 A
for VALVE ELETTROSIT-820 NOVA-824 NOVASIT





Suitable for:

3526269 VALVE 820 NOVA EXTENSION
D shaft \varnothing 10x8 mm



CAPIC



Suitable for:

3526176 VALVE 820 NOVA \varnothing 1/2"FF
inlet \varnothing 1/2"F - outlet \varnothing 1/2"F
thermocouple connection M9x1
maximum gas inlet pressure 60 mbar
outlet pressure adjustment range
3÷30 mbar
ambient temperature 0÷70°C
power supply 230V 50Hz
for Bratt pan (CAPIC) W086048



CAPIC G653028

2100054 COIL 220V 60Hz
for VALVE 820 NOVA-822 NOVA-828 NOVA



3526077 ELBOW FLANGE \varnothing 1/2"F
with screws and OR
for valves SIT 820-Honeywell V4400-V4600-VR4605P



CAPIC G652031

3526102 ELECTRIC COUPLING WITH CABLE
cable length 1000 mm - 3 wires
for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA



3526098 COIL 220V
for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA



3526099 COIL 24V
for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA



3526078 ELBOW FLANGE \varnothing 3/4"F
with screws and OR
for valves SIT 820-Honeywell V4400-V4600-VR4605P



CAPIC G653032


5047586 EXTENSION FOR VALVE 820 NOVA
D-shaped pin \varnothing 10x8 mm





Suitable for:

3020083 FITTING AND OLIVE \varnothing 4 mm



3526075 FLANGE STRAIGHT \varnothing 1/2"
with screws and OR
for valves SIT 820-Honeywell V4400-V4600-VR4605P



CAPIC G653033

3526124 KNOB EXTENSION LENGTH 67 mm
for VALVE 820 NOVA-824 NOVASIT



CAPIC G653037

3348041 OLIVE FOR PIPE \varnothing 16 mm
for model PEL 23



3001008 PIEZO IGNITER
a \varnothing 14 mm hole is required for the assembly
faston M \varnothing 2.4 mm




3020077 PIPE FITTING \varnothing 4 mm
thread M10x1



CAPIC

Suitable for:


3020084 FITTING AND OLIVE \varnothing 6 mm



3526076 FLANGE STRAIGHT \varnothing 3/4"
with screws and OR
for valves SIT 820-Honeywell V4400-V4600-VR4605P



3182008 MAGNETIC UNIT SIT
head \varnothing 35 mm - end piece \varnothing 20 mm - length 47 mm
for valve SIT NOVASIT 820



3348036 OLIVE FOR PIPE \varnothing 4 mm
for model PEL 21-22-24-25



3348034 PIPE FITTING \varnothing 16 mm
thread M24x1.5
for model PEL 23




3526103 PROTECTING COVER
for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA





Suitable for:

5053766 PROTECTION RUBBER VALVE 820 NOVA
ø external 46 mm - ø internal 20 mm
depth 5,5 mm



3526096 VALVE MICROSWITCH
maximum load 0.2 A
for VALVE ELETTROSIT-820 NOVA-824 NOVASIT



CAPIC



Suitable for:

5012595 VALVE EXTENSION 820 NOVA
D-shaped pin ø 6x4.6 mm



3526175 VALVE 822 NOVA 230V 50Hz
inlet ø 1/2"F - outlet ø 1/2"F
gas inlet max. pressure 60 mbar
outlet pressure range
3÷30 mbar
room temperature 0÷60°C
power supply 230V 50Hz



CAPIC G653026

2100054 COIL 220V 60Hz
for VALVE 820 NOVA-822 NOVA-828 NOVA



3526098 COIL 220V
for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA



3526099 COIL 24V
for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA



3526077 ELBOW FLANGE ø 1/2"F
with screws and OR
for valves SIT 820-Honeywell V4400-V4600-VR4605P



CAPIC G652031

3526078 ELBOW FLANGE ø 3/4"F
with screws and OR
for valves SIT 820-Honeywell V4400-V4600-VR4605P



CAPIC G653032



Suitable for:

3526102 ELECTRIC COUPLING WITH CABLE
cable length 1000 mm - 3 wires
for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA



CAPIC




Suitable for:

3020083 FITTING AND OLIVE \varnothing 4 mm



3020084 FITTING AND OLIVE \varnothing 6 mm



3526075 FLANGE STRAIGHT \varnothing 1/2"
with screws and OR
for valves SIT 820-Honeywell V4400-V4600-VR4605P



3526076 FLANGE STRAIGHT \varnothing 3/4"
with screws and OR
for valves SIT 820-Honeywell V4400-V4600-VR4605P



CAPIC G653033

2110316 MAGNETIC COIL
220/240V 50Hz
for VALVE 822 NOVA-824 NOVA-826 NOVA
for VALVE 827 NOVA-828 NOVAMIX




3526103 PROTECTING COVER
for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA



Electronic boards

3445382 ELECTRONIC PCB DISPLAY 142x45 mm
for Fryer electric (CAPIC) AM10 - AM20
for Bratt pan electric (CAPIC) W295125



CAPIC E050539

3390359 PC BOARD LEVEL 90x70 mm
for Boiling pan electric (CAPIC) W294111




CAPIC E054059




Energy regulators

3350024 ENERGY REGULATOR
 contact capacity 240V 13A
 max temperature 125°C
 D-shaped pin \varnothing 6x4.6 mm
 double rotation direction
 for Bratt pan (CAPIC) W295125



CAPIC E402540

3350031 ENERGY REGULATOR
 contact capacity 400V 7A
 max temperature 125°C
 D-shaped pin \varnothing 6x4.6 mm
 for Boiling pan electric (CAPIC) W294111




CAPIC E402545

3350065 ENERGY REGULATOR
 contact capacity 230V 12A
 D-shaped pin \varnothing 6x4.6 mm




CAPIC E402516

3350066 ENERGY REGULATOR
 contact capacity 400V 7A
 D-shaped pin \varnothing 6x4.6 mm



CAPIC E402520

3350067 ENERGY REGULATOR
 contact capacity 24V 16A
 D-shaped pin \varnothing 6x4.6 mm



CAPIC E402504

Feet

3313074 ADJUSTABLE PLASTIC FOOT \varnothing 18 mm
 for tubular 30x30 mm
 adjustable height 24÷56 mm
 max capacity 90 Kg



CAPIC Q053000

3313075 ADJUSTABLE PLASTIC FOOT \varnothing 26,5 mm
 for tubular 35x35 mm
 adjustable height 34÷68 mm
 max capacity 90 Kg



CAPIC Q053036



Suitable for:

CAPIC



Suitable for:

Fryer baskets and accessories

3055595 FRYER BASKET 315x120x190 mm
made of chrome-plated iron
for Fryer electric (CAPIC) 612
for Fryer (CAPIC) W051041



CAPIC A401022

3055594 FRYER BASKET 315x245x190 mm
with removable hooks
made of chrome-plated iron
for Fryer (CAPIC) C10AM
for Fryer electric (CAPIC) 612 - 815
for Fryer (CAPIC) W051041



CAPIC A401019

3055596 FRYER BASKET 320x160x140 mm
made of chrome-plated iron
for Fryer (CAPIC) TURBO



CAPIC A401023

3055550 FRYER BASKET 545x370x200 mm
made of chrome-plated iron
for Fryer gas (CAPIC) 2045 - 3085



CAPIC A401030

Gas hoses

3449229 COPPER TUBE 1x6 mm - 25 mt



CAPIC B400106

3020078 PIPE FITTING \varnothing 6 mm
thread M10x1



CAPIC G701010

3348037 OLIVE FOR PIPE \varnothing 6 mm
for model PEL 21-22-24-25



3449629 COPPER TUBE 1x6 mm - 5 mt



CAPIC B400106

CAPIC B400106_5MT

3348037 OLIVE FOR PIPE \varnothing 6 mm
for model PEL 21-22-24-25





Suitable for:

3020078 PIPE FITTING \varnothing 6 mm
thread M10x1



CAPIC G701010


CAPIC



Suitable for:

Gas taps and accessories

3348138 GAS TAP STN3R
with pilot flame
flange pipe connection \varnothing 20 mm
outlet fitting \varnothing 3/8" F
thermocouple connection M9x1
pin length 21 mm
D-shaped pin \varnothing 10x8 mm



CAPIC G304010


3348037 OLIVE FOR PIPE \varnothing 6 mm
for model PEL 21-22-24-25



5014757 PIPE FITTING \varnothing 6 mm
thread M10x1 mm




3182019 MAGNETIC UNIT
head \varnothing 19 mm - end piece \varnothing 18 mm - length 50 mm
for gas tap



CAPIC

3020078 PIPE FITTING \varnothing 6 mm
thread M10x1



CAPIC G701010




Suitable for:

CAPIC



3348144 GAS TAP 22N/O
 complete with connections and olives
 with pilot flame
 horizontal flange
 clamp connection for pipe \varnothing 21 mm
 fittings M20x1.5 mm
 with flow regulator
 pin length 38 mm
 D-shaped pin \varnothing 8x6.5 mm



CAPIC G303075


3348229 CAP WITH PIN \varnothing 10 mm
 pin length 31 mm
 for model PEL 22S/O



3348019 CAP WITH PIN \varnothing 10x9 mm
 pin length 26 mm
 for model PEL 22



3348213 FLANGE \varnothing 12/10 mm
 without adjustment
 thread M20x1.5 mm
 for model PEL 22S



3348189 FLANGE COMPLETE FOR PEL22
 holes mounting distance 34 mm - pipe \varnothing 21 mm



Suitable for:

3241746 BLACK KNOB \varnothing 53 mm
 with yellow pointer
 round hole \varnothing 10 mm
 for GAS VALVE



CAPIC K102060

CAPIC Q104071

3348017 CAP WITH PIN \varnothing 10x8 mm
 pin length 26 mm
 for model PEL 22



3348231 CAP WITH PIN \varnothing 6x4.6 mm
 pin length 35/21 mm upper/lower
 for model PEL 22



3348188 FLANGE COMPLETE FOR PEL22
 holes mounting distance 40 mm - pipe \varnothing 27 mm



3348023 FLANGE HORIZONTAL \varnothing 12/10 mm
 thread M20x1.5
 for model PEL 22






Suitable for:

3348025 FLANGE HORIZONTAL CONICAL \varnothing 12/10 mm
thread M20x1.5
for model PEL 22



3348214 FLANGIA WITH PRESSURE FITTING \varnothing 12/10 mm
thread M20x1.5 mm
for model PEL 22S



3348058 MAGNET PROTECTION NUT M8x1
thread M18x1 mm
for model PEL 20-21-22



3182009 MAGNETIC UNIT PEL BIG HEAD
head \varnothing 15.5 mm - end piece \varnothing 14 mm - length 44 mm
for PEL tap model 22-24



CAPIC G402060


3348038 OLIVE FOR PIPE \varnothing 10 mm
for model PEL 22-24-25



CAPIC

Suitable for:

3348024 FLANGE VERTICAL \varnothing 12/10 mm
thread M20x1.5
for model PEL 22



3786376 GASKET MODEL FKM
for gas tap
external \varnothing 17 mm /internal \varnothing 12 mm



CAPIC G402505

3348059 MAGNET PROTECTION NUT M9x1
thread M18x1mm
for model PEL 20-21-22



3182021 MAGNETIC UNIT PEL LARGE HEAD
head \varnothing 15.5 mm - end piece \varnothing 14 mm - length 44 mm



3020082 OLIVE FOR PIPE \varnothing 12 mm
for model PEL 22-24-25



CAPIC G701026





Suitable for:

3348036 OLIVE FOR PIPE \varnothing 4 mm
for model PEL 21-22-24-25



3348230 PIN FOT GAS TAP \varnothing 6x4.6 mm
pin length 45/20 mm rh/lh
for model PEL 22



3348032 PIPE FITTING \varnothing 12 mm
thread M20x1.5 mm
for model PEL 22-24-25




3020078 PIPE FITTING \varnothing 6 mm
thread M10x1



CAPIC G701010

3348145 GAS TAP 22S/O
complete with connections and olives
with pilot flame
horizontal flange
clamp connection for pipe \varnothing 21 mm
fittings M20x1.5 mm
with flow regulator
thermocouple connection M8x1
pin length 38 mm
D-shaped pin \varnothing 8x6.5 mm
for Bratt pan (CAPIC) W086048



CAPIC G304040

CAPIC




Suitable for:

3348037 OLIVE FOR PIPE \varnothing 6 mm
for model PEL 21-22-24-25



3348031 PIPE FITTING \varnothing 10 mm
thread M20x1.5 mm
for model PEL 22-24-25



3348029 PIPE FITTING \varnothing 4 mm
thread M10x1 mm
for model PEL 21-22-24-25



5014757 PIPE FITTING \varnothing 6 mm
thread M10x1 mm



3348229 CAP WITH PIN \varnothing 10 mm
pin length 31 mm
for model PEL 22S/O






Suitable for:


3348017 CAP WITH PIN \varnothing 10x8 mm
pin length 26 mm
for model PEL 22



3348019 CAP WITH PIN \varnothing 10x9 mm
pin length 26 mm
for model PEL 22



3348232 CAP WITH PIN \varnothing 8x6.5 mm
pin length 39/7 mm upper/lower
for model PEL 22




3348188 FLANGE COMPLETE FOR PEL22
holes mounting distance 40 mm - pipe \varnothing 27 mm



3348023 FLANGE HORIZONTAL \varnothing 12/10 mm
thread M20x1.5
for model PEL 22



3348024 FLANGE VERTICAL \varnothing 12/10 mm
thread M20x1.5
for model PEL 22



CAPIC

Suitable for:

3348245 CAP WITH PIN \varnothing 10x8 mm
pin length 34/26 mm upper/lower
for model PEL 22S



3348231 CAP WITH PIN \varnothing 6x4.6 mm
pin length 35/21 mm upper/lower
for model PEL 22



3348213 FLANGE \varnothing 12/10 mm
without adjustment
thread M20x1.5 mm
for model PEL 22S




3348189 FLANGE COMPLETE FOR PEL22
holes mounting distance 34 mm - pipe \varnothing 21 mm



3348025 FLANGE HORIZONTAL CONICAL \varnothing 12/10 mm
thread M20x1.5
for model PEL 22



3348214 FLANGIA WITH PRESSURE FITTING \varnothing 12/10 mm
thread M20x1.5 mm
for model PEL 22S





Suitable for:

3348058 **MAGNET PROTECTION NUT M8x1**
thread M18x1 mm
for model PEL 20-21-22



3182009 **MAGNETIC UNIT PEL BIG HEAD**
head \varnothing 15.5 mm - end piece \varnothing 14 mm - length 44 mm
for PEL tap model 22-24



CAPIC G402060

3348038 **OLIVE FOR PIPE \varnothing 10 mm**
for model PEL 22-24-25



3348036 **OLIVE FOR PIPE \varnothing 4 mm**
for model PEL 21-22-24-25



3348230 **PIN FOT GAS TAP \varnothing 6x4.6 mm**
pin length 45/20 mm rh/lh
for model PEL 22



3348032 **PIPE FITTING \varnothing 12 mm**
thread M20x1.5 mm
for model PEL 22-24-25



CAPIC

Suitable for:

3348059 **MAGNET PROTECTION NUT M9x1**
thread M18x1mm
for model PEL 20-21-22



3182021 **MAGNETIC UNIT PEL LARGE HEAD**
head \varnothing 15.5 mm - end piece \varnothing 14 mm - length 44 mm



3020082 **OLIVE FOR PIPE \varnothing 12 mm**
for model PEL 22-24-25




CAPIC G701026

3348037 **OLIVE FOR PIPE \varnothing 6 mm**
for model PEL 21-22-24-25



3348031 **PIPE FITTING \varnothing 10 mm**
thread M20x1.5 mm
for model PEL 22-24-25



3348029 **PIPE FITTING \varnothing 4 mm**
thread M10x1 mm
for model PEL 21-22-24-25






Suitable for:

**3020078 PIPE FITTING \varnothing 6 mm
thread M10x1**



CAPIC G701010

3348146 GAS TAP 22S/O
complete with connections and olives
with pilot flame
horizontal flange
clamp connection for pipe \varnothing 27 mm
outlet fittings M20x1.5 mm
with flow regulator
thermocouple connection M8x1
pin length 38 mm
D-shaped pin \varnothing 8x6.5 mm




CAPIC G304045

3348017 CAP WITH PIN \varnothing 10x8 mm
pin length 26 mm
for model PEL 22



3348019 CAP WITH PIN \varnothing 10x9 mm
pin length 26 mm
for model PEL 22



3348232 CAP WITH PIN \varnothing 8x6.5 mm
pin length 39/7 mm upper/lower
for model PEL 22



CAPIC

Suitable for:

**5014757 PIPE FITTING \varnothing 6 mm
thread M10x1 mm**



3348229 CAP WITH PIN \varnothing 10 mm
pin length 31 mm
for model PEL 22S/O




3348245 CAP WITH PIN \varnothing 10x8 mm
pin length 34/26 mm upper/lower
for model PEL 22S



3348231 CAP WITH PIN \varnothing 6x4.6 mm
pin length 35/21 mm upper/lower
for model PEL 22



3348213 FLANGE \varnothing 12/10 mm
without adjustment
thread M20x1.5 mm
for model PEL 22S





Suitable for:


3348188 FLANGE COMPLETE FOR PEL22
holes mounting distance 40 mm - pipe \varnothing 27 mm



3348023 FLANGE HORIZONTAL \varnothing 12/10 mm
thread M20x1.5
for model PEL 22



3348024 FLANGE VERTICAL \varnothing 12/10 mm
thread M20x1.5
for model PEL 22



3348058 MAGNET PROTECTION NUT M8x1
thread M18x1 mm
for model PEL 20-21-22



3182009 MAGNETIC UNIT PEL BIG HEAD
head \varnothing 15.5 mm - end piece \varnothing 14 mm - length 44 mm
for PEL tap model 22-24



CAPIC G402060

3348038 OLIVE FOR PIPE \varnothing 10 mm
for model PEL 22-24-25



CAPIC



Suitable for:

3348189 FLANGE COMPLETE FOR PEL22
holes mounting distance 34 mm - pipe \varnothing 21 mm



3348025 FLANGE HORIZONTAL CONICAL \varnothing 12/10 mm
thread M20x1.5
for model PEL 22



3348214 FLANGIA WITH PRESSURE FITTING \varnothing 12/10 mm
thread M20x1.5 mm
for model PEL 22S



3348059 MAGNET PROTECTION NUT M9x1
thread M18x1mm
for model PEL 20-21-22



3182021 MAGNETIC UNIT PEL LARGE HEAD
head \varnothing 15.5 mm - end piece \varnothing 14 mm - length 44 mm



3020082 OLIVE FOR PIPE \varnothing 12 mm
for model PEL 22-24-25



CAPIC G701026



Suitable for:

3348036 OLIVE FOR PIPE \varnothing 4 mm
for model PEL 21-22-24-25



3348230 PIN FOT GAS TAP \varnothing 6x4.6 mm
pin length 45/20 mm rh/lh
for model PEL 22



3348032 PIPE FITTING \varnothing 12 mm
thread M20x1.5 mm
for model PEL 22-24-25




3020078 PIPE FITTING \varnothing 6 mm
thread M10x1



CAPIC G701010

7112268 GAS TAP 22S/V
complete with connections and olives
with pilot flame
with vertical flange
clamp connection for pipe \varnothing 21 mm
outlet fittings M20x1.5 mm
with flow regulator
thermocouple connection M9x1
pin length 38 mm
D-shaped pin \varnothing 8x6.5 mm



CAPIC G304047

CAPIC




Suitable for:

3348037 OLIVE FOR PIPE \varnothing 6 mm
for model PEL 21-22-24-25



3348031 PIPE FITTING \varnothing 10 mm
thread M20x1.5 mm
for model PEL 22-24-25



3348029 PIPE FITTING \varnothing 4 mm
thread M10x1 mm
for model PEL 21-22-24-25



5014757 PIPE FITTING \varnothing 6 mm
thread M10x1 mm



3348229 CAP WITH PIN \varnothing 10 mm
pin length 31 mm
for model PEL 22S/O






Suitable for:


3348017 CAP WITH PIN \varnothing 10x8 mm
pin length 26 mm
for model PEL 22



3348019 CAP WITH PIN \varnothing 10x9 mm
pin length 26 mm
for model PEL 22



3348232 CAP WITH PIN \varnothing 8x6.5 mm
pin length 39/7 mm upper/lower
for model PEL 22




3348188 FLANGE COMPLETE FOR PEL22
holes mounting distance 40 mm - pipe \varnothing 27 mm



3348023 FLANGE HORIZONTAL \varnothing 12/10 mm
thread M20x1.5
for model PEL 22



3348024 FLANGE VERTICAL \varnothing 12/10 mm
thread M20x1.5
for model PEL 22



CAPIC

Suitable for:

3348245 CAP WITH PIN \varnothing 10x8 mm
pin length 34/26 mm upper/lower
for model PEL 22S



3348231 CAP WITH PIN \varnothing 6x4.6 mm
pin length 35/21 mm upper/lower
for model PEL 22



3348213 FLANGE \varnothing 12/10 mm
without adjustment
thread M20x1.5 mm
for model PEL 22S




3348189 FLANGE COMPLETE FOR PEL22
holes mounting distance 34 mm - pipe \varnothing 21 mm



3348025 FLANGE HORIZONTAL CONICAL \varnothing 12/10 mm
thread M20x1.5
for model PEL 22



3348214 FLANGIA WITH PRESSURE FITTING \varnothing 12/10 mm
thread M20x1.5 mm
for model PEL 22S





Suitable for:

3348058 **MAGNET PROTECTION NUT M8x1**
thread M18x1 mm
for model PEL 20-21-22



3182009 **MAGNETIC UNIT PEL BIG HEAD**
head \varnothing 15.5 mm - end piece \varnothing 14 mm - length 44 mm
for PEL tap model 22-24



CAPIC G402060

3348038 **OLIVE FOR PIPE \varnothing 10 mm**
for model PEL 22-24-25



3348036 **OLIVE FOR PIPE \varnothing 4 mm**
for model PEL 21-22-24-25



3348230 **PIN FOT GAS TAP \varnothing 6x4.6 mm**
pin length 45/20 mm rh/lh
for model PEL 22



3348032 **PIPE FITTING \varnothing 12 mm**
thread M20x1.5 mm
for model PEL 22-24-25



CAPIC

Suitable for:

3348059 **MAGNET PROTECTION NUT M9x1**
thread M18x1mm
for model PEL 20-21-22



3182021 **MAGNETIC UNIT PEL LARGE HEAD**
head \varnothing 15.5 mm - end piece \varnothing 14 mm - length 44 mm



3020082 **OLIVE FOR PIPE \varnothing 12 mm**
for model PEL 22-24-25




CAPIC G701026

3348037 **OLIVE FOR PIPE \varnothing 6 mm**
for model PEL 21-22-24-25



3348031 **PIPE FITTING \varnothing 10 mm**
thread M20x1.5 mm
for model PEL 22-24-25



3348029 **PIPE FITTING \varnothing 4 mm**
thread M10x1 mm
for model PEL 21-22-24-25





Suitable for:

3020078 PIPE FITTING \varnothing 6 mm
thread M10x1



CAPIC G701010

CAPIC



Suitable for:

5014757 PIPE FITTING \varnothing 6 mm
thread M10x1 mm




Gas valves and accessories

3523035 KNOB MINISIT BLACK \varnothing 37 mm



CAPIC G652225

3523047 LID MINISIT



CAPIC G652202

3523092 MINISIT VALVE FOR FOOD-WARMER 40÷110°C
inlet \varnothing 1/2"F - outlet \varnothing 3/8"F
thermocouple connection M9x1
maximum gas inlet pressure 50 mbar
ambient temperature 0÷80°C
capillary length 1050 mm
bulb \varnothing 5x125 mm



CAPIC G652006

2100757 CONNECTION FOR OLIVE \varnothing 16 mm
thread \varnothing 1/2"M



3523038 ELBOW FLANGE MINISIT \varnothing 1/2"F
with screws and OR



3523037 ELBOW FLANGE MINISIT \varnothing 3/8"
with screws and OR




3523035 KNOB MINISIT BLACK \varnothing 37 mm



CAPIC G652225

3523047 LID MINISIT



CAPIC G652202




Suitable for:

3182003 MAGNETIC UNIT SIT
head \varnothing 25 mm - end piece \varnothing 17 mm - length 56 mm
for valve SIT AC2 - VR8-MINISIT



CAPIC G402010

3523060 OIL SEAL FITTING \varnothing 6.5 mm
internal thread M10x0.75 - external thread M14x1.5



CAPIC G652208

3020082 OLIVE FOR PIPE \varnothing 12 mm
for model PEL 22-24-25



CAPIC G701026

3001070 PIEZO IGNITER MINISIT
a \varnothing 22 mm hole is required for the assembly
faston M \varnothing 2.4 mm



3020079 PIPE FITTING \varnothing 12 mm
thread \varnothing 3/8" M



CAPIC

Suitable for:

3523061 NUT \varnothing 1/4"x6 mm




3348044 OLIVE FOR PIPE \varnothing 10 mm
for model PEL 20-21-24-25



3348041 OLIVE FOR PIPE \varnothing 16 mm
for model PEL 23



3001071 PIEZO IGNITER MINISIT WITH COVER
M faston 2.4 mm




3523036 REDUCTION STRAIGHT \varnothing 3/8" F - \varnothing 1/2" F
in brass with internal and external thread
internal thread \varnothing 3/8" F - external thread \varnothing 1/2" F
for MINISIT flange





Suitable for:

3523039 SENSING ELEMENT MINISIT 30÷100°C
capillary length 1050 mm
bulb ø 5x125 mm



CAPIC




Suitable for:

5058320 TUBE NUT FITTING ø 10 mm
thread M14x1,5 mm



3523093 MINISIT VALVE FOR FRYER 70÷210°C
inlet ø 1/2"F - outlet ø 3/8"F
thermocouple connection M9x1
maximum gas inlet pressure 50 mbar
ambient temperature 0÷60°C
length capillary 1300 mm
bulb ø 4x122 mm
without cover. knob and flanges



2100757 CONNECTION FOR OLIVE ø 16 mm
thread ø 1/2"M




CAPIC G652004

3523038 ELBOW FLANGE MINISIT ø 1/2"F
with screws and OR




3523037 ELBOW FLANGE MINISIT ø 3/8"
with screws and OR



3523035 KNOB MINISIT BLACK ø 37 mm



3523047 LID MINISIT



CAPIC G652225

3182003 MAGNETIC UNIT SIT
head ø 25 mm - end piece ø 17 mm - length 56 mm
for valve SIT AC2 - VR8-MINISIT



CAPIC G652202

3523061 NUT ø 1/4"x6 mm




CAPIC G402010



Suitable for:

3523060 OIL SEAL FITTING \varnothing 6.5 mm
internal thread M10x0.75 - external thread M14x1.5



CAPIC G652208

3020082 OLIVE FOR PIPE \varnothing 12 mm
for model PEL 22-24-25



CAPIC G701026


3001070 PIEZO IGNITER MINISIT
a \varnothing 22 mm hole is required for the assembly
faston M \varnothing 2.4 mm



3020079 PIPE FITTING \varnothing 12 mm
thread \varnothing 3/8" M



3523096 SENSING ELEMENT MINISIT 50÷190°C
stainless steel capillary length 1200 mm
bulb \varnothing 4x120 mm



CAPIC

Suitable for:


3348044 OLIVE FOR PIPE \varnothing 10 mm
for model PEL 20-21-24-25



3348041 OLIVE FOR PIPE \varnothing 16 mm
for model PEL 23



3001071 PIEZO IGNITER MINISIT WITH COVER
M faston 2.4 mm



3523036 REDUCTION STRAIGHT \varnothing 3/8" F - \varnothing 1/2" F
in brass with internal and external thread
internal thread \varnothing 3/8" F - external thread \varnothing 1/2" F
for MINISIT flange



5058320 TUBE NUT FITTING \varnothing 10 mm
thread M14x1,5 mm






Suitable for:

CAPIC



Suitable for:

3523060 OIL SEAL FITTING \varnothing 6.5 mm
internal thread M10x0.75 - external thread M14x1.5



CAPIC G652208

3523011 VALVE 440 D3 \varnothing 3/4"FF
inlet \varnothing 3/4"F - outlet \varnothing 3/4"F
thermocouple connection M9x1
maximum gas inlet pressure 50 mbar
room temperature 0÷80°C
with thread for ring nut under the push-button



CAPIC G652415

3020083 FITTING AND OLIVE \varnothing 4 mm



3523091 VALVE 710 MINISIT OVEN 70÷310°C
inlet \varnothing 1/2"F - outlet \varnothing 3/8"F
thermocouple connection M9x1
maximum gas inlet pressure 50 mbar
ambient temperature 0÷60°C
capillary length 1300 mm
bulb \varnothing 4x75 mm
without cover, knob and flanges
for Kitchen (CAPIC) G0441 W052540
for Oven under cooktop (CAPIC) W380461



CAPIC G652002

2100757 CONNECTION FOR OLIVE \varnothing 16 mm
thread \varnothing 1/2"M



3523038 ELBOW FLANGE MINISIT \varnothing 1/2"
with screws and OR



3523037 ELBOW FLANGE MINISIT \varnothing 3/8"
with screws and OR




3523035 KNOB MINISIT BLACK \varnothing 37 mm



CAPIC G652225

3523047 LID MINISIT



CAPIC G652202




Suitable for:

3182003 MAGNETIC UNIT SIT
head \varnothing 25 mm - end piece \varnothing 17 mm - length 56 mm
for valve SIT AC2 - VR8-MINISIT



CAPIC G402010

3523060 OIL SEAL FITTING \varnothing 6.5 mm
internal thread M10x0.75 - external thread M14x1.5



CAPIC G652208

3020082 OLIVE FOR PIPE \varnothing 12 mm
for model PEL 22-24-25



CAPIC G701026

3001070 PIEZO IGNITER MINISIT
a \varnothing 22 mm hole is required for the assembly
faston M \varnothing 2.4 mm



3020079 PIPE FITTING \varnothing 12 mm
thread \varnothing 3/8" M



CAPIC

Suitable for:

3523061 NUT \varnothing 1/4"x6 mm




3348044 OLIVE FOR PIPE \varnothing 10 mm
for model PEL 20-21-24-25



3348041 OLIVE FOR PIPE \varnothing 16 mm
for model PEL 23



3001071 PIEZO IGNITER MINISIT WITH COVER
M faston 2.4 mm



3523036 REDUCTION STRAIGHT \varnothing 3/8" F - \varnothing 1/2" F
in brass with internal and external thread
internal thread \varnothing 3/8" F - external thread \varnothing 1/2" F
for MINISIT flange





Suitable for:

5058320 TUBE NUT FITTING \varnothing 10 mm
thread M14x1,5 mm



CAPIC

Suitable for:



Gaskets and seals

5010462 GASKET FLAT ASBESTOS FREE \varnothing 24x17x2 mm



CAPIC L554215

3786376 GASKET MODEL FKM
for gas tap
external \varnothing 17 mm /internal \varnothing 12 mm



CAPIC G402505

3786608 HEATING ELEMENT GASKET
external dimensions 80x40 mm
for Fryer electric (CAPIC) AM10
for Fryer gas (CAPIC) 3085



CAPIC I101008

Grids for kitchen

3185199 PAN SUPPORT GRID 400x275 mm
for Pot stove (CAPIC)



CAPIC A251030

3185198 PAN SUPPORT GRID 500x315 mm
for Pot stove (CAPIC) - Series 900



CAPIC A251045

CAPIC A251048

Grids for oven

3185052 STAINLESS STEEL GRID GN 1/1 530x325 mm
thickness 7 mm



CAPIC A303005

3185053 STAINLESS STEEL GRID GN 2/1 650x530 mm



CAPIC A303020

Suitable for:

3185940 STAINLESS STEEL GRID 600x400 mm
thickness 7 mm



CAPIC A303015

Suitable for:

7103563 STAINLESS STEEL GRILL GN 2/1 530x650 mm



CAPIC A303020

Handles

3242945 LH-RH CATCH WITH LOCK 571 CR
straight handgrip
base length 150x23x30h mm
mounting distance 110 mm
catch height 16.5 mm



CAPIC Q105508

3242922 STRIKE FOR DOOR CATCH
fitting height 16.5 mm



CAPIC

3242583 LH-RH CATCH WITH LOCK 885 CR
straight handgrip
base length 122x28x35h mm
mounting distance 104 mm
adjustable catch mounting distance 31 mm



CAPIC

3242042 STRIKE FOR DOOR HANDLE
distance between holes 45 mm



3242579 LH-RH CATCH WITHOUT LOCK 570 CR
straight handgrip
base length 150x23x30h mm
mounting distance 110 mm
catch height 16.5 mm



CAPIC Q105505

3242922 STRIKE FOR DOOR CATCH
fitting height 16.5 mm



CAPIC

3242922 STRIKE FOR DOOR CATCH
fitting height 16.5 mm



CAPIC



Suitable for:

CAPIC



Suitable for:

Heating elements

3755830 CERAMIC HEATING ELEMENT 1000W 230V
length 240 mm - width 60 mm



CAPIC E150230

3455091 HEATING ELEMENT 1000W 230V
length 550 mm - width 110 mm
fittings M12x1 mm
for Oven under cooktop electric (CAPIC)



CAPIC E150572

3455356 HEATING ELEMENT 1000W 230V
length 530 mm - width 110 mm
flange 160x30 mm
operating ambient: dry
for Bain-marie electric (CAPIC) W338010



CAPIC E150570

7104937 HEATING ELEMENT 1000W 230V
length 445 mm - width 60 mm
height 65 mm
for Fry top electric (CAPIC)



CAPIC E150808

3455352 HEATING ELEMENT 1000W 230V
length 400 mm - width 150 mm
height 265 mm - flange 80x40 mm
with cables



CAPIC E152060

3455098 HEATING ELEMENT 1500W 230V
length 393 mm - width 75 mm
connections M10x1 mm



CAPIC E150824

3455217 HEATING ELEMENT 1500W 230V
length 450 mm - width 60 mm
height 60 mm



CAPIC E150855

3355363 HEATING ELEMENT 2000W 230V
length 200 mm - width 35 mm
for 180 mm tangential fan
for Bain-marie (CAPIC) W338071



CAPIC E254001



Suitable for:

3455095 HEATING ELEMENT 2500W 230V
length 510 mm - width 110 mm
for Bratt pan electric (CAPIC) AS48DM3



CAPIC E151125

Suitable for:

7106328 HEATING ELEMENT 2850W 230V
length 120 mm - width 490 mm
height 95 mm
for Bratt pan electric (CAPIC) W295125



CAPIC E151185

3455218 HEATING ELEMENT 3000W 230V
length 430 mm - width 320 mm
height 60 mm




CAPIC E151138

3756000 HEATING ELEMENT 3000W 230V
length 510 mm - width 115 mm
for Bratt pan electric (CAPIC) W086065



CAPIC E151175

5044510 HEATING ELEMENT 3000W 230V
length 425 mm - width 190 mm
height 30 mm
for Bratt pan electric (CAPIC) W054133



CAPIC E151135

3455096 HEATING ELEMENT 3500W 230V
length 515 mm - width 150 mm
height 36 mm



CAPIC E151455

3455245 HEATING ELEMENT 4000W 230V
length 475 mm - width 80 mm
height 280 mm - fittings M12x1 mm
for Fryer electric (CAPIC) 815



CAPIC E152008

CAPIC E152009

3455097 HEATING ELEMENT 4500W 220/380V
immersion depth 390 mm
flange external \varnothing 63 mm
with O-ring
for Boiling pan electric (CAPIC) W294111



CAPIC E153010

3186013 O-RING 06187 EPDM \varnothing 58 mm
ring thickness 5.34 mm - internal \varnothing 47.00 mm



CAPIC E153011

CAPIC L554118




Suitable for:

3455355 HEATING ELEMENT 750W 230V
length 485 mm - width 110 mm
flange 160x30 mm
for Bain-marie (CAPIC) W338011



CAPIC E150544

3455123 HEATING ELEMENT 850W 220V
length 645 mm - width 145 mm
flange 70x22 mm



CAPIC E150556

3455353 HEATING ELEMENT 9000W 230V
length 550 mm - width 75 mm
for Fryer gas (CAPIC) 2045 - 3085



CAPIC E151935

CAPIC



Suitable for:

3455208 HEATING ELEMENT 8000W 220/380V
length 355 mm - width 230 mm
height 270 mm
for Fryer electric (CAPIC) 612



CAPIC E152050


3455124 HEATING ELEMENT 850W 230V
length 645 mm - width 150 mm



CAPIC E150564

Hinges, catches and accessories

3053391 CHROME-PLATED HINGE 361
length 140 mm - mounting distance 30-35 mm
for door thickness from 37 mm, gasket included



CAPIC Q104505

Hot plates

3311057 COOKING PLATE - DISK ø 235 mm
made of cast iron
for Pot stove (CAPIC) - Series RESTO



CAPIC A254010

3311056 COOKING PLATE - DISK ø 255 mm
made of cast iron



CAPIC A254020

Suitable for:

3311067 COOKING PLATE RIBBED 330x310 mm
made of cast iron



CAPIC A251512

Suitable for:

3311069 COOKING PLATE RIBBED 550x400 mm
made of cast iron



CAPIC A251532

Hydraulic piping


3450109 RUBBER PIPE \varnothing 13x20 mm - 5 m
operating temperature $-40+100^{\circ}\text{C}$



CAPIC L155025

Incandescent lamps and neon lamps

3221041 LAMP E14 15W 230V
max temperature 300°C - \varnothing 22x50 mm



CAPIC E201060

3221259 OVEN NEON LAMP Ba9s 0.9mA 400V
dimensions \varnothing 10x28 mm



CAPIC

3221270 OVEN NEON LAMP E10 1,2mA 380/400V
dimensions \varnothing 10x28 mm



CAPIC E201007

Indicator lights

3221132 INDICATOR LIGHT GREEN 230V
head \varnothing 13.5 mm - hole \varnothing 10 mm - 120°C
universal application



CAPIC E202025

3221497 INDICATOR LIGHT GREEN 250V
head \varnothing 14 mm - hole \varnothing 12 mm
wire connection length 190 mm
nickel-plated brass case



CAPIC E202094



Suitable for:

CAPIC



Suitable for:

3221180 INDICATOR LIGHT GREEN 400V
head \varnothing 10 mm - hole \varnothing 9 mm - 120°C



CAPIC E202091

3221183 INDICATOR LIGHT GREEN 400V
head \varnothing 13.5 mm - hole \varnothing 10 mm - 120°C
universal application



CAPIC E202028

3221097 INDICATOR LIGHT NEUTRAL 220V
head \varnothing 8 mm - 120°C



CAPIC L452515

3221496 INDICATOR LIGHT ORANGE 250V
head \varnothing 14 mm - hole \varnothing 12 mm
wire connection length 190 mm
nichel plated brass case



CAPIC

3221624 INDICATOR LIGHT ORANGE 400V
head \varnothing 10 mm - hole \varnothing 9 mm
wire connection 200 mm long



CAPIC E202092

3221184 INDICATOR LIGHT ORANGE 400V
 \varnothing head 13.5 mm - hole \varnothing 10 mm - 120°C
universal application



CAPIC E202029

3221095 INDICATOR LIGHT ORANGE 230V
head \varnothing 13.5 mm - hole \varnothing 10 mm - 120°C
universal application



CAPIC E202026

3221184 INDICATOR LIGHT ORANGE 400V
 \varnothing head 13.5 mm - hole \varnothing 10 mm - 120°C
universal application



CAPIC E202029

Suitable for:

3221111 INDICATOR LIGHT RED 230V
 head \varnothing 7 mm - hole \varnothing 6 mm - 120°C
 application to the board



CAPIC L452522

3221687 LAMP CAP TAPERED CONICAL WHITE SU3



Suitable for:

3221594 LAMP CAP TAPERED CONICAL RED SU3
 mounting hole \varnothing 6 mm - head \varnothing 7 mm



Knobs

3241725 BLACK KNOB \varnothing 45 mm
 D-shaped hole 6x4.6 mm
 for energy regulator



CAPIC E402720

3241724 INDEXED PLATE \varnothing 70 mm 0-100
 for energy regulator



CAPIC E402710

3241827 BLACK KNOB \varnothing 50 mm 100-180°C
 D-shaped pin \varnothing 6x4.6 mm
 for EGO thermostat



CAPIC E401240

3241870 BEZEL RING NUT \varnothing 52 mm
 chrome plated metal Bezel
 for EGO thermostate knob



CAPIC E401313

3444126 BLACK KNOB \varnothing 50 mm 30-110°C
 D-shaped pin \varnothing 6x4.6 mm
 for EGO thermostat



CAPIC E401220

3444128 BLACK KNOB \varnothing 50 mm 50-300°C
 D-shaped pin \varnothing 6x4.6 mm
 for EGO thermostat



CAPIC E401280



Suitable for:

CAPIC



3241637 BLACK KNOB \varnothing 50 mm 60°-200°C
D-shaped hole 6x4.6 mm
for EGO thermostat



CAPIC E401260

CAPIC E401265

Suitable for:

3241746 BLACK KNOB \varnothing 53 mm
with yellow pointer
round hole \varnothing 10 mm
for GAS VALVE



CAPIC K102060

CAPIC Q104071

3241747 BLACK KNOB \varnothing 53 mm
with yellow pointer
D-shaped hole 6x4.6 mm
for selector switch-thermostat
for Bratt pan electric (CAPIC) W054135



CAPIC Q104072

3241055 FIXING CLIP
for knob with \varnothing 8 mm hole



3241724 INDEXED PLATE \varnothing 70 mm 0-100
for energy regulator



CAPIC E402710

3241735 KNOB BLACK \varnothing 34 mm 2-3-4-5-6-7-8
D-shaped hole 6x4.6 mm
for GAS VALVE GC1300



CAPIC G652221

3241734 RED KNOB \varnothing 34 mm STOP
threaded hole M4
for GAS VALVE GC1300



CAPIC G652220

Lamp receptacles and spare parts

3221172 FRAME FOR OVEN LAMP RECEPTACLE
external dimensions 96x80 mm



CAPIC E202049

3186173 GASKET FOR OVEN LAMP RECEPTACLE
external dimensions 93x79 mm



CAPIC E202048



Suitable for:

3221173 GLASS FOR OVEN LAMP RECEPTACLE
external dimensions 73x58 mm



CAPIC E202047

Suitable for:

3221233 GLASS FOR OVEN LAMP RECEPTACLE \varnothing 42 mm
thread \varnothing 33 mm - overall height 26 mm



CAPIC E202056

3621005 LAMP CAP FOR HALOGEN G9 40W 230V
external dimensions 74x59 mm
max. temperature 300°C




CAPIC E202046

3221350 LAMP RECEPTACLE WITH LAMP E14 15W 230V
lamp glass \varnothing 42 mm
mounting hole \varnothing 38 mm
max temperature 300°C



CAPIC E202055


3186522 GASKET FOR OVEN LAMP RECEPTACLE
dimensions \varnothing 40x30x2 mm




3221053 GASKET FOR OVEN LAMP RECEPTACLE
dimensions \varnothing 48x38x5 mm
for OVEN



3786614 GASKET FOR OVEN LAMP RECEPTACLE
dimensions 48x41x3 mm



3221392 GASKET KIT FOR OVEN LAMP RECEPTACLE
dimensions \varnothing 53x44x3 mm



3221233 GLASS FOR OVEN LAMP RECEPTACLE \varnothing 42 mm
thread \varnothing 33 mm - overall height 26 mm




CAPIC E202056




Suitable for:

3221041 LAMP E14 15W 230V
max temperature 300°C - ø 22x50 mm



CAPIC E201060

2101372 LAMP RECEPTACLE FOR LAMP E14 15-25W 230V
mounting hole ø 38 mm
max temperature 300°C



CAPIC



Suitable for:

3221061 LAMP E14 25W 230V
max temperature 300°C - ø 26x57 mm



D421015 OVEN LAMP DR FISCHER E14 15W 230V
ø 22x49 mm - max temperature 300°C




D421016 OVEN LAMP DR FISCHER E14 25W 230V
ø 25x57 mm - max temperature 300°C



Magnet groups

3182019 MAGNETIC UNIT
head ø 19 mm - end piece ø18 mm - length 50 mm
for gas tap



CAPIC

3182009 MAGNETIC UNIT PEL BIG HEAD
head ø 15.5 mm - end piece ø 14 mm - length 44 mm
for PEL tap model 22-24



CAPIC G402060

3182010 MAGNETIC UNIT PEL
head ø 24 mm - end piece ø 18 mm - length 59 mm
thermocouple coupling M10x1
for PEL tap model 23



CAPIC G402065

3182003 MAGNETIC UNIT SIT
head ø 25 mm - end piece ø 17 mm - length 56 mm
for valve SIT AC2 - VR8-MINISIT



CAPIC G402010



Microswitches, magnetic

3240955 **MAGNET FOR MICROSWITCH**
 ø extern 14 mm - ø intern 4,5 mm
 thickness 6 mm



CAPIC E054077

9100050 **MAGNETIC MICROSWITCH PSA60010**
 2A 240Vac - contact NO - head 52x16x7 mm
 with cable length 350 mm



CAPIC E054006

3240953 **MICROSWITCH MAGNETIC**
 head 23x6x14 mm - with cable length 1000 mm
 for OVEN 150N-220N-240N-350N-AC150-AC220
 for Bratt pan electric (CAPIC) W295125



CAPIC E054075

3240955 **MAGNET FOR MICROSWITCH**
 ø extern 14 mm - ø intern 4,5 mm
 thickness 6 mm



CAPIC E054077

Microswitches, mechanical

5047579 **MICROSWITCH CROUZET 83169.0**
 8A 250V - testa 31x24x10 mm
 with cable length 1500 mm



CAPIC E054078

3240407 **MICROSWITCH KIT 16A 250V**
 2 locking positions
 the kit includes 5 levers:
 lever 75 mm - lever 27 mm - lever 15 mm
 lever 15 mm with wheel - lever 27 mm with wheel
 for Fryer (CAPIC) W052041 C20



CAPIC E053005

3240568 **MICROSWITCH CROUZET EF83161.3**
 1NO+NC 16A 250V
 complete with roll lever 28 mm





Suitable for:

CAPIC



Suitable for:

Nozzles

3500179 CONICAL GAS JET M17x1 \varnothing 0.85 mm



CAPIC G206503

3500180 CONICAL GAS JET M17x1 \varnothing 0.90 mm



CAPIC G206505

3500182 CONICAL GAS JET M17x1 \varnothing 1.00 mm



CAPIC G206504

3500183 CONICAL GAS JET M17x1 \varnothing 1.10 mm



CAPIC G206508

3500187 CONICAL GAS JET M17x1 \varnothing 1.40 mm



CAPIC G206520

3500188 CONICAL GAS JET M17x1 \varnothing 1.50 mm



CAPIC G206524

3500189 CONICAL GAS JET M17x1 \varnothing 1.60 mm



CAPIC G206526

3500190 CONICAL GAS JET M17x1 \varnothing 1.70 mm



CAPIC G206528

**3500191 CONICAL GAS JET M17x1 \varnothing 1.80 mm
for Kitchen gas (CAPIC) W050240**



CAPIC G206532

3500192 CONICAL GAS JET M17x1 \varnothing 1.90 mm



CAPIC G206534

3500194 CONICAL GAS JET M17x1 \varnothing 2.10 mm



CAPIC G206538

3500198 CONICAL GAS JET M17x1 \varnothing 2.50 mm



CAPIC G206546

Suitable for:

Suitable for:

3500201 CONICAL GAS JET M17x1 \varnothing 2.80 mm

3500203 CONICAL GAS JET M17x1 \varnothing 3.00 mm



CAPIC G206552

CAPIC G206554

3500206 CONICAL GAS JET M17x1 \varnothing 3.30 mm

3500184 GAS JET CONICAL M17x1 \varnothing 1.15 mm



CAPIC G206558

CAPIC G206510

3500185 GAS JET CONICAL M17x1 \varnothing 1.20 mm

3500186 GAS JET CONICAL M17x1 \varnothing 1.30 mm



CAPIC G206512

CAPIC G206516

3500193 GAS JET CONICAL M17x1 \varnothing 2.00 mm

3500195 GAS JET CONICAL M17x1 \varnothing 2.20 mm



CAPIC G206536

CAPIC G206540

3500196 GAS JET CONICAL M17x1 \varnothing 2.30 mm

3500340 GAS JET M5x1 \varnothing 0.20 mm



CAPIC G206542

CAPIC G206947

3500341 GAS JET M5x1 \varnothing 0.35 mm



CAPIC G206946



Suitable for:

CAPIC



Suitable for:

O-Ring and ORM gaskets

3243009 O-RING 0106 EPDM
ring thickness 1.78 mm - internal \varnothing 6.75 mm



CAPIC L554127

1186422 O-RING 0108 EPDM
ring thickness 1.78 mm - internal \varnothing 8.73 mm



CAPIC L055030

1186626 O-RING 0114 EPDM
ring thickness 1.78 mm - internal \varnothing 11.11 mm



CAPIC L554145

CAPIC L554152

3186606 O-RING 0144 EPDM
ring thickness 3.53 mm - internal \varnothing 39.69 mm



CAPIC L554150

3160615 O-RING 0201 EPDM
ring thickness 5.34 mm - internal \varnothing 120.70 mm



CAPIC L554165

1186612 O-RING 02025 VITON
ring thickness 1.78 mm - internal \varnothing 6.07 mm



CAPIC L554126

1186237 O-RING 03300 EPDM
ring thickness 2.62 mm - internal \varnothing 75.87 mm



CAPIC L351412

1186655 O-RING 04131 EPDM
ring thickness 3.53 mm - internal \varnothing 32.93 mm



CAPIC L554162

3186580 O-RING 04131 VITON
ring thickness 3.53 mm - internal \varnothing 32.93 mm



CAPIC L554131

5022973 O-RING 04275 EPDM
ring thickness 3.53 mm - internal \varnothing 69.44 mm



CAPIC L554136



Suitable for:

3186271 O-RING 04312 EPDM
ring thickness 3.53 mm - internal \varnothing 78.97 mm



CAPIC L351410

Suitable for:

5026454 O-RING 06162 EPDM
ring thickness 5.34 mm - internal \varnothing 40.65 mm



CAPIC L554155

3186013 O-RING 06187 EPDM \varnothing 58 mm
ring thickness 5.34 mm - internal \varnothing 47.00 mm



CAPIC E153011

CAPIC L554118

3186014 O-RING 06225 EPDM \varnothing 67 mm
ring thickness 5.34 mm - internal \varnothing 56.52 mm



CAPIC L554120

Pilot burners and accessories

3020082 OLIVE FOR PIPE \varnothing 12 mm
for model PEL 22-24-25



CAPIC G701026

3020081 OLIVE FOR PIPE \varnothing 6 mm



CAPIC G701011

3020435 ONE-FLAME PILOT BURNER
for Kitchen gas (CAPIC) AB1 - A1
for Oven under cooktop gas (CAPIC) AB2 - AB5 - A2
A5 - CA1 - CA2 - CA5 - CO1 - CO2 - CO5 - C1
C2 - C5 - RECORD



CAPIC G207522

3500340 GAS JET M5x1 \varnothing 0.20 mm



CAPIC G206947

3500341 GAS JET M5x1 \varnothing 0.35 mm



CAPIC G206946



Suitable for:

CAPIC



3020001 ONE-FLAME PILOT BURNER SIT
multigas with jet \varnothing 0.20 mm
with 2 positions bracket



CAPIC LF-3020434

3020092 BRACKET PILOT BURNER SUPP. LH 92x55x45mm
for mounting of pilot assembly




3020293 BRACKET PILOT BURNER SUPPORT 65x50x45 mm
for burner \varnothing 115 mm



3020100 BRACKET 2 POSITIONS



3020083 FITTING AND OLIVE \varnothing 4 mm



3020102 HEXAGON HEAD SCREW 3/16"x18 mm




Suitable for:

3020101 BRACKET CLAMP 2 POSITIONS



3020292 BRACKET PILOT BURNER SUPPORT 47x40x15 mm
for burner \varnothing 90 mm




3020291 BRACKET PILOT BURNER SUPPORT 85x45x55 mm
for burner \varnothing 135 mm



3020108 DEFLECTOR 1 FLAME



3020084 FITTING AND OLIVE \varnothing 6 mm



3001003 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M4x1 mm
overall length 65 mm



CAPIC G207511



Suitable for:

3020060 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M 4x1 mm
overall length 82 mm
model CB505/021 Junkers
for model P502F



3020294 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M4x1 mm
overall length 67 mm



3020082 OLIVE FOR PIPE \varnothing 12 mm
for model PEL 22-24-25



CAPIC G701026

3020081 OLIVE FOR PIPE \varnothing 6 mm



CAPIC G701011

3020115 PILOT CAP 1 FLAME



3020156 PILOT JET \varnothing 0.25 mm



CAPIC

Suitable for:

3020124 IGNITION PLUG ROUND \varnothing 7x44 mm
connection \varnothing 2.4 mm
overall length 58 mm



3020365 IGNITION PLUG ROUND \varnothing 7x44 mm
connection \varnothing 2.4 mm
overall length 52 mm



3348036 OLIVE FOR PIPE \varnothing 4 mm
for model PEL 21-22-24-25



3020097 PILOT AERATION REGULATOR
internal \varnothing 7 mm - external \varnothing 9 mm
height 10 mm



3020054 PILOT JET \varnothing 0.20 mm



4058525 PILOT JET \varnothing 0.30 mm





Suitable for:

3020055 PILOT JET \varnothing 0.35 mm



3500269 PILOT JET \varnothing 0.45 mm



3020308 PILOT WITH NOZZLE \varnothing 0.40 mm



3020106 PILOT WITH 0.25 mm \varnothing JET



3020079 PIPE FITTING \varnothing 12 mm
thread \varnothing 3/8" M



3020078 PIPE FITTING \varnothing 6 mm
thread M10x1



CAPIC

Suitable for:

5015516 PILOT JET \varnothing 0.40 mm



5075989 PILOT JET \varnothing 0.70 mm



3020105 PILOT WITH 0.20 mm \varnothing JET



3020107 PILOT WITH 0.35 mm \varnothing JET



3020077 PIPE FITTING \varnothing 4 mm
thread M10x1



5014757 PIPE FITTING \varnothing 6 mm
thread M10x1 mm





Suitable for:

Suitable for:

3020422 PILOT BURNER HONEYWELL Q349
 supplied without sparking plug, nozzle
 with pilot pipe fitting \varnothing 6 mm
 for Boiling pan (CAPIC) W084021
 for Bratt pan (CAPIC) G0103 W054033
 for Bratt pan gas (CAPIC) W295125



CAPIC G207527
 CAPIC G207529+G207532

CAPIC G207529

CAPIC G207529+...

3806001 IGNITION PLUG ROUND \varnothing 6x44 mm
 fitting M8x10 mm - complete with fastening nut
 overall length 75 mm
 for pilot burner Honeywell serie Q327-Q349
 for Fryer gas (CAPIC) CT1 - CTIB - C10 - T1 - TIB
 for Fryer (CAPIC) R10



CAPIC G207534

3500328 PILOT JET
 forLPG - pilot Honeywell Q349



CAPIC G206925

3500329 PILOT JET
 for NATURAL GAS - pilot Honeywell Q349
 for Kitchen gas (CAPIC) W050240



CAPIC G206932

3020419 PILOT BURNER LPG 1 FLAME
 with bracket



CAPIC G207523

3500328 PILOT JET
 forLPG - pilot Honeywell Q349



CAPIC G206925

3500329 PILOT JET
 for NATURAL GAS - pilot Honeywell Q349
 for Kitchen gas (CAPIC) W050240



CAPIC G206932

3500385 PILOT JET \varnothing 0.30 mm



CAPIC G206942

3020414 PILOT JET LPG
 thread M7x1 mm



CAPIC G202010

3020415 PILOT JET NATURAL GAS
 thread M7x1 mm



CAPIC G202030



Suitable for:

CAPIC



Suitable for:

3020078 PIPE FITTING \varnothing 6 mm
thread M10x1



CAPIC G701010

3020006 THREE-FLAME PILOT BURNER SIT
multigas with jet \varnothing 0.20 mm
with 3 positions bracket



CAPIC G207510


3020103 BRACKET 3 POSITIONS



3020110 DEFLECTOR 3 FLAMES



3020083 FITTING AND OLIVE \varnothing 4 mm



3020102 HEXAGON HEAD SCREW 3/16"x18 mm



3020104 BRACKET CLAMP 3 POSITIONS




3020109 DEFLECTOR 2 FLAMES



5048713 DEFLECTOR 3 FLAMES



3020084 FITTING AND OLIVE \varnothing 6 mm



3001003 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M4x1 mm
overall length 65 mm



CAPIC G207511



Suitable for:

3020060 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M 4x1 mm
overall length 82 mm
model CB505/021 Junkers
for model P502F



3020294 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M4x1 mm
overall length 67 mm



3020082 OLIVE FOR PIPE \varnothing 12 mm
for model PEL 22-24-25



CAPIC G701026


5027953 OLIVE FOR PIPE \varnothing 4 mm
for COPRECI CAL3200



3020097 PILOT AERATION REGULATOR
internal \varnothing 7 mm - external \varnothing 9 mm
height 10 mm



3020156 PILOT JET \varnothing 0.25 mm



CAPIC

Suitable for:

3020124 IGNITION PLUG ROUND \varnothing 7x44 mm
connection \varnothing 2.4 mm
overall length 58 mm



3020365 IGNITION PLUG ROUND \varnothing 7x44 mm
connection \varnothing 2.4 mm
overall length 52 mm



3348036 OLIVE FOR PIPE \varnothing 4 mm
for model PEL 21-22-24-25



3020081 OLIVE FOR PIPE \varnothing 6 mm



CAPIC G701011

3020054 PILOT JET \varnothing 0.20 mm



4058525 PILOT JET \varnothing 0.30 mm





Suitable for:

3020055 PILOT JET \varnothing 0.35 mm



3500269 PILOT JET \varnothing 0.45 mm



3020308 PILOT WITH NOZZLE \varnothing 0.40 mm



3020106 PILOT WITH 0.25 mm \varnothing JET



3020079 PIPE FITTING \varnothing 12 mm
thread \varnothing 3/8" M



5033138 PIPE FITTING \varnothing 4 mm
thread \varnothing 1/8" M



CAPIC

Suitable for:

5015516 PILOT JET \varnothing 0.40 mm



5075989 PILOT JET \varnothing 0.70 mm



3020105 PILOT WITH 0.20 mm \varnothing JET




3020107 PILOT WITH 0.35 mm \varnothing JET



3020077 PIPE FITTING \varnothing 4 mm
thread M10x1



3020078 PIPE FITTING \varnothing 6 mm
thread M10x1





Suitable for:

5014757 PIPE FITTING \varnothing 6 mm
thread M10x1 mm



CAPIC



Suitable for:

3020002 TWO-FLAME PILOT BURNER SIT
multigas with jet \varnothing 0.20 mm
with 2 positions bracket



3020101 BRACKET CLAMP 2 POSITIONS



CAPIC


3020100 BRACKET 2 POSITIONS




3020109 DEFLECTOR 2 FLAMES



3020083 FITTING AND OLIVE \varnothing 4 mm



3020084 FITTING AND OLIVE \varnothing 6 mm



3020102 HEXAGON HEAD SCREW 3/16"x18 mm



3001003 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M4x1 mm
overall length 65 mm



3020060 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M 4x1 mm
overall length 82 mm
model CB505/021 Junkers
for model P502F



CAPIC G207511

3020124 IGNITION PLUG ROUND \varnothing 7x44 mm
connection \varnothing 2.4 mm
overall length 58 mm





Suitable for:

3020294 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M4x1 mm
overall length 67 mm



CAPIC



Suitable for:

3020365 IGNITION PLUG ROUND \varnothing 7x44 mm
connection \varnothing 2.4 mm
overall length 52 mm



3020082 OLIVE FOR PIPE \varnothing 12 mm
for model PEL 22-24-25



3348036 OLIVE FOR PIPE \varnothing 4 mm
for model PEL 21-22-24-25



CAPIC G701026

5027953 OLIVE FOR PIPE \varnothing 4 mm
for COPRECI CAL3200



3020081 OLIVE FOR PIPE \varnothing 6 mm



3020097 PILOT AERATION REGULATOR
internal \varnothing 7 mm - external \varnothing 9 mm
height 10 mm




CAPIC G701011

3020054 PILOT JET \varnothing 0.20 mm



3020156 PILOT JET \varnothing 0.25 mm



4058525 PILOT JET \varnothing 0.30 mm



3020055 PILOT JET \varnothing 0.35 mm



5015516 PILOT JET \varnothing 0.40 mm





Suitable for:

3500269 PILOT JET \varnothing 0.45 mm



CAPIC



Suitable for:

5075989 PILOT JET \varnothing 0.70 mm



3020308 PILOT WITH NOZZLE \varnothing 0.40 mm



3020105 PILOT WITH 0.20 mm \varnothing JET



3020106 PILOT WITH 0.25 mm \varnothing JET



3020107 PILOT WITH 0.35 mm \varnothing JET



3020079 PIPE FITTING \varnothing 12 mm
thread \varnothing 3/8" M



3020077 PIPE FITTING \varnothing 4 mm
thread M10x1



5033138 PIPE FITTING \varnothing 4 mm
thread \varnothing 1/8" M



3020078 PIPE FITTING \varnothing 6 mm
thread M10x1



5014757 PIPE FITTING \varnothing 6 mm
thread M10x1 mm



CAPIC G701010



Suitable for:


CAPIC



Suitable for:

Probes

3397185 TEMPERATURE PROBE TCJ \varnothing 6x85 mm
2 wires - cable 2000 mm
for Fryer electric (CAPIC) AM10



CAPIC E403534

Relays

3351007 POWER RELAY FINDER 55.32.8.230.0040
230V 50/60Hz
2 exchange contacts 10A
with to test push-button + mechanic gauge



CAPIC E052347

CAPIC E052349

3351021 POWER RELAY FINDER 62.82.8.230.0000
230V 50/60Hz
2 exchange contacts 16A



CAPIC L451712

3351008 POWER RELAY FINDER 62.83.8.230.0000
230V 50/60Hz
3 exchange contacts 16A



CAPIC L451725

3351602 POWER RELAY FINDER 65.31.8.230.0300
230V 50/60Hz
1 contact NO 30A



CAPIC L451715


Selector switches

3057050 CONNECTING BRACKET 28x21x16 mm
distance between hooking brackets 27 mm
f/connection between selector switch and thermostat.



CAPIC E401320

3057255 SELECTOR SWITCH 0-1 POSITIONS
contact capacity 16A 250V - max 150°C
D-shaped pin \varnothing 6x4.6 mm
for Bratt pan (CAPIC)
for Fryer gas (CAPIC) AB20 - A20 - CA10 - C10
2045 - 3085
for Grill (CAPIC)




CAPIC E052584



Suitable for:


3057073 SELECTOR SWITCH 0-1 0-1 POSITIONS
 contact capacity 16A 250V - max 150°C
 D-shaped pin \varnothing 6x4.6 mm



CAPIC E052505


Suitable for:

3057001 SELECTOR SWITCH 0-3 POSITIONS
 contact capacity 32A 250V - max 150°C
 D-shaped pin \varnothing 6x4.6 mm




CAPIC E052520

3057002 SELECTOR SWITCH 0-3 POSITIONS
 contact capacity 32A 250V - max 150°C
 D-shaped pin \varnothing 6x4.6 mm



CAPIC E052530

3057254 SELECTOR SWITCH 0-3 POSITIONS
 contact capacity 16A 250V - max 150°C
 D-shaped pin \varnothing 6x4.6 mm
 for Oven under cooktop electric (CAPIC)



CAPIC E052510

Sleeving for cables

3050752 SILICONE SEALING BRAIDING \varnothing 6 mm - 10 m
 temperature -60° +280°C
 for 100 m rolls see 3050152



CAPIC E301025


Solenoid valves

3120007 SOLEN. VALVE ELBI TYPE 349 2 WAY 180°
 220/240V 50/60Hz - max. temperature 90°C
 inlet 3/4" - two outlets \varnothing 10.5 mm



CAPIC L601005

3120019 ADJUSTER FOR INLET ELBI BLACK
 flow rate 5.5 L/min - tolerance +/- 15%



3120021 ADJUSTER FOR INLET ELBI BLACK
 flow rate 12 L/min - tolerance +/- 15%



3120022 ADJUSTER FOR INLET ELBI BLACK
 flow rate 16 L/min - tolerance +/- 15%





Suitable for:

3120037 ADJUSTER FOR OUTLET ELBI GREEN
flow rate 0.25 L/min - tolerance +/- 25%



3120016 ADJUSTER FOR OUTLET ELBI NEUTRAL
flow rate 1.2 L/min - tolerance +/- 25%



3120015 ADJUSTER FOR OUTLET ELBI RED
flow rate 0.5 L/min - tolerance +/- 25%



3120202 ADJUSTER FOR OUTLET ELBI YELLOW
flow rate 0.35 L/min / tolerance +/- 25%



3120204 OUTLET ADJUSTER ELBI BLACK
flow rate 5.5 L/min - tolerance +/- 25%



3120405 SOLEN. VALVE T&P 1 WAY 180°
230V 50/60Hz - max. temperature 90°C
inlet 3/4" - outlet ø 10.5 mm



CAPIC



Suitable for:

3120201 ADJUSTER FOR OUTLET ELBI GREY
flow rate 4.7 L/min - tolerance +/- 25%



3120017 ADJUSTER FOR OUTLET ELBI ORANGE
flow rate 2.5 L/min - tolerance +/- 25%



3120203 ADJUSTER FOR OUTLET ELBI WHITE
flow rate 2 L/min - tolerance +/- 25%



3120000 FILTER FOR INLET SOLENOID VALVE ELBI



3120421 ADJUSTER FOR OUTLET T&P BLACK
flow rate 5 L/min - tolerance +/- 20%





Suitable for:

3120608 ADJUSTER FOR OUTLET T&P DARK BROWN
flow rate 1.2 L/min - tolerance +/- 25%



3120391 ADJUSTER FOR OUTLET T&P LIGHT BLUE
flow rate 1 L/min - tolerance +/- 25%



3120423 ADJUSTER FOR OUTLET T&P ORANGE
flow rate 0.5 L/min - tolerance +/- 25%



3120386 ADJUSTER FOR OUTLET T&P WHITE
flow rate 0.8 L/min - tolerance +/- 25%



D120056 ADJUSTER INLET T&P BRONZE
flowrate 12 L/min



D120057 ADJUSTER INLET T&P LIGHT BROWN
flowrate 16 L/min



CAPIC

Suitable for:

3120568 ADJUSTER FOR OUTLET T&P GREEN
flow rate 3 L/min - tolerance +/- 25%



3120387 ADJUSTER FOR OUTLET T&P LIGHT BROWN
flow rate 1.5 L/min - tolerance +/- 25%



3120424 ADJUSTER FOR OUTLET T&P RED
flow rate 0.25 L/min - tolerance +/- 25%



3120422 ADJUSTER FOR OUTLET T&P YELLOW
flow rate 2.5 L/min - tolerance +/- 25%



D120054 ADJUSTER INLET T&P GREY
flowrate 6 L/min



D120058 ADJUSTER INLET T&P ORANGE
flowrate 20 L/min





Suitable for:

D120052 ADJUSTER INLET T&P RED
flowrate 3 L/min




D120053 ADJUSTER INLET T&P YELLOW
flowrate 5.5 L/min



3120431 COIL T&P 12Vac 50/60Hz
for solenoid valves T&P




D120090 COIL T&P 120V 60Hz 8VA
for solenoid valves T&P



3120432 COIL T&P 24Vac 50/60Hz
for solenoid valves T&P



3120407 SOLEN. VALVE T&P 2 WAY 180°
230V 50/60Hz - max. temperature 90°C
inlet 3/4" - two outlets ø 10.5 mm



CAPIC



Suitable for:

D120055 ADJUSTER INLET T&P WHITE
flowrate 10 L/min



D120059 ADJUSTER OUTLET T&P BLUE
flow rate 8 L/min - tolerance +/-25%



D120092 COIL T&P 12Vdc
for solenoid valves T&P



3120433 COIL T&P 220V 50/60Hz
for solenoid valves T&P



D120093 COIL T&P 24Vdc
for solenoid valves T&P



3120421 ADJUSTER FOR OUTLET T&P BLACK
flow rate 5 L/min - tolerance +/- 20%





Suitable for:

3120608 ADJUSTER FOR OUTLET T&P DARK BROWN
flow rate 1.2 L/min - tolerance +/- 25%



3120391 ADJUSTER FOR OUTLET T&P LIGHT BLUE
flow rate 1 L/min - tolerance +/- 25%



3120423 ADJUSTER FOR OUTLET T&P ORANGE
flow rate 0.5 L/min - tolerance +/- 25%



3120386 ADJUSTER FOR OUTLET T&P WHITE
flow rate 0.8 L/min - tolerance +/- 25%



D120056 ADJUSTER INLET T&P BRONZE
flowrate 12 L/min



D120057 ADJUSTER INLET T&P LIGHT BROWN
flowrate 16 L/min



CAPIC

Suitable for:

3120568 ADJUSTER FOR OUTLET T&P GREEN
flow rate 3 L/min - tolerance +/- 25%



3120387 ADJUSTER FOR OUTLET T&P LIGHT BROWN
flow rate 1.5 L/min - tolerance +/- 25%



3120424 ADJUSTER FOR OUTLET T&P RED
flow rate 0.25 L/min - tolerance +/- 25%



3120422 ADJUSTER FOR OUTLET T&P YELLOW
flow rate 2.5 L/min - tolerance +/- 25%



D120054 ADJUSTER INLET T&P GREY
flowrate 6 L/min



D120058 ADJUSTER INLET T&P ORANGE
flowrate 20 L/min





Suitable for:

D120052 ADJUSTER INLET T&P RED
flowrate 3 L/min



D120053 ADJUSTER INLET T&P YELLOW
flowrate 5.5 L/min




3120431 COIL T&P 12Vac 50/60Hz
for solenoid valves T&P



D120090 COIL T&P 120V 60Hz 8VA
for solenoid valves T&P



3120432 COIL T&P 24Vac 50/60Hz
for solenoid valves T&P



3120014 SOLENOID VALVE ELBI TYPE 369 3-WAY 180°
220/240V 50/60Hz - max temperature 90°C
inlet 3/4" - three outlets ø 10.5 mm



CAPIC



Suitable for:

D120055 ADJUSTER INLET T&P WHITE
flowrate 10 L/min




D120059 ADJUSTER OUTLET T&P BLUE
flow rate 8 L/min - tolerance +/-25%



D120092 COIL T&P 12Vdc
for solenoid valves T&P



3120433 COIL T&P 220V 50/60Hz
for solenoid valves T&P



D120093 COIL T&P 24Vdc
for solenoid valves T&P



3120019 ADJUSTER FOR INLET ELBI BLACK
flow rate 5.5 L/min - tolerance +/- 15%





Suitable for:

3120021 ADJUSTER FOR INLET ELBI BLACK
flow rate 12 L/min - tolerance +/- 15%



3120037 ADJUSTER FOR OUTLET ELBI GREEN
flow rate 0.25 L/min - tolerance +/- 25%



3120016 ADJUSTER FOR OUTLET ELBI NEUTRAL
flow rate 1.2 L/min - tolerance +/- 25%



3120015 ADJUSTER FOR OUTLET ELBI RED
flow rate 0.5 L/min - tolerance +/- 25%



3120202 ADJUSTER FOR OUTLET ELBI YELLOW
flow rate 0.35 L/min / tolerance +/- 25%



3120204 OUTLET ADJUSTER ELBI BLACK
flow rate 5.5 L/min - tolerance +/- 25%



CAPIC

Suitable for:

3120022 ADJUSTER FOR INLET ELBI BLACK
flow rate 16 L/min - tolerance +/- 15%



3120201 ADJUSTER FOR OUTLET ELBI GREY
flow rate 4.7 L/min - tolerance +/- 25%



3120017 ADJUSTER FOR OUTLET ELBI ORANGE
flow rate 2.5 L/min - tolerance +/- 25%



3120203 ADJUSTER FOR OUTLET ELBI WHITE
flow rate 2 L/min - tolerance +/- 25%



3120000 FILTER FOR INLET SOLENOID VALVE ELBI





Suitable for:

CAPIC



3120414 SOLENOID VALVE T&P 3-WAY 180°
230V 50/60Hz - max. temperature 90°C
inlet 3/4" with flowrate adjuster 10 L/min
three ø 10.5 mm outlets



CAPIC L601015

3120608 ADJUSTER FOR OUTLET T&P DARK BROWN
flow rate 1.2 L/min - tolerance +/- 25%



3120421 ADJUSTER FOR OUTLET T&P BLACK
flow rate 5 L/min - tolerance +/- 20%



3120568 ADJUSTER FOR OUTLET T&P GREEN
flow rate 3 L/min - tolerance +/- 25%



3120391 ADJUSTER FOR OUTLET T&P LIGHT BLUE
flow rate 1 L/min - tolerance +/- 25%



3120387 ADJUSTER FOR OUTLET T&P LIGHT BROWN
flow rate 1.5 L/min - tolerance +/- 25%



3120423 ADJUSTER FOR OUTLET T&P ORANGE
flow rate 0.5 L/min - tolerance +/- 25%



3120424 ADJUSTER FOR OUTLET T&P RED
flow rate 0.25 L/min - tolerance +/- 25%



3120386 ADJUSTER FOR OUTLET T&P WHITE
flow rate 0.8 L/min - tolerance +/- 25%



3120422 ADJUSTER FOR OUTLET T&P YELLOW
flow rate 2.5 L/min - tolerance +/- 25%



D120056 ADJUSTER INLET T&P BRONZE
flowrate 12 L/min



D120054 ADJUSTER INLET T&P GREY
flowrate 6 L/min





Suitable for:

D120057 ADJUSTER INLET T&P LIGHT BROWN
flowrate 16 L/min



D120052 ADJUSTER INLET T&P RED
flowrate 3 L/min



D120053 ADJUSTER INLET T&P YELLOW
flowrate 5.5 L/min



3120431 COIL T&P 12Vac 50/60Hz
for solenoid valves T&P



D120090 COIL T&P 120V 60Hz 8VA
for solenoid valves T&P



3120432 COIL T&P 24Vac 50/60Hz
for solenoid valves T&P



CAPIC

Suitable for:

D120058 ADJUSTER INLET T&P ORANGE
flowrate 20 L/min



D120055 ADJUSTER INLET T&P WHITE
flowrate 10 L/min



D120059 ADJUSTER OUTLET T&P BLUE
flow rate 8 L/min - tolerance +/-25%



D120092 COIL T&P 12Vdc
for solenoid valves T&P



3120433 COIL T&P 220V 50/60Hz
for solenoid valves T&P



D120093 COIL T&P 24Vdc
for solenoid valves T&P





Suitable for:

3523094 SOLENOID-VALVE \varnothing 1/8"FF 230V
for gas-coil 230V 50/60Hz 4W
for Fryer gas (CAPIC) AB20 - A20 - CA10 - CTI
CTIB - C10 - TI - TIB - 2045



CAPIC E131002

Suitable for:

3120044 CONNECTOR FEMALE SMALL
for coils



Spark generators

3181002 SPARK GENERATOR 2 OUTLETS
220/240V 50/60Hz



CAPIC E050505

3181004 SPARK GENERATOR 6 OUTLETS
220/240V - 50/60Hz



CAPIC E050506

Sparking and detection plugs

3806001 IGNITION PLUG ROUND \varnothing 6x44 mm
fitting M8x10 mm - complete with fastening nut
overall length 75 mm
for pilot burner Honeywell serie Q327-Q349
for Fryer gas (CAPIC) CTI - CTIB - C10 - TI - TIB
for Fryer (CAPIC) R10



CAPIC G207534

3001003 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M4x1 mm
overall length 65 mm



CAPIC G207511

3455354 ROUND IGNITION PLUG \varnothing 7x45 mm
overall length 52 mm
complete with cable of length 1500 mm
for Pot stove gas (CAPIC) W290116



CAPIC G207554

3806020 ROUND IGNITION PLUG \varnothing 7x50 mm
overall length 67 mm
for Pot stove gas (CAPIC) W042301



CAPIC G101030

Suitable for:

Suitable for:


3806003 ROUND IGNITION PLUG \varnothing 9.5x48 mm
total length 97 mm
for HONEYWELL BURNER



CAPIC G101034

Switches

3319545 LEVER SWITCH 1-POLE 15A 250V
threaded coupling M12x1 mm
ON-OFF function



CAPIC E053510

3319686 START-STOP STRIP
for lever switches-reversers



3319685 SWITCH PROTECTION CAP
for lever switches-reversers



CAPIC E053512

3452004 SWITCH COVER
external dimensions 25x20 mm
for switch with mounting hole 20x13 mm



CAPIC E053532

3319685 SWITCH PROTECTION CAP
for lever switches-reversers



CAPIC E053512

Taps for tank refilling

3356139 WATER INLET TAP \varnothing 3/8" F
intenal output \varnothing 7.5 mm
for Boiling pan (CAPIC) W085121



CAPIC Q450506



Suitable for:

CAPIC




Suitable for:

Telethermometers

3441007 TELE-THERMOMETER WHITE \varnothing 60 mm 0-120°C

metal case
PVC covered capillary 3000 mm
spring bulb \varnothing 8x32 mm
bulb fitting M10x1



CAPIC L057010

Terminal blocks

3247009 TERMINAL BLOCK 6-POLES FV122/B 40A 600V

for cable max 6 mm²
operating temperature 150°C
nominal voltage 450 V



CAPIC L450310

Terminals and electrical connectors

3051101 RED CABLE TERM F 2.8x0.8 mm 100 PCS

wire cross-section \varnothing 0.25÷1.5 mm



CAPIC E352217

3051104 RED CABLE TERM F 6.3x0.8 mm 100 PCS

wire cross-section \varnothing 0.25÷1.5 mm



CAPIC E352218

Thermocouples and accessories

3440154 THERMOCOUPLE M9x1 90 cm

bulb \varnothing 10x54 mm - with fixing connection M11x1
for PILOT HONEYWELL Q349-Q327
for Bratt pan gas (CAPIC) W295125



CAPIC G401005



Thermocouples and accessories

3440036 THERMOCOUPLE SIT M9x1 85 cm.
for Fryer gas (CAPIC) EL5 - W030520



CAPIC G401030

3440836 THERMOCOUPLE SIT M9x1 85 cm - 10 PCS



Thermostats

3241870 BEZEL RING NUT \varnothing 52 mm
chrome plated metal Bezel
for EGO thermostate knob



CAPIC E401313

3444616 BULB CONNECTION M12 HOLE \varnothing 6 mm
stuffing gland M9x1- washer \varnothing 7.7 mm
gasket \varnothing 7.8 mm - thickness 5 mm



CAPIC E401310

3744008 SINGLE-PHASE THERMOSTAT 100-180°C
D-shaped pin \varnothing 6x4.6 mm
capillary length 900 mm
bulb \varnothing 6x130 mm - with adapter nipple bland M9x1
with complete tank coupling M12x1
for Fryer gas (CAPIC) AB20 - A20 - CA10 - CTI
CTIB - C10 - 2045 - 3085
for Fryer (CAPIC) AV23 - R10 - W052041 C20 W051041
for Fryer electric (CAPIC) W082081



CAPIC E401075

3444974 SINGLE-PHASE THERMOSTAT 100-615°C
complete with switch
D-shaped pin \varnothing 6x4.6 mm
covered capillary length 1100 mm - 16A 250V
bulb \varnothing 4x230 mm
for Glass-ceramic plate electric (CAPIC) W381511
W381521 - W381531



CAPIC E401084

3444922 SINGLE-PHASE THERMOSTAT 225°C
with manual reset
capillary length 900 mm
bulb \varnothing 6x90 mm
for Fryer (CAPIC)



CAPIC E401007

3444765 SINGLE-PHASE THERMOSTAT 240°C
with automatic reset
capillary length covered 550 mm - 16A 230V
bulb \varnothing 4x90 mm



CAPIC E401002




Suitable for:

CAPIC



3444747 SINGLE-PHASE THERMOSTAT 50-250°C

D-shaped pin \varnothing 6x4.6 mm
capillary length 1150 mm - 16A 230V
bulb \varnothing 3.1x197 mm



CAPIC E401078

CAPIC E401088

Suitable for:

3744011 SINGLE-PHASE THERMOSTAT 60-287°C

D-shaped pin \varnothing 6x4.6 mm
capillary length 1470 mm
bulb \varnothing 3.1x226 mm
for Bratt pan electric (CAPIC) W295125



CAPIC E401082

3444915 THERMOSTAT SINGLE-PHASE 220°C

with automatic reset
capillary length 1500 mm
bulb \varnothing 6x80 mm - with stuffing gland fitting M9x1
with tank seal connection complete M12x1
for Fryer gas (CAPIC) AB20 - A20 - CA10 - CTI
CTIB - C10 - 2045 - 3085
for Fryer (CAPIC) W052041 C20 W051041
for Fryer electric (CAPIC) TURBOFRIT 25L - W082081
W382031



CAPIC E401006

3444980 THERMOSTAT SINGLE-PHASE 30-120°C

D-shaped pin \varnothing 6x4.6 mm
capillary length 870 mm
bulb \varnothing 6x100 mm - with stuffing gland fitting M9x1
for Boiling pan (CAPIC)



CAPIC E401077

3744064 THERMOSTAT THREE-PHASE 30-90°C


D-shaped pin \varnothing 6x4.6 mm
capillary length 900 mm
bulb \varnothing 6x130 mm



CAPIC E401011

3443072 THREE-PHASE THERMOSTAT 130°C

with manual reset
capillary length 890 mm
bulb \varnothing 6x90 mm - with stuffing gland M8x1
with tank seal \varnothing 1/4"
for Boiling pan electric (CAPIC) W294111




CAPIC E401008

CAPIC E401012

3444088 THREE-PHASE THERMOSTAT 30-110°C

D-shaped pin \varnothing 6x4.6 mm
capillary length 900 mm - 10A 400V
bulb \varnothing 6x140 mm - with stuffing gland fitting M9x1
for Pasta cooker (CAPIC) W291181



CAPIC E401015

3444505 THREE-PHASE THERMOSTAT 50-300°C

D-shaped pin \varnothing 6x4.6 mm
capillary length 1440 mm - 10A 400V
bulb \varnothing 4x292 mm




CAPIC E401066

Suitable for:

3444694 THREE-PHASE THERMOSTAT 50-300°C

D-shaped pin \varnothing 6x4.6 mm
capillary length 880 mm
bulb \varnothing 6x77 mm




CAPIC E401060

Suitable for:

3444594 THREE-PHASE THERMOSTAT 65-200°C

D-shaped pin \varnothing 6x4.6 mm
capillary length 880 mm
bulb \varnothing 6x77 mm - with adapter nipple bland M9x1
with complete tank coupling M12x1
for Boiling pan (CAPIC) W294012



CAPIC E401045

Timers

3446159 TIMER 120 MINUTES C53

manually set mechanical timer
manually set cycle 120 minutes
contact capacity 16A 250V
max temperature 125°C
2 normally closed contacts
2 normally closed contacts
complete with silkscreen printed plate and knob
dimensions 49.5x58 mm depth 52 mm



CAPIC E452080

3446150 TIMER 30 MINUTES S43V

mechanical timer with sound alarm
manual winding cycle 30 minutes
complete with screenprinted plate and knob
size \varnothing 60x27 mm



CAPIC Q051001

Wheels and accessories

3522044 WHEEL HANDLE

hole for square shaft 12x12 mm - length 130 mm
BAKELITE handle
for Bratt pan (CAPIC) W295125
for Bratt pan electric (CAPIC) W054133



CAPIC Q104076

The data herewith contained may change without notice and LF SpA cannot be held responsible for possible errors stated or resulting by the use of this document. All rights reserved. No part of this publication may be reproduced without written permission by LF SpA.



Distributing Components, Spare Parts & Accessories in original quality worldwide

-
- LF SpA HEADQUARTERS**
via Voltri, 80 - 47522 Cesena (FC) ITALY
Tel. +39 0547 34 11 11 - Fax +39 0547 34 11 10
www.lfricambi724.it - info@lfricambi.it
Export Dept. Tel. +39 0547 34 11 50 - Fax +39 0547 34 11 55
www.lfspareparts724.com - export@lfspareparts.com
- LF SpA HOUSEHOLD COMPONENTS DIVISION**
Via Padriciano, 99 - AREA Science Park - 34149 Trieste (TS) ITALY
Tel. +39 0547 34 12 42 - Fax +39 0547 34 12 48
www.lfspareparts724.com - info@lfspareparts.com
- EPGC Sas FRANCE**
13, Rue des Forts - 59960 Neuville en Ferrain
Tel. +33 (0)3 20 25 06 21 - Fax +33 (0)3 20 25 34 12
www.epgc.com - epgc@epgc.com
- LF GmbH GERMANY**
Junkersstrasse, 3 - D-82178 Puchheim - München
Tel. +49 89 89 45 78 66 - Fax +49 89 89 45 78 88
www.lfersatzteile724.de - info@lfersatzteile.de
- LF China REPUBLIC OF CHINA**
Room 403, No.2, Huadu Mansion, Lane 422, Huanghua Rd.
Minhang Dist. - 201103 Shanghai
Tel. +86 (0)21 33 53 66 31 - Fax +86 (0)21 33 53 66 32
www.lfspareparts724.com - china@lfspareparts.com
- OOO LF RUSSIAN FEDERATION**
Ul. Anatoliya Zhivova, 8 - office 1 - 123100 Moscow
Tel./Fax +7 495 725 26 53
www.lfspareparts724.ru - info@lfspareparts.ru
- LF Repuestos Horeca S.L.U. SPAIN**
Poligono Industrial Carpetania - C/Miguel Faraday, 8 - 28906 Getafe
Tel. +34 91 477 91 00 - Fax +34 91 477 90 81
www.lfrepuestos-horeca724.es - info@lfrepuestos.es
- LF Scandinavia Aps - LF Spareparts S.p.A. DENMARK**
Nupark, 51 - 7500 Holstebro
Tel. +45 70 70 77 33
www.lfspareparts724.dk - denmark@lfspareparts.dk
- LF SpA Cesena (IT) Swiss Branch Steinhausen SWITZERLAND**
Sennweidstrasse, 45 - CH-6312 Steinhausen
Tel. +41 (0)41 760 15 80/1 - Fax +41 (0)41 760 15 85
www.lfersatzteile724.ch - info@lfersatzteile.ch
- LF Spare Parts Ltd. UNITED KINGDOM**
A10a Lakeside Business Park, Broadway Lane
South Cerney, Gloucestershire GL7 5XL
Tel. +44 (0)1285 86 16 25 - Fax +44 (0)1285 86 39 49
www.lfspareparts724.co.uk - info@lfspareparts.co.uk
- LF Central Est Europe S.r.o. CZECH REPUBLIC**
Antala Staska 1859/34
14000 Praha 4 - KRC
Tel. +420 730 156 910
www.lfspareparts724.cz - info@lfspareparts.cz
- LF SPARE PARTS INC. USA**
Legal address:
155 Office Plaza Dr - Suite A - Tallahassee, FL 32301
Business/Mailing address:
1100 South Tower, 225 Peachtree St., N.E. - Atlanta, GA 30303, USA
Tel. +1-404-525-2600 - Fax +1-404-586-3528
www.lfspareparts724.us - info@lfspareparts.us
Tel. West Coast and Midwest: 206-349-1525 Sauro
Tel. East Coast and the Caribbean: 786-817-1764 Luis
-
- AUSTRALIA AND NEW ZEALAND**
www.lfspareparts724.com
andrea.calvio@lfspareparts.com
- AUSTRIA**
www.lfersatzteile724.at
info@lfersatzteile.at
- BALKAN COUNTRIES**
www.lfspareparts724.com
matija.ramov@lfspareparts.com
- BALTIC COUNTRIES**
www.lfspareparts724.com
inara.silina@lfspareparts.com
- LATIN AMERICA AND THE CARRIBEANS**
www.lfrepuestos-horeca724.es
export@lfrepuestos.es
- POLAND**
www.lfspareparts724.pl
info@lfspareparts.pl
- SOUTH KOREA**
www.lfspareparts724.com
fabio.doni@lfspareparts.com
- TURKEY**
www.lfyedekparca724.com
export@lfspareparts.com