



Spare parts for the professional sector:  
**Cooking equipment**



Suitable for:

**COMETTO**



This catalogue is automatically generated.  
Therefore, the sequence of the items might  
not be always shown at best.  
Updates will be issued in case of additions  
and/or amendments.

*Suitable **universal spare parts** may not be included*





Suitable for:

# COMETTO



Suitable for:

## Burners, flame spreaders and accessories

**3025674 BURNER  $\varnothing$  100 mm**



COMETTO COM40506

COMETTO 40506

**3025598 BURNER  $\varnothing$  106 mm**



COMETTO

**3025628 BURNER  $\varnothing$  111 mm**



COMETTO

**3025629 BURNER  $\varnothing$  119 mm**



COMETTO

**3025634 BURNER  $\varnothing$  143 mm**



COMETTO

**3025673 BURNER  $\varnothing$  80 mm**



COMETTO COM40501

COMETTO 40501

**3025596 FLAME SPREADER  $\varnothing$  80 mm**



COMETTO COM40502


COMETTO 40502

**3025595 BURNER  $\varnothing$  83 mm**



COMETTO

**3025758 BURNER ASSEMBLY MOUNTING DISTANCE 110 mm**  
with vertical flame  
6000-9000 Kcal/h  
height 90 mm -  $\varnothing$  100 mm - pipe  $\varnothing$  27 mm



COMETTO

**3025598 BURNER  $\varnothing$  106 mm**



COMETTO



Suitable for:

**3025599 FLAME SPREADER  $\varnothing$  100 mm**



COMETTO COM40507

COMETTO 40507

**3500186 GAS JET CONICAL M17x1  $\varnothing$  1.30 mm**



# COMETTO



Suitable for:

**3025679 GAS BURNER SUPPORT GR5  $\varnothing$  27 mm**



**3500195 GAS JET CONICAL M17x1  $\varnothing$  2.20 mm**



**3025797 BURNER ASSEMBLY MOUNTING DISTANCE 110 mm**

with vertical flame  
4000-7000 Kcal/h  
height 90 mm -  $\varnothing$  80 mm - pipe  $\varnothing$  27 mm



COMETTO

**3025596 FLAME SPREADER  $\varnothing$  80 mm**



COMETTO COM40502

COMETTO 40502

**3500185 GAS JET CONICAL M17x1  $\varnothing$  1.20 mm**



**3025595 BURNER  $\varnothing$  83 mm**



COMETTO

**3025679 GAS BURNER SUPPORT GR5  $\varnothing$  27 mm**



**3500193 GAS JET CONICAL M17x1  $\varnothing$  2.00 mm**



**3025756 BURNER ASSEMBLY MOUNTING DISTANCE 165 mm**

with vertical flame  
4000-7000 Kcal/h  
height 90 mm -  $\varnothing$  80 mm - pipe  $\varnothing$  27 mm



COMETTO

**3025595 BURNER  $\varnothing$  83 mm**



COMETTO



Suitable for:

**3025596 FLAME SPREADER  $\varnothing$  80 mm**



COMETTO COM40502

COMETTO 40502

**3500185 GAS JET CONICAL M17x1  $\varnothing$  1.20 mm**



# COMETTO



Suitable for:

**3025679 GAS BURNER SUPPORT GR5  $\varnothing$  27 mm**



**3500193 GAS JET CONICAL M17x1  $\varnothing$  2.00 mm**



**3025759 BURNER ASSEMBLY MOUNTING DISTANCE 165 mm**  
with vertical flame  
6000-9000 Kcal/h  
height 90 mm -  $\varnothing$  100 mm - pipe  $\varnothing$  27 mm



COMETTO

**3025599 FLAME SPREADER  $\varnothing$  100 mm**



COMETTO COM40507

COMETTO 40507

**3500186 GAS JET CONICAL M17x1  $\varnothing$  1.30 mm**



**3025598 BURNER  $\varnothing$  106 mm**



COMETTO

**3025679 GAS BURNER SUPPORT GR5  $\varnothing$  27 mm**



**3500195 GAS JET CONICAL M17x1  $\varnothing$  2.20 mm**



**3025760 BURNER ASSEMBLY MOUNTING DISTANCE 240 mm**  
with vertical flame  
6000-9000 Kcal/h  
height 90 mm -  $\varnothing$  100 mm - pipe  $\varnothing$  27 mm



COMETTO

**3025598 BURNER  $\varnothing$  106 mm**



COMETTO



Suitable for:

**3025599 FLAME SPREADER  $\varnothing$  100 mm**



COMETTO COM40507

COMETTO 40507

**3500186 GAS JET CONICAL M17x1  $\varnothing$  1.30 mm**



# COMETTO

Suitable for:

**3025679 GAS BURNER SUPPORT GR5  $\varnothing$  27 mm**



**3500195 GAS JET CONICAL M17x1  $\varnothing$  2.20 mm**



**3025799 BURNER ASSEMBLY MOUNTING DISTANCE 240 mm**

with vertical flame  
4000-7000 Kcal/h  
height 90 mm -  $\varnothing$  80 mm - pipe  $\varnothing$  27 mm



COMETTO

**3025596 FLAME SPREADER  $\varnothing$  80 mm**



COMETTO COM40502

COMETTO 40502

**3500185 GAS JET CONICAL M17x1  $\varnothing$  1.20 mm**



**3025595 BURNER  $\varnothing$  83 mm**



COMETTO

**3025679 GAS BURNER SUPPORT GR5  $\varnothing$  27 mm**



**3500193 GAS JET CONICAL M17x1  $\varnothing$  2.00 mm**



**3025768 BURNER ASSEMBLY MOUNTING DISTANCE 245 mm**

with vertical flame  
5000-7000 kcal/h  
height 100 mm -  $\varnothing$  80 mm - pipe  $\varnothing$  34 mm



COMETTO

**3025595 BURNER  $\varnothing$  83 mm**



COMETTO



Suitable for:

**3025624 FLAME SPREADER  $\varnothing$  80 mm**




COMETTO

**3500185 GAS JET CONICAL M17x1  $\varnothing$  1.20 mm**



**3025716 COMPLETE BURNER MOUNTING DISTANCE 185 mm**

vertical flame outlet  
7000-11000 Kcal/h  
height 90 mm -  $\varnothing$  100 mm - pipe  $\varnothing$  34 mm



COMETTO

**3500187 CONICAL GAS JET M17x1  $\varnothing$  1.40 mm**



**3025599 FLAME SPREADER  $\varnothing$  100 mm**




COMETTO COM40507

COMETTO 40507

**3025717 COMPLETE BURNER MOUNTING DISTANCE 245 mm**

vertical flame outlet  
7000-11000 Kcal/h  
height 90 mm -  $\varnothing$  100 mm - pipe  $\varnothing$  34 mm



COMETTO

# COMETTO

Suitable for:

**3025680 GAS BURNER SUPPORT GR6  $\varnothing$  34 mm**



**3500193 GAS JET CONICAL M17x1  $\varnothing$  2.00 mm**



**3025598 BURNER  $\varnothing$  106 mm**



COMETTO

**3500197 CONICAL GAS JET M17x1  $\varnothing$  2.40 mm**



**3025680 GAS BURNER SUPPORT GR6  $\varnothing$  34 mm**



**3025598 BURNER  $\varnothing$  106 mm**



COMETTO





Suitable for:

3500187 CONICAL GAS JET M17x1  $\phi$  1.40 mm



3025599 FLAME SPREADER  $\phi$  100 mm



COMETTO COM40507

COMETTO 40507

3025599 FLAME SPREADER  $\phi$  100 mm



COMETTO COM40507

COMETTO 40507

3025624 FLAME SPREADER  $\phi$  80 mm



COMETTO

# COMETTO



Suitable for:

3500197 CONICAL GAS JET M17x1  $\phi$  2.40 mm



3025680 GAS BURNER SUPPORT GR6  $\phi$  34 mm



3025596 FLAME SPREADER  $\phi$  80 mm



COMETTO COM40502

COMETTO 40502

## Drain taps and accessories

3356004 DRAIN TAP  $\phi$  1" F  
TAPERED SEAL - fixed connection  $\phi$  1" F  
for BOILING PAN



COMETTO

3186009 ASBESTOS FREE FLAT GASKET  $\phi$  45x33x2 mm





Suitable for:

**3179010 FITTINGS SEALING TAPE LOCTITE 55 - 50 m**  
 length 50 mt  
 suitable to hot and cold drinking water, gas  
 replaces pastes, hemp and sealing tapes  
 it allows the repositioning of couplings  
 in compliance with the latest regulations  
 Drinking water (Italian certification by C.S.A.,  
 according to standard KTW and WRC approved)  
 gas - water IMQ-UNICIG.  
 compliant with UNI EN 51-2 class Arp  
 approved by DVGW and DIN 30660



**3356029 HANDLE FOR DRAIN TAP**  
 for drain tap  $\varnothing$  3/4" and 1"



**3180039 VASELINE WUERTH 750 g**  
 for lubrication of food processing machines  
 it protects chromed and rubber parts from  
 weather factors, moisture resistant,  
 operating temperature from -10°C up to +120°C  
 from +50°C to +120 °C the grease becomes oily



## COMETTO



Suitable for:

**1180001 GREASE KLUBERSYNTH UH1 14-151 45 g**  
 food safe grease for lubrication  
 of all friction points  
 ideal for water and steam taps  
 operating temperature -45°/+120°  
 beige color - NSF H1 certified  
 hot and cold water resistant  
 high anti-corrosion power  
 can replace vaseline



**3180061 TAPE F. COUPLING SEALING LOCTITE 55-150m**  
 length 150 metri  
 suitable for hot / cold drinking water. gas  
 replaces pastes, hemp and sealing tapes  
 it allows the correct replacement of fittings  
 compliant with the latest regulatory requirements  
 Drinking water (C.S.A. italian certified.  
 in line with KTW standard and WRC approved )  
 IMQ-UNICIG gas-water,  
 compliant with UNI EN 51-2 class Arp  
 DVGW and DIN 30660 approved







**3356109 DRAIN TAP  $\varnothing$  1" F**  
fixed connection  $\varnothing$  1" F - fixed handle  
for Boiling pan (COMETTO)



COMETTO

**1180001 GREASE KLUBERSYNTH UH1 14-151 45 g**  
food safe grease for lubrication  
of all friction points  
ideal for water and steam taps  
operating temperature  $-45^{\circ}/+120^{\circ}$   
beige color - NSF H1 certified  
hot and cold water resistant  
high anti-corrosion power  
can replace vaseline



**3180039 VASELINE WUERTH 750 g**  
for lubrication of food processing machines  
it protects chromed and rubber parts from  
weather factors, moisture resistant,  
operating temperature from  $-10^{\circ}\text{C}$  up to  $+120^{\circ}\text{C}$   
from  $+50^{\circ}\text{C}$  to  $+120^{\circ}\text{C}$  the grease becomes oily



Suitable for:

**3179010 FITTINGS SEALING TAPE LOCTITE 55 - 50 m**  
length 50 mt  
suitable to hot and cold drinking water, gas  
replaces pastes, hemp and sealing tapes  
it allows the repositioning of couplings  
in compliance with the latest regulations  
Drinking water (Italian certification by C.S.A.,  
according to standard KTW and WRC approved)  
gas - water IMQ-UNICIG.  
compliant with UNI EN 51-2 class Arp  
approved by DVGW and DIN 30660



**3180061 TAPE F. COUPLING SEALING LOCTITE 55-150m**  
length 150 metri  
suitable for hot / cold drinking water. gas  
replaces pastes, hemp and sealing tapes  
it allows the correct replacement of fittings  
compliant with the latest regulatory requirements  
Drinking water (C.S.A. italian certified.  
in line with KTW standard and WRC approved )  
IMQ-UNICIG gas-water,  
compliant with UNI EN 51-2 class Arp  
DVGW and DIN 30660 approved





Suitable for:

# COMETTO



Suitable for:

**3356112 DRAIN TAP ø 1"1/2F**  
fixed connection ø 1"1/2"F - fixed handle  
for Boiling pan (COMETTO)



COMETTO

**1180001 GREASE KLUBERSYNTH UH1 14-151 45 g**  
food safe grease for lubrication  
of all friction points  
ideal for water and steam taps  
operating temperature -45°/+120°  
beige color - NSF H1 certified  
hot and cold water resistant  
high anti-corrosion power  
can replace vaseline



**3180039 VASELINE WUERTH 750 g**  
for lubrication of food processing machines  
it protects chromed and rubber parts from  
weather factors, moisture resistant,  
operating temperature from -10°C up to +120°C  
from +50°C to +120 °C the grease becomes oily



**3179010 FITTINGS SEALING TAPE LOCTITE 55 - 50 m**  
length 50 mt  
suitable to hot and cold drinking water, gas  
replaces pastes, hemp and sealing tapes  
it allows the repositioning of couplings  
in compliance with the latest regulations  
Drinking water (Italian certification by C.S.A.,  
according to standard KTW and WRC approved)  
gas - water IMQ-UNICIG.  
compliant with UNI EN 51-2 class Arp  
approved by DVGW and DIN 30660



**3180061 TAPE F. COUPLING SEALING LOCTITE 55-150m**  
length 150 metri  
suitable for hot / cold drinking water. gas  
replaces pastes, hemp and sealing tapes  
it allows the correct replacement of fittings  
compliant with the latest regulatory requirements  
Drinking water (C.S.A. italian certified.  
in line with KTW standard and WRC approved )  
IMQ-UNICIG gas-water,  
compliant with UNI EN 51-2 class Arp  
DVGW and DIN 30660 approved





**3356110 DRAIN TAP  $\varnothing$  1"1/4F**  
fixed connection  $\varnothing$  1"1/4"F - fixed handle  
for Boiling pan (COMETTO)



COMETTO

**1180001 GREASE KLUBERSYNTH UH1 14-151 45 g**  
food safe grease for lubrication  
of all friction points  
ideal for water and steam taps  
operating temperature  $-45^{\circ}/+120^{\circ}$   
beige color - NSF H1 certified  
hot and cold water resistant  
high anti-corrosion power  
can replace vaseline



**3180039 VASELINE WUERTH 750 g**  
for lubrication of food processing machines  
it protects chromed and rubber parts from  
weather factors, moisture resistant,  
operating temperature from  $-10^{\circ}\text{C}$  up to  $+120^{\circ}\text{C}$   
from  $+50^{\circ}\text{C}$  to  $+120^{\circ}\text{C}$  the grease becomes oily



**3356005 DRAIN TAP  $\varnothing$  1"1/4F TECNO**  
TAPERED SEAL - fixed connection  $\varnothing$  1"1/4F  
with gasket  
for BOILING PAN



COMETTO

Suitable for:

**3179010 FITTINGS SEALING TAPE LOCTITE 55 - 50 m**  
length 50 mt  
suitable to hot and cold drinking water, gas  
replaces pastes, hemp and sealing tapes  
it allows the repositioning of couplings  
in compliance with the latest regulations  
Drinking water (Italian certification by C.S.A.,  
according to standard KTW and WRC approved)  
gas - water IMQ-UNICIG.  
compliant with UNI EN 51-2 class Arp  
approved by DVGW and DIN 30660



**3180061 TAPE F. COUPLING SEALING LOCTITE 55-150m**  
length 150 metri  
suitable for hot / cold drinking water. gas  
replaces pastes, hemp and sealing tapes  
it allows the correct replacement of fittings  
compliant with the latest regulatory requirements  
Drinking water (C.S.A. italian certified.  
in line with KTW standard and WRC approved )  
IMQ-UNICIG gas-water,  
compliant with UNI EN 51-2 class Arp  
DVGW and DIN 30660 approved



**3186240 ASBESTOS FREE FLAT GASKET  $\varnothing$  46x38x2 mm**  
for drain tap  $\varnothing$  1"1/2





Suitable for:

3356010 ESCUTCHEON FOR DRAIN TAP ø 1"1/4



3186199 GASKET INTERNAL EPDM FOR TAPS  
NSF certified  
for DRAIN TAP ø 1"1/4 and 1"1/2



3242189 HANDGRIP FOR DRAIN TAP  
for DRAIN TAP ø 1"1/2F e 1"1/4F



3180061 TAPE F. COUPLING SEALING LOCTITE 55-150m  
length 150 metri  
suitable for hot / cold drinking water. gas  
replaces pastes, hemp and sealing tapes  
it allows the correct replacement of fittings  
compliant with the latest regulatory requirements  
Drinking water (C.S.A. italian certified.  
in line with KTW standard and WRC approved )  
IMQ-UNICIG gas-water,  
compliant with UNI EN 51-2 class Arp  
DVGW and DIN 30660 approved



# COMETTO

Suitable for:

3179010 FITTINGS SEALING TAPE LOCTITE 55 - 50 m  
length 50 mt  
suitable to hot and cold drinking water, gas  
replaces pastes, hemp and sealing tapes  
it allows the repositioning of couplings  
in compliance with the latest regulations  
Drinking water (Italian certification by C.S.A.,  
according to standard KTW and WRC approved)  
gas - water IMQ-UNICIG.  
compliant with UNI EN 51-2 class Arp  
approved by DVGW and DIN 30660



1180001 GREASE KLUBERSYNTH UH1 14-151 45 g  
food safe grease for lubrication  
of all friction points  
ideal for water and steam taps  
operating temperature -45°/+120°  
beige color - NSF H1 certified  
hot and cold water resistant  
high anti-corrosion power  
can replace vaseline



3356128 PIN ø 5x30 mm  
complete with blind nut



3180039 VASELINE WUERTH 750 g  
for lubrication of food processing machines  
it protects chromed and rubber parts from  
weather factors, moisture resistant,  
operating temperature from -10°C up to +120°C  
from +50°C to +120 °C the grease becomes oily





**3356113 DRAIN TAP Ø 2" F**  
fixed connection Ø 2" F - fixed handle  
for Boiling pan (COMETTO)



COMETTO

**1180001 GREASE KLUBERSYNTH UH1 14-151 45 g**  
food safe grease for lubrication  
of all friction points  
ideal for water and steam taps  
operating temperature -45°/+120°  
beige color - NSF H1 certified  
hot and cold water resistant  
high anti-corrosion power  
can replace vaseline



**3180039 VASELINE WUERTH 750 g**  
for lubrication of food processing machines  
it protects chromed and rubber parts from  
weather factors, moisture resistant,  
operating temperature from -10°C up to +120°C  
from +50°C to +120 °C the grease becomes oily



Suitable for:

**3179010 FITTINGS SEALING TAPE LOCTITE 55 - 50 m**  
length 50 mt  
suitable to hot and cold drinking water, gas  
replaces pastes, hemp and sealing tapes  
it allows the repositioning of couplings  
in compliance with the latest regulations  
Drinking water (Italian certification by C.S.A.,  
according to standard KTW and WRC approved)  
gas - water IMQ-UNICIG.  
compliant with UNI EN 51-2 class Arp  
approved by DVGW and DIN 30660



**3180061 TAPE F. COUPLING SEALING LOCTITE 55-150m**  
length 150 metri  
suitable for hot / cold drinking water. gas  
replaces pastes, hemp and sealing tapes  
it allows the correct replacement of fittings  
compliant with the latest regulatory requirements  
Drinking water (C.S.A. italian certified.  
in line with KTW standard and WRC approved )  
IMQ-UNICIG gas-water,  
compliant with UNI EN 51-2 class Arp  
DVGW and DIN 30660 approved





Suitable for:

# COMETTO



**3356108 DRAIN TAP  $\varnothing$  3/4" F**  
fixed connection  $\varnothing$  3/4" F - fixed handle  
for Boiling pan (COMETTO)



COMETTO

**1180001 GREASE KLUBERSYNTH UH1 14-151 45 g**  
food safe grease for lubrication  
of all friction points  
ideal for water and steam taps  
operating temperature  $-45^{\circ}/+120^{\circ}$   
beige color - NSF H1 certified  
hot and cold water resistant  
high anti-corrosion power  
can replace vaseline



**3180039 VASELINE WUERTH 750 g**  
for lubrication of food processing machines  
it protects chromed and rubber parts from  
weather factors, moisture resistant,  
operating temperature from  $-10^{\circ}\text{C}$  up to  $+120^{\circ}\text{C}$   
from  $+50^{\circ}\text{C}$  to  $+120^{\circ}\text{C}$  the grease becomes oily



Suitable for:

**3179010 FITTINGS SEALING TAPE LOCTITE 55 - 50 m**  
length 50 mt  
suitable to hot and cold drinking water, gas  
replaces pastes, hemp and sealing tapes  
it allows the repositioning of couplings  
in compliance with the latest regulations  
Drinking water (Italian certification by C.S.A.,  
according to standard KTW and WRC approved)  
gas - water IMQ-UNICIG.  
compliant with UNI EN 51-2 class Arp  
approved by DVGW and DIN 30660



**3180061 TAPE F. COUPLING SEALING LOCTITE 55-150m**  
length 150 metri  
suitable for hot / cold drinking water. gas  
replaces pastes, hemp and sealing tapes  
it allows the correct replacement of fittings  
compliant with the latest regulatory requirements  
Drinking water (C.S.A. italian certified.  
in line with KTW standard and WRC approved )  
IMQ-UNICIG gas-water,  
compliant with UNI EN 51-2 class Arp  
DVGW and DIN 30660 approved





## Electrical gas valves and accessories

**3526141 VALVE 830 TANDEM  $\varnothing$  1/2"FF**  
 inlet  $\varnothing$  1/2" F - outlet  $\varnothing$  1/2" F  
 thermocouple fitting M10x1  
 maximum gas inlet pressure 60 mbar  
 outlet gas pressure setting range 3-50 mbar  
 room temperature 0-60°C  
 power supply 230V 50Hz



COMETTO


**2100757 CONNECTION FOR OLIVE  $\varnothing$  16 mm**  
 thread  $\varnothing$  1/2" M



**3526292 ELECTRIC COUPLING WITH CABLE**  
 cable length 1000 mm - 3 wires  
 for sit valve 830-836 TANDEM



**3020084 FITTING AND OLIVE  $\varnothing$  6 mm**




**2100724 COIL 24V**  
 for valve 830 TANDEM-836 TANDEM



**3526142 DOUBLE COIL FOR VALVE**  
 220V 50Hz  
 for VALVE 830 TANDEM-836 TANDEM



**3020083 FITTING AND OLIVE  $\varnothing$  4 mm**



**3348041 OLIVE FOR PIPE  $\varnothing$  16 mm**  
 for model PEL 23





Suitable for:


# COMETTO



Suitable for:

## Gas taps and accessories

**3348154 GAS TAP**  
 with connections and olives  
 without pilot flame  
 fittings  $\varnothing$  10 mm  
 thermocouple connection M8x1  
 pin length 27 mm  
 D-shaped pin  $\varnothing$  10x8 mm




COMETTO COM40704

COMETTO 40704

**3182022 MAGNETIC GROUP PEL SMALL HEAD**  
 head  $\varnothing$  15.5 mm - end piece  $\varnothing$  11.5 mm - length 44mm



**3182011 MAGNETIC UNIT PEL SMALL HEAD**  
 head  $\varnothing$  15 mm - end piece  $\varnothing$  11 mm - length 44 mm  
 for PEL tap models 20-21  
 for EGA tap model 25213  
 for JUNKERS tap model CH110



**3348012 GAS TAP 23S/O**  
 with pilot flame  
 with horizontal flange  
 inlet fitting M28x1.5mm  
 outlet connection M24x1.5mm  
 with flow regulator  
 thermocouple connection M10x1  
 D-shaped pin  $\varnothing$  10x8 mm  
 for Bratt pan (COMETTO) CCOR OLRG50  
 49AR1431 RRG85M ROBUSTE MLN575.08




COMETTO COM40722

**3348060 CAP WITH PIN  $\varnothing$  10x8 mm**  
 pin length 25 mm  
 for model PEL 23



**3348062 CAP WITH PIN  $\varnothing$  10x8 mm**  
 pin length 35 mm  
 for model PEL 23



**3348027 FLANGE HORIZONTAL  $\varnothing$  12/16 mm**  
 thread M24x1.5 mm  
 for model PEL 23







Suitable for:

**3348237 FLANGE HORIZONTAL  $\varnothing$  12/16 mm**  
without adjustment  
thread M24x1.5 mm  
for model PEL 23



**3182010 MAGNETIC UNIT PEL**  
head  $\varnothing$  24 mm - end piece  $\varnothing$  18 mm - length 59 mm  
thermocouple coupling M10x1  
for PEL tap model 23



**3348041 OLIVE FOR PIPE  $\varnothing$  16 mm**  
for model PEL 23



**3348036 OLIVE FOR PIPE  $\varnothing$  4 mm**  
for model PEL 21-22-24-25



**3348033 PIPE FITTING  $\varnothing$  12 mm**  
thread M24x1.5  
for model PEL 23




**3348035 PIPE FITTING  $\varnothing$  20 mm**  
thread M28x1.5  
for model PEL 23



## COMETTO

Suitable for:

**3348028 FLANGE VERTICAL  $\varnothing$  12/16 mm**  
thread M24x1.5  
for model PEL 23



**3348040 OLIVE FOR PIPE  $\varnothing$  12 mm**  
for model PEL 23



**3348042 OLIVE FOR PIPE  $\varnothing$  20 mm**  
for model PEL 23



**3348037 OLIVE FOR PIPE  $\varnothing$  6 mm**  
for model PEL 21-22-24-25



**3348034 PIPE FITTING  $\varnothing$  16 mm**  
thread M24x1.5  
for model PEL 23



**3348029 PIPE FITTING  $\varnothing$  4 mm**  
thread M10x1 mm  
for model PEL 21-22-24-25





Suitable for:

**3020078** PIPE FITTING  $\varnothing$  6 mm  
thread M10x1



# COMETTO




Suitable for:

**5014757** PIPE FITTING  $\varnothing$  6 mm  
thread M10x1 mm



## Gas valves and accessories

**3523092** MINISIT VALVE FOR FOOD-WARMER  $40 \div 110^{\circ}\text{C}$   
inlet  $\varnothing$  1/2"F - outlet  $\varnothing$  3/8"F  
thermocouple connection M9x1  
maximum gas inlet pressure 50 mbar  
ambient temperature  $0 \div 80^{\circ}\text{C}$   
capillary length 1050 mm  
bulb  $\varnothing$  5x125 mm



COMETTO COM40818

**3523038** ELBOW FLANGE MINISIT  $\varnothing$  1/2"  
with screws and OR



**2100757** CONNECTION FOR OLIVE  $\varnothing$  16 mm  
thread  $\varnothing$  1/2"M




**3523037** ELBOW FLANGE MINISIT  $\varnothing$  3/8"  
with screws and OR



**3523035** KNOB MINISIT BLACK  $\varnothing$  37 mm



**3523047** LID MINISIT



**3182003** MAGNETIC UNIT SIT  
head  $\varnothing$  25 mm - end piece  $\varnothing$  17 mm - length 56 mm  
for valve SIT AC2 - VR8-MINISIT




**3523061** NUT  $\varnothing$  1/4"x6 mm





Suitable for:

**3523060 OIL SEAL FITTING  $\varnothing$  6.5 mm**  
internal thread M10x0.75 - external thread M14x1.5



**3020082 OLIVE FOR PIPE  $\varnothing$  12 mm**  
for model PEL 22-24-25




**3001070 PIEZO IGNITER MINISIT**  
a  $\varnothing$  22 mm hole is required for the assembly  
faston M  $\varnothing$  2.4 mm



**3020079 PIPE FITTING  $\varnothing$  12 mm**  
thread  $\varnothing$  3/8" M



**3523039 SENSING ELEMENT MINISIT 30÷100°C**  
capillary length 1050 mm  
bulb  $\varnothing$  5x125 mm



## COMETTO

Suitable for:


**3348044 OLIVE FOR PIPE  $\varnothing$  10 mm**  
for model PEL 20-21-24-25



**3348041 OLIVE FOR PIPE  $\varnothing$  16 mm**  
for model PEL 23



**3001071 PIEZO IGNITER MINISIT WITH COVER**  
M faston 2.4 mm



**3523036 REDUCTION STRAIGHT  $\varnothing$  3/8" F -  $\varnothing$  1/2" F**  
in brass with internal and external thread  
internal thread  $\varnothing$  3/8" F - external thread  $\varnothing$  1/2" F  
for MINISIT flange



**5058320 TUBE NUT FITTING  $\varnothing$  10 mm**  
thread M14x1,5 mm





Suitable for:

# COMETTO



**3523091 VALVE 710 MINISIT OVEN 70÷310°C**  
 inlet  $\varnothing$  1/2"F - outlet  $\varnothing$  3/8"F  
 thermocouple connection M9x1  
 maximum gas inlet pressure 50 mbar  
 ambient temperature 0÷60°C  
 capillary length 1300 mm  
 bulb  $\varnothing$  4x75 mm  
 without cover, knob and flanges  
 for Fry top (COMETTO) CWG3



COMETTO COM40815

**3523038 ELBOW FLANGE MINISIT  $\varnothing$  1/2"**  
 with screws and OR




**3523035 KNOB MINISIT BLACK  $\varnothing$  37 mm**



**3182003 MAGNETIC UNIT SIT**  
 head  $\varnothing$  25 mm - end piece  $\varnothing$  17 mm - length 56 mm  
 for valve SIT AC2 - VR8-MINISIT



**3523060 OIL SEAL FITTING  $\varnothing$  6.5 mm**  
 internal thread M10x0.75 - external thread M14x1.5




**2100757 CONNECTION FOR OLIVE  $\varnothing$  16 mm**  
 thread  $\varnothing$  1/2"M



**3523037 ELBOW FLANGE MINISIT  $\varnothing$  3/8"**  
 with screws and OR



**3523047 LID MINISIT**



**3523061 NUT  $\varnothing$  1/4"x6 mm**



**3348044 OLIVE FOR PIPE  $\varnothing$  10 mm**  
 for model PEL 20-21-24-25





Suitable for:

**3020082 OLIVE FOR PIPE  $\varnothing$  12 mm**  
for model PEL 22-24-25



**3001070 PIEZO IGNITER MINISIT**  
a  $\varnothing$  22 mm hole is required for the assembly  
faston M  $\varnothing$  2.4 mm



**3020079 PIPE FITTING  $\varnothing$  12 mm**  
thread  $\varnothing$  3/8" M



**5058320 TUBE NUT FITTING  $\varnothing$  10 mm**  
thread M14x1,5 mm



## COMETTO



Suitable for:

**3348041 OLIVE FOR PIPE  $\varnothing$  16 mm**  
for model PEL 23



**3001071 PIEZO IGNITER MINISIT WITH COVER**  
M faston 2.4 mm



**3523036 REDUCTION STRAIGHT  $\varnothing$  3/8" F -  $\varnothing$  1/2" F**  
in brass with internal and external thread  
internal thread  $\varnothing$  3/8" F - external thread  $\varnothing$  1/2" F  
for MINISIT flange



## Heating elements

**3455192 HEATING ELEMENT 1000W 230V**  
length 790 mm - fitting M14x1 mm  
for Rotisserie electric (COMETTO) RB8  
for Salamander electric (COMETTO)



COMETTO COM50167

COMETTO 50167

**3455190 HEATING ELEMENT 2000W 220V**  
length 595 mm - width 68 mm  
fittings M12x1 mm  
for Grill electric (COMETTO)



COMETTO COM50116

COMETTO 50116



Suitable for:

# COMETTO



**3455188 HEATING ELEMENT 2000W 230V**  
length 720 mm - width 55 mm  
fittings M14x1 mm  
for Oven under cooktop electric (COMETTO) 350L



COMETTO COM50108

COMETTO 50108

Suitable for:

**3455189 HEATING ELEMENT 800W 220V**  
length 460 mm - width 80 mm  
couplings  $\varnothing$  1/4"  
operating ambient: dry  
for Bain-marie electric (COMETTO) CDE - CEE



COMETTO COM50113

COMETTO 50113

**3455187 HEATING ELEMENT 850W 220V**  
length 360 mm - width 60 mm  
connections M14x1 mm  
for BAIN MARIE SDE  
operating ambient: dry  
for Bain-marie electric (COMETTO) SDE



COMETTO COM50101

COMETTO 50101

## Hinges, catches and accessories

**3053882 CHROME-PLATED HINGE 4484**  
length 100 mm - mounting distance 60 mm



COMETTO 32200080

COMETTO 33200080

**3053442 RIGHT-LEFTHAND DOOR HINGE FOR OVEN**  
mounting distance mobile part 65 mm  
mounting distance fix part 33 mm  
length 97 mm - width 20 mm  
height 46 mm



COMETTO COM61805

## Incandescent lamps and neon lamps

**3221473 NEON LAMP FOR OVEN E10 220V**  
dimensions  $\varnothing$  10x28 mm



COMETTO COM51730

COMETTO 51730

**3221472 OVEN LAMP Ba9s 3W 52V**  
dimensions  $\varnothing$  10x28 mm



COMETTO COM51732

COMETTO 51732

Suitable for:

Suitable for:

**3221140 OVEN LAMP E14 40W 230V**  
max temperature 300°C



COMETTO COM51722

COMETTO 51722

## Knobs

**3241707 GREY KNOB  $\varnothing$  30 mm ON-OFF-PILOT**  
for USA MARKET



COMETTO IMP-28328

**3241778 KNOB GREY  $\varnothing$  70 mm**  
D-shaped hole 6x4.6 mm  
for Pot stove electric (COMETTO)



COMETTO COM64915

COMETTO 64915

## Lamp receptacles and spare parts


**3221550 CAP LAMP RECEPTACLE ORANGE  $\varnothing$  23 mm**



COMETTO COM51403

COMETTO 51403

**3221549 LAMP RECEPTACLE FOR INDICATOR LIGHT**  
mounting hole  $\varnothing$  22 mm



COMETTO COM51401

COMETTO 51401

**3221550 CAP LAMP RECEPTACLE ORANGE  $\varnothing$  23 mm**



COMETTO COM51403

COMETTO 51403

**3221473 NEON LAMP FOR OVEN E10 220V**  
dimensions  $\varnothing$  10x28 mm



COMETTO COM51730

COMETTO 51730



Suitable for:

# COMETTO



Suitable for:

## Nozzles

3500177 CONICAL GAS JET M17x1 ø 0.70 mm



COMETTO 40558

3500181 CONICAL GAS JET M17x1 ø 0.95 mm



COMETTO 40610

## Pilot burners and accessories

**3020006 THREE-FLAME PILOT BURNER SIT**  
multigas with jet ø 0.20 mm  
with 3 positions bracket  
for Boiling pan (COMETTO) CR150 - MLN566.08  
for Kitchen (COMETTO) FORNEAU COMPACT 53911 - LJ.3



COMETTO COM40802  
COMETTO 40802

COMETTO 40800

COMETTO 40801

3020104 BRACKET CLAMP 3 POSITIONS



3020103 BRACKET 3 POSITIONS



3020109 DEFLECTOR 2 FLAMES




3020110 DEFLECTOR 3 FLAMES




5048713 DEFLECTOR 3 FLAMES



3020083 FITTING AND OLIVE ø 4 mm



3020084 FITTING AND OLIVE ø 6 mm







Suitable for:

**3020102 HEXAGON HEAD SCREW 3/16"x18 mm**



# COMETTO



Suitable for:

**3001003 IGNITION PLUG ROUND  $\varnothing$  7x44 mm**  
M faston M4x1 mm  
overall length 65 mm  
for Bratt pan (COMETTO) LUXE



**3020060 IGNITION PLUG ROUND  $\varnothing$  7x44 mm**  
M faston M 4x1 mm  
overall length 82 mm  
model CB505/021 Junkers  
for model P502F



COMETTO COM40830

COMETTO 40830

**3020124 IGNITION PLUG ROUND  $\varnothing$  7x44 mm**  
connection  $\varnothing$  2.4 mm  
overall length 58 mm



**3020294 IGNITION PLUG ROUND  $\varnothing$  7x44 mm**  
M faston M4x1 mm  
overall length 67 mm



**3020365 IGNITION PLUG ROUND  $\varnothing$  7x44 mm**  
connection  $\varnothing$  2.4 mm  
overall length 52 mm



**3020082 OLIVE FOR PIPE  $\varnothing$  12 mm**  
for model PEL 22-24-25



**3348036 OLIVE FOR PIPE  $\varnothing$  4 mm**  
for model PEL 21-22-24-25



**5027953 OLIVE FOR PIPE  $\varnothing$  4 mm**  
for COPRECI CAL3200



**3020081 OLIVE FOR PIPE  $\varnothing$  6 mm**





Suitable for:

**3020097 PILOT AERATION REGULATOR**  
internal  $\varnothing$  7 mm - external  $\varnothing$  9 mm  
height 10 mm



**3020156 PILOT JET  $\varnothing$  0.25 mm**



**3020055 PILOT JET  $\varnothing$  0.35 mm**



**3500269 PILOT JET  $\varnothing$  0.45 mm**



**3020308 PILOT WITH NOZZLE  $\varnothing$  0.40 mm**



**3020106 PILOT WITH 0.25 mm  $\varnothing$  JET**



**3020079 PIPE FITTING  $\varnothing$  12 mm**  
thread  $\varnothing$  3/8" M



# COMETTO

Suitable for:

**3020054 PILOT JET  $\varnothing$  0.20 mm**



**4058525 PILOT JET  $\varnothing$  0.30 mm**



**5015516 PILOT JET  $\varnothing$  0.40 mm**



**5075989 PILOT JET  $\varnothing$  0.70 mm**



**3020105 PILOT WITH 0.20 mm  $\varnothing$  JET**



**3020107 PILOT WITH 0.35 mm  $\varnothing$  JET**



**3020077 PIPE FITTING  $\varnothing$  4 mm**  
thread M10x1





Suitable for:

**5033138** PIPE FITTING  $\varnothing$  4 mm  
thread  $\varnothing$  1/8" M



**5014757** PIPE FITTING  $\varnothing$  6 mm  
thread M10x1 mm



# COMETTO




Suitable for:

**3020078** PIPE FITTING  $\varnothing$  6 mm  
thread M10x1




## Selector switches

**3057014** SELECTOR SWITCH 0-1 POSITIONS  
contact capacity 16A 250V - max 150°C  
D-shaped pin  $\varnothing$  6x4.6 mm  
back connection for thermostat



COMETTO COM50022


**3057073** SELECTOR SWITCH 0-1 0-1 POSITIONS  
contact capacity 16A 250V - max 150°C  
D-shaped pin  $\varnothing$  6x4.6 mm



COMETTO COM50025

COMETTO 50025


**3057023** SELECTOR SWITCH 0-6 POSITIONS  
contact capacity 32A 250V - max 150°C  
D shaft  $\varnothing$  6x4.6 mm  
for Bratt pan electric (COMETTO)  
for Hot plate electric (COMETTO)  
for Pot stove electric (COMETTO)



COMETTO COM50002

COMETTO 50002

**3057256** SELECTOR SWITCH 4 POSITIONS  
contact capacity 16A 250V - max 150°C  
D-shaped pin  $\varnothing$  6x4.6 mm  
for Oven under cooktop (COMETTO)



COMETTO COM50026

COMETTO 50026

## Sparking and detection plugs

**3001003** IGNITION PLUG ROUND  $\varnothing$  7x44 mm  
M faston M4x1 mm  
overall length 65 mm  
for Bratt pan (COMETTO) LUXE



COMETTO COM40830

COMETTO 40830



Suitable for:

# COMETTO



Suitable for:

## Taps for tank refilling

**2102024 COLD WATER INLET TAP  $\varnothing$  1/2" MM**

**3759137 TAP KNOB - BLUE**



COMETTO COM61221

**2102023 HOT WATER INLET TAP  $\varnothing$  1/2" MM**

**3759146 TAP KNOB - RED**



COMETTO COM61220

## Terminals and electrical connectors

**3051007 FASTON 100 PCS PACKING UNIT**  
nickel-plated metal made  
eyelet terminal 5 mm  
for cable section from  $\varnothing$  1 to 2.5 mm  
max temperature +300°C



COMETTO COM51625

## Thermocouples and accessories

**3440039 THERMOCOUPLE SIT M9x1 150 cm**  
for Boiling pan (COMETTO) MLN566.08  
for Bratt pan (COMETTO) CCOR OLRG50 - LRG50M  
ROBUSTE MLN575.08

**3440839 THERMOCOUPLE SIT M9x1 150 cm - 10 PCS**



COMETTO COM40811

COMETTO COM40811

**3440839 THERMOCOUPLE SIT M9x1 150 cm - 10 PCS**



COMETTO COM40811



**Thermostats**

**3444903 SINGLE-PHASE THERMOSTAT 220°C**  
 with manual reset  
 capillary length 900 mm  
 bulb  $\varnothing$  6x80 mm - with stuffing gland fitting M9x1



COMETTO COM50020

**3744002 THERMOSTAT SINGLE-PHASE 230°C**  
 with manual reset  
 capillary length 1200 mm  
 bulb  $\varnothing$  6x77 mm - with stuffing gland fitting M9x1  
 with tank sealing fitting complete M12x1  
 for Bratt pan (COMETTO)  
 for Fryer (COMETTO)



COMETTO COM50069

COMETTO 50069


**3444361 THERMOSTAT SINGLE-PHASE 50-320°C**  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 capillary 950 mm - 16A 250V  
 bulb  $\varnothing$  3x160 mm



COMETTO COM50014


COMETTO 50014

**3444562 THREE-PHASE THERMOSTAT 100-350°C**  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 covered capillary length 1800 mm - 16A 230V  
 bulb  $\varnothing$  6x80 mm



COMETTO COM50042

**3444088 THREE-PHASE THERMOSTAT 30-110°C**  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 capillary length 900 mm - 10A 400V  
 bulb  $\varnothing$  6x140 mm - with stuffing gland fitting M9x1



COMETTO COM50011

COMETTO 50011

**Timers**

**3446161 TIMER 12 HOURS C53**  
 manually set mechanical timer  
 manually set cycle 12 hours  
 contact capacity 16A 250V  
 max temperature 125°C  
 2 normally closed contacts  
 2 normally closed contacts  
 complete with silkscreen printed plate and knob  
 dimensions 49.5x58 mm depth 52 mm



COMETTO

**3446162 TIMER 24 HOURS C53**  
 manually set mechanical timer  
 manually set cycle 24 hours  
 contact capacity 16A 250V  
 max temperature 125°C  
 2 normally closed contacts  
 2 normally closed contacts  
 complete with silkscreen printed plate and knob  
 dimensions 49.5x58 mm depth 52 mm



COMETTO



Suitable for:

# COMETTO



## 3446160 TIMER 6 HOURS C53

manually set mechanical timer  
manually set cycle 6 hours  
contact capacity 16A 250V  
max temperature 125°C  
2 normally closed contacts  
complete with silkscreen printed plate and knob  
dimensions 49.5x58 mm depth 52 mm



COMETTO

## 3446158 TIMER 60 MINUTES C53

manually set mechanical timer  
manually set cycle 60 minutes  
contact capacity 16A 250V  
max temperature 125°C  
2 normally closed contacts  
complete with silkscreen printed plate and knob  
dimensions 49.5x58 mm depth 52 mm



COMETTO

## 3446183 TIMER 60 MINUTES C53

manually set mechanical timer  
manually set cycle 60 minutes  
contact capacity 16A 250V  
complete with silkscreen printed plate and knob  
for Rotisserie electric (COMETTO) RB8  
for Salamander (COMETTO)



COMETTO 50501

COMETTO 50501+50528+50517

The data herewith contained may change without notice and LF SpA cannot be held responsible for possible errors stated or resulting by the use of this document. All rights reserved. No part of this publication may be reproduced without written permission by LF SpA.



## Distributing Components, Spare Parts & Accessories in original quality worldwide

- 
- LF SpA HEADQUARTERS**  
via Voltri, 80 - 47522 Cesena (FC) ITALY  
Tel. +39 0547 34 11 11 - Fax +39 0547 34 11 10  
[www.lfircambi724.it](http://www.lfircambi724.it) - [info@lfircambi.it](mailto:info@lfircambi.it)  
Export Dept. Tel. +39 0547 34 11 50 - Fax +39 0547 34 11 55  
[www.lfspareparts724.com](http://www.lfspareparts724.com) - [export@lfspareparts.com](mailto:export@lfspareparts.com)
- LF SpA HOUSEHOLD COMPONENTS DIVISION**  
Via Padriciano, 99 - AREA Science Park - 34149 Trieste (TS) ITALY  
Tel. +39 0547 34 12 42 - Fax +39 0547 34 12 48  
[www.lfspareparts724.com](http://www.lfspareparts724.com) - [info@lfspareparts.com](mailto:info@lfspareparts.com)
- EPGC Sas FRANCE**  
13, Rue des Forts - 59960 Neuville en Ferrain  
Tel. +33 (0)3 20 25 06 21 - Fax +33 (0)3 20 25 34 12  
[www.epgc.com](http://www.epgc.com) - [epgc@epgc.com](mailto:epgc@epgc.com)
- LF GmbH GERMANY**  
Junkersstrasse, 3 - D-82178 Puchheim - München  
Tel. +49 89 89 45 78 66 - Fax +49 89 89 45 78 88  
[www.lfersatzteile724.de](http://www.lfersatzteile724.de) - [info@lfersatzteile.de](mailto:info@lfersatzteile.de)
- LF China REPUBLIC OF CHINA**  
Room 403, No.2, Huadu Mansion, Lane 422, Huanghua Rd.  
Minhang Dist. - 201103 Shanghai  
Tel. +86 (0)21 33 53 66 31 - Fax +86 (0)21 33 53 66 32  
[www.lfspareparts724.com](http://www.lfspareparts724.com) - [china@lfspareparts.com](mailto:china@lfspareparts.com)
- OOO LF RUSSIAN FEDERATION**  
Ul. Anatoliya Zhivova, 8 - office 1 - 123100 Moscow  
Tel./Fax +7 495 725 26 53  
[www.lfspareparts724.ru](http://www.lfspareparts724.ru) - [info@lfspareparts.ru](mailto:info@lfspareparts.ru)
- LF Repuestos Horeca S.L.U. SPAIN**  
Poligono Industrial Carpetania - C/Miguel Faraday, 8 - 28906 Getafe  
Tel. +34 91 477 91 00 - Fax +34 91 477 90 81  
[www.lfrepuestos-horeca724.es](http://www.lfrepuestos-horeca724.es) - [info@lfrepuestos.es](mailto:info@lfrepuestos.es)
- LF Scandinavia Aps - LF Spareparts S.p.A. DENMARK**  
Nupark, 51 - 7500 Holstebro  
Tel. +45 70 70 77 33  
[www.lfspareparts724.dk](http://www.lfspareparts724.dk) - [denmark@lfspareparts.dk](mailto:denmark@lfspareparts.dk)
- LF SpA Cesena (IT) Swiss Branch Steinhausen SWITZERLAND**  
Sennweidstrasse, 45 - CH-6312 Steinhausen  
Tel. +41 (0)41 760 15 80/1 - Fax +41 (0)41 760 15 85  
[www.lfersatzteile724.ch](http://www.lfersatzteile724.ch) - [info@lfersatzteile.ch](mailto:info@lfersatzteile.ch)
- LF Spare Parts Ltd. UNITED KINGDOM**  
A10a Lakeside Business Park, Broadway Lane  
South Cerney, Gloucestershire GL7 5XL  
Tel. +44 (0)1285 86 16 25 - Fax +44 (0)1285 86 39 49  
[www.lfspareparts724.co.uk](http://www.lfspareparts724.co.uk) - [info@lfspareparts.co.uk](mailto:info@lfspareparts.co.uk)
- LF Central Est Europe S.r.o. CZECH REPUBLIC**  
Antala Staska 1859/34  
14000 Praha 4 - KRC  
Tel. +420 730 156 910  
[www.lfspareparts724.cz](http://www.lfspareparts724.cz) - [info@lfspareparts.cz](mailto:info@lfspareparts.cz)
- LF SPARE PARTS INC. USA**  
Legal address:  
155 Office Plaza Dr - Suite A - Tallahassee, FL 32301  
Business/Mailing address:  
1100 South Tower, 225 Peachtree St., N.E. - Atlanta, GA 30303, USA  
Tel. +1-404-525-2600 - Fax +1-404-586-3528  
[www.lfspareparts724.us](http://www.lfspareparts724.us) - [info@lfspareparts.us](mailto:info@lfspareparts.us)  
Tel. West Coast and Midwest: 206-349-1525 Sauro  
Tel. East Coast and the Caribbean: 786-817-1764 Luis
- 
- AUSTRALIA AND NEW ZEALAND**  
[www.lfspareparts724.com](http://www.lfspareparts724.com)  
[andrea.calvio@lfspareparts.com](mailto:andrea.calvio@lfspareparts.com)
- AUSTRIA**  
[www.lfersatzteile724.at](http://www.lfersatzteile724.at)  
[info@lfersatzteile.at](mailto:info@lfersatzteile.at)
- BALKAN COUNTRIES**  
[www.lfspareparts724.com](http://www.lfspareparts724.com)  
[matija.ramov@lfspareparts.com](mailto:matija.ramov@lfspareparts.com)
- BALTIC COUNTRIES**  
[www.lfspareparts724.com](http://www.lfspareparts724.com)  
[inara.silina@lfspareparts.com](mailto:inara.silina@lfspareparts.com)
- LATIN AMERICA AND THE CARRIBEANS**  
[www.lfrepuestos-horeca724.es](http://www.lfrepuestos-horeca724.es)  
[export@lfrepuestos.es](mailto:export@lfrepuestos.es)
- POLAND**  
[www.lfspareparts724.pl](http://www.lfspareparts724.pl)  
[info@lfspareparts.pl](mailto:info@lfspareparts.pl)
- SOUTH KOREA**  
[www.lfspareparts724.com](http://www.lfspareparts724.com)  
[fabio.doni@lfspareparts.com](mailto:fabio.doni@lfspareparts.com)
- TURKEY**  
[www.lfyedekparca724.com](http://www.lfyedekparca724.com)  
[export@lfspareparts.com](mailto:export@lfspareparts.com)