



# Spare parts for the professional sector: Cooking equipment



Suitable for:

# ELIWELL



This catalogue is automatically generated.  
Therefore, the sequence of the items might  
not be always shown at best.  
Updates will be issued in case of additions  
and/or amendments.

*Suitable universal spare parts may not be included*





Suitable for:

# ELIWELL



Suitable for:

## Electronic controllers

**3445375 CONTROLLER ELIWELL ID PLUS 902**  
 230V 50/60Hz  
 1 relay output 8A for compressor  
 1 selectable NTC/PTC/PT1000 probe (not included)  
 1 programmable digital/temperature input  
 TTL input for copy card connection  
 front dimension 74x32xdepth 59 mm  
 mounting hole 71x29 mm



ELIWELL EW11D10XB4780  
 ELIWELL IC11C10XHD700  
 ELIWELL IC11C00TCF700  
 ELIWELL IC11C00THD700  
 ELIWELL IC11D00TCD700  
 ELIWELL IC16C00TCA700  
 ELIWELL IC16D00TCD700  
 ELIWELL IC17C00TCA700

ELIWELL IC11C10MHD700  
 ELIWELL IC11C00TCA700  
 ELIWELL IC11C00TCH700  
 ELIWELL IC11D10XCD700  
 ELIWELL IC11D00THA700  
 ELIWELL IC16C00TCD700  
 ELIWELL IC16D00THA700  
 ELIWELL IDP11D0700000

ELIWELL IC11C10XCD700  
 ELIWELL IC11C00TCD700  
 ELIWELL IC11C00THA700  
 ELIWELL IC11D00TCA700  
 ELIWELL IC11D00THD700  
 ELIWELL IC16D00TCA700  
 ELIWELL IC16D00THF700  
 ELIWELL T1B1CC300

**3445157 PROBE NTC PVC 1500 mm**  
 probe 2 wires - temperature range -30°+80°C  
 bulb ø 6x40 mm



ELIWELL SN8P0A1500

**3445156 PROBE NTC PVC 3000 mm**  
 temperature range -30+80°C  
 bulb ø 6x40 mm



ELIWELL SN8P0A3000

**3445167 PROBE NTC TPE IP68 1500 mm**  
 temperature range -50+110°C  
 bulb ø 5x20 mm watertight



ELIWELL SN8T6H1502

**3445184 PROBE NTC TPE STEEL IP68 1500 mm**  
 temperature range -40+110°C  
 bulb ø 6x40 mm watertight



ELIWELL SN8T6A1502

**3445028 PROBE NTC PVC 4000 mm**  
 temperature field -30+80°C  
 bulb ø 6x20 mm



**3445335 PROBE NTC TPE IP68 3000 mm**  
 temperature range -50+110°C  
 bulb ø 5x20 mm watertight



ELIWELL SN8T6H3002

**3445154 PROBE NTC TPE STEEL IP68 3000 mm**  
 temperature range -40+110°C  
 bulb ø 6x40 mm watertight



ELIWELL SN8T6A3002



Suitable for:

**3445379** PROBE PT1000 IP68 1500 mm  
temperature range -50+110°C  
bulb ø 6x20 mm watertight



ELIWELL SN9DAE11502C6

**3445070** PTC PVC PROBE 1500 mm  
2-wire probe temperature range -30+80°C  
bulb ø 6x40 mm



ELIWELL SN7P0A1500

**3445913** SILICONE PROBE NTC 1500 mm  
temperature range -50+110°C  
bulb ø 6x40 mm



ELIWELL SN8S0A1500

**3445183** SILICONE PTC PROBE 3000 mm  
2-wire probe temperature range -55+150°C  
bulb ø 6x40 mm



ELIWELL SN7S0A3000

**3445110** TRANSFORMER 230V/12V 3VA  
primary tension 230Vca 50/60Hz  
secondary tension 12Vca 3VA  
room temperature 0+60°C  
screw terminal block  
IMQ approved



ELIWELL EWTM3

ELIWELL TF111173

# ELIWELL



Suitable for:

**3445380** PROBE PT1000 IP68 3000 mm  
temperature range -50+110°C  
bulb ø 6x20 mm watertight



ELIWELL SN9DAE13002C6

**3445107** PTC PVC PROBE 3000 mm  
2-wire probe temperature range -30+80°C  
bulb ø 6x40 mm



ELIWELL SN7P0A3000

**3445155** SILICONE PROBE NTC 3000 mm  
temperature range -50+110°C  
bulb ø 6x40 mm



ELIWELL SN8S0A3000

**3445959** SILICONE PTC PROBE 5000 mm  
temperature range -55+150°C  
bulb ø 6x40 mm



ELIWELL SN7S0A5000

**3445111** TRANSFORMER 24V/12V 3VA  
primary tension 24Vca 50/60Hz  
secondary tension 12Vca 3VA  
room temperature 0+60°C  
screw terminal block  
IMQ approved



ELIWELL EWTM3

ELIWELL TF111115



Suitable for:

# ELIWELL



**3445399 CONTROLLER ELIWELL ID PLUS 902**  
 12Vac/dc  
 1 relay output 8A for compressor  
 1 selectable NTC/PTC/PT1000 probe (not included)  
 1 programmable digital/temperature input  
 TTL input for copy card connection  
 front dimension 74x32x59 mm  
 mounting hole 71x29 mm



ELIWELL IC11C10XCD300  
 ELIWELL IC11C00TCA300  
 ELIWELL IC11C00TCH300  
 ELIWELL IC11C00THD300  
 ELIWELL IC11D00TCA300  
 ELIWELL IC16C00TCA300  
 ELIWELL IC16D00TCD300  
 ELIWELL T1A1ACH300

ELIWELL IC11C10XHD300  
 ELIWELL IC11C00TCD300  
 ELIWELL IC11C00TCL300  
 ELIWELL IC11C00THF300  
 ELIWELL IC11D00TCD300  
 ELIWELL IC16C00TCD300  
 ELIWELL IC17C00TCA300  
 ELIWELL T1B1CCH300

ELIWELL IC11C10XHD700  
 ELIWELL IC11C00TCF300  
 ELIWELL IC11C00THA300  
 ELIWELL IC11D10XCD300  
 ELIWELL IC11D00TCH300  
 ELIWELL IC16D00TCA300  
 ELIWELL IDP11D0300000

Suitable for:

**3445157 PROBE NTC PVC 1500 mm**  
 probe 2 wires - temperature range -30°+80°C  
 bulb ø 6x40 mm



ELIWELL SN8P0A1500

**3445156 PROBE NTC PVC 3000 mm**  
 temperature range -30+80°C  
 bulb ø 6x40 mm



ELIWELL SN8P0A3000

**3445167 PROBE NTC TPE IP68 1500 mm**  
 temperature range -50+110°C  
 bulb ø 5x20 mm watertight



ELIWELL SN8T6H1502

**3445184 PROBE NTC TPE STEEL IP68 1500 mm**  
 temperature range -40+110°C  
 bulb ø 6x40 mm watertight



ELIWELL SN8T6A1502

**3445028 PROBE NTC PVC 4000 mm**  
 temperature field -30+80°C  
 bulb ø 6x20 mm



**3445335 PROBE NTC TPE IP68 3000 mm**  
 temperature range -50+110°C  
 bulb ø 5x20 mm watertight



ELIWELL SN8T6H3002

**3445154 PROBE NTC TPE STEEL IP68 3000 mm**  
 temperature range -40+110°C  
 bulb ø 6x40 mm watertight



ELIWELL SN8T6A3002



Suitable for:

**3445379 PROBE PT1000 IP68 1500 mm**  
temperature range -50+110°C  
bulb ø 6x20 mm watertight



ELIWELL SN9DAE11502C6

**3445070 PTC PVC PROBE 1500 mm**  
2-wire probe temperature range -30+80°C  
bulb ø 6x40 mm



ELIWELL SN7P0A1500

**3445913 SILICONE PROBE NTC 1500 mm**  
temperature range -50+110°C  
bulb ø 6x40 mm



ELIWELL SN8S0A1500

**3445183 SILICONE PTC PROBE 3000 mm**  
2-wire probe temperature range -55+150°C  
bulb ø 6x40 mm



ELIWELL SN7S0A3000

**3445110 TRANSFORMER 230V/12V 3VA**  
primary tension 230Vca 50/60Hz  
secondary tension 12Vca 3VA  
room temperature 0+60°C  
screw terminal block  
IMQ approved



ELIWELL EWTM3

ELIWELL TF111173

# ELIWELL



Suitable for:

**3445380 PROBE PT1000 IP68 3000 mm**  
temperature range -50+110°C  
bulb ø 6x20 mm watertight



ELIWELL SN9DAE13002C6

**3445107 PTC PVC PROBE 3000 mm**  
2-wire probe temperature range -30+80°C  
bulb ø 6x40 mm



ELIWELL SN7P0A3000

**3445155 SILICONE PROBE NTC 3000 mm**  
temperature range -50+110°C  
bulb ø 6x40 mm



ELIWELL SN8S0A3000

**3445959 SILICONE PTC PROBE 5000 mm**  
temperature range -55+150°C  
bulb ø 6x40 mm



ELIWELL SN7S0A5000

**3445111 TRANSFORMER 24V/12V 3VA**  
primary tension 24Vca 50/60Hz  
secondary tension 12Vca 3VA  
room temperature 0+60°C  
screw terminal block  
IMQ approved



ELIWELL EWTM3

ELIWELL TF111115



Suitable for:

# ELIWELL



**3445376 CONTROLLER ELIWELL ID PLUS 961**  
 230V 50/60Hz  
 1 relay output 2Hp for compressor  
 1 selectable NTC/PTC/PT1000 probe (not included)  
 1 programmable digital/temperature input  
 pause defrosting  
 TTL input for copy card connection  
 front dimension 74x32xdepth 59 mm  
 mounting hole 71x29 mm



ELIWELL IDP17D0700000  
 ELIWELL ID11DM0XCD700  
 ELIWELL ID16C00TCA700  
 ELIWELL ID17C00TCA700

ELIWELL ID11C00TCA700  
 ELIWELL ID11D00TCA700  
 ELIWELL ID16D10XCH700  
 ELIWELL ID17D00TCA700

ELIWELL ID11D10XCH700  
 ELIWELL ID11D00TCA780  
 ELIWELL ID16D00TCA700

Suitable for:

**3445157 PROBE NTC PVC 1500 mm**  
 probe 2 wires - temperature range -30°+80°C  
 bulb ø 6x40 mm



ELIWELL SN8P0A1500

**3445156 PROBE NTC PVC 3000 mm**  
 temperature range -30+80°C  
 bulb ø 6x40 mm



ELIWELL SN8P0A3000

**3445167 PROBE NTC TPE IP68 1500 mm**  
 temperature range -50+110°C  
 bulb ø 5x20 mm watertight



ELIWELL SN8T6H1502

**3445184 PROBE NTC TPE STEEL IP68 1500 mm**  
 temperature range -40+110°C  
 bulb ø 6x40 mm watertight



ELIWELL SN8T6A1502

**3445028 PROBE NTC PVC 4000 mm**  
 temperature field -30+80°C  
 bulb ø 6x20 mm



**3445335 PROBE NTC TPE IP68 3000 mm**  
 temperature range -50+110°C  
 bulb ø 5x20 mm watertight



ELIWELL SN8T6H3002

**3445154 PROBE NTC TPE STEEL IP68 3000 mm**  
 temperature range -40+110°C  
 bulb ø 6x40 mm watertight



ELIWELL SN8T6A3002



Suitable for:

**3445379** PROBE PT1000 IP68 1500 mm  
temperature range -50+110°C  
bulb ø 6x20 mm watertight



ELIWELL SN9DAE11502C6

**3445070** PTC PVC PROBE 1500 mm  
2-wire probe temperature range -30+80°C  
bulb ø 6x40 mm



ELIWELL SN7P0A1500

**3445913** SILICONE PROBE NTC 1500 mm  
temperature range -50+110°C  
bulb ø 6x40 mm



ELIWELL SN8S0A1500

**3445183** SILICONE PTC PROBE 3000 mm  
2-wire probe temperature range -55+150°C  
bulb ø 6x40 mm



ELIWELL SN7S0A3000

**3445110** TRANSFORMER 230V/12V 3VA  
primary tension 230Vca 50/60Hz  
secondary tension 12Vca 3VA  
room temperature 0+60°C  
screw terminal block  
IMQ approved



ELIWELL EWTM3

ELIWELL TF111173

# ELIWELL



Suitable for:

**3445380** PROBE PT1000 IP68 3000 mm  
temperature range -50+110°C  
bulb ø 6x20 mm watertight



ELIWELL SN9DAE13002C6

**3445107** PTC PVC PROBE 3000 mm  
2-wire probe temperature range -30+80°C  
bulb ø 6x40 mm



ELIWELL SN7P0A3000

**3445155** SILICONE PROBE NTC 3000 mm  
temperature range -50+110°C  
bulb ø 6x40 mm



ELIWELL SN8S0A3000

**3445959** SILICONE PTC PROBE 5000 mm  
temperature range -55+150°C  
bulb ø 6x40 mm



ELIWELL SN7S0A5000

**3445111** TRANSFORMER 24V/12V 3VA  
primary tension 24Vca 50/60Hz  
secondary tension 12Vca 3VA  
room temperature 0+60°C  
screw terminal block  
IMQ approved



ELIWELL EWTM3

ELIWELL TF111115



Suitable for:

# ELIWELL



## 7104861 DIGITAL THERMOMETER ELIWELL EM300 NTC

power supply 230V  
thermometer setting range -50+110°C  
room temperature -5+55°C  
NTC type probe (not included)  
connections with screw terminal box  
front dimensions 76x35x70 mm  
mounting hole 71x29mm



ELIWELL TM10D0000D700

## 3445156 PROBE NTC PVC 3000 mm

temperature range -30+80°C  
bulb ø 6x40 mm



ELIWELL SN8P0A3000

## 3445167 PROBE NTC TPE IP68 1500 mm

temperature range -50+110°C  
bulb ø 5x20 mm watertight



ELIWELL SN8T6H1502

## 3445184 PROBE NTC TPE STEEL IP68 1500 mm

temperature range -40+110°C  
bulb ø 6x40 mm watertight



ELIWELL SN8T6A1502

## 3445398 SILICONE PROBE NTC 1500 mm

2-wire probe temperature range -50+120°C  
bulb ø 6x50 mm



Suitable for:

## 3445157 PROBE NTC PVC 1500 mm

probe 2 wires - temperature range -30+80°C  
bulb ø 6x40 mm



ELIWELL SN8P0A1500

## 3445028 PROBE NTC PVC 4000 mm

temperature field -30+80°C  
bulb ø 6x20 mm



## 3445335 PROBE NTC TPE IP68 3000 mm

temperature range -50+110°C  
bulb ø 5x20 mm watertight



ELIWELL SN8T6H3002

## 3445154 PROBE NTC TPE STEEL IP68 3000 mm

temperature range -40+110°C  
bulb ø 6x40 mm watertight



ELIWELL SN8T6A3002

## 3445913 SILICONE PROBE NTC 1500 mm

temperature range -50+110°C  
bulb ø 6x40 mm



ELIWELL SN8S0A1500





Suitable for:

**3445155 SILICONE PROBE NTC 3000 mm**  
temperature range -50+110°C  
bulb ø 6x40 mm



ELIWELL SN8S0A3000

**3445111 TRANSFORMER 24V/12V 3VA**  
primary tension 24Vca 50/60Hz  
secondary tension 12Vca 3VA  
room temperature 0±60°C  
screw terminal block  
IMQ approved



ELIWELL EWTCM3

ELIWELL TF111115

**5073146 KIT THERMOSTAT IC902 PTC/NTC**  
power 230V  
thermostat setting range -50+140°C  
ON-OFF control with one actuation point only  
1 output on exchange relay 8(3)A 250V  
ambient temperature -5+55°C  
probe type PTC (included)  
connections by screw terminal block  
front dimensions 74x32x59 mm  
mounting hole 71x29mm



ELIWELL IC11W00TCD701

**3445156 PROBE NTC PVC 3000 mm**  
temperature range -30+80°C  
bulb ø 6x40 mm



ELIWELL SN8P0A3000

# ELIWELL



Suitable for:

**3445110 TRANSFORMER 230V/12V 3VA**  
primary tension 230Vca 50/60Hz  
secondary tension 12Vca 3VA  
room temperature 0+60°C  
screw terminal block  
IMQ approved



ELIWELL EWTCM3

ELIWELL TF111173

**3445157 PROBE NTC PVC 1500 mm**  
probe 2 wires - temperature range -30+80°C  
bulb ø 6x40 mm



ELIWELL SN8P0A1500

**3445028 PROBE NTC PVC 4000 mm**  
temperature field -30+80°C  
bulb ø 6x20 mm





Suitable for:

**3445167 PROBE NTC TPE IP68 1500 mm**  
temperature range -50+110°C  
bulb ø 5x20 mm watertight



ELIWELL SN8T6H1502

**3445184 PROBE NTC TPE STEEL IP68 1500 mm**  
temperature range -40+110°C  
bulb ø 6x40 mm watertight



ELIWELL SN8T6A1502

**3445070 PTC PVC PROBE 1500 mm**  
2-wire probe temperature range -30+80°C  
bulb ø 6x40 mm



ELIWELL SN7P0A1500

**3445398 SILICONE PROBE NTC 1500 mm**  
2-wire probe temperature range -50+120°C  
bulb ø 6x50 mm



**3445155 SILICONE PROBE NTC 3000 mm**  
temperature range -50+110°C  
bulb ø 6x40 mm



ELIWELL SN8S0A3000

# ELIWELL



Suitable for:

**3445335 PROBE NTC TPE IP68 3000 mm**  
temperature range -50+110°C  
bulb ø 5x20 mm watertight



ELIWELL SN8T6H3002

**3445154 PROBE NTC TPE STEEL IP68 3000 mm**  
temperature range -40+110°C  
bulb ø 6x40 mm watertight



ELIWELL SN8T6A3002

**3445107 PTC PVC PROBE 3000 mm**  
2-wire probe temperature range -30+80°C  
bulb ø 6x40 mm



ELIWELL SN7P0A3000

**3445913 SILICONE PROBE NTC 1500 mm**  
temperature range -50+110°C  
bulb ø 6x40 mm



ELIWELL SN8S0A1500

**3445183 SILICONE PTC PROBE 3000 mm**  
2-wire probe temperature range -55+150°C  
bulb ø 6x40 mm



ELIWELL SN7S0A3000



Suitable for:

**3445959 SILICONE PTC PROBE 5000 mm**  
temperature range  $-55+150^{\circ}\text{C}$   
bulb  $\varnothing$  6x40 mm



ELIWELL SN7S0A5000


**3445111 TRANSFORMER 24V/12V 3VA**  
primary tension 24Vca 50/60Hz  
secondary tension 12Vca 3VA  
room temperature  $0\pm 60^{\circ}\text{C}$   
screw terminal block  
IMQ approved



ELIWELL EWTCM3

ELIWELL TF111115

**2106247 SPEED ADJUSTMENT BOARD 90x83 mm**  
power supply voltage 230V 50Hz  
ambient temperature  $-10+50^{\circ}\text{C}$



ELIWELL CF10221011000

**3394331 THERMOMETER DIGITAL ELIWELL EM300 PTC**  
power supply 12V  
setting range  $-50+120^{\circ}\text{C}$   
room temperature  $-5+55^{\circ}\text{C}$   
PTC type probe (not included)  
connections with screw terminal box  
front dimensions 76x35x70 mm  
mounting hole 71x29 mm



ELIWELL TM10D0000D300

# ELIWELL



Suitable for:

**3445110 TRANSFORMER 230V/12V 3VA**  
primary tension 230Vca 50/60Hz  
secondary tension 12Vca 3VA  
room temperature  $0+60^{\circ}\text{C}$   
screw terminal block  
IMQ approved



ELIWELL EWTCM3

ELIWELL TF111173

**3445070 PTC PVC PROBE 1500 mm**  
2-wire probe temperature range  $-30+80^{\circ}\text{C}$   
bulb  $\varnothing$  6x40 mm



ELIWELL SN7P0A1500



Suitable for:

**3445107 PTC PVC PROBE 3000 mm**  
2-wire probe temperature range -30+80°C  
bulb ø 6x40 mm



ELIWELL SN7P0A3000

**3445183 SILICONE PTC PROBE 3000 mm**  
2-wire probe temperature range -55+150°C  
bulb ø 6x40 mm



ELIWELL SN7S0A3000

**3445110 TRANSFORMER 230V/12V 3VA**  
primary tension 230Vca 50/60Hz  
secondary tension 12Vca 3VA  
room temperature 0+60°C  
screw terminal block  
IMQ approved



ELIWELL EWTM3

ELIWELL TF111173

**3394320 THERMOMETER EM300LX PT100/TCJ/TCK**  
power supply 12Vac/dc  
thermostat setting range -200+1350°C  
room temperature -5+55°C  
suitable for TELEVIS SYSTEM  
alarm buzzer  
probe type PT100-TCJ-TCK (not included)  
serial port TTL  
connections by screw terminal block  
front dimensions 74x32x30 mm  
mounting hole 71x29mm



ELIWELL EM300LX

ELIWELL TM10200X0M300

**ELIWELL**



Suitable for:

**3397164 SILICONE PTC PROBE 1500 mm**  
2 wire probe temperature range -55+150°C  
bulb ø 6x40 mm



ELIWELL SN650150

ELIWELL SN650170

ELIWELL SN7S0A1500

**3445959 SILICONE PTC PROBE 5000 mm**  
temperature range -55+150°C  
bulb ø 6x40 mm



ELIWELL SN7S0A5000

**3445111 TRANSFORMER 24V/12V 3VA**  
primary tension 24Vca 50/60Hz  
secondary tension 12Vca 3VA  
room temperature 0+60°C  
screw terminal block  
IMQ approved



ELIWELL EWTM3

ELIWELL TF111115

**3445117 PROBE PT100 VETROTEX 3000 mm**  
3-wire probe temperature range 0+350°C  
bulb ø 6x100 mm



ELIWELL SN200009



Suitable for:

**3445109 PROBE TCJ VETROTEX 3000 mm**  
 2-wire probe temperature range 0+600°C  
 temperature cable max 350°C  
 error limit  $\pm 0.75\%$  below 0°C  
 response time 30 sec  
 bulb  $\varnothing$  6x100 mm



ELIWELL SN300000

ELIWELL TC0T3M

**3445110 TRANSFORMER 230V/12V 3VA**  
 primary tension 230Vca 50/60Hz  
 secondary tension 12Vca 3VA  
 room temperature 0+60°C  
 screw terminal block  
 IMQ approved



ELIWELL EWT0M3

ELIWELL TF111173

**3445015 THERMOSTAT EWPC800/T PTC**  
 power supply 220V  
 ON-OFF control with one actuation point only  
 1 changeover relay outlet 8(3)A 250V  
 2 types of programmable temperature alarms  
 room temperature  $-5 \div 65^\circ\text{C}$   
 probe type PTC (not included)  
 connections by screw terminal block  
 front dimensions 72x72x98 mm



ELIWELL T2B10CC700

**3445107 PTC PVC PROBE 3000 mm**  
 2-wire probe temperature range  $-30+80^\circ\text{C}$   
 bulb  $\varnothing$  6x40 mm



ELIWELL SN7P0A3000

# ELIWELL



Suitable for:

**3397140 THERMOCOUPLE PROBE TCK 3000 mm**  
 2 wires - temperature  $-40+1150^\circ\text{C}$   
 bulb  $\varnothing$  6x140 mm



ELIWELL SN400011

**3445111 TRANSFORMER 24V/12V 3VA**  
 primary tension 24Vca 50/60Hz  
 secondary tension 12Vca 3VA  
 room temperature  $0 \div 60^\circ\text{C}$   
 screw terminal block  
 IMQ approved



ELIWELL EWT0M3

ELIWELL TF111115

**3445070 PTC PVC PROBE 1500 mm**  
 2-wire probe temperature range  $-30+80^\circ\text{C}$   
 bulb  $\varnothing$  6x40 mm



ELIWELL SN7P0A1500

**3445183 SILICONE PTC PROBE 3000 mm**  
 2-wire probe temperature range  $-55+150^\circ\text{C}$   
 bulb  $\varnothing$  6x40 mm



ELIWELL SN7S0A3000



Suitable for:

**3445959 SILICONE PTC PROBE 5000 mm**  
temperature range -55+150°C  
bulb ø 6x40 mm



ELIWELL SN7S0A5000

**3445111 TRANSFORMER 24V/12V 3VA**  
primary tension 24Vca 50/60Hz  
secondary tension 12Vca 3VA  
room temperature 0÷60°C  
screw terminal block  
IMQ approved



ELIWELL EWTCM3

ELIWELL TF111115

**3445019 THERMOSTAT ICPLUS902 PT100/TCJ/TCK**  
power supply 24V  
thermostat setting range -150+1350°C  
control with 1 actuation point  
1 changeover relay output 8(4)A 250V  
serial port for data exchange  
ambient temperature -5÷55°C  
PT100-TCJ-TCK probe (not included)  
connections by screw terminal block  
front dimensions 78x37x64 mm  
mounting hole 71x29mm



ELIWELL ICP11J0550000

ELIWELL IC11J00THD500

ELIWELL IC11P00THD500

ELIWELL T1B1CPH500

**3445109 PROBE TCJ VETROTEX 3000 mm**  
2-wire probe temperature range 0+600°C  
temperature cable max 350°C  
error limit ±0.75% below 0°C  
response time 30 sec  
bulb ø 6x100 mm



ELIWELL SN300000

ELIWELL TCOT3M

**ELIWELL**



Suitable for:

**3445110 TRANSFORMER 230V/12V 3VA**  
primary tension 230Vca 50/60Hz  
secondary tension 12Vca 3VA  
room temperature 0+60°C  
screw terminal block  
IMQ approved



ELIWELL EWTCM3

ELIWELL TF111173

**3445117 PROBE PT100 VETROTEX 3000 mm**  
3-wire probe temperature range 0+350°C  
bulb ø 6x100 mm



ELIWELL SN200009

**3445112 PROBE TCK VETROTEX 3000 mm**  
2-wire probe temperature range 0+350°C  
error limits ±2% above 0°C  
30 seconds response time  
bulb ø 6x100 mm





Suitable for:

**3445145 TEMPERATURE PROBE PT100 1400 mm**  
2-wire probe  
bulb  $\varnothing$  4x40 mm



**ELIWELL**



Suitable for:

**3397140 THERMOCOUPLE PROBE TCK 3000 mm**  
2 wires - temperature  $-40+1150^{\circ}\text{C}$   
bulb  $\varnothing$  6x140 mm



**3445110 TRANSFORMER 230V/12V 3VA**  
primary tension 230Vca 50/60Hz  
secondary tension 12Vca 3VA  
room temperature  $0+60^{\circ}\text{C}$   
screw terminal block  
IMQ approved



ELIWELL SN400011

**3445111 TRANSFORMER 24V/12V 3VA**  
primary tension 24Vca 50/60Hz  
secondary tension 12Vca 3VA  
room temperature  $0\div 60^{\circ}\text{C}$   
screw terminal block  
IMQ approved



ELIWELL EWTCM3

ELIWELL TF111173

ELIWELL EWTCM3

ELIWELL TF111115

**3445326 THERMOSTAT ICPUS915 PT100/TCJ/TCK**  
power supply 230V  
thermostat setting range  $-150+1350^{\circ}\text{C}$   
ON-OFF control with two actuation points  
2 changeover relay outputs 8(4)A 250V  
room temperature  $-5+55^{\circ}\text{C}$   
probe type PT100-TCJ-TCK (not included)  
connections by screw terminal block  
front dimensions 78x37x64 mm  
mounting hole 71x29 mm



**3445117 PROBE PT100 VETROTEX 3000 mm**  
3-wire probe temperature range  $0+350^{\circ}\text{C}$   
bulb  $\varnothing$  6x100 mm



ELIWELL ICP22J1750000

ELIWELL IC11J10XHD700

ELIWELL IC11P00THD700

ELIWELL SN200009

**3445109 PROBE TCJ VETROTEX 3000 mm**  
2-wire probe temperature range  $0+600^{\circ}\text{C}$   
temperature cable max  $350^{\circ}\text{C}$   
error limit  $\pm 0.75\%$  below  $0^{\circ}\text{C}$   
response time 30 sec  
bulb  $\varnothing$  6x100 mm



**3445112 PROBE TCK VETROTEX 3000 mm**  
2-wire probe temperature range  $0+350^{\circ}\text{C}$   
error limits  $\pm 2\%$  above  $0^{\circ}\text{C}$   
30 seconds response time  
bulb  $\varnothing$  6x100 mm




ELIWELL SN300000

ELIWELL TCOT3M



Suitable for:

**3397140 THERMOCOUPLE PROBE TCK 3000 mm**  
2 wires - temperature -40+1150°C  
bulb ø 6x140 mm



ELIWELL SN400011

**3445111 TRANSFORMER 24V/12V 3VA**  
primary tension 24Vca 50/60Hz  
secondary tension 12Vca 3VA  
room temperature 0±60°C  
screw terminal block  
IMQ approved



ELIWELL EWTCM3

ELIWELL TF111115

**3445327 THERMOSTAT ICPUS915 PT100/TCJ/TCK**  
power supply 12V  
thermostat setting range -150+1350°C  
ON-OFF control with two actuation points  
2 exchange relay outputs 8(4)A 250V  
room temperature -5+55°C  
probe type PT100-TCJ-TCK (not included)  
connections by screwed terminal block  
front dimension 78x37x64 mm  
mounting hole 71x29 mm



ELIWELL ICP22Ji350000

ELIWELL IC11Ji0XHD300

ELIWELL IC11J00THD300

ELIWELL IC11Pi0XHD300

ELIWELL T1B1CPH300

**3445109 PROBE TCJ VETROTEX 3000 mm**  
2-wire probe temperature range 0+600°C  
temperature cable max 350°C  
error limit ±0.75% below 0°C  
response time 30 sec  
bulb ø 6x100 mm



ELIWELL SN300000

ELIWELL TC0T3M

# ELIWELL



Suitable for:

**3445110 TRANSFORMER 230V/12V 3VA**  
primary tension 230Vca 50/60Hz  
secondary tension 12Vca 3VA  
room temperature 0+60°C  
screw terminal block  
IMQ approved



ELIWELL EWTCM3

ELIWELL TF111173

**3445117 PROBE PT100 VETROTEX 3000 mm**  
3-wire probe temperature range 0+350°C  
bulb ø 6x100 mm



ELIWELL SN200009

**3445112 PROBE TCK VETROTEX 3000 mm**  
2-wire probe temperature range 0+350°C  
error limits ±2% above 0°C  
30 seconds response time  
bulb ø 6x100 mm







Suitable for:

**3397140 THERMOCOUPLE PROBE TCK 3000 mm**  
2 wires - temperature -40+1150°C  
bulb ø 6x140 mm



ELIWELL SN400011


**3445111 TRANSFORMER 24V/12V 3VA**  
primary tension 24Vca 50/60Hz  
secondary tension 12Vca 3VA  
room temperature 0±60°C  
screw terminal block  
IMQ approved



ELIWELL EWTCM3

ELIWELL TF111115

**3445328 THERMOSTAT IC912/H/PH PT100/TCJ/TCK**  
power supply 250V  
thermostat setting range -150+1350°C  
ON-OFF control with one actuation point only  
1 changeover relay output 8(3)A 250V  
room temperature -5+55°C  
probe type PT100-TCJ-TCK (not included)  
connections by screw terminal block  
front dimensions 74x32x59 mm  
mounting hole 71x29 mm



ELIWELL IC11J00THD706

**3445109 PROBE TCJ VETROTEX 3000 mm**  
2-wire probe temperature range 0+600°C  
temperature cable max 350°C  
error limit ±0.75% below 0°C  
response time 30 sec  
bulb ø 6x100 mm



ELIWELL SN300000

ELIWELL TCOT3M

# ELIWELL



Suitable for:

**3445110 TRANSFORMER 230V/12V 3VA**  
primary tension 230Vca 50/60Hz  
secondary tension 12Vca 3VA  
room temperature 0+60°C  
screw terminal block  
IMQ approved



ELIWELL EWTCM3

ELIWELL TF111173

**3445117 PROBE PT100 VETROTEX 3000 mm**  
3-wire probe temperature range 0+350°C  
bulb ø 6x100 mm



ELIWELL SN200009


**3445112 PROBE TCK VETROTEX 3000 mm**  
2-wire probe temperature range 0+350°C  
error limits ±2% above 0°C  
30 seconds response time  
bulb ø 6x100 mm





Suitable for:

**3397140 THERMOCOUPLE PROBE TCK 3000 mm**  
2 wires - temperature -40+1150°C  
bulb ø 6x140 mm



ELIWELL SN400011

**3445111 TRANSFORMER 24V/12V 3VA**  
primary tension 24Vca 50/60Hz  
secondary tension 12Vca 3VA  
room temperature 0÷60°C  
screw terminal block  
IMQ approved



ELIWELL EWTM3

ELIWELL TF111115

**3446209 TIMER EWTS950 LX 12Vac**  
1 exchange relay outlet 8(3)A 250V  
thermostat display range:  
9999h, 99h and 59', 99' and 59", 99" and 99 cents  
operating range 0÷55°C  
voltage 12Vca/dc  
connections with screw terminal  
dimensions 74x32x60 mm  
mounting hole 71x29 mm



ELIWELL ET010I0XTT300

ELIWELL ET010I0XTT301

ELIWELL E4SSSS300

**ELIWELL**



Suitable for:

**3445110 TRANSFORMER 230V/12V 3VA**  
primary tension 230Vca 50/60Hz  
secondary tension 12Vca 3VA  
room temperature 0+60°C  
screw terminal block  
IMQ approved



ELIWELL EWTM3

ELIWELL TF111173

## Measuring tools

**3394207 DIGITAL THERMOMETER -50+70°C BLACK**  
battery powered  
front battery  
working temperature 0+50°C  
accuracy ±1°C  
resolution 0.1°C  
dimensions 62.5x29.5x19 mm  
remote probe 1600 mm



ELIWELL T1M1BT0109



**Measuring tools**

**3394209 DIGITAL THERMOMETER T-2919 BLACK**  
 precision  $\pm 1^{\circ}\text{C}$   
 size frequency: every 10 seconds  
 lithium battery power 1x1,5V "LR44"  
 probe with polycarbonate cable 1500 mm  
 bulb  $\varnothing 6 \times 30$  mm  
 CE approved  
 built-in mounting hole 45x25 mm




ELIWELL T1M1BT0107

**3394231 BOX FOR DIGITAL THERMOMETER**  
 white or black  
 external dimensions 53x29x12 mm  
 internal dimensions 48x26 mm



**3394218 ADAPTER FOR DIGITAL THERMOMETER**  
 for rectangular hole 58.5x25.5 mm



**3394217 BRACKET FOR EXTERNAL FIXING**  
 external dimensions 52.5x33x18 mm  
 internal hole 41x22 mm - mounting distance 65 mm  
 for digital thermometer



**Probes**

**3445157 PROBE NTC PVC 1500 mm**  
 probe 2 wires - temperature range  $-30^{\circ}+80^{\circ}\text{C}$   
 bulb  $\varnothing 6 \times 40$  mm



ELIWELL SN8P0A1500

**3445156 PROBE NTC PVC 3000 mm**  
 temperature range  $-30+80^{\circ}\text{C}$   
 bulb  $\varnothing 6 \times 40$  mm



ELIWELL SN8P0A3000

**3445167 PROBE NTC TPE IP68 1500 mm**  
 temperature range  $-50+110^{\circ}\text{C}$   
 bulb  $\varnothing 5 \times 20$  mm watertight



ELIWELL SN8T6H1502

**3445335 PROBE NTC TPE IP68 3000 mm**  
 temperature range  $-50+110^{\circ}\text{C}$   
 bulb  $\varnothing 5 \times 20$  mm watertight



ELIWELL SN8T6H3002



Suitable for:

**3445184 PROBE NTC TPE STEEL IP68 1500 mm**  
temperature range -40+110°C  
bulb ø 6x40 mm watertight



ELIWELL SN8T6A1502

Suitable for:

**3445154 PROBE NTC TPE STEEL IP68 3000 mm**  
temperature range -40+110°C  
bulb ø 6x40 mm watertight



ELIWELL SN8T6A3002

**3445117 PROBE PT100 VETROTEX 3000 mm**  
3-wire probe temperature range 0+350°C  
bulb ø 6x100 mm



ELIWELL SN200009

**3445379 PROBE PT1000 IP68 1500 mm**  
temperature range -50+110°C  
bulb ø 6x20 mm watertight



ELIWELL SN9DAE11502C6

**3445380 PROBE PT1000 IP68 3000 mm**  
temperature range -50+110°C  
bulb ø 6x20 mm watertight



ELIWELL SN9DAE13002C6

**3445109 PROBE TCJ VETROTEX 3000 mm**  
2-wire probe temperature range 0+600°C  
temperature cable max 350°C  
error limit ±0.75% below 0°C  
response time 30 sec  
bulb ø 6x100 mm



ELIWELL SN300000

ELIWELL TCOT3M

**3397093 PROBE THERMOCOUPLE TCJ**  
2 fili - temperature 0-250°C  
bulb ø 6x100 mm  
cable length 950 mm



ELIWELL SN300017

**3445070 PTC PVC PROBE 1500 mm**  
2-wire probe temperature range -30+80°C  
bulb ø 6x40 mm



ELIWELL SN7P0A1500

**3445107 PTC PVC PROBE 3000 mm**  
2-wire probe temperature range -30+80°C  
bulb ø 6x40 mm



ELIWELL SN7P0A3000

**3445913 SILICONE PROBE NTC 1500 mm**  
temperature range -50+110°C  
bulb ø 6x40 mm



ELIWELL SN8S0A1500



Suitable for:

**3445155 SILICONE PROBE NTC 3000 mm**  
 temperature range -50+110°C  
 bulb ø 6x40 mm



ELIWELL SN8S0A3000

Suitable for:

**3397164 SILICONE PTC PROBE 1500 mm**  
 2 wire probe temperature range -55+150°C  
 bulb ø 6x40 mm



ELIWELL SN650150

ELIWELL SN650170

ELIWELL SN7S0A1500

**3445183 SILICONE PTC PROBE 3000 mm**  
 2-wire probe temperature range -55+150°C  
 bulb ø 6x40 mm



**3445959 SILICONE PTC PROBE 5000 mm**  
 temperature range -55+150°C  
 bulb ø 6x40 mm



ELIWELL SN7S0A3000

ELIWELL SN7S0A5000

**3445195 TCJ VETROTEX PROBE 700 mm**  
 2-wire probe temperature range -50+600°C  
 error limit  $\pm 0.75\%$  below 0°C  
 30 seconds response time  
 bulb ø 6x200 mm




**5048865 THERMOCOUPLE PROBE TCJ 550 mm**  
 2 wires with faston  
 bulb ø 4x40 mm



ELIWELL

ELIWELL

**3397140 THERMOCOUPLE PROBE TCK 3000 mm**  
 2 wires - temperature -40+1150°C  
 bulb ø 6x140 mm



ELIWELL SN400011


## Relays

**3351154 BASE OCTAL ES8 10A 400V**  
 8 poles



ELIWELL CN111114

**3351158 BASE UNDECAL FINDER 90.83.3**  
 11 poles - 10A 400V



ELIWELL CN111134



Suitable for:

# ELIWELL




Suitable for:

## Solenoid valves

**3120254 SOLEN. VALVE ROBERTSHAW 1 WAY 180°**  
230/240V 50/60Hz - max. temperature 90°C  
inlet 3/4" - outlet ø 13.5 mm



**3120473 ADJUSTER FOR INLET ROBERTSHAW BROWN**  
flow rate 5 L/min - tolerance +/- 15%



ELIWELL

**3120474 ADJUSTER FOR INLET ROBERTSHAW DARK BLUE**  
flow rate 6 L/min - tolerance +/- 15%



**3120478 ADJUSTER FOR INLET ROBERTSHAW GREEN**  
flow rate 11 L/min - tolerance +/- 15%



**3120479 ADJUSTER FOR INLET ROBERTSHAW GREY**  
flow rate 12 L/min - tolerance +/- 15%



**3120476 ADJUSTER FOR INLET ROBERTSHAW LIGHT BLUE**  
flow rate 9 L/min - tolerance +/- 15%



**3120475 ADJUSTER FOR INLET ROBERTSHAW ORANGE**  
flow rate 8 L/min - tolerance +/- 15%



**3120472 ADJUSTER FOR INLET ROBERTSHAW PURPLE**  
flow rate 4 L/min - tolerance +/- 15%



**3120477 ADJUSTER FOR INLET ROBERTSHAW WHITE**  
flow rate 10 L/min - tolerance +/- 15%



**3120481 ADJUSTER FOR INLET ROBERTSHAW YELLOW**  
flow rate 14.5 L/min - tolerance +/- 15%



**3120499 ADJUSTER FOR OUTLET ROBERTSHAW BLU**  
flow rate 1.2 L/min - tolerance +/- 25%



**3120484 ADJUSTER FOR OUTLET ROBERTSHAW GREEN**  
flow rate 0.8 L/min - tolerance +/- 25%





Suitable for:

**3120488 ADJUSTER FOR OUTLET ROBERTSHAW PINK**  
flow rate 3.3 L/min - tolerance +/- 20%



**3120483 ADJUSTER FOR OUTLET ROBERTSHAW YELLOW**  
flow rate 0.5 L/min - tolerance +/- 15%



**3120485 OUTLET ADJUSTER ROBERTSHAW LIGHT BROWN**  
flow rate 1.3 L/min - tolerance +/- 25%



**3120625 OUTLET REDUCER ROBERTSHAW GRIGIO**  
flow rate 0.35 L/min - tolerance +/- 10%



## ELIWELL



Suitable for:

**3120482 ADJUSTER FOR OUTLET ROBERTSHAW WHITE**  
flow rate 0.25 L/min - tolerance +/- 10%



**3120487 OUTLET ADJUSTER ROBERTSHAW DARK BROWN**  
flow rate 2.5 L/min - tolerance +/- 20%



**3120486 OUTLET ADJUSTER ROBERTSHAW LIGHT GREEN**  
flow rate 2 L/min - tolerance +/- 25%



## Transformers

**3445110 TRANSFORMER 230V/12V 3VA**  
primary tension 230Vca 50/60Hz  
secondary tension 12Vca 3VA  
room temperature 0+60°C  
screw terminal block  
IMQ approved



ELIWELL EWTM3

ELIWELL TF111173

**3445111 TRANSFORMER 24V/12V 3VA**  
primary tension 24Vca 50/60Hz  
secondary tension 12Vca 3VA  
room temperature 0÷60°C  
screw terminal block  
IMQ approved



ELIWELL EWTM3

ELIWELL TF111115

The data herewith contained may change without notice and LF SpA cannot be held responsible for possible errors stated or resulting by the use of this document. All rights reserved. No part of this publication may be reproduced without written permission by LF SpA.



## Distributing Components, Spare Parts & Accessories in original quality worldwide

- 
- LF SpA HEADQUARTERS**  
via Voltri, 80 - 47522 Cesena (FC) ITALY  
Tel. +39 0547 34 11 11 - Fax +39 0547 34 11 10  
[www.lfricambi724.it](http://www.lfricambi724.it) - [info@lfricambi.it](mailto:info@lfricambi.it)  
Export Dept. Tel. +39 0547 34 11 50 - Fax +39 0547 34 11 55  
[www.lfspareparts724.com](http://www.lfspareparts724.com) - [export@lfspareparts.com](mailto:export@lfspareparts.com)
- LF SpA HOUSEHOLD COMPONENTS DIVISION**  
Via Padriciano, 99 - AREA Science Park - 34149 Trieste (TS) ITALY  
Tel. +39 0547 34 12 42 - Fax +39 0547 34 12 48  
[www.lfspareparts724.com](http://www.lfspareparts724.com) - [info@lfspareparts.com](mailto:info@lfspareparts.com)
- EPGC Sas FRANCE**  
13, Rue des Forts - 59960 Neuville en Ferrain  
Tel. +33 (0)3 20 25 06 21 - Fax +33 (0)3 20 25 34 12  
[www.epgc.com](http://www.epgc.com) - [epgc@epgc.com](mailto:epgc@epgc.com)
- LF GmbH GERMANY**  
Junkersstrasse, 3 - D-82178 Puchheim - München  
Tel. +49 89 89 45 78 66 - Fax +49 89 89 45 78 88  
[www.lfersatzteile724.de](http://www.lfersatzteile724.de) - [info@lfersatzteile.de](mailto:info@lfersatzteile.de)
- LF China REPUBLIC OF CHINA**  
Room 403, No.2, Huadu Mansion, Lane 422, Huanghua Rd.  
Minhang Dist. - 201103 Shanghai  
Tel. +86 (0)21 33 53 66 31 - Fax +86 (0)21 33 53 66 32  
[www.lfspareparts724.com](http://www.lfspareparts724.com) - [china@lfspareparts.com](mailto:china@lfspareparts.com)
- OOO LF RUSSIAN FEDERATION**  
Ul. Anatoliya Zhivova, 8 - office 1 - 123100 Moscow  
Tel./Fax +7 495 725 26 53  
[www.lfspareparts724.ru](http://www.lfspareparts724.ru) - [info@lfspareparts.ru](mailto:info@lfspareparts.ru)
- LF Repuestos Horeca S.L.U. SPAIN**  
Poligono Industrial Carpetania - C/Miguel Faraday, 8 - 28906 Getafe  
Tel. +34 91 477 91 00 - Fax +34 91 477 90 81  
[www.lfrepuestos-horeca724.es](http://www.lfrepuestos-horeca724.es) - [info@lfrepuestos.es](mailto:info@lfrepuestos.es)
- LF Scandinavia Aps - LF Spareparts S.p.A. DENMARK**  
Nupark, 51 - 7500 Holstebro  
Tel. +45 70 70 77 33  
[www.lfspareparts724.dk](http://www.lfspareparts724.dk) - [denmark@lfspareparts.dk](mailto:denmark@lfspareparts.dk)
- LF SpA Cesena (IT) Swiss Branch Steinhausen SWITZERLAND**  
Sennweidstrasse, 45 - CH-6312 Steinhausen  
Tel. +41 (0)41 760 15 80/1 - Fax +41 (0)41 760 15 85  
[www.lfersatzteile724.ch](http://www.lfersatzteile724.ch) - [info@lfersatzteile.ch](mailto:info@lfersatzteile.ch)
- LF Spare Parts Ltd. UNITED KINGDOM**  
A10a Lakeside Business Park, Broadway Lane  
South Cerney, Gloucestershire GL7 5XL  
Tel. +44 (0)1285 86 16 25 - Fax +44 (0)1285 86 39 49  
[www.lfspareparts724.co.uk](http://www.lfspareparts724.co.uk) - [info@lfspareparts.co.uk](mailto:info@lfspareparts.co.uk)
- LF Central Est Europe S.r.o. CZECH REPUBLIC**  
Antala Staska 1859/34  
14000 Praha 4 - KRC  
Tel. +420 730 156 910  
[www.lfspareparts724.cz](http://www.lfspareparts724.cz) - [info@lfspareparts.cz](mailto:info@lfspareparts.cz)
- LF SPARE PARTS INC. USA**  
Legal address:  
155 Office Plaza Dr - Suite A - Tallahassee, FL 32301  
Business/Mailing address:  
1100 South Tower, 225 Peachtree St., N.E. - Atlanta, GA 30303, USA  
Tel. +1-404-525-2600 - Fax +1-404-586-3528  
[www.lfspareparts724.us](http://www.lfspareparts724.us) - [info@lfspareparts.us](mailto:info@lfspareparts.us)  
Tel. West Coast and Midwest: 206-349-1525 Sauro  
Tel. East Coast and the Caribbean: 786-817-1764 Luis
- 
- AUSTRALIA AND NEW ZEALAND**  
[www.lfspareparts724.com](http://www.lfspareparts724.com)  
[andrea.calvio@lfspareparts.com](mailto:andrea.calvio@lfspareparts.com)
- AUSTRIA**  
[www.lfersatzteile724.at](http://www.lfersatzteile724.at)  
[info@lfersatzteile.at](mailto:info@lfersatzteile.at)
- BALKAN COUNTRIES**  
[www.lfspareparts724.com](http://www.lfspareparts724.com)  
[matija.ramov@lfspareparts.com](mailto:matija.ramov@lfspareparts.com)
- BALTIC COUNTRIES**  
[www.lfspareparts724.com](http://www.lfspareparts724.com)  
[inara.silina@lfspareparts.com](mailto:inara.silina@lfspareparts.com)
- LATIN AMERICA AND THE CARRIBEANS**  
[www.lfrepuestos-horeca724.es](http://www.lfrepuestos-horeca724.es)  
[export@lfrepuestos.es](mailto:export@lfrepuestos.es)
- POLAND**  
[www.lfspareparts724.pl](http://www.lfspareparts724.pl)  
[info@lfspareparts.pl](mailto:info@lfspareparts.pl)
- SOUTH KOREA**  
[www.lfspareparts724.com](http://www.lfspareparts724.com)  
[fabio.doni@lfspareparts.com](mailto:fabio.doni@lfspareparts.com)
- TURKEY**  
[www.lfyedekparca724.com](http://www.lfyedekparca724.com)  
[export@lfspareparts.com](mailto:export@lfspareparts.com)