



Spare parts for the professional sector: Cooking equipment



Suitable for:

ERRE 2



This catalogue is automatically generated.
Therefore, the sequence of the items might
not be always shown at best.
Updates will be issued in case of additions
and/or amendments.

Suitable universal spare parts may not be included





Suitable for:

ERRE 2



Suitable for:

Axial motor fans

3240501 AXIAL FAN SUNON 120x120x38 mm
 ball bearings
 230V 50/60Hz 22W 2850rpm
 DP200A 2123XBT.GN



ERRE 2 607008

3805037 CABLE FOR AXIAL MOTOR FAN
 cable length 2000 mm



Contactors

3446556 CONTACTOR LOVATO BG0910A
 coil 9A 230V 50/60Hz 4Kw
 3 normally open contacts
 1 normally open auxiliary contact



ERRE 2 6300240600

3446227 AUXILIARY CONTACT LOVATO G218
 10A
 1 contact NO
 1 contact NC



5068368 THERMAL RELAY LOVATO 0,6-1 A
 RF9-1
 1 contact NO
 1 contact NC



ERRE 2 6310004

Electrical gas valves and accessories

3526061 VALVE VR4605P HONEYWELL \varnothing 1/2"FF
 inlet \varnothing 1/2" F - outlet \varnothing 1/2" F
 thermocouple connection ASA pitch
 maximum gas inlet pressure 100 mbar
 room temperature 0÷60°C
 power supply 220V 50Hz



ERRE 2 43330001

3526077 ELBOW FLANGE \varnothing 1/2" F
 with screws and OR
 for valves SIT 820-Honeywell V4400-V4600-VR4605P





Suitable for:

3526078 ELBOW FLANGE \varnothing 3/4" F
with screws and OR
for valves SIT 820-Honeywell V4400-V4600-VR4605P



3526076 FLANGE STRAIGHT \varnothing 3/4"
with screws and OR
for valves SIT 820-Honeywell V4400-V4600-VR4605P



ERRE 2



Suitable for:

3526075 FLANGE STRAIGHT \varnothing 1/2"
with screws and OR
for valves SIT 820-Honeywell V4400-V4600-VR4605P



3526090 VALVE 810 Elettrosit \varnothing 3/4" FF
inlet \varnothing 3/4" F - outlet \varnothing 3/4" F
thermocouple connection M9x1
maximum gas inlet pressure 50 mbar
pressure adjustment range
3 ÷ 18 mbar
ambient temperature 0 ÷ 60°C
power supply 230V 50Hz
long buttons
pilot connection and LATERAL thermocouple



ERRE 2 43300012

ERRE 2 433012224

ERRE 2 790202500

3526100 COIL 220V
for VALVE Elettrosit



3526137 BUTTON FOR Elettrosit VALVE 46 mm



3526108 ELBOW FLANGE \varnothing 1/2" F
with screws and OR
for Elettrosit VALVE



3526093 EXTENSION FOR Elettrosit BUTTON 34 mm
for switching on/off buttons



3526106 FLANGE STRAIGHT \varnothing 1/2"
with screws and OR
for Elettrosit VALVE





Suitable for:

3526107 FLANGE STRAIGHT \varnothing 3/4" F
with screws and OR
for ELETTROSIT VALVE



3526136 SPRING FOR PUSH-BUTTON



ERRE 2



Suitable for:

3001008 PIEZO IGNITER
a \varnothing 14 mm hole is required for the assembly
faston M \varnothing 2.4 mm




3526096 VALVE MICROSWITCH
maximum load 0.2 A
for VALVE ELETTROSIT-820 NOVA-824 NOVASIT



Electronic boxes

3526402 CONTROL BOX S4560A1008
model HONEYWELL - 220/240V 50Hz 10VA



ERRE 2 43331001

Electronic controllers

3445076 THERMOSTAT EVK411 PTC/NTC/PT100/PT1000
power supply 12Vca/dc 1.5VA
thermostat setting range 99+600°C
ON-OFF control with one actuation point
1 exchange relay output 6(3)A 250V
inbuilt alarm buzzer
access to configuration parameters through
password
serial port for data exchange
room temperature 0+60°C
PTC/NTC/PT100/PT1000 type probe (not included)
connections by screwed terminal block
front dimensions 74x32x65 mm
mounting hole 71x29 mm



ERRE 2 629601

3445157 PROBE NTC PVC 1500 mm
probe 2 wires - temperature range -30°+80°C
bulb \varnothing 6x40 mm





Suitable for:

3445156 PROBE NTC PVC 3000 mm
temperature range -30+80°C
bulb ø 6x40 mm



3445167 PROBE NTC TPE IP68 1500 mm
temperature range -50+110°C
bulb ø 5x20 mm watertight



3445184 PROBE NTC TPE STEEL IP68 1500 mm
temperature range -40+110°C
bulb ø 6x40 mm watertight



3445117 PROBE PT100 VETROTEX 3000 mm
3-wire probe temperature range 0+350°C
bulb ø 6x100 mm



ERRE 2 A00317

3445380 PROBE PT1000 IP68 3000 mm
temperature range -50+110°C
bulb ø 6x20 mm watertight



ERRE 2

Suitable for:

3445028 PROBE NTC PVC 4000 mm
temperature field -30+80°C
bulb ø 6x20 mm



3445335 PROBE NTC TPE IP68 3000 mm
temperature range -50+110°C
bulb ø 5x20 mm watertight



3445154 PROBE NTC TPE STEEL IP68 3000 mm
temperature range -40+110°C
bulb ø 6x40 mm watertight



3445379 PROBE PT1000 IP68 1500 mm
temperature range -50+110°C
bulb ø 6x20 mm watertight



3445070 PTC PVC PROBE 1500 mm
2-wire probe temperature range -30+80°C
bulb ø 6x40 mm





Suitable for:

3445107 PTC PVC PROBE 3000 mm
2-wire probe temperature range -30+80°C
bulb ø 6x40 mm



ERRE 2



Suitable for:

3445913 SILICONE PROBE NTC 1500 mm
temperature range -50+110°C
bulb ø 6x40 mm



3445155 SILICONE PROBE NTC 3000 mm
temperature range -50+110°C
bulb ø 6x40 mm



3445183 SILICONE PTC PROBE 3000 mm
2-wire probe temperature range -55+150°C
bulb ø 6x40 mm



3445959 SILICONE PTC PROBE 5000 mm
temperature range -55+150°C
bulb ø 6x40 mm



3445110 TRANSFORMER 230V/12V 3VA
primary tension 230Vca 50/60Hz
secondary tension 12Vca 3VA
room temperature 0+60°C
screw terminal block
IMQ approved



ERRE 2 639603

3445111 TRANSFORMER 24V/12V 3VA
primary tension 24Vca 50/60Hz
secondary tension 12Vca 3VA
room temperature 0÷60°C
screw terminal block
IMQ approved





Energy regulators

3350026 ENERGY REGULATOR

contact capacity 230V 13A - max temperature 125°C
 D-shaped pin \varnothing 6x4.6 mm
 double rotation direction
 for PYROCERAM. TOPS-SALAMANDERS-POTATO WARMERS




ERRE 2 539205


Gas valves and accessories

2110349 VALVE 630 EUROSIT BAIN MARIE $30 \div 100^\circ\text{C}$

inlet \varnothing 3/8" F - outlet \varnothing 3/8" F
 thermocouple connection M9x1
 gas inlet maximum pressure 50 mbar
 calibration field of outlet
 pressure $3 \div 18$ mbar
 ambient temperature $0 \div 80^\circ\text{C}$
 capillary length 1050 mm
 bulb \varnothing 5x122 mm






ERRE 2 A00414

4056009 CAP FOR VALVE EUROSIT-MERTIK \varnothing 3/8"
with OR

3526260 CAP FOR VALVE EUROSIT \varnothing 3/8"
with OR

3241435 EUROSIT VALVE EXTENSION
D shaft \varnothing 10x8 mm


3526126 EUROSIT VALVE EXTENSION
D shaft \varnothing 10x8 mm

3526677 EXTENSION FOR EUROSIT VALVE
D-shaped pin \varnothing 10x8 mm

3020083 FITTING AND OLIVE \varnothing 4 mm

3020084 FITTING AND OLIVE \varnothing 6 mm




Suitable for:

5050400 FITTING FOR OLIVE \varnothing 10 mm
thread \varnothing 3/8" M



5021481 GAS OUTLET VALVE FITTING
thread \varnothing 3/8" M - M16x1 mm



3020082 OLIVE FOR PIPE \varnothing 12 mm
for model PEL 22-24-25



3020079 PIPE FITTING \varnothing 12 mm
thread \varnothing 3/8" M



ERRE 2

Suitable for:

3526127 FLANGE FOR EXTENSION




5050401 OLIVE FOR PIPE \varnothing 10 mm
external \varnothing 13 mm - height 8 mm



3001111 PIEZO IGNITER EUROSIT
M faston \varnothing 2.4 mm



3526123 RUBBER PROTECTION FOR EUROSIT VALVE



Incandescent lamps and neon lamps

3221638 HALOGEN LAMP NEUT. OSRAM G4 20W 12V
max. temperature 300°C



ERRE 2 6242122001

3221105 NEUTRAL HALOGEN LAMP G4 20W 12V
max. temperature 250°C



ERRE 2 6242122001





Indicator lights

3221162 GREEN LAMP RECEPTACLE
head \varnothing 14.5 mm - hole \varnothing 10 mm



ERRE 2 6229044

3221132 INDICATOR LIGHT GREEN 230V
head \varnothing 13.5 mm - hole \varnothing 10 mm - 120°C
universal application



ERRE 2 A00409

3221117 INDICATOR LIGHT GREEN 400V
head \varnothing 18 mm - hole \varnothing 12 mm - 150°C



ERRE 2 5229054

3221194 INDICATOR LIGHT NEON GREEN 220V
 \varnothing head 8 mm



ERRE 2 6229046

3221197 GREY CAP \varnothing 12 mm



3221196 LAMP CAP CLEAR
 \varnothing 12 mm



3221195 LAMP CAP GREEN \varnothing 12 mm
 \varnothing 12 mm



3221192 LAMP SUPPORT



3221193 ORANGE LAMP CAP
 \varnothing 12 mm



3319219 SUPPORT FOR DARK GREY PUSH-BUTTON
mounting hole 16x16 mm - for push-button \varnothing 12 mm





Suitable for:

ERRE 2



3221097 INDICATOR LIGHT NEUTRAL 220V
head \varnothing 8 mm - 120°C



ERRE 2

3221116 INDICATOR LIGHT ORANGE 400V
head \varnothing 18 mm - hole \varnothing 12 mm - max 150°C



ERRE 2 5229052

3221167 RED LAMP RECEPTACLE
head \varnothing 15 mm - hole \varnothing 10 mm



ERRE 2 6229047

3221163 ORANGE LAMP RECEPTACLE
head \varnothing 15 mm - hole \varnothing 10 mm



ERRE 2 6229043

Suitable for:

3221095 INDICATOR LIGHT ORANGE 230V
head \varnothing 13.5 mm - hole \varnothing 10 mm - 120°C
universal application



ERRE 2 A00410

3221163 ORANGE LAMP RECEPTACLE
head \varnothing 15 mm - hole \varnothing 10 mm




ERRE 2 6229043

3221162 GREEN LAMP RECEPTACLE
head \varnothing 14.5 mm - hole \varnothing 10 mm




ERRE 2 6229044

3221168 TRANSPARENT LAMP RECEPTACLE
head \varnothing 15 mm - hole \varnothing 10 mm



Knobs

3241038 GREY KNOB \varnothing 60 mm SILK-SCREEN PRINTED
D-shaped hole 10x8 mm



ERRE 2 790109350

3241139 KNOB RING RED
external \varnothing 72 mm



3241143 KNOB SPRING \varnothing 42x26 mm



5010804 KNOB BLACK \varnothing 52 mm
D-shaped hole 6x4.6 mm



ERRE 2 A00250

Lamp receptacles and spare parts

3221115 HALOGEN LAMP RECEPTACLE G4 20W 12V
wire connection length 130 mm




ERRE 2 6242122002

3221638 HALOGEN LAMP NEUT. OSRAM G4 20W 12V
max. temperature 300°C



ERRE 2 6242122001

3221060 LAMP RECEPTACLE WITH LAMP E14 25W 230V
lamp glass \varnothing 42 mm
mounting hole \varnothing 38 mm
max temperature 300°C
for OVEN



ERRE 2 6230001

3786366 GASKET FOR OVEN LAMP RECEPTACLE
external dimensions 78x40 mm
intern.dimens.45x34 mm - dist.bw.mount.holes 65 mm
for CONVECTION OVEN 4 LEVELS




3221105 NEUTRAL HALOGEN LAMP G4 20W 12V
max. temperature 250°C



ERRE 2 6242122001

3186522 GASKET FOR OVEN LAMP RECEPTACLE
dimensions \varnothing 40x30x2 mm





Suitable for:

3786614 GASKET FOR OVEN LAMP RECEPTACLE
dimensions 48x41x3 mm



3221061 LAMP E14 25W 230V
max temperature 300°C - ø 26x57 mm



D421016 OVEN LAMP DR FISCHER E14 25W 230V
ø 25x57 mm - max temperature 300°C




ERRE 2




Suitable for:

3221392 GASKET KIT FOR OVEN LAMP RECEPTACLE
dimensions ø 53x44x3 mm



2101372 LAMP RECEPTACLE FOR LAMP E14 15-25W 230V
mounting hole ø 38 mm
max temperature 300°C



2110636 OVEN LAMP RECEPTACLE GLASS ø 41 mm
thread ø 34 mm - overall height 36 mm



Level probes

3341020 LEVEL PROBE ø 1/4"M-220 mm



ERRE 2 639314125

Level regulators

3341000 LEVEL REGULATOR RL30/3ES/F/G
230V 50/60Hz



ERRE 2 639624051

3341002 LEVEL PROBE ø 1/4"M-114.5 mm



3341003 LEVEL PROBE ø 1/4"M-110 mm



3341001 LEVEL PROBE ø 1/4"M-155 mm





Suitable for:

3391037 LEVEL PROBE SPACER
external \varnothing 8 mm
internal \varnothing 2.5 mm
overall length 11.5 mm



ERRE 2

Suitable for:

3391038 LEVEL PROBE SPACER
external \varnothing 8 mm - 7.5 mm height



Motors

3240000 MOTOR WITH FAN 45W 220V 50/60Hz
fan \varnothing 150 mm



ERRE 2 507005

ERRE 2 507007

Pilot burners and accessories

3020157 PILOT JET \varnothing 0.25 mm



ERRE 2 43701025

3020040 PILOT JET \varnothing 0.30 mm



ERRE 2 43703030

3020010 TARGET PILOT BURNER SIT 2 FLAMES
supplied without sparking plug, nozzle and gasket
with thermocouple fitting




ERRE 2 790200900

3020085 FITTING FOR SPARKING PLUG FIXING M10x1mm



3020200 FITTING FOR THERMOCOUPLE \varnothing 6.5 mm
thread M10x1



3001003 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M4x1 mm
overall length 65 mm



ERRE 2 4398070



Suitable for:

3020060 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M 4x1 mm
overall length 82 mm
model CB505/021 Junkers
for model P502F



ERRE 2



Suitable for:

3020124 IGNITION PLUG ROUND \varnothing 7x44 mm
connection \varnothing 2.4 mm
overall length 58 mm



ERRE 2 270200700

3020294 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M4x1 mm
overall length 67 mm



3020365 IGNITION PLUG ROUND \varnothing 7x44 mm
connection \varnothing 2.4 mm
overall length 52 mm



3020113 OLIVE FOR PIPE \varnothing 4 mm



3348036 OLIVE FOR PIPE \varnothing 4 mm
for model PEL 21-22-24-25



3020114 OLIVE FOR PIPE \varnothing 6 mm



3020086 PILOT GASKET



3020201 PILOT JET \varnothing 0.14 mm



3020042 PILOT JET \varnothing 0.19 mm



3020542 PILOT JET \varnothing 0.20 mm



5047578 PILOT JET \varnothing 0.24 mm





Suitable for:

3020202 PILOT JET \varnothing 0.27 mm



3020043 PILOT JET \varnothing 0.36 mm



5022050 PILOT JET \varnothing 0.50 mm



3348029 PIPE FITTING \varnothing 4 mm
thread M10x1 mm
for model PEL 21-22-24-25




5014757 PIPE FITTING \varnothing 6 mm
thread M10x1 mm



ERRE 2

Suitable for:

2102405 PILOT JET \varnothing 0.35 mm



3020543 PILOT JET \varnothing 0.38 mm



3020077 PIPE FITTING \varnothing 4 mm
thread M10x1



3020078 PIPE FITTING \varnothing 6 mm
thread M10x1



3020006 THREE-FLAME PILOT BURNER SIT
multigas with jet \varnothing 0.20 mm
with 3 positions bracket



3020104 BRACKET CLAMP 3 POSITIONS





Suitable for:


3020103 BRACKET 3 POSITIONS



3020110 DEFLECTOR 3 FLAMES



3020083 FITTING AND OLIVE ø 4 mm



3020102 HEXAGON HEAD SCREW 3/16"x18 mm



3020060 IGNITION PLUG ROUND ø 7x44 mm
M faston M 4x1 mm
overall length 82 mm
model CB505/021 Junkers
for model P502F



ERRE 2 270200700

3020294 IGNITION PLUG ROUND ø 7x44 mm
M faston M4x1 mm
overall length 67 mm



ERRE 2

Suitable for:


3020109 DEFLECTOR 2 FLAMES



5048713 DEFLECTOR 3 FLAMES



3020084 FITTING AND OLIVE ø 6 mm



3001003 IGNITION PLUG ROUND ø 7x44 mm
M faston M4x1 mm
overall length 65 mm



ERRE 2 4398070

3020124 IGNITION PLUG ROUND ø 7x44 mm
connection ø 2.4 mm
overall length 58 mm



3020365 IGNITION PLUG ROUND ø 7x44 mm
connection ø 2.4 mm
overall length 52 mm





Suitable for:

3020082 OLIVE FOR PIPE \varnothing 12 mm
for model PEL 22-24-25



5027953 OLIVE FOR PIPE \varnothing 4 mm
for COPRECI CAL3200



3020097 PILOT AERATION REGULATOR
internal \varnothing 7 mm - external \varnothing 9 mm
height 10 mm



3020156 PILOT JET \varnothing 0.25 mm



3020055 PILOT JET \varnothing 0.35 mm



3500269 PILOT JET \varnothing 0.45 mm



ERRE 2

Suitable for:

3348036 OLIVE FOR PIPE \varnothing 4 mm
for model PEL 21-22-24-25



3020081 OLIVE FOR PIPE \varnothing 6 mm



3020054 PILOT JET \varnothing 0.20 mm



4058525 PILOT JET \varnothing 0.30 mm



5015516 PILOT JET \varnothing 0.40 mm



5075989 PILOT JET \varnothing 0.70 mm





Suitable for:

3020308 PILOT WITH NOZZLE \varnothing 0.40 mm



3020106 PILOT WITH 0.25 mm \varnothing JET



3020079 PIPE FITTING \varnothing 12 mm
thread \varnothing 3/8" M



5033138 PIPE FITTING \varnothing 4 mm
thread \varnothing 1/8" M



5014757 PIPE FITTING \varnothing 6 mm
thread M10x1 mm



ERRE 2

Suitable for:

3020105 PILOT WITH 0.20 mm \varnothing JET




3020107 PILOT WITH 0.35 mm \varnothing JET



3020077 PIPE FITTING \varnothing 4 mm
thread M10x1



3020078 PIPE FITTING \varnothing 6 mm
thread M10x1



Probes

3445117 PROBE PT100 VETROTEX 3000 mm
3-wire probe temperature range 0+350°C
bulb \varnothing 6x100 mm






Selector switches

3057050 CONNECTING BRACKET 28x21x16 mm
distance between hooking brackets 27 mm
f/connection between selector switch and thermost.



ERRE 2 5200995

3057014 SELECTOR SWITCH 0-1 POSITIONS
contact capacity 16A 250V - max 150°C
D-shaped pin \varnothing 6x4.6 mm
back connection for thermostat



ERRE 2 00423

ERRE 2 52004115

3057026 SELECTOR SWITCH 0-1 POSITIONS
contact capacity 16A 250V - max 150°C
D shaft \varnothing 6x4.6 mm



ERRE 2 52002115

Solenoid valves

3120004 SOLEN. VALVE ELBI TYPE 319 1 WAY 90°
220/240V 50/60Hz - max. temperature 90°C
inlet 3/4" - outlet \varnothing 10.5 mm



ERRE 2 53943410240

ERRE 2 63943410240

3120019 ADJUSTER FOR INLET ELBI BLACK
flow rate 5.5 L/min - tolerance +/- 15%



3120021 ADJUSTER FOR INLET ELBI BLACK
flow rate 12 L/min - tolerance +/- 15%



3120022 ADJUSTER FOR INLET ELBI BLACK
flow rate 16 L/min - tolerance +/- 15%



3120037 ADJUSTER FOR OUTLET ELBI GREEN
flow rate 0.25 L/min - tolerance +/- 25%



3120201 ADJUSTER FOR OUTLET ELBI GREY
flow rate 4.7 L/min - tolerance +/- 25%





Suitable for:

3120016 ADJUSTER FOR OUTLET ELBI NEUTRAL
flow rate 1.2 L/min - tolerance +/- 25%



3120015 ADJUSTER FOR OUTLET ELBI RED
flow rate 0.5 L/min - tolerance +/- 25%



3120202 ADJUSTER FOR OUTLET ELBI YELLOW
flow rate 0.35 L/min / tolerance +/- 25%



3120204 OUTLET ADJUSTER ELBI BLACK
flow rate 5.5 L/min - tolerance +/- 25%



3120005 SOLEN. VALVE ELBI TYPE 329 1 WAY 180°
220/240V 50/60Hz - max. temperature 90°C
inlet 3/4" - outlet ø 10.5 mm



ERRE 2 53943410240

3120021 ADJUSTER FOR INLET ELBI BLACK
flow rate 12 L/min - tolerance +/- 15%



ERRE 2

Suitable for:

3120017 ADJUSTER FOR OUTLET ELBI ORANGE
flow rate 2.5 L/min - tolerance +/- 25%



3120203 ADJUSTER FOR OUTLET ELBI WHITE
flow rate 2 L/min - tolerance +/- 25%



3120000 FILTER FOR INLET SOLENOID VALVE ELBI



3120019 ADJUSTER FOR INLET ELBI BLACK
flow rate 5.5 L/min - tolerance +/- 15%



3120022 ADJUSTER FOR INLET ELBI BLACK
flow rate 16 L/min - tolerance +/- 15%





Suitable for:

3120037 ADJUSTER FOR OUTLET ELBI GREEN
flow rate 0.25 L/min - tolerance +/- 25%



3120016 ADJUSTER FOR OUTLET ELBI NEUTRAL
flow rate 1.2 L/min - tolerance +/- 25%



3120015 ADJUSTER FOR OUTLET ELBI RED
flow rate 0.5 L/min - tolerance +/- 25%



3120202 ADJUSTER FOR OUTLET ELBI YELLOW
flow rate 0.35 L/min / tolerance +/- 25%



3120204 OUTLET ADJUSTER ELBI BLACK
flow rate 5.5 L/min - tolerance +/- 25%



ERRE 2

Suitable for:

3120201 ADJUSTER FOR OUTLET ELBI GREY
flow rate 4.7 L/min - tolerance +/- 25%



3120017 ADJUSTER FOR OUTLET ELBI ORANGE
flow rate 2.5 L/min - tolerance +/- 25%



3120203 ADJUSTER FOR OUTLET ELBI WHITE
flow rate 2 L/min - tolerance +/- 25%



3120000 FILTER FOR INLET SOLENOID VALVE ELBI



Spark generators

3181002 SPARK GENERATOR 2 OUTLETS
220/240V 50/60Hz



ERRE 2 539613240

ERRE 2 539613242



Suitable for:

ERRE 2



Suitable for:

Sparking and detection plugs

3001003 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M4x1 mm
overall length 65 mm



ERRE 2 4398070

3020060 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M 4x1 mm
overall length 82 mm
model CB505/021 Junkers
for model P502F



ERRE 2 270200700

Switches

3319151 SWITCH PROTECTION CAP
 \varnothing external 34 mm
for push-buttons with mounting hole \varnothing 25 mm



ERRE 2 55463001

Telethermometers


3441027 TELE-THERMOMETER WHITE \varnothing 60 mm 50-350°C
metal body
capillary length 1500 mm
bulb \varnothing 4x105 mm



ERRE 2 4251103552

Thermocouples and accessories

3440067 INTERRUPTED THERMOCOUPLE M9x1 100 cm.
interrupted contact with terminals



ERRE 2 434009100

ERRE 2 4343103

3440066 INTERRUPTED THERMOCOUPLE M9x1 60 cm
interrupted contact with fastons



ERRE 2 434099045

ERRE 2 4343106



ERRE 2



Suitable for:

Suitable for:

**3440855 THERMOCOUPLE SIT M8x1 100 cm - 10 PCS
CONNECTOR M8x1**



ERRE 2 A00270

ERRE 2 434008100

3440055 THERMOCOUPLE SIT M8x1 100 cm THREAD M8x1



ERRE 2 A00270

ERRE 2 434008100

3440064 NUT FOR THERMOCOUPLE M8x1



**3440855 THERMOCOUPLE SIT M8x1 100 cm - 10 PCS
CONNECTOR M8x1**



ERRE 2 A00270

ERRE 2 434008100

3440032 THERMOCOUPLE SIT M8x1 150 cm




ERRE 2 A00201

3440832 THERMOCOUPLE SIT M8x1 150 cm - 10 PCS



ERRE 2 A00201

3440832 THERMOCOUPLE SIT M8x1 150 cm - 10 PCS



ERRE 2 A00201

3440049 THERMOCOUPLE SIT M9X1 75 cm



ERRE 2 434009175

3440849 THERMOCOUPLE SIT M9x1 75 cm - 10 PCS





Suitable for:


ERRE 2

Suitable for:




Thermostats

3444120 SINGLE-PHASE THERMOSTAT 320°C
 with manual reset
 capillary length 900 mm - 16A 250V
 bulb \varnothing 6x80 mm



ERRE 2 6340004032001

3444043 SINGLE-PHASE THERMOSTAT 50-270°C
 D-shaped pin \varnothing 6x4.6 mm
 covered capillary length 1300 mm - 16A 250V
 bulb \varnothing 3x220 mm



ERRE 2 53401005270

ERRE 2 63401005270

3444354 THREE-PHASE THERMOSTAT 350°C
 with manual reset
 capillary length coated 950 mm - 10A 400V
 bulb \varnothing 3x190 mm



ERRE 2 53403000350

3444052 THREE-PHASE THERMOSTAT 50-320°C
 D-shaped pin \varnothing 6x4.6 mm
 capillary length 900 mm - 10A 400V
 bulb \varnothing 3x230 mm




ERRE 2 00402

ERRE 2 270200341

ERRE 2 53403050300

Timers

3446001 TIMER 120 MINUTES
 complete with silk-screen printed plate
 mechanical timer with sound alarm
 mechanical movement with balance wheel
 manual left hand positioning possible
 120 minutes manually set cycle
 bipolar with contact capacity 16(3)A 250V
 max temperature 125°C
 D-shaped pin \varnothing 6x4.6 mm




ERRE 2 63511120

3446005 BLACK KNOB ABS 38x38 mm
 D-shaped hole \varnothing 6x4.6 mm
 for timer



3446002 TIMER 120 MINUTES
 complete with silk-screen printed plate
 mechanical timer with sound alarm
 mechanical movement with balance wheel
 120 minutes manually set cycle
 bipolar with contact capacity 16(3)A 250V
 max temperature 125°C
 D-shaped pin \varnothing 6x4.6 mm



ERRE 2 63510120

3446005 BLACK KNOB ABS 38x38 mm
 D-shaped hole \varnothing 6x4.6 mm
 for timer





Transformers

3445110 TRANSFORMER 230V/12V 3VA
primary tension 230Vca 50/60Hz
secondary tension 12Vca 3VA
room temperature 0+60°C
screw terminal block
IMQ approved



ERRE 2 639603

The data herewith contained may change without notice and LF SpA cannot be held responsible for possible errors stated or resulting by the use of this document. All rights reserved. No part of this publication may be reproduced without written permission by LF SpA.



Distributing Components, Spare Parts & Accessories in original quality worldwide

-
- LF SpA HEADQUARTERS**
via Voltri, 80 - 47522 Cesena (FC) ITALY
Tel. +39 0547 34 11 11 - Fax +39 0547 34 11 10
www.lfircambi724.it - info@lfircambi.it
Export Dept. Tel. +39 0547 34 11 50 - Fax +39 0547 34 11 55
www.lfspareparts724.com - export@lfspareparts.com
- LF SpA HOUSEHOLD COMPONENTS DIVISION**
Via Padriciano, 99 - AREA Science Park - 34149 Trieste (TS) ITALY
Tel. +39 0547 34 12 42 - Fax +39 0547 34 12 48
www.lfspareparts724.com - info@lfspareparts.com
- EPGC Sas FRANCE**
13, Rue des Forts - 59960 Neuville en Ferrain
Tel. +33 (0)3 20 25 06 21 - Fax +33 (0)3 20 25 34 12
www.epgc.com - epgc@epgc.com
- LF GmbH GERMANY**
Junkersstrasse, 3 - D-82178 Puchheim - München
Tel. +49 89 89 45 78 66 - Fax +49 89 89 45 78 88
www.lfersatzteile724.de - info@lfersatzteile.de
- LF China REPUBLIC OF CHINA**
Room 403, No.2, Huadu Mansion, Lane 422, Huanghua Rd.
Minhang Dist. - 201103 Shanghai
Tel. +86 (0)21 33 53 66 31 - Fax +86 (0)21 33 53 66 32
www.lfspareparts724.com - china@lfspareparts.com
- OOO LF RUSSIAN FEDERATION**
Ul. Anatoliya Zhivova, 8 - office 1 - 123100 Moscow
Tel./Fax +7 495 725 26 53
www.lfspareparts724.ru - info@lfspareparts.ru
- LF Repuestos Horeca S.L.U. SPAIN**
Poligono Industrial Carpetania - C/Miguel Faraday, 8 - 28906 Getafe
Tel. +34 91 477 91 00 - Fax +34 91 477 90 81
www.lfrepuestos-horeca724.es - info@lfrepuestos.es
- LF Scandinavia Aps - LF Spareparts S.p.A. DENMARK**
Nupark, 51 - 7500 Holstebro
Tel. +45 70 70 77 33
www.lfspareparts724.dk - denmark@lfspareparts.dk
- LF SpA Cesena (IT) Swiss Branch Steinhausen SWITZERLAND**
Sennweidstrasse, 45 - CH-6312 Steinhausen
Tel. +41 (0)41 760 15 80/1 - Fax +41 (0)41 760 15 85
www.lfersatzteile724.ch - info@lfersatzteile.ch
- LF Spare Parts Ltd. UNITED KINGDOM**
A10a Lakeside Business Park, Broadway Lane
South Cerney, Gloucestershire GL7 5XL
Tel. +44 (0)1285 86 16 25 - Fax +44 (0)1285 86 39 49
www.lfspareparts724.co.uk - info@lfspareparts.co.uk
- LF Central Est Europe S.r.o. CZECH REPUBLIC**
Antala Staska 1859/34
14000 Praha 4 - KRC
Tel. +420 730 156 910
www.lfspareparts724.cz - info@lfspareparts.cz
- LF SPARE PARTS INC. USA**
Legal address:
155 Office Plaza Dr - Suite A - Tallahassee, FL 32301
Business/Mailing address:
1100 South Tower, 225 Peachtree St., N.E. - Atlanta, GA 30303, USA
Tel. +1-404-525-2600 - Fax +1-404-586-3528
www.lfspareparts724.us - info@lfspareparts.us
Tel. West Coast and Midwest: 206-349-1525 Sauro
Tel. East Coast and the Caribbean: 786-817-1764 Luis
-
- AUSTRALIA AND NEW ZEALAND**
www.lfspareparts724.com
andrea.calvio@lfspareparts.com
- AUSTRIA**
www.lfersatzteile724.at
info@lfersatzteile.at
- BALKAN COUNTRIES**
www.lfspareparts724.com
matija.ramov@lfspareparts.com
- BALTIC COUNTRIES**
www.lfspareparts724.com
inara.silina@lfspareparts.com
- LATIN AMERICA AND THE CARRIBEANS**
www.lfrepuestos-horeca724.es
export@lfrepuestos.es
- POLAND**
www.lfspareparts724.pl
info@lfspareparts.pl
- SOUTH KOREA**
www.lfspareparts724.com
fabio.doni@lfspareparts.com
- TURKEY**
www.lfyedekparca724.com
export@lfspareparts.com