



Spare parts for the professional sector: Cooking equipment



Suitable for:

OM GAS



This catalogue is automatically generated.
Therefore, the sequence of the items might
not be always shown at best.
Updates will be issued in case of additions
and/or amendments.

Suitable universal spare parts may not be included





Suitable for:

OM GAS

Suitable for:



Burners, flame spreaders and accessories

3025505 FLAME SPREADER \varnothing 110 mm
for Pot stove gas (OM GAS) - Series TIQU7
Series VESTA



OM GAS 04/9990089

Drain taps and accessories

3356004 DRAIN TAP \varnothing 1" F
TAPERED SEAL - fixed connection \varnothing 1" F
for BOILING PAN



OM GAS

3179010 FITTINGS SEALING TAPE LOCTITE 55 - 50 m
length 50 mt
suitable to hot and cold drinking water, gas
replaces pastes, hemp and sealing tapes
it allows the repositioning of couplings
in compliance with the latest regulations
Drinking water (Italian certification by C.S.A.,
according to standard KTW and WRC approved)
gas - water IMQ-UNICIG.
compliant with UNI EN 51-2 class Arp
approved by DVGW and DIN 30660



3356029 HANDLE FOR DRAIN TAP
for drain tap \varnothing 3/4" and 1"



3186009 ASBESTOS FREE FLAT GASKET \varnothing 45x33x2 mm



1180001 GREASE KLUBERSYNTH UH1 14-151 45 g
food safe grease for lubrication
of all friction points
ideal for water and steam taps
operating temperature $-45^{\circ}/+120^{\circ}$
beige color - NSF H1 certified
hot and cold water resistant
high anti-corrosion power
can replace vaseline



3180061 TAPE F. COUPLING SEALING LOCTITE 55-150m
length 150 metri
suitable for hot / cold drinking water. gas
replaces pastes, hemp and sealing tapes
it allows the correct replacement of fittings
compliant with the latest regulatory requirements
Drinking water (C.S.A. italian certified.
in line with KTW standard and WRC approved)
IMQ-UNICIG gas-water,
compliant with UNI EN 51-2 class Arp
DVGW and DIN 30660 approved





Suitable for:

3180039 VASELINE WUERTH 750 g
for lubrication of food processing machines
it protects chromed and rubber parts from
weather factors, moisture resistant,
operating temperature from -10°C up to +120°C
from +50°C to +120 °C the grease becomes oily



OM GAS

Suitable for:



3356005 DRAIN TAP ø 1"1/4F TECNO
TAPERED SEAL - fixed connection ø 1"1/4F
with gasket
for BOILING PAN



OM GAS

3356010 ESCUTCHEON FOR DRAIN TAP ø 1"1/4



3186199 GASKET INTERNAL EPDM FOR TAPS
NSF certified
for DRAIN TAP ø 1"1/4 and 1"1/2



3186240 ASBESTOS FREE FLAT GASKET ø 46x38x2 mm
for drain tap ø 1"1/2



3179010 FITTINGS SEALING TAPE LOCTITE 55 - 50 m
length 50 mt
suitable to hot and cold drinking water, gas
replaces pastes, hemp and sealing tapes
it allows the repositioning of couplings
in compliance with the latest regulations
Drinking water (Italian certification by C.S.A.,
according to standard KTW and WRC approved)
gas - water IMQ-UNICIG.
compliant with UNI EN 51-2 class Arp
approved by DVGW and DIN 30660



1180001 GREASE KLUBERSYNTH UH1 14-151 45 g
food safe grease for lubrication
of all friction points
ideal for water and steam taps
operating temperature -45°/+120°
beige color - NSF H1 certified
hot and cold water resistant
high anti-corrosion power
can replace vaseline





Suitable for:

3242189 HANDGRIP FOR DRAIN TAP
for DRAIN TAP \varnothing 1"1/2F e 1"1/4F



OM GAS



Suitable for:

3356128 PIN \varnothing 5x30 mm
complete with blind nut



3180061 TAPE F. COUPLING SEALING LOCTITE 55-150m
length 150 metri
suitable for hot / cold drinking water. gas
replaces pastes, hemp and sealing tapes
it allows the correct replacement of fittings
compliant with the latest regulatory requirements
Drinking water (C.S.A. italian certified.
in line with KTW standard and WRC approved)
IMQ-UNICIG gas-water,
compliant with UNI EN 51-2 class Arp
DVGW and DIN 30660 approved



3180039 VASELINE WUERTH 750 g
for lubrication of food processing machines
it protects chromed and rubber parts from
weather factors, moisture resistant,
operating temperature from -10°C up to +120°C
from +50°C to +120 °C the grease becomes oily



Electrical gas valves and accessories

3526085 VALVE 810 ELETTROSIT \varnothing 3/4"FF
inlet \varnothing 3/4" F - outlet \varnothing 3/4" F
thermocouple connection M9x1
maximum gas inlet pressure 50 mbar
pressure adjustment range
3÷18 mbar
ambient temperature 0÷60°C
power supply 230V 50Hz
pilot connection and LATERAL thermocouple



3526100 COIL 220V
for VALVE ELETTROSIT



OM GAS 1712150059

3526108 ELBOW FLANGE \varnothing 1/2" F
with screws and OR
for ELETTROSIT VALVE



3526106 FLANGE STRAIGHT \varnothing 1/2"
with screws and OR
for ELETTROSIT VALVE





Suitable for:

3526107 FLANGE STRAIGHT \varnothing 3/4" F
with screws and OR
for ELETTROSIT VALVE



3526096 VALVE MICROSWITCH
maximum load 0.2 A
for VALVE ELETTROSIT-820 NOVA-824 NOVASIT



OM GAS



Suitable for:

3001008 PIEZO IGNITER
a \varnothing 14 mm hole is required for the assembly
faston M \varnothing 2.4 mm



Gas valves and accessories

3523920 VALVE 710 MINISIT OVEN 100 \pm 340°C
inlet \varnothing 1/2" F - outlet \varnothing 3/8" F
thermocouple connection M9x1
maximum gas inlet pressure 50 mbar
ambient temperature 0 \pm 60°C
capillary length 1050 mm
bulb \varnothing 5x70 mm
without cover, knob and flanges



OM GAS 1712150039

3523038 ELBOW FLANGE MINISIT \varnothing 1/2" F
with screws and OR



2100757 CONNECTION FOR OLIVE \varnothing 16 mm
thread \varnothing 1/2" M




3523037 ELBOW FLANGE MINISIT \varnothing 3/8"
with screws and OR



3523035 KNOB MINISIT BLACK \varnothing 37 mm



3523047 LID MINISIT






Suitable for:

3182003 MAGNETIC UNIT SIT
head \varnothing 25 mm - end piece \varnothing 17 mm - length 56 mm
for valve SIT AC2 - VR8-MINISIT



3523060 OIL SEAL FITTING \varnothing 6.5 mm
internal thread M10x0.75 - external thread M14x1.5



3020082 OLIVE FOR PIPE \varnothing 12 mm
for model PEL 22-24-25




3001070 PIEZO IGNITER MINISIT
a \varnothing 22 mm hole is required for the assembly
faston M \varnothing 2.4 mm



3020079 PIPE FITTING \varnothing 12 mm
thread \varnothing 3/8" M



3523040 SENSING ELEMENT MINISIT 100 \pm 340 $^{\circ}$ C
capillary length 1050 mm
bulb \varnothing 5x70 mm



OM GAS

Suitable for:

3523061 NUT \varnothing 1/4"x6 mm




3348044 OLIVE FOR PIPE \varnothing 10 mm
for model PEL 20-21-24-25



3348041 OLIVE FOR PIPE \varnothing 16 mm
for model PEL 23



3001071 PIEZO IGNITER MINISIT WITH COVER
M faston 2.4 mm



3523036 REDUCTION STRAIGHT \varnothing 3/8" F - \varnothing 1/2" F
in brass with internal and external thread
internal thread \varnothing 3/8" F - external thread \varnothing 1/2" F
for MINISIT flange



5058320 TUBE NUT FITTING \varnothing 10 mm
thread M14x1,5 mm





Heating elements

- 3355237 HEATING ELEMENT 1200W 220V**
length 330 mm - width 280 mm
couplings \varnothing 1/4"
operating ambient: immersion
for Bain-marie electric (OM GAS) - Series MERCURY
for Pot stove electric (OM GAS) - Series MERCURY



OM GAS 0716510019

Indicator lights


- 3221499 INDICATOR LIGHT GREEN 250V**
head \varnothing 14 mm - hole \varnothing 13 mm



OM GAS

Magnet groups


- 3182011 MAGNETIC UNIT PEL SMALL HEAD**
head \varnothing 15 mm - end piece \varnothing 11 mm - length 44 mm
for PEL tap models 20-21
for EGA tap model 25213
for JUNKERS tap model CH110



OM GAS 17/12170069

Pilot burners and accessories

- 3020084 FITTING AND OLIVE \varnothing 6 mm**



OM GAS 17/12170140

- 3020107 PILOT WITH 0.35 mm \varnothing JET**



OM GAS 17/999900209



Suitable for:

OM GAS



Suitable for:

Spark generators

3181501 SPARK GENERATOR 4 OUTLETS
1.5Vdc battery powered



OM GAS 17/99600149

3001043 IGNITION BATTERY HOLDER
a \varnothing 22 mm hole is required for the assembly
faston M 2.8/6.3 mm
for battery 1.5V



Thermostats

3444064 SINGLE-PHASE THERMOSTAT 220°C
with manual reset
capillary length 790 mm - 16A 250V
bulb \varnothing 3x178 mm
for Fryer (OM GAS)



OM GAS 0816520109

The data herewith contained may change without notice and LF SpA cannot be held responsible for possible errors stated or resulting by the use of this document. All rights reserved. No part of this publication may be reproduced without written permission by LF SpA.



Distributing Components, Spare Parts & Accessories in original quality worldwide

-
- LF SpA HEADQUARTERS**
via Voltri, 80 - 47522 Cesena (FC) ITALY
Tel. +39 0547 34 11 11 - Fax +39 0547 34 11 10
www.lfricambi724.it - info@lfricambi.it
Export Dept. Tel. +39 0547 34 11 50 - Fax +39 0547 34 11 55
www.lfspareparts724.com - export@lfspareparts.com
- LF SpA HOUSEHOLD COMPONENTS DIVISION**
Via Padriciano, 99 - AREA Science Park - 34149 Trieste (TS) ITALY
Tel. +39 0547 34 12 42 - Fax +39 0547 34 12 48
www.lfspareparts724.com - info@lfspareparts.com
- EPGC Sas FRANCE**
13, Rue des Forts - 59960 Neuville en Ferrain
Tel. +33 (0)3 20 25 06 21 - Fax +33 (0)3 20 25 34 12
www.epgc.com - epgc@epgc.com
- LF GmbH GERMANY**
Junkersstrasse, 3 - D-82178 Puchheim - München
Tel. +49 89 89 45 78 66 - Fax +49 89 89 45 78 88
www.lfersatzteile724.de - info@lfersatzteile.de
- LF China REPUBLIC OF CHINA**
Room 403, No.2, Huadu Mansion, Lane 422, Huanghua Rd.
Minhang Dist. - 201103 Shanghai
Tel. +86 (0)21 33 53 66 31 - Fax +86 (0)21 33 53 66 32
www.lfspareparts724.com - china@lfspareparts.com
- OOO LF RUSSIAN FEDERATION**
Ul. Anatoliya Zhivova, 8 - office 1 - 123100 Moscow
Tel./Fax +7 495 725 26 53
www.lfspareparts724.ru - info@lfspareparts.ru
- LF Repuestos Horeca S.L.U. SPAIN**
Poligono Industrial Carpetania - C/Miguel Faraday, 8 - 28906 Getafe
Tel. +34 91 477 91 00 - Fax +34 91 477 90 81
www.lfrepuestos-horeca724.es - info@lfrepuestos.es
- LF Scandinavia Aps - LF Spareparts S.p.A. DENMARK**
Nupark, 51 - 7500 Holstebro
Tel. +45 70 70 77 33
www.lfspareparts724.dk - denmark@lfspareparts.dk
- LF SpA Cesena (IT) Swiss Branch Steinhausen SWITZERLAND**
Sennweidstrasse, 45 - CH-6312 Steinhausen
Tel. +41 (0)41 760 15 80/1 - Fax +41 (0)41 760 15 85
www.lfersatzteile724.ch - info@lfersatzteile.ch
- LF Spare Parts Ltd. UNITED KINGDOM**
A10a Lakeside Business Park, Broadway Lane
South Cerney, Gloucestershire GL7 5XL
Tel. +44 (0)1285 86 16 25 - Fax +44 (0)1285 86 39 49
www.lfspareparts724.co.uk - info@lfspareparts.co.uk
- LF Central Est Europe S.r.o. CZECH REPUBLIC**
Antala Staska 1859/34
14000 Praha 4 - KRC
Tel. +420 730 156 910
www.lfspareparts724.cz - info@lfspareparts.cz
- LF SPARE PARTS INC. USA**
Legal address:
155 Office Plaza Dr - Suite A - Tallahassee, FL 32301
Business/Mailing address:
1100 South Tower, 225 Peachtree St., N.E. - Atlanta, GA 30303, USA
Tel. +1-404-525-2600 - Fax +1-404-586-3528
www.lfspareparts724.us - info@lfspareparts.us
Tel. West Coast and Midwest: 206-349-1525 Sauro
Tel. East Coast and the Caribbean: 786-817-1764 Luis
-
- AUSTRALIA AND NEW ZEALAND**
www.lfspareparts724.com
andrea.calvio@lfspareparts.com
- AUSTRIA**
www.lfersatzteile724.at
info@lfersatzteile.at
- BALKAN COUNTRIES**
www.lfspareparts724.com
matija.ramov@lfspareparts.com
- BALTIC COUNTRIES**
www.lfspareparts724.com
inara.silina@lfspareparts.com
- LATIN AMERICA AND THE CARRIBEANS**
www.lfrepuestos-horeca724.es
export@lfrepuestos.es
- POLAND**
www.lfspareparts724.pl
info@lfspareparts.pl
- SOUTH KOREA**
www.lfspareparts724.com
fabio.doni@lfspareparts.com
- TURKEY**
www.lfyedekparca724.com
export@lfspareparts.com