



Spare parts for the professional sector: Cooking equipment



Suitable for:

ROSINOX



This catalogue is automatically generated.
Therefore, the sequence of the items might
not be always shown at best.
Updates will be issued in case of additions
and/or amendments.

Suitable universal spare parts may not be included





Suitable for:

ROSINOX

Suitable for:



Ball valves and accessories


3359535 2-WAY BALL TAP
with brass case
operating pressure 20 bar



ROSINOX RX94020443

Bearings

9063012 BEARING 6004 DDU NSK
external \varnothing 42mm - internal \varnothing 20mm - thickness 12mm



ROSINOX RX94008067

D063031 BEARING 6004-2RS SKF
 \varnothing extern 42 mm - \varnothing intern 20 mm - thickness 12 mm
single box packaging



Burners, flame spreaders and accessories

3025168 BURNER \varnothing 75 mm 3.5 KW
for Kitchen gas (ROSINOX) SI766E
for Pot stove gas (ROSINOX) SI766E



ROSINOX RX94800125

3025171 BURNER \varnothing 95 mm 5.5Kw
for Kitchen gas (ROSINOX) SI766E
for Pot stove (ROSINOX) SI766E



ROSINOX RX94800166

3025713 BURNER ASSEMBLY MOUNTING DISTANCE 325 mm
with central flame
15000-20000 Kcal/h
height 80 mm - \varnothing 200 mm - pipe \varnothing 34 mm



ROSINOX RX94008463

3025680 GAS BURNER SUPPORT GR6 \varnothing 34 mm



Suitable for:

3025811 BURNER BASE \varnothing 100 mm 7Kw
for Pot stove gas (ROSINOX)
since 1/02/03



ROSINOX RX94044421


Suitable for:

3025810 BURNER BASE \varnothing 120 mm 10Kw
for Pot stove gas (ROSINOX)
since 1/02/03
for Kitchen (ROSINOX) Rosichef 900 121G-SNG1200



ROSINOX RX94044422

3025179 BURNER RING \varnothing 90 mm



ROSINOX RX94805595

3025599 FLAME SPREADER \varnothing 100 mm



ROSINOX 94800265

3025627 FLAME SPREADER \varnothing 100 mm



ROSINOX RX94044419


ROSINOX 94044419

3025613 FLAME SPREADER \varnothing 120 mm



ROSINOX RX24180598

3025809 FLAME SPREADER \varnothing 120 mm
for Pot stove gas (ROSINOX)
since 1/02/03
for Kitchen (ROSINOX) Rosichef 900 121G-SNG1200



ROSINOX RX94044420

3025810 BURNER BASE \varnothing 120 mm 10Kw
for Pot stove gas (ROSINOX)
since 1/02/03
for Kitchen (ROSINOX) Rosichef 900 121G-SNG1200



ROSINOX RX94044422

3025808 VENTURI 100 mm 4.5kW
inlet \varnothing 3/8" - height 45 mm
for Pot stove gas (ROSINOX)
since 1/02/03



ROSINOX RX94044469



Suitable for:

ROSINOX



3025169 FLAME SPREADER \varnothing 75 mm 4.3Kw
for Kitchen gas (ROSINOX) SI766E
for Pot stove gas (ROSINOX) SI766E



ROSINOX RX94800182

3025911 BURNER \varnothing 75 mm 3.5Kw



3025297 BURNER \varnothing 75 mm 4.3Kw



3025312 SPARKING PLUG SUPPORT
for burners \varnothing 75-95 mm



ROSINOX RX94806049

3025176 FLAME SPREADER \varnothing 80 mm



ROSINOX RX94805553

Suitable for:

3025168 BURNER \varnothing 75 mm 3.5 KW
for Kitchen gas (ROSINOX) SI766E
for Pot stove gas (ROSINOX) SI766E




ROSINOX RX94800125

5017734 BURNER \varnothing 75 mm 3.5Kw



3020093 NOZZLE HOLDER FOR PIPE \varnothing 12 mm
with nut and olive
thread connection for hose M20x1.5 mm
fastening fitting M14x1 mm



3025170 VENTURI F/FLAME SPREADER 75 mm 3.5Kw
for Kitchen gas (ROSINOX) SI766E
for Kitchen gas (ROSINOX) SI766E



ROSINOX RX94806841

Suitable for:

3025172 FLAME SPREADER 6.4Kw \varnothing 95 mm
for Kitchen gas (ROSINOX) SI766E
for Kitchen (ROSINOX) SI766E



ROSINOX RX94800174


3025912 BURNER \varnothing 95 mm 5.5Kw



3025298 BURNER \varnothing 95 mm 6.4Kw



3025312 SPARKING PLUG SUPPORT
for burners \varnothing 75-95 mm



ROSINOX RX94806049

3025679 GAS BURNER SUPPORT GR5 \varnothing 27 mm



ROSINOX RX94007267

Suitable for:

3025171 BURNER \varnothing 95 mm 5.5Kw
for Kitchen gas (ROSINOX) SI766E
for Pot stove (ROSINOX) SI766E



ROSINOX RX94800166

5035019 BURNER \varnothing 95 mm 5.5Kw



3020093 NOZZLE HOLDER FOR PIPE \varnothing 12 mm
with nut and olive
thread connection for hose M20x1.5 mm
fastening fitting M14x1 mm




3025173 VENTURI F/FLAME SPREADER 95 mm 5.5Kw
for Kitchen gas (ROSINOX) SI766E
for Kitchen gas (ROSINOX) SI766E



ROSINOX RX94806437

3025312 SPARKING PLUG SUPPORT
for burners \varnothing 75-95 mm



ROSINOX RX94806049



Suitable for:

ROSINOX



3025170 VENTURI F/FLAME SPREADER 75 mm 3.5Kw
for Kitchen gas (ROSINOX) SI766E
for Kitchen gas (ROSINOX) SI766E



ROSINOX RX94806841

Suitable for:

3025173 VENTURI F/FLAME SPREADER 95 mm 5.5Kw
for Kitchen gas (ROSINOX) SI766E
for Kitchen gas (ROSINOX) SI766E



ROSINOX RX94806437

3025807 VENTURI FOR BURNER 7-10kW
mounting distance 180 mm - lateral outlet \varnothing 3/8"
pipe fixing - internal \varnothing 35 mm
for Pot stove gas (ROSINOX)
since 1/02/03
for Kitchen (ROSINOX) Rosichef 900 121G-SNG1200



ROSINOX RX94044423


3025808 VENTURI 100 mm 4.5kW
inlet \varnothing 3/8" - height 45 mm
for Pot stove gas (ROSINOX)
since 1/02/03



ROSINOX RX94044469

Buzzers

3397302 ALARM BELL 220V



ROSINOX RX94027794

Cables for piezo igniters

3001016 IGNITION LEAD 1000 mm
with faston \varnothing 2.4 mm for ignition
with faston \varnothing 4 mm for electrode



ROSINOX RX94805074

ROSINOX RX94805694

5017976 IGNITION LEAD 1700 mm
with faston \varnothing 2.4 mm for ignition
with faston \varnothing 4 mm for electrode



ROSINOX RX94805199



Castors, rollers and accessories

3738016 SWIVELLING WHEEL
with STAINLESS STEEL supports - polyamide nucleus
polyurethane coating
dimension \varnothing 100x30 mm - load capacity 150 Kg
pin hole \varnothing 13 mm



ROSINOX RX94051265

3738017 SWIVELLING WHEEL WITH BRAKE
with STAINLESS STEEL supports - polyamide nucleus
polyurethane thermoplastic ring
dimension \varnothing 100x32 mm - load capacity 150 Kg
pin hole \varnothing 13 mm



ROSINOX RX94051273

Contact thermostats

3444283 CONTACT THERMOSTAT +110°C
boiler security
with manual reset - 10A 250V



ROSINOX RX94808326


3444609 CONTACT THERMOSTAT KSD301-R 95°C
manual reset - 10A 250V



ROSINOX RX94803111

Contactors

3351209 CONTACTOR AEG LS05 9A 230V 4Kw
coil 230V 50/60Hz
3 normally open contacts
1 normally closed auxiliary contact



ROSINOX RX94804408

ROSINOX RX94813830

3351260 AUXILIARY CONTACT AEG HS0501
10A
1 normally closed contact



3351261 AUXILIARY CONTACT AEG HS0510
10A
1 normally open contact





Suitable for:

ROSINOX



Suitable for:

3351221 CONTACTOR AEG LS15K 32A 230V 16Kw
 coil 230V 50/60Hz
 3 normally open contacts
 no auxiliary contact



ROSINOX RX27400282

3446516 AUXILIARY CONTACT AEG HS7K01
 10A
 1 normally closed contact



3351222 CONTACTOR AEG LS22K 50A 230V 22Kw
 coil 230V 50/60Hz
 3 normally open contacts
 no auxiliary contact



ROSINOX RX27400290

3351223 CONTACTOR AEG LS30K 65A 230V 30Kw
 coil 230V 50/60Hz
 3 normally open contacts
 no auxiliary contact



ROSINOX RX27400308

3351212 CONTACTOR AEG LS4K 9A 230V 4Kw
 coil 230V 50/60Hz
 3 normally open contacts
 1 normally open auxiliary contact



ROSINOX RX27400324

3446516 AUXILIARY CONTACT AEG HS7K01
 10A
 1 normally closed contact



3454032 AUXILIARY CONTACT AEG HS7K10
 1 NO contact



3446582 CONTACTOR LOVATO BF1810A
 coil 18A 230V 50/60Hz 7.5Kw
 3 normally open contacts
 1 normally open auxiliary contact



ROSINOX RX94810801

3446227 AUXILIARY CONTACT LOVATO G218
 10A
 1 contact NO
 1 contact NC



Suitable for:


3446214 CONTACTOR LOVATO BG09T4A
4KW 400V 9A - 4 normally open contacts
coil 230V 50/60Hz



ROSINOX RX94807062

Suitable for:

3446557 CONTACTOR LOVATO BG0901A
coil 9A 230V 50/60Hz 4Kw
3 normally open contacts
1 normally closed auxiliary contact



ROSINOX RX94814048

3454066 CONTACTOR SCHNEIDER LC1D25P7
25A 400V 11Kw - coil 230V 50/60Hz
3 normally open contacts
1 normally open auxiliary contact
1 normally closed auxiliary contact
for Bratt pan electric (ROSINOX) MBM80E



ROSINOX RX94019155

3397402 MOTOR PROTECTION SWITCH AEG Mbs25
50/60Hz - 1.1Kw
1.6÷2.5A
3 NO contacts



ROSINOX RX94810904

3397405 MOTOR PROTECTION SWITCH AEG Mbs25
50/60Hz - 1.5Kw
2.5÷4A
3 NO contacts



ROSINOX RX94810902

Cooking baskets and accessories

3055489 PASTA COOKER BASKET 140x140x200 mm
made of STAINLESS steel



ROSINOX RX94806494

3055282 PASTA COOKER BASKET 280x135x160 mm
made of stainless steel



ROSINOX RX94812611

3055362 PASTA COOKER BASKET 300x150x215 mm
made of stainless steel



ROSINOX RX94044348



Suitable for:

ROSINOX



Suitable for:

Drain assembly

3316150 DRAIN ASSEMBLY \varnothing 3/4" COMPLETE
h 30 mm - overflow pipe seat \varnothing 20.35 mm
external \varnothing 38 mm
with gasket and fixing nut



ROSINOX RX94806775


3448279 OVERFLOW PIPE \varnothing 20x64 mm
made of stainless steel



3448237 OVERFLOW PIPE \varnothing 20x165 mm
made of stainless steel




3448086 OVERFLOW PIPE IN CHROME PLATED BRASS
 \varnothing 20 mm
overall height 84 mm
for drain assembly \varnothing 3/4"



3448087 OVERFLOW PIPE IN CHROME PLATED BRASS
 \varnothing 20 mm
overall height 94 mm
for drain assembly \varnothing 3/4"



3448088 OVERFLOW PIPE IN CHROME PLATED BRASS
 \varnothing 20 mm
overall height 104 mm
for drain assembly \varnothing 3/4"



3448091 OVERFLOW PIPE IN CHROME PLATED BRASS
 \varnothing 20 mm
overall height 144 mm
for drain assembly \varnothing 3/4"



Drain hoses

3356049 OIL DRAIN PIPE WITH SAFETY DEVICE
 \varnothing 22 mm - length 210 mm - bayonet coupling
for TECNOINOX BAIN-MARIE-FRYER



ROSINOX RX94013232



Drain taps and accessories

5028318 BALL VALVE \varnothing 1"FF



ROSINOX RX94812667

5069700 DRAIN TAP FITTING \varnothing 1"MM-3/4"M
fitting height 80 mm



5017823 BLACK HANDLE \varnothing 62 mm
with index
round hole \varnothing 8 mm
for DRAIN VALVE



3356116 DRAIN TAP \varnothing 1"1/2F
fixed connection \varnothing 1"1/2"F - folding handle
for Boiling pan (ROSINOX)



ROSINOX RX94020237

1180001 GREASE KLUBERSYNTH UH1 14-151 45 g
food safe grease for lubrication
of all friction points
ideal for water and steam taps
operating temperature $-45^{\circ}/+120^{\circ}$
beige color - NSF H1 certified
hot and cold water resistant
high anti-corrosion power
can replace vaseline



3179010 FITTINGS SEALING TAPE LOCTITE 55 - 50 m
length 50 mt
suitable to hot and cold drinking water, gas
replaces pastes, hemp and sealing tapes
it allows the repositioning of couplings
in compliance with the latest regulations
Drinking water (Italian certification by C.S.A.,
according to standard KTW and WRC approved)
gas - water IMQ-UNICIG.
compliant with UNI EN 51-2 class Arp
approved by DVGW and DIN 30660



3180061 TAPE F. COUPLING SEALING LOCTITE 55-150m
length 150 metri
suitable for hot / cold drinking water. gas
replaces pastes, hemp and sealing tapes
it allows the correct replacement of fittings
compliant with the latest regulatory requirements
Drinking water (C.S.A. italian certified.
in line with KTW standard and WRC approved)
IMQ-UNICIG gas-water,
compliant with UNI EN 51-2 class Arp
DVGW and DIN 30660 approved





Suitable for:

3180039 VASELINE WUERTH 750 g
for lubrication of food processing machines
it protects chromed and rubber parts from
weather factors, moisture resistant,
operating temperature from -10°C up to +120°C
from +50°C to +120 °C the grease becomes oily



ROSINOX



Suitable for:

5009882 DRAIN TAP \varnothing 3/4" F
outlet \varnothing internal 22 mm



ROSINOX RX94806742

5009883 OIL DRAIN PIPE WITH SAFETY DEVICE
 \varnothing 22 mm - length 210 mm - bayonet coupling



3356049 OIL DRAIN PIPE WITH SAFETY DEVICE
 \varnothing 22 mm - length 210 mm - bayonet coupling
for TECNOINOX BAIN-MARIE-FRYER



ROSINOX RX94013232

3526632 GAS/WATER BALLCOCK VALVE \varnothing 3/4" FF
heavy series with PN 40 total passage
DIN - DVGW approved
aluminium throttle



ROSINOX RX94032687

ROSINOX RX94812688

3356078 BUSHING \varnothing 11x20 mm



3241275 BLACK KNOB
square hole: 7x7mm



3356077 CLASP \varnothing 3.5x30 mm
UNI 6873 - DIN 1481 - ISO 8752





Suitable for:

5009883 OIL DRAIN PIPE WITH SAFETY DEVICE
ø 22 mm - length 210 mm - bayonet coupling

ROSINOX

Suitable for:




Electric hot plates

3311092 ELECTRIC HOT PLATE ø 145 mm 1500W 230V
terminal block electric connections
with STAINLESS steel edge 8 mm
for electric cooking top



ROSINOX

3311096 ELECTRIC HOT PLATE ø 180 mm 2000W 230V
terminal block electric connections
with STAINLESS steel edge 8 mm
for electric cooking top



ROSINOX RX94012804

3311100 ELECTRIC HOT PLATE ø 220 mm 2600W 230V
terminal block electric connections
with STAINLESS steel edge
for electric cooking top



ROSINOX RX94012796

3311101 ELECTRIC HOT PLATE ø 220 mm 2600W 400V
terminal block electric connections
with STAINLESS steel edge
for electric cooking top



ROSINOX

3311089 ELECTRIC HOT PLATE ø 300 mm 3500W 230V
screw electric connections
with STAINLESS steel edge
for electric cooking top



ROSINOX RX94012770

3311078 ELECTRIC HOT PLATE ø 300 mm 3500W 400V
terminal block electric connections
with STAINLESS steel edge
for electric cooking top



ROSINOX

3311053 ELECTRIC HOT PLATE 2600W 230V
dimensions 220x220 mm
terminal block electric connections
with STAINLESS steel edge
for electric cooking top



ROSINOX RX94806866



Suitable for:

ROSINOX

Suitable for:



Electrical capacitors

3068019 CAPACITOR DUCATI ENERGIA 12,5µF
450V 50/60Hz
operating temperature -25 +85°C
lead connection 6.35x0.8 mm
ø 36xh70 mm



ROSINOX RX94814010

3068008 CAPACITOR DUCATI ENERGIA 5µF
450V 50/60Hz
operating temperature -25 +85°C
lead connection 6.35x0.8 mm
ø 28xh55 mm



ROSINOX RX94801305

3068081 CAPACITOR ELECTRICAL 12.5µF
450V 50/60Hz - ø 35xh71 mm



ROSINOX RX94814010

3068086 CAPACITOR ELECTRICAL 25µF
450V 50/60Hz - ø 45xh71 mm



ROSINOX RX94051638


3068096 CAPACITOR ELECTRICAL 5µF
450V 50/60Hz - ø 30xh51 mm



ROSINOX RX94801305

Electrical gas valves and accessories

3526285 COIL mV
for LPG GAS
for GAS VALVE UNITROL 7000



ROSINOX

3526098 COIL 220V
for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA



ROSINOX 27440130

3523073 GAS VALVE UNITROL U7000ER-240-S7CL/S
inlet ø 3/4" F - outlet ø 3/4" F
thermocouple connection 11/32"
NATURAL GAS pressure switch 6.7"W.C.
power supply 220/240Vac 50/60Hz



ROSINOX

3523080 COIL 24V
for LPG GAS
for GAS VALVE UNITROL 7000





Suitable for:

3526236 COIL 240V
with pressure regulator - for NATURAL GAS
for GAS VALVE UNITROL 7000




3241929 GREY KNOB ø 30 mm SILK-SCREEN PRINTED
for EUROPEAN MARKET



3120360 MAGNETIC UNIT UNITROL
head ø 23 mm - length 59 mm
thermocouple connection 11/32"
for GAS VALVE UNITROL 7000 BMSER/BMSGOR



3526287 PRESSURE REGULATOR FOR GAS VALVE
for NATURAL GAS 6.7"W.C.
for VALVOLA GAS UNITROL 7000



3523082 VALVE MICROSWITCH
length 415 mm
for GAS VALVE UNITROL 7000 BER



ROSINOX



Suitable for:

3241707 GREY KNOB ø 30 mm ON-OFF-PILOT
for USA MARKET




ROSINOX RX26645069

3526235 LPG BLIND PLATE
for GAS VALVE UNITROL 7000



3526238 PRESSURE REGULATOR FOR GAS VALVE
for NATURAL GAS 3.5"W.C.
for GAS VALVE UNITROL 7000



3440125 VALVE MICROSWITCH
length 300 mm
for GAS VALVE UNITROL



3526283 VALVE MICROSWITCH
length 450 mm
for GAS VALVE UNITROL





Suitable for:

ROSINOX



3523076 GAS VALVE UNITROL 7000BER-S7CL
 inlet \varnothing 3/4" F - outlet \varnothing 3/4" F
 thermocouple connection 11/32"
 NATURAL GAS pressure switch 6.7"W.C.
 slow opening
 supply 12Vdc/24Vac 50/60Hz



ROSINOX

3241929 GREY KNOB \varnothing 30 mm SILK-SCREEN PRINTED
 for EUROPEAN MARKET



3526238 PRESSURE REGULATOR FOR GAS VALVE
 for NATURAL GAS 3.5"W.C.
 for GAS VALVE UNITROL 7000



3440125 VALVE MICROSWITCH
 length 300 mm
 for GAS VALVE UNITROL



3526283 VALVE MICROSWITCH
 length 450 mm
 for GAS VALVE UNITROL




Suitable for:

3241707 GREY KNOB \varnothing 30 mm ON-OFF-PILOT
 for USA MARKET




ROSINOX RX26645069

3120360 MAGNETIC UNIT UNITROL
 head \varnothing 23 mm - length 59 mm
 thermocouple connection 11/32"
 for GAS VALVE UNITROL 7000 BMSER/BMSGOR



3526287 PRESSURE REGULATOR FOR GAS VALVE
 for NATURAL GAS 6.7"W.C.
 for VALVOLA GAS UNITROL 7000



3523082 VALVE MICROSWITCH
 length 415 mm
 for GAS VALVE UNITROL 7000 BER



ROSINOX

3523079 GAS VALVE UNITROL 7000BGO-S7B
 inlet \varnothing 3/4" F - outlet \varnothing 3/4" F
 thermocouple connection 11/32"
 without pressure regulator



ROSINOX

3241929 GREY KNOB \varnothing 30 mm SILK-SCREEN PRINTED
 for EUROPEAN MARKET



3120360 MAGNETIC UNIT UNITROL
 head \varnothing 23 mm - length 59 mm
 thermocouple connection 11/32"
 for GAS VALVE UNITROL 7000 BMSER/BMSGOR



3440125 VALVE MICROSWITCH
 length 300 mm
 for GAS VALVE UNITROL



3526283 VALVE MICROSWITCH
 length 450 mm
 for GAS VALVE UNITROL



Suitable for:

3241707 GREY KNOB \varnothing 30 mm ON-OFF-PILOT
 for USA MARKET



ROSINOX RX26645069

3526235 LPG BLIND PLATE
 for GAS VALVE UNITROL 7000



3440160 THERMOPILE \varnothing 10x54 mm
 cable length 900 mm
 for GAS VALVE UNITROL 7000



3523082 VALVE MICROSWITCH
 length 415 mm
 for GAS VALVE UNITROL 7000 BER



ROSINOX



Suitable for:

ROSINOX



3523074 GAS VALVE UNITROL 7000BMV-S7CL
inlet \varnothing 3/4" F - outlet \varnothing 3/4" F
without pressure regulator
power supply 350mV through THERMOPILE



ROSINOX RX24867038

3241707 GREY KNOB \varnothing 30 mm ON-OFF-PILOT
for USA MARKET



ROSINOX RX26645069

3526235 LPG BLIND PLATE
for GAS VALVE UNITROL 7000



3440160 THERMOPILE \varnothing 10x54 mm
cable length 900 mm
for GAS VALVE UNITROL 7000



3440172 THERMOPILE WITH TWIN LEAD \varnothing 9x65 mm
250÷750mV
cable length 850 mm - with fitting M11x1
for GAS VALVE UNITROL 7000



3526285 COIL mV
for LPG GAS
for GAS VALVE UNITROL 7000



ROSINOX

3241929 GREY KNOB \varnothing 30 mm SILK-SCREEN PRINTED
for EUROPEAN MARKET



3120360 MAGNETIC UNIT UNITROL
head \varnothing 23 mm - length 59 mm
thermocouple connection 1 1/32"
for GAS VALVE UNITROL 7000 BMSER/BMSGOR



3440128 THERMOPILE \varnothing 9x65 mm
250÷750mV
cable length 900 mm - with fitting M9X1
with fixing coupling M10x1
for GAS VALVE UNITROL 7000



ROSINOX RX24802365

3440173 THERMOPILE WITH TWIN LEAD \varnothing 9x65 mm
with adjuster
250÷750mV
cable length 1450 mm
with fixing coupling M11x1
for GAS VALVE UNITROL 7000





Suitable for:

3440125 VALVE MICROSWITCH
length 300 mm
for GAS VALVE UNITROL



ROSINOX



Suitable for:

3523082 VALVE MICROSWITCH
length 415 mm
for GAS VALVE UNITROL 7000 BER



3526283 VALVE MICROSWITCH
length 450 mm
for GAS VALVE UNITROL



ROSINOX

3440128 THERMOPILE \varnothing 9x65 mm
250÷750mV
cable length 900 mm - with fitting M9X1
with fixing coupling M10x1
for GAS VALVE UNITROL 7000



ROSINOX RX24802365

3523082 VALVE MICROSWITCH
length 415 mm
for GAS VALVE UNITROL 7000 BER



ROSINOX

3526096 VALVE MICROSWITCH
maximum load 0.2 A
for VALVE ELETTROSIT-820 NOVA-824 NOVASIT



ROSINOX RX94034683

7108292 VALVE VK4105B HONEYWELL \varnothing 18 mm
inlet-outlet \varnothing 18 mm without thread
gas inlet max pressure 60 mbar
ambient temperature 15÷60°C
power supply 220/240V



ROSINOX RX94042249



Suitable for:

ROSINOX



3526090 VALVE 810 ELETTROSIT \varnothing 3/4"FF
 inlet \varnothing 3/4" F - outlet \varnothing 3/4" F
 thermocouple connection M9x1
 maximum gas inlet pressure 50 mbar
 pressure adjustment range
 3 ÷ 18 mbar
 ambient temperature 0 ÷ 60°C
 power supply 230V 50Hz
 long buttons
 pilot connection and LATERAL thermocouple



ROSINOX RX94024965

3526100 COIL 220V
 for VALVE ELETTROSIT



3526093 EXTENSION FOR ELETTROSIT BUTTON 34 mm
 for switching on/off buttons



3526107 FLANGE STRAIGHT \varnothing 3/4" F
 with screws and OR
 for ELETTROSIT VALVE



3526136 SPRING FOR PUSH-BUTTON



3526137 BUTTON FOR ELETTROSIT VALVE 46 mm



3526108 ELBOW FLANGE \varnothing 1/2" F
 with screws and OR
 for ELETTROSIT VALVE



3526106 FLANGE STRAIGHT \varnothing 1/2" F
 with screws and OR
 for ELETTROSIT VALVE



3001008 PIEZO IGNITER
 a \varnothing 14 mm hole is required for the assembly
 faston M \varnothing 2.4 mm



3526096 VALVE MICROSWITCH
 maximum load 0.2 A
 for VALVE ELETTROSIT-820 NOVA-824 NOVASIT



ROSINOX RX94034683

Suitable for:

Suitable for:

3526079 VALVE 820 NOVA \varnothing 1/2"FF
 inlet \varnothing 1/2" F - outlet \varnothing 1/2" F
 thermocouple fitting M9x1
 maximum gas inlet pressure 60 mbar
 outlet pressure setting range
 3÷30 mbar
 room temperature 0÷70°C
 power supply 230V 50Hz



ROSINOX 94023744

3526098 COIL 220V
 for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA



ROSINOX 27440130

3526099 COIL 24V
 for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA



3526078 ELBOW FLANGE \varnothing 3/4" F
 with screws and OR
 for valves SIT 820-Honeywell V4400-V4600-VR4605P



5047586 EXTENSION FOR VALVE 820 NOVA
 D-shaped pin \varnothing 10x8 mm



3526270 VALVE 820 NOVA EXTENSION
 D shaft \varnothing 10x8 mm



2100054 COIL 220V 60Hz
 for VALVE 820 NOVA-822 NOVA-828 NOVA



3526077 ELBOW FLANGE \varnothing 1/2" F
 with screws and OR
 for valves SIT 820-Honeywell V4400-V4600-VR4605P



3526102 ELECTRIC COUPLING WITH CABLE
 cable length 1000 mm - 3 wires
 for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA




3241141 EXTENSION FOR 820 NOVA VALVE
 D-shaped pin 10x8 mm





Suitable for:

3020083 FITTING AND OLIVE \varnothing 4 mm



3526075 FLANGE STRAIGHT \varnothing 1/2"
with screws and OR
for valves SIT 820-Honeywell V4400-V4600-VR4605P



3526124 KNOB EXTENSION LENGTH 67 mm
for VALVE 820 NOVA-824 NOVASIT



3182008 MAGNETIC UNIT SIT
head \varnothing 35 mm - end piece \varnothing 20 mm - length 47 mm
for valve SIT NOVASIT 820



3526103 PROTECTING COVER
for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA




5012595 VALVE EXTENSION 820 NOVA
D-shaped pin \varnothing 6x4.6 mm



ROSINOX

Suitable for:

3020084 FITTING AND OLIVE \varnothing 6 mm



3526076 FLANGE STRAIGHT \varnothing 3/4"
with screws and OR
for valves SIT 820-Honeywell V4400-V4600-VR4605P




3241142 KNOB GASKET \varnothing 44 mm



3001008 PIEZO IGNITER
a \varnothing 14 mm hole is required for the assembly
faston M \varnothing 2.4 mm



5017951 PROTECTION RUBBER VALVE 820-824 NOVA
 \varnothing external 50 mm - \varnothing internal 20 mm
depth 1 mm



3526096 VALVE MICROSWITCH
maximum load 0.2 A
for VALVE ELETTROSIT-820 NOVA-824 NOVASIT




3526269 VALVE 820 NOVA EXTENSION
D shaft \varnothing 10x8 mm



Electronic boards

3390356 CONTROL PC BOARD 130x80 mm
for Fryer gas (ROSINOX) FR25G
for Fryer (ROSINOX) FR30EHP - FR30ENP
RCS FR30EHP - ROSI FR30EHP RCS FR25GHP



ROSINOX RX94035029


3390359 PC BOARD LEVEL 90x70 mm
for Bratt pan electric (ROSINOX) MBM80E
for Bratt pan gas (ROSINOX) MBM80G



ROSINOX RX94023587

Energy regulators

3350024 ENERGY REGULATOR
contact capacity 240V 13A
max temperature 125°C
D-shaped pin \varnothing 6x4.6 mm
double rotation direction
for Hot plate electric (ROSINOX) ROSICHEF 200E
ROSICHEF 400E



ROSINOX RX94045299

3350026 ENERGY REGULATOR
contact capacity 230V 13A - max temperature 125°C
D-shaped pin \varnothing 6x4.6 mm
double rotation direction
for PYROCERAM. TOPS-SALAMANDERS-POTATO WARMERS



ROSINOX RX94812641

3350065 ENERGY REGULATOR
contact capacity 230V 12A
D-shaped pin \varnothing 6x4.6 mm



ROSINOX RX94027786

3350066 ENERGY REGULATOR
contact capacity 400V 7A
D-shaped pin \varnothing 6x4.6 mm



ROSINOX RX24848012




Suitable for:

ROSINOX



Suitable for:

3350067 ENERGY REGULATOR
contact capacity 24V 16A
D-shaped pin \varnothing 6x4.6 mm



ROSINOX 94043338

Feet

3313061 ADJUSTABLE PLASTIC FOOT \varnothing 30 mm
for tubular 40x40 mm
adjustable height 26÷47 mm
max capacity 90 Kg



ROSINOX

3313041 ADJUSTABLE S/ST. FOOT \varnothing 1"3/4 x h 115 mm
with fixed screw M10x25 mm
adjustable height 115÷180 mm



ROSINOX RX94806148

3313005 ADJUSTABLE S/STEEL FOOT \varnothing 2" x h 135 mm
with fixed screw M12x40 mm
adjustable height 135÷200 mm



ROSINOX RX94809563

Filters

3160007 WATER FILTER \varnothing 3/4"FF



ROSINOX RX94024528

Fittings

3349346 NICHEL-PL.HOSE-END FITTING \varnothing 1/4" M \varnothing 12



ROSINOX RX94813991

3349337 NICHEL-PL.T-FITTING \varnothing 1/4" F-1/4" F-1/4" F



ROSINOX RX94814314

Suitable for:

3349324 NICHEL-PLATED FITTING \varnothing 1/4"M-1/2"M



ROSINOX 12033

Suitable for:

3349330 NICHEL-PLATED FITTING \varnothing 1/4"M-1/8"F



ROSINOX RX94814405

Fryer baskets and accessories

3055197 FRYER BASKET 290x165x120 mm
in chromium plated iron



ROSINOX RX94806247

3055466 FRYER BASKET HANDLE 140x40 mm
distance between holes 115 mm
of plastic



3055360 FRYER BASKET 290x230x120 mm
made of chrome plated iron



ROSINOX RX94806221

3055466 FRYER BASKET HANDLE 140x40 mm
distance between holes 115 mm
of plastic



Fuses

3049020 DELAY FUSE \varnothing 5x20 mm - 10 PCS
250V 6.3A



ROSINOX RX27630086

3049052 QUICK ACTING FUSE \varnothing 5x20 mm - 10 PCS
250V 4A



ROSINOX RX27630268

Gas burners

3023341 BURNER \varnothing 40x190 mm
total length 230 mm
made of STAINLESS steel
for Fry top gas (ROSINOX) GR20G
for Pot stove gas (ROSINOX) 120MFNDET



ROSINOX RX94561040



Suitable for:

ROSINOX



Suitable for:

Gas burners

3023339 BURNER \varnothing 40x510 mm
 of stainless steel
 total length 540 mm
 for Bratt pan gas (ROSINOX) MBM80G
 for Pot stove gas (ROSINOX) 121G



ROSINOX RX94006715

3023338 NOZZLE HOLDER FOR BURNER
 tapered coupling for pipe M18x1.5 mm
 nozzle threading M13x1 mm
 external thread \varnothing 3/8" - internal \varnothing 10 mm
 pipe \varnothing 12 mm
 for Bratt pan gas (ROSINOX) MBM80G - SBM50G
 for Fry top gas (ROSINOX) GR20G
 for Pot stove gas (ROSINOX) 120MFMDDET



ROSINOX RX94018736

3023340 BURNER \varnothing 40x510 mm
 of stainless steel
 total length totale 550 mm
 for Bratt pan gas (ROSINOX) SBM50G - SBM80G
 for Bratt pan gas (ROSINOX) SBM50G



ROSINOX RX94494564

3023230 BURNER 525x205 mm
 made of STAINLESS steel



ROSINOX RX94814483

5028943 NOZZLE HOLDER FOR BURNER
 tapered coupling for pipe M16x1.5 mm
 fixing M14x1 mm - tube \varnothing 10 mm



5017733 BURNER 610x320 mm
 made of cromed iron



ROSINOX RX94812661

3023338 NOZZLE HOLDER FOR BURNER
 tapered coupling for pipe M18x1.5 mm
 nozzle threading M13x1 mm
 external thread \varnothing 3/8" - internal \varnothing 10 mm
 pipe \varnothing 12 mm
 for Bratt pan gas (ROSINOX) MBM80G - SBM50G
 for Fry top gas (ROSINOX) GR20G
 for Pot stove gas (ROSINOX) 120MFMDDET



ROSINOX RX94018736


**3023236 VERTICAL BURNER LH 300x55 mm
NICKEL PLATED**



ROSINOX RX94805710


Gas taps and accessories

3348159 GAS TAP
without pilot flame
clamp connection for pipe \varnothing 18 mm
outlet fitting M14x1.5 mm
pin length 35 mm
D-shaped pin \varnothing 6x4.6 mm



ROSINOX RX94019874

3348149 GAS TAP STN3R
with pilot flame
clamp connection for pipe \varnothing 27 mm
outlet fitting \varnothing 1/2" F - pilot fitting \varnothing 1/8" F
thermocouple connection M9x1
pin length 38 mm
square pin 8x8 mm
for Bratt pan gas (ROSINOX) SB50G
for Kitchen gas (ROSINOX) 121GTS



ROSINOX RX94019932

3348014 GAS TAP 20/S
without pilot flame
fittings \varnothing M16x1.5mm
thermocouple fitting M8x1
D-shaped pin \varnothing 8x6.5mm



ROSINOX RX94805017

3348020 CAP WITH PIN \varnothing 8x6.5 mm
pin length 22 mm
for model PEL 20S



3348058 MAGNET PROTECTION NUT M8x1
thread M18x1 mm
for model PEL 20-21-22



3348059 MAGNET PROTECTION NUT M9x1
thread M18x1mm
for model PEL 20-21-22





Suitable for:

3182022 MAGNETIC GROUP PEL SMALL HEAD
head \varnothing 15.5 mm - end piece \varnothing 11.5 mm - length 44mm



ROSINOX



Suitable for:

3182011 MAGNETIC UNIT PEL SMALL HEAD
head \varnothing 15 mm - end piece \varnothing 11 mm - length 44 mm
for PEL tap models 20-21
for EGA tap model 25213
for JUNKERS tap model CH110



3348044 OLIVE FOR PIPE \varnothing 10 mm
for model PEL 20-21-24-25



3348036 OLIVE FOR PIPE \varnothing 4 mm
for model PEL 21-22-24-25



3348037 OLIVE FOR PIPE \varnothing 6 mm
for model PEL 21-22-24-25



ROSINOX RX94812588


3348043 PIPE FITTING \varnothing 10 mm
thread M16x1.5 mm
for model PEL 20-21-24-25



3348029 PIPE FITTING \varnothing 4 mm
thread M10x1 mm
for model PEL 21-22-24-25




3020078 PIPE FITTING \varnothing 6 mm
thread M10x1



5014757 PIPE FITTING \varnothing 6 mm
thread M10x1 mm




3348191 GAS TAP 21/N
 with connections and olives \varnothing 10 mm
 without pilot flame
 connections M16x1.5 mm
 D-shaped pin \varnothing 6x4.6 mm - long pin 40/16mm
 for Pot stove gas (ROSINOX) 020G - 040G
 120MFNDET - 121GFNC - 121GFND



ROSINOX RX94020500


3348219 CAP WITH PIN \varnothing 6x4.6 mm
 pin length 45/20 mm upper/lower
 for model PEL 21



3348221 CAP WITH PIN \varnothing 6x4.6 mm
 pin length 30/17,5 mm upper/lower
 for model PEL 21




3348238 CAP WITH PIN \varnothing 8x6.5 mm
 pin 35/15 mm upper/lower
 for model PEL 21S




3348236 FLANGIA WITH PRESSURE FITTING \varnothing 16/10 mm
 thread M16x1,5 mm - M10x1,25 mm
 for model PEL 21S




7102841 BODY FITTING TAP
 \varnothing pipe 10 mm
 thread \varnothing 3/8" F - M16x1 mm
 for taps PEL 20S-21S




3348220 CAP WITH PIN \varnothing 6x4.6 mm
 pin length 30/23 mm upper/lower
 for model PEL 21



3348021 CAP WITH PIN \varnothing 8x6.5 mm
 pin length 22 mm
 for model PEL 21S



3348243 CAP WITH PIN \varnothing 8x6.5 mm
 pin length 22/15 mm right/lef
 for model PEL 21S



3348058 MAGNET PROTECTION NUT M8x1
 thread M18x1 mm
 for model PEL 20-21-22





Suitable for:

3348059 **MAGNET PROTECTION NUT M9x1**
thread M18x1mm
for model PEL 20-21-22



ROSINOX




Suitable for:

3182022 **MAGNETIC GROUP PEL SMALL HEAD**
head \varnothing 15.5 mm - end piece \varnothing 11.5 mm - length 44mm



3182011 **MAGNETIC UNIT PEL SMALL HEAD**
head \varnothing 15 mm - end piece \varnothing 11 mm - length 44 mm
for PEL tap models 20-21
for EGA tap model 25213
for JUNKERS tap model CH110



3348044 **OLIVE FOR PIPE \varnothing 10 mm**
for model PEL 20-21-24-25



3348036 **OLIVE FOR PIPE \varnothing 4 mm**
for model PEL 21-22-24-25



3348037 **OLIVE FOR PIPE \varnothing 6 mm**
for model PEL 21-22-24-25



ROSINOX RX94812588

3348043 **PIPE FITTING \varnothing 10 mm**
thread M16x1.5 mm
for model PEL 20-21-24-25



3348029 **PIPE FITTING \varnothing 4 mm**
thread M10x1 mm
for model PEL 21-22-24-25



3020078 **PIPE FITTING \varnothing 6 mm**
thread M10x1



5014757 **PIPE FITTING \varnothing 6 mm**
thread M10x1 mm



3348016 GAS TAP 21/S
 with pilot flame
 fittings \varnothing M16x1.5mm
 with flow regulator
 thermocouple connection M9x1
 D-shaped pin \varnothing 8x6.5 mm




ROSINOX RX94805868

3348085 BUSH FOR TAP




3348220 CAP WITH PIN \varnothing 6x4.6 mm
 pin length 30/23 mm upper/lower
 for model PEL 21



3348021 CAP WITH PIN \varnothing 8x6.5 mm
 pin length 22 mm
 for model PEL 21S




3348243 CAP WITH PIN \varnothing 8x6.5 mm
 pin length 22/15 mm right/lef
 for model PEL 21S




7102841 BODY FITTING TAP
 \varnothing pipe 10 mm
 thread \varnothing 3/8" F - M16x1 mm
 for taps PEL 20S-21S



3348219 CAP WITH PIN \varnothing 6x4.6 mm
 pin length 45/20 mm upper/lower
 for model PEL 21



3348221 CAP WITH PIN \varnothing 6x4.6 mm
 pin length 30/17,5 mm upper/lower
 for model PEL 21



3348238 CAP WITH PIN \varnothing 8x6.5 mm
 pin 35/15 mm upper/lower
 for model PEL 21S



3348236 FLANGIA WITH PRESSURE FITTING \varnothing 16/10 mm
 thread M16x1,5 mm - M10x1,25 mm
 for model PEL 21S





Suitable for:

3348058 **MAGNET PROTECTION NUT M8x1**
thread M18x1 mm
for model PEL 20-21-22



3182022 **MAGNETIC GROUP PEL SMALL HEAD**
head \varnothing 15.5 mm - end piece \varnothing 11.5 mm - length 44mm



3348044 **OLIVE FOR PIPE \varnothing 10 mm**
for model PEL 20-21-24-25



3348037 **OLIVE FOR PIPE \varnothing 6 mm**
for model PEL 21-22-24-25



3348029 **PIPE FITTING \varnothing 4 mm**
thread M10x1 mm
for model PEL 21-22-24-25




ROSINOX

Suitable for:

3348059 **MAGNET PROTECTION NUT M9x1**
thread M18x1mm
for model PEL 20-21-22



3182011 **MAGNETIC UNIT PEL SMALL HEAD**
head \varnothing 15 mm - end piece \varnothing 11 mm - length 44 mm
for PEL tap models 20-21
for EGA tap model 25213
for JUNKERS tap model CH110




3348036 **OLIVE FOR PIPE \varnothing 4 mm**
for model PEL 21-22-24-25



ROSINOX RX94812588

3348043 **PIPE FITTING \varnothing 10 mm**
thread M16x1.5 mm
for model PEL 20-21-24-25



3020078 **PIPE FITTING \varnothing 6 mm**
thread M10x1





Suitable for:

5014757 PIPE FITTING \varnothing 6 mm
thread M10x1 mm



ROSINOX




Suitable for:

3348190 GAS TAP 21/S
complete with connections and olives
with pilot flame
fittings M16x1.5 mm
thermocouple connection M9x1
D-shaped long pin \varnothing 6x4.6 mm
for Fry top gas (ROSINOX) GR20G
for Pot stove gas (ROSINOX) 120MFNDET - 121GFNC
121GFND




ROSINOX RX94020518


3348219 CAP WITH PIN \varnothing 6x4.6 mm
pin length 45/20 mm upper/lower
for model PEL 21



3348221 CAP WITH PIN \varnothing 6x4.6 mm
pin length 30/17,5 mm upper/lower
for model PEL 21




3348238 CAP WITH PIN \varnothing 8x6.5 mm
pin 35/15 mm upper/lower
for model PEL 21S



7102841 BODY FITTING TAP
 \varnothing pipe 10 mm
thread \varnothing 3/8" F - M16x1 mm
for taps PEL 20S-21S



3348220 CAP WITH PIN \varnothing 6x4.6 mm
pin length 30/23 mm upper/lower
for model PEL 21



3348021 CAP WITH PIN \varnothing 8x6.5 mm
pin length 22 mm
for model PEL 21S



3348243 CAP WITH PIN \varnothing 8x6.5 mm
pin length 22/15 mm right/lef
for model PEL 21S





Suitable for:

3348236 **FLANGIA WITH PRESSURE FITTING \varnothing 16/10 mm**
thread M16x1,5 mm - M10x1,25 mm
for model PEL 21S



ROSINOX



Suitable for:


3348058 **MAGNET PROTECTION NUT M8x1**
thread M18x1 mm
for model PEL 20-21-22




3348059 **MAGNET PROTECTION NUT M9x1**
thread M18x1mm
for model PEL 20-21-22



3182022 **MAGNETIC GROUP PEL SMALL HEAD**
head \varnothing 15.5 mm - end piece \varnothing 11.5 mm - length 44mm



3182011 **MAGNETIC UNIT PEL SMALL HEAD**
head \varnothing 15 mm - end piece \varnothing 11 mm - length 44 mm
for PEL tap models 20-21
for EGA tap model 25213
for JUNKERS tap model CH110



3348044 **OLIVE FOR PIPE \varnothing 10 mm**
for model PEL 20-21-24-25



3348036 **OLIVE FOR PIPE \varnothing 4 mm**
for model PEL 21-22-24-25




3348037 **OLIVE FOR PIPE \varnothing 6 mm**
for model PEL 21-22-24-25



ROSINOX RX94812588

3348043 **PIPE FITTING \varnothing 10 mm**
thread M16x1.5 mm
for model PEL 20-21-24-25



3348029 **PIPE FITTING \varnothing 4 mm**
thread M10x1 mm
for model PEL 21-22-24-25





Suitable for:

3020078 PIPE FITTING \varnothing 6 mm
thread M10x1



ROSINOX




Suitable for:

5014757 PIPE FITTING \varnothing 6 mm
thread M10x1 mm



3348002 GAS TAP 22S/O
with pilot flame
with horizontal flange
fittings \varnothing M20x1.5mm
with flow regulator
thermocouple connection M9x1
D-shaped pin \varnothing 10x8 mm




3348229 CAP WITH PIN \varnothing 10 mm
pin length 31 mm
for model PEL 22S/O



ROSINOX RX94805298

3348017 CAP WITH PIN \varnothing 10x8 mm
pin length 26 mm
for model PEL 22



3348245 CAP WITH PIN \varnothing 10x8 mm
pin length 34/26 mm upper/lower
for model PEL 22S



3348019 CAP WITH PIN \varnothing 10x9 mm
pin length 26 mm
for model PEL 22



3348231 CAP WITH PIN \varnothing 6x4.6 mm
pin length 35/21 mm upper/lower
for model PEL 22



3348232 CAP WITH PIN \varnothing 8x6.5 mm
pin length 39/7 mm upper/lower
for model PEL 22



3348213 FLANGE \varnothing 12/10 mm
without adjustment
thread M20x1.5 mm
for model PEL 22S






Suitable for:

3348023 FLANGE HORIZONTAL \varnothing 12/10 mm
thread M20x1.5
for model PEL 22



3348024 FLANGE VERTICAL \varnothing 12/10 mm
thread M20x1.5
for model PEL 22



3348058 MAGNET PROTECTION NUT M8x1
thread M18x1 mm
for model PEL 20-21-22



3182009 MAGNETIC UNIT PEL BIG HEAD
head \varnothing 15.5 mm - end piece \varnothing 14 mm - length 44 mm
for PEL tap model 22-24



ROSINOX 244761275

3348038 OLIVE FOR PIPE \varnothing 10 mm
for model PEL 22-24-25



ROSINOX

Suitable for:

3348025 FLANGE HORIZONTAL CONICAL \varnothing 12/10 mm
thread M20x1.5
for model PEL 22



3348214 FLANGIA WITH PRESSURE FITTING \varnothing 12/10 mm
thread M20x1.5 mm
for model PEL 22S



3348059 MAGNET PROTECTION NUT M9x1
thread M18x1mm
for model PEL 20-21-22



3182021 MAGNETIC UNIT PEL LARGE HEAD
head \varnothing 15.5 mm - end piece \varnothing 14 mm - length 44 mm



3020082 OLIVE FOR PIPE \varnothing 12 mm
for model PEL 22-24-25



ROSINOX RX94810978





Suitable for:

3348036 OLIVE FOR PIPE \varnothing 4 mm
for model PEL 21-22-24-25



ROSINOX RX94812588

3348230 PIN FOT GAS TAP \varnothing 6x4.6 mm
pin length 45/20 mm rh/lh
for model PEL 22



3348032 PIPE FITTING \varnothing 12 mm
thread M20x1.5 mm
for model PEL 22-24-25



3020078 PIPE FITTING \varnothing 6 mm
thread M10x1



3348158 GAS TAP 22S/O
with connections and olives
with pilot flame
with horizontal flange
fittings M20x1.5 mm
with flow regulator
thermocouple connection M9x1
pin length 48 mm
square pin 8x8 mm
for Bratt pan gas (ROSINOX) SBM35G - SBM50G
for Bratt pan (ROSINOX) ROSICHEF SEM50G 30/10



ROSINOX RX94020484

ROSINOX



Suitable for:

3348037 OLIVE FOR PIPE \varnothing 6 mm
for model PEL 21-22-24-25



3348031 PIPE FITTING \varnothing 10 mm
thread M20x1.5 mm
for model PEL 22-24-25




3348029 PIPE FITTING \varnothing 4 mm
thread M10x1 mm
for model PEL 21-22-24-25



5014757 PIPE FITTING \varnothing 6 mm
thread M10x1 mm



3348229 CAP WITH PIN \varnothing 10 mm
pin length 31 mm
for model PEL 22S/O





Suitable for:


3348017 CAP WITH PIN \varnothing 10x8 mm
pin length 26 mm
for model PEL 22



3348019 CAP WITH PIN \varnothing 10x9 mm
pin length 26 mm
for model PEL 22



3348232 CAP WITH PIN \varnothing 8x6.5 mm
pin length 39/7 mm upper/lower
for model PEL 22



3348025 FLANGE HORIZONTAL CONICAL \varnothing 12/10 mm
thread M20x1.5
for model PEL 22



3348058 MAGNET PROTECTION NUT M8x1
thread M18x1 mm
for model PEL 20-21-22



ROSINOX

Suitable for:

3348245 CAP WITH PIN \varnothing 10x8 mm
pin length 34/26 mm upper/lower
for model PEL 22S




3348231 CAP WITH PIN \varnothing 6x4.6 mm
pin length 35/21 mm upper/lower
for model PEL 22



3348023 FLANGE HORIZONTAL \varnothing 12/10 mm
thread M20x1.5
for model PEL 22



3348024 FLANGE VERTICAL \varnothing 12/10 mm
thread M20x1.5
for model PEL 22



3348059 MAGNET PROTECTION NUT M9x1
thread M18x1 mm
for model PEL 20-21-22





Suitable for:

3182009 MAGNETIC UNIT PEL BIG HEAD
head \varnothing 15.5 mm - end piece \varnothing 14 mm - length 44 mm
for PEL tap model 22-24



ROSINOX 244761275

3348038 OLIVE FOR PIPE \varnothing 10 mm
for model PEL 22-24-25



3348036 OLIVE FOR PIPE \varnothing 4 mm
for model PEL 21-22-24-25



ROSINOX RX94812588

3348230 PIN FOT GAS TAP \varnothing 6x4.6 mm
pin length 45/20 mm rh/lh
for model PEL 22



3348032 PIPE FITTING \varnothing 12 mm
thread M20x1.5 mm
for model PEL 22-24-25



3020078 PIPE FITTING \varnothing 6 mm
thread M10x1



ROSINOX



Suitable for:

3182021 MAGNETIC UNIT PEL LARGE HEAD
head \varnothing 15.5 mm - end piece \varnothing 14 mm - length 44 mm



3020082 OLIVE FOR PIPE \varnothing 12 mm
for model PEL 22-24-25




ROSINOX RX94810978

3348037 OLIVE FOR PIPE \varnothing 6 mm
for model PEL 21-22-24-25



3348031 PIPE FITTING \varnothing 10 mm
thread M20x1.5 mm
for model PEL 22-24-25



3348029 PIPE FITTING \varnothing 4 mm
thread M10x1 mm
for model PEL 21-22-24-25



5014757 PIPE FITTING \varnothing 6 mm
thread M10x1 mm





Suitable for:

5043101 SCREWS NO HEAD WITH HEXAGON SOCKET M4x5

stainless steel - flat edge
UNI 5923 - DIN 913 - ISO 4026
for Bratt pan (ROSINOX) ROSICHEF SEM50G 30/10



ROSINOX RX94027281

ROSINOX



Suitable for:

3348012 GAS TAP 23S/O


with pilot flame
with horizontal flange
inlet fitting M28x1.5mm
outlet connection M24x1.5mm
with flow regulator
thermocouple connection M10x1
D-shaped pin \varnothing 10x8 mm



ROSINOX RX94805462

3348062 CAP WITH PIN \varnothing 10x8 mm

pin length 35 mm
for model PEL 23




3348060 CAP WITH PIN \varnothing 10x8 mm

pin length 25 mm
for model PEL 23



3348237 FLANGE HORIZONTAL \varnothing 12/16 mm

without adjustment
thread M24x1.5 mm
for model PEL 23




3348027 FLANGE HORIZONTAL \varnothing 12/16 mm

thread M24x1.5 mm
for model PEL 23



3348028 FLANGE VERTICAL \varnothing 12/16 mm

thread M24x1.5
for model PEL 23



3182010 MAGNETIC UNIT PEL

head \varnothing 24 mm - end piece \varnothing 18 mm - length 59 mm
thermocouple coupling M10x1
for PEL tap model 23



3348040 OLIVE FOR PIPE \varnothing 12 mm

for model PEL 23



ROSINOX 244761276



Suitable for:

3348041 OLIVE FOR PIPE \varnothing 16 mm
for model PEL 23



3348036 OLIVE FOR PIPE \varnothing 4 mm
for model PEL 21-22-24-25



ROSINOX RX94812588

3348033 PIPE FITTING \varnothing 12 mm
thread M24x1.5
for model PEL 23



3348035 PIPE FITTING \varnothing 20 mm
thread M28x1.5
for model PEL 23



3020078 PIPE FITTING \varnothing 6 mm
thread M10x1



ROSINOX

Suitable for:

3348042 OLIVE FOR PIPE \varnothing 20 mm
for model PEL 23



3348037 OLIVE FOR PIPE \varnothing 6 mm
for model PEL 21-22-24-25



3348034 PIPE FITTING \varnothing 16 mm
thread M24x1.5
for model PEL 23



3348029 PIPE FITTING \varnothing 4 mm
thread M10x1 mm
for model PEL 21-22-24-25



5014757 PIPE FITTING \varnothing 6 mm
thread M10x1 mm






Suitable for:

ROSINOX



3348192 GAS TAP 235/0
 with connections and olives
 with pilot flame
 with horizontal flange
 inlet connection M28x1.5 mm
 outlet fitting M24x1.5 mm
 thermocouple fitting M9x1
 pin length 46 mm
 square pin 8x8 mm
 for Bratt pan gas (ROSINOX) SBM80G
 for Bratt pan (ROSINOX) R/C MODULAIRE



ROSINOX RX94020492

3348062 CAP WITH PIN \varnothing 10x8 mm
 pin length 35 mm
 for model PEL 23




Suitable for:

3348060 CAP WITH PIN \varnothing 10x8 mm
 pin length 25 mm
 for model PEL 23




3348237 FLANGE HORIZONTAL \varnothing 12/16 mm
 without adjustment
 thread M24x1.5 mm
 for model PEL 23



3348027 FLANGE HORIZONTAL \varnothing 12/16 mm
 thread M24x1.5 mm
 for model PEL 23



3348028 FLANGE VERTICAL \varnothing 12/16 mm
 thread M24x1.5
 for model PEL 23



3348040 OLIVE FOR PIPE \varnothing 12 mm
 for model PEL 23



3348041 OLIVE FOR PIPE \varnothing 16 mm
 for model PEL 23



3348042 OLIVE FOR PIPE \varnothing 20 mm
 for model PEL 23



3348036 OLIVE FOR PIPE \varnothing 4 mm
 for model PEL 21-22-24-25



ROSINOX RX94812588



Suitable for:

3348037 OLIVE FOR PIPE \varnothing 6 mm
for model PEL 21-22-24-25



3348033 PIPE FITTING \varnothing 12 mm
thread M24x1.5
for model PEL 23



3348035 PIPE FITTING \varnothing 20 mm
thread M28x1.5
for model PEL 23



3020078 PIPE FITTING \varnothing 6 mm
thread M10x1



3348036 OLIVE FOR PIPE \varnothing 4 mm
for model PEL 21-22-24-25



ROSINOX

Suitable for:

3182020 PEL MAGNETIC GROUP
head \varnothing 24 mm - end \varnothing 18 mm - length 59 mm
thermocouple fitting M9x1
for tap PEL model 23S



3348034 PIPE FITTING \varnothing 16 mm
thread M24x1.5
for model PEL 23



3348029 PIPE FITTING \varnothing 4 mm
thread M10x1 mm
for model PEL 21-22-24-25



5014757 PIPE FITTING \varnothing 6 mm
thread M10x1 mm





Suitable for:

ROSINOX

Suitable for:




Gas valves and accessories

3526131 EUROSIT VALVE FOR FRYER 110÷190°C
 inlet \varnothing 3/8" F - outlet \varnothing 3/8" F
 thermocouple connection M9x1
 maximum gas inlet pressure 50 mbar
 outlet pressure setting range
 3÷18 mbar outlet
 ambient temperature 0÷120°C
 capillary length 1050 mm
 bulb \varnothing 4x200 mm



ROSINOX RX94812670

4056009 CAP FOR VALVE EUROSIT-MERTIK \varnothing 3/8"
 with OR



3526260 CAP FOR VALVE EUROSIT \varnothing 3/8"
 with OR




3241435 EUROSIT VALVE EXTENSION
 D shaft \varnothing 10x8 mm




3526126 EUROSIT VALVE EXTENSION
 D shaft \varnothing 10x8 mm




3526677 EXTENSION FOR EUROSIT VALVE
 D-shaped pin \varnothing 10x8 mm




3020083 FITTING AND OLIVE \varnothing 4 mm



3020084 FITTING AND OLIVE \varnothing 6 mm



5050400 FITTING FOR OLIVE \varnothing 10 mm
 thread \varnothing 3/8" M



3526127 FLANGE FOR EXTENSION





Suitable for:

5021481 GAS OUTLET VALVE FITTING
thread \varnothing 3/8" M - M16x1 mm



3020082 OLIVE FOR PIPE \varnothing 12 mm
for model PEL 22-24-25



ROSINOX RX94810978

3020079 PIPE FITTING \varnothing 12 mm
thread \varnothing 3/8" M




3523035 KNOB MINISIT BLACK \varnothing 37 mm



ROSINOX RX26645036

3523093 MINISIT VALVE FOR FRYER 70÷210°C
inlet \varnothing 1/2" F - outlet \varnothing 3/8" F
thermocouple connection M9x1
maximum gas inlet pressure 50 mbar
ambient temperature 0÷60°C
length capillary 1300 mm
bulb \varnothing 4x122 mm
without cover. knob and flanges



ROSINOX

ROSINOX



Suitable for:


5050401 OLIVE FOR PIPE \varnothing 10 mm
external \varnothing 13 mm - height 8 mm




3001111 PIEZO IGNITER EUROSIT
M faston \varnothing 2.4 mm



3526123 RUBBER PROTECTION FOR EUROSIT VALVE



3523047 LID MINISIT



ROSINOX

2100757 CONNECTION FOR OLIVE \varnothing 16 mm
thread \varnothing 1/2" M





Suitable for:

3523038 ELBOW FLANGE MINISIT \varnothing 1/2" F
with screws and OR



3523035 KNOB MINISIT BLACK \varnothing 37 mm




ROSINOX RX26645036

3182003 MAGNETIC UNIT SIT
head \varnothing 25 mm - end piece \varnothing 17 mm - length 56 mm
for valve SIT AC2 - VR8-MINISIT



ROSINOX

3523060 OIL SEAL FITTING \varnothing 6.5 mm
internal thread M10x0.75 - external thread M14x1.5




ROSINOX RX94008893

3020082 OLIVE FOR PIPE \varnothing 12 mm
for model PEL 22-24-25



ROSINOX RX94810978

3001070 PIEZO IGNITER MINISIT
a \varnothing 22 mm hole is required for the assembly
faston M \varnothing 2.4 mm



ROSINOX




Suitable for:

3523037 ELBOW FLANGE MINISIT \varnothing 3/8"
with screws and OR



3523047 LID MINISIT



ROSINOX

3523061 NUT \varnothing 1/4"x6 mm




3348044 OLIVE FOR PIPE \varnothing 10 mm
for model PEL 20-21-24-25



3348041 OLIVE FOR PIPE \varnothing 16 mm
for model PEL 23



3001071 PIEZO IGNITER MINISIT WITH COVER
M faston 2.4 mm



ROSINOX LF-3001011




Suitable for:

3020079 PIPE FITTING \varnothing 12 mm
thread \varnothing 3/8" M



3523096 SENSING ELEMENT MINISIT 50÷190°C
stainless steel capillary length 1200 mm
bulb \varnothing 4x120 mm



3523949 MINISIT VALVE FOR FRYER 110÷190°C
inlet \varnothing 1/2" F - outlet \varnothing 3/8" F
thermocouple connection M9x1
maximum gas inlet pressure 50 mbar
ambient temperature 0÷60°C
capillary length 1050 mm
bulb \varnothing 6x105 mm
supplied without lid knob and flanges



ROSINOX RX94805793

3523038 ELBOW FLANGE MINISIT \varnothing 1/2" F
with screws and OR



3523035 KNOB MINISIT BLACK \varnothing 37 mm



ROSINOX RX26645036

ROSINOX



Suitable for:

3523036 REDUCTION STRAIGHT \varnothing 3/8" F - \varnothing 1/2" F
in brass with internal and external thread
internal thread \varnothing 3/8" F - external thread \varnothing 1/2" F
for MINISIT flange



5058320 TUBE NUT FITTING \varnothing 10 mm
thread M14x1,5 mm




2100757 CONNECTION FOR OLIVE \varnothing 16 mm
thread \varnothing 1/2" M



3523037 ELBOW FLANGE MINISIT \varnothing 3/8" F
with screws and OR



3523047 LID MINISIT



ROSINOX




Suitable for:

3182003 MAGNETIC UNIT SIT
head \varnothing 25 mm - end piece \varnothing 17 mm - length 56 mm
for valve SIT AC2 - VR8-MINISIT



ROSINOX

3523060 OIL SEAL FITTING \varnothing 6.5 mm
internal thread M10x0.75 - external thread M14x1.5



ROSINOX RX94008893

3020082 OLIVE FOR PIPE \varnothing 12 mm
for model PEL 22-24-25



ROSINOX RX94810978

3001070 PIEZO IGNITER MINISIT
a \varnothing 22 mm hole is required for the assembly
faston M \varnothing 2.4 mm



3020079 PIPE FITTING \varnothing 12 mm
thread \varnothing 3/8" M



ROSINOX

Suitable for:

3523061 NUT \varnothing 1/4"x6 mm




3348044 OLIVE FOR PIPE \varnothing 10 mm
for model PEL 20-21-24-25



3348041 OLIVE FOR PIPE \varnothing 16 mm
for model PEL 23



3001071 PIEZO IGNITER MINISIT WITH COVER
M faston 2.4 mm



ROSINOX LF-3001011


3523036 REDUCTION STRAIGHT \varnothing 3/8" F - \varnothing 1/2" F
in brass with internal and external thread
internal thread \varnothing 3/8" F - external thread \varnothing 1/2" F
for MINISIT flange





Suitable for:

3523051 SENSING ELEMENT MINISIT 110±190°C
capillary length 1050 mm
bulb ø 6x105 mm



ROSINOX




Suitable for:

5058320 TUBE NUT FITTING ø 10 mm
thread M14x1,5 mm



3523060 OIL SEAL FITTING ø 6.5 mm
internal thread M10x0.75 - external thread M14x1.5



ROSINOX RX94008893

3526134 VALVE 630 EUROSIT FRY TOP 40±280°C
inlet ø 3/8" F - outlet ø 3/8" F
thermocouple connection M9x1
maximum gas inlet pressure 50 mbar
outlet pressure calibration range
outlet 3÷18 mbar
ambient temperature 0÷80°C
capillary length 1050 mm
bulb ø 4x72 mm



3526260 CAP FOR VALVE EUROSIT ø 3/8"
with OR




ROSINOX RX94805660


4056009 CAP FOR VALVE EUROSIT-MERTIK ø 3/8"
with OR




3020083 FITTING AND OLIVE ø 4 mm



3020084 FITTING AND OLIVE ø 6 mm



5050400 FITTING FOR OLIVE ø 10 mm
thread ø 3/8" M





Suitable for:


3526127 FLANGE FOR EXTENSION




5050401 OLIVE FOR PIPE \varnothing 10 mm
external \varnothing 13 mm - height 8 mm



3001111 PIEZO IGNITER EUROSIT
M faston \varnothing 2.4 mm



3526123 RUBBER PROTECTION FOR EUROSIT VALVE



3526130 VALVE 630 EUROSIT OVEN 100÷340°C
inlet \varnothing 3/8" F - outlet \varnothing 3/8" F
thermocouple connection M9x1
maximum gas inlet pressure 50 mbar
outlet pressure adjustment range
3÷18 mbar
ambient temperature 0÷120°C
capillary length 1050 mm
bulb \varnothing 4x72 mm



ROSINOX 94044054

ROSINOX

Suitable for:

5021481 GAS OUTLET VALVE FITTING
thread \varnothing 3/8" M - M16x1 mm



3020082 OLIVE FOR PIPE \varnothing 12 mm
for model PEL 22-24-25



ROSINOX RX94810978

3020079 PIPE FITTING \varnothing 12 mm
thread \varnothing 3/8" M



3526260 CAP FOR VALVE EUROSIT \varnothing 3/8"
with OR





Suitable for:


4056009 CAP FOR VALVE EUROSIT-MERTIK \varnothing 3/8"
with OR



3526677 EXTENSION FOR EUROSIT VALVE
D-shaped pin \varnothing 10x8 mm



3020084 FITTING AND OLIVE \varnothing 6 mm



3526127 FLANGE FOR EXTENSION



3526128 KNOB EXTENSION LENGTH 34 mm
D-shaped pin \varnothing 8x6.5 mm



5050401 OLIVE FOR PIPE \varnothing 10 mm
external \varnothing 13 mm - height 8 mm




ROSINOX

Suitable for:

3526129 CLASP \varnothing 3x14 mm
UNI 6873 - DIN 1481 - ISO 8752



3020083 FITTING AND OLIVE \varnothing 4 mm



5050400 FITTING FOR OLIVE \varnothing 10 mm
thread \varnothing 3/8"M



5021481 GAS OUTLET VALVE FITTING
thread \varnothing 3/8"M - M16x1 mm



3526125 KNOB EXTENSION LENGTH 44 mm
D-shaped pin \varnothing 8x6.5 mm



3020082 OLIVE FOR PIPE \varnothing 12 mm
for model PEL 22-24-25





Suitable for:

3001111 **PIEZO IGNITER EUROSIT**
M faston \varnothing 2.4 mm



ROSINOX




Suitable for:

3020079 **PIPE FITTING \varnothing 12 mm**
thread \varnothing 3/8" M



3526123 **RUBBER PROTECTION FOR EUROSIT VALVE**



3523091 **VALVE 710 MINISIT OVEN 70÷310°C**
inlet \varnothing 1/2" F - outlet \varnothing 3/8" F
thermocouple connection M9x1
maximum gas inlet pressure 50 mbar
ambient temperature 0÷60°C
capillary length 1300 mm
bulb \varnothing 4x75 mm
without cover. knob and flanges



2100757 **CONNECTION FOR OLIVE \varnothing 16 mm**
thread \varnothing 1/2" M



ROSINOX RX94024916

3523038 **ELBOW FLANGE MINISIT \varnothing 1/2" F**
with screws and OR




3523037 **ELBOW FLANGE MINISIT \varnothing 3/8"**
with screws and OR



3523035 **KNOB MINISIT BLACK \varnothing 37 mm**



3523047 **LID MINISIT**



ROSINOX RX26645036

ROSINOX




Suitable for:

3182003 MAGNETIC UNIT SIT
head \varnothing 25 mm - end piece \varnothing 17 mm - length 56 mm
for valve SIT AC2 - VR8-MINISIT



ROSINOX

3523060 OIL SEAL FITTING \varnothing 6.5 mm
internal thread M10x0.75 - external thread M14x1.5



ROSINOX RX94008893

3020082 OLIVE FOR PIPE \varnothing 12 mm
for model PEL 22-24-25



ROSINOX RX94810978

3001070 PIEZO IGNITER MINISIT
a \varnothing 22 mm hole is required for the assembly
faston M \varnothing 2.4 mm



3020079 PIPE FITTING \varnothing 12 mm
thread \varnothing 3/8" M



ROSINOX

Suitable for:

3523061 NUT \varnothing 1/4"x6 mm




3348044 OLIVE FOR PIPE \varnothing 10 mm
for model PEL 20-21-24-25



3348041 OLIVE FOR PIPE \varnothing 16 mm
for model PEL 23



3001071 PIEZO IGNITER MINISIT WITH COVER
M faston 2.4 mm



ROSINOX LF-3001011

3523036 REDUCTION STRAIGHT \varnothing 3/8" F - \varnothing 1/2" F
in brass with internal and external thread
internal thread \varnothing 3/8" F - external thread \varnothing 1/2" F
for MINISIT flange





Suitable for:

5058320 TUBE NUT FITTING \varnothing 10 mm
thread M14x1,5 mm



ROSINOX

Suitable for:




Gaskets and seals

3186009 ASBESTOS FREE FLAT GASKET \varnothing 45x33x2 mm



ROSINOX RX94801446

3786831 FIBERGLASS GASKET \varnothing 14 mm - 3mt
max temperature 600°C
COLOUR WHITE




ROSINOX RX94051659

3186756 FLAT GASKET OF RUBBER \varnothing 31x21x2 mm



ROSINOX RX94802212

3186297 GASKET FLAT \varnothing 18x10x2 mm



ROSINOX RX94802659

5010462 GASKET FLAT ASBESTOS FREE \varnothing 24x17x2 mm



ROSINOX RX94804820

7104425 GASKET FLAT ASBESTOS-FREE \varnothing 37x27x2 mm



ROSINOX RX94808870

Glues

3392012 BLACK SEALING NOVASIL S56 310 ml
max operating temperature +265°C
HIGHLY ADHESIVE AND SEALING
suitable for GLASS-CERAMIC RANGE



ROSINOX RX94032679

ROSINOX 94032679



Handles

3242945 LH-RH CATCH WITH LOCK 571 CR
 straight handgrip
 base length 150x23x30h mm
 mounting distance 110 mm
 catch height 16.5 mm



ROSINOX

3242922 STRIKE FOR DOOR CATCH
 fitting height 16.5 mm



ROSINOX

3242579 LH-RH CATCH WITHOUT LOCK 570 CR
 straight handgrip
 base length 150x23x30h mm
 mounting distance 110 mm
 catch height 16.5 mm



ROSINOX RX94026184

3242922 STRIKE FOR DOOR CATCH
 fitting height 16.5 mm



ROSINOX

3242922 STRIKE FOR DOOR CATCH
 fitting height 16.5 mm



ROSINOX

Heating elements

3355286 BUSH FOR HEATING ELEMENT



ROSINOX RX94812604

3355829 CERAMIC HEATING ELEMENT 650W 230V
 length 245 mm - width 60 mm



ROSINOX RX94805876



Suitable for:

ROSINOX



Suitable for:

3355066 HEATING ELEMENT 1000W 220V
length 295 mm - width 90 mm
fittings M14x1 mm
operating ambient: dry



ROSINOX RX94812669

3755856 HEATING ELEMENT 10200W 230/400V
length 300 mm - width 180 mm
coupling M54 - complete with cables
with two holes for bulb
complete with OR gaskets



ROSINOX RX94805397

3186601 O-RING 04200 EPDM
ring thickness 3.53 mm - internal \varnothing 50.39 mm



ROSINOX RX94806924

ROSINOX RX94812565

3186697 O-RING 0159 EPDM
ring thickness 3.53 mm - internal \varnothing 55.56 mm



ROSINOX RX94806155

3755652 RING NUT 1"-3/4" FOR HEATING ELEMENT



ROSINOX RX94805330

ROSINOX RX94812677

3755649 HEATING ELEMENT 10500W 230V
length 320 mm - width 253 mm
connection M54x1.5 mm - complete with cables
with two holes for bulb



ROSINOX RX94812639

3755652 RING NUT 1"-3/4" FOR HEATING ELEMENT



ROSINOX RX94805330

ROSINOX RX94812677

3786459 O-RING 04200 VITON
ring thickness 3.53 mm - internal \varnothing 50.39 mm



ROSINOX RX94812518

Suitable for:

3355888 HEATING ELEMENT 1100W 240V
length 375 mm - width 95 mm
fittings M10x1 mm



ROSINOX RX94805223

3455380 HEATING ELEMENT 1200W 240V
length 535 mm - width 75 mm
fittings M14x1.5 mm



ROSINOX RX94004264

7111334 HEATING ELEMENT 1600W 230V
length 670 mm - width 240 mm
fittings M12x1 mm
for Oven under cooktop electric (ROSINOX) RCM401E



ROSINOX RX27307578

7111339 HEATING ELEMENT 1600W 230V
length 660 mm - width 240 mm
fittings M12x1 mm
for Oven under cooktop electric (ROSINOX) RCM401E



ROSINOX RX27307586

3755487 HEATING ELEMENT 1840W 230V
length 280 mm - width 70 mm
fittings \varnothing 1/4"



ROSINOX

Suitable for:

3355441 HEATING ELEMENT 1135W 220/240V
length 425 mm - width 65 mm
height 80 mm



ROSINOX RX94805678

3755488 HEATING ELEMENT 1580W 230V
length 455 mm - width 65 mm
height 70 mm



ROSINOX RX94814020

7111336 HEATING ELEMENT 1600W 230V
length 490 mm - width 365 mm
fittings M12x1 mm
for Oven under cooktop electric (ROSINOX) RCM401E



ROSINOX RX27307560

3755004 HEATING ELEMENT 1650W 240V
length 490 mm - width 43 mm
height 45 mm - fittings \varnothing 1/4"



ROSINOX RX94800224

7109160 HEATING ELEMENT 1850W 220V
length 395 mm - width 220 mm
flange 222x32x22 mm
for Salamander electric (ROSINOX) SPM750E



ROSINOX 27301050



Suitable for:

ROSINOX




3455382 HEATING ELEMENT 2000/2600W 220/240V
 length 425 mm - width 115 mm
 height 40 mm - fittings \varnothing 1/4"
 for Fry top electric (ROSINOX) GR20E



ROSINOX RX94001930


Suitable for:

3455136 HEATING ELEMENT 2000W 220V
 length 265 mm width 160 mm
 height 40 mm - fittings M12x1 mm
 for Fry top electric (ROSINOX) ROYALCHEF PL25E
 ROYALCHEF SPM25E
 for Fry top (ROSINOX) ROSIPLSN20E PLAQUE25E RCM



ROSINOX RX94001872

3455137 HEATING ELEMENT 2000W 230V
 length 270 mm width 190 mm
 height 40 mm - fittings M12x1 mm
 for Fry top electric (ROSINOX) ERACHEF 200E
 ERACHEF 400E - ROYALCHEF PL25E
 ROYALCHEF SPM25E
 for Fry top (ROSINOX) PLAQUE25E RCM



ROSINOX RX94001807

3755482 HEATING ELEMENT 2500W 230V
 external \varnothing 193 mm - total height 75 mm
 flange 70x22 mm



ROSINOX RX94806387

3186098 HEATING ELEMENT GASKET
 external dimensions 71x23 mm



3755592 HEATING ELEMENT 2900W 230V
 length 285 mm - width 80 mm
 height 250 mm - flange 85x30 mm



ROSINOX RX94808631

3755490 HEATING ELEMENT 3400W 230V
 length 305 mm - width 190 mm
 height 80 mm



ROSINOX RX94806718

Suitable for:

3455383 HEATING ELEMENT 4200W 240V
length 580 mm - width 170 mm
overall height 100 mm
for Bratt pan electric (ROSINOX) SBM35E



ROSINOX RX94030558


Suitable for:

3455381 HEATING ELEMENT 4500/5400W 220/240V
length 540 mm - width 30 mm
height 33 mm - fittings M14x1.5 mm
for Bratt pan electric (ROSINOX) MBM80E



ROSINOX RX94004629

7104753 HEATING ELEMENT 4650W 230V
length 580 mm - width 190 mm
height 180 mm - fittings M14x1,5 mm
for Bratt pan electric (ROSINOX) SBM80E



ROSINOX 94038197

3755468 HEATING ELEMENT 5670W 230V
length 295 mm - width 225 mm
fitting \varnothing 40 mm
with gaskets and cables
with cables - with bulb sheath



ROSINOX RX94812607

3355286 BUSH FOR HEATING ELEMENT



ROSINOX RX94812604

3355284 HEATING ELEMENT GASKET \varnothing 45x40x4 mm



3355287 LOCKING BUSH FOR HEATING ELEMENT



3186580 O-RING 04131 VITON
ring thickness 3.53 mm - internal \varnothing 32.93 mm



3355288 THREADED PIPE M10 FOR HEATING ELEMENT



ROSINOX RX94803079

ROSINOX RX94803616

ROSINOX RX94812605



Suitable for:

3355445 HEATING ELEMENT 6000W 230V
length 310 mm - width 250 mm
overall height 257 mm - complete with cables
operating ambient: immersion



ROSINOX RX94812636

Suitable for:

5012749 HEATING ELEMENT 650W 230V
length 280 mm - width 75 mm
flange 115x25 mm



ROSINOX RX94812603

3755489 HEATING ELEMENT 6800W 230V
length 300 mm - width 110 mm
fitting M54x1.5 mm - with cables
with O-rings
with 2 holes for bulb



ROSINOX RX94806916

3186697 O-RING 0159 EPDM
ring thickness 3.53 mm - internal \varnothing 55.56 mm



ROSINOX RX94806155

3186601 O-RING 04200 EPDM
ring thickness 3.53 mm - internal \varnothing 50.39 mm



ROSINOX RX94806924

ROSINOX RX94812565

3755652 RING NUT 1"-3/4" FOR HEATING ELEMENT



ROSINOX RX94805330

ROSINOX RX94812677

3755486 HEATING ELEMENT 990W 240V
length 470 mm - width 105 mm
height 25 mm - 2 flanges 55x17 mm



ROSINOX RX94806460

3755101 MIDDLE HEATING ELEMENT 2500W 220V
immersed length 490 mm - body \varnothing 30 mm
threaded connection \varnothing 1"-1/2 - flange 70x60 mm
with bulb sheath - complete with cables



ROSINOX RX94800273

5005316 COUNTER NUT OF CAST IRON \varnothing 1"1/2





Suitable for:

1186655 O-RING 04131 EPDM
ring thickness 3.53 mm - internal \varnothing 32.93 mm



ROSINOX



Suitable for:

3755652 RING NUT 1"-3/4" FOR HEATING ELEMENT



ROSINOX RX94805330

ROSINOX RX94812677

Hinges, catches and accessories

3053003 DOOR HINGE ROLL HOLDER
mounting distance 95 mm - overall length 118
height 23 mm



ROSINOX RX94805280

3053007 LEFTHAND DOOR HINGE FOR OVEN
mounting distance 175 mm - overall length 205
height 160 mm



ROSINOX RX94805272

3053234 HINGE COVER
mounting distance 95 mm - dimensions 124x20 mm



3053003 DOOR HINGE ROLL HOLDER
mounting distance 95 mm - overall length 118
height 23 mm



ROSINOX RX94805280

3053299 HINGE COVER
mounting distance 77 mm - dimensions 129x26 mm





Suitable for:

Suitable for:

3053006 RIGHTHAND DOOR HINGE FOR OVEN
mounting distance 175 mm - overall length 205
height 160 mm



ROSINOX RX94805264

3053003 DOOR HINGE ROLL HOLDER
mounting distance 95 mm - overall length 118
height 23 mm



ROSINOX RX94805280

3053234 HINGE COVER
mounting distance 95 mm - dimensions 124x20 mm



3053299 HINGE COVER
mounting distance 77 mm - dimensions 129x26 mm



Hydraulic piping

3450152 HOSE RUBBER REINFORCED \varnothing 13/19 mm
internal \varnothing 13 mm - external \varnothing 19 mm
temperature -40+100°C
sold per meter



ROSINOX RX94813948

Ignitors

3001005 PIEZO IGNITER
a \varnothing 18 mm hole is needed for the assembly
faston M \varnothing 2.4 mm




ROSINOX RX94805009

5035512 WATERTIGHT PIEZO CAP
of silicone rubber



3001071 PIEZO IGNITER MINISIT WITH COVER
M faston 2.4 mm




ROSINOX LF-3001011



Incandescent lamps and neon lamps

3221041 LAMP E14 15W 230V
max temperature 300°C - ø 22x50 mm



ROSINOX RX27610120


3221105 NEUTRAL HALOGEN LAMP G4 20W 12V
max. temperature 250°C



ROSINOX RX94820004

Indicator lights

3221162 GREEN LAMP RECEPTACLE
head ø 14.5 mm - hole ø 10 mm



ROSINOX RX94810956

3221166 INDICATOR LIGHT GREEN 400V
ø head 14 mm - ø hole 11.5 mm - 120°C
universal application



ROSINOX RX94806346

3221544 INDICATOR LIGHT GREEN 400V
head ø 14 mm - hole ø 12 mm
wire connection length 190 mm
nichel plated brass case
for Glass-ceramic plate (ROSINOX) RCM3F



ROSINOX RX94005832

3221194 INDICATOR LIGHT NEON GREEN 220V
ø head 8 mm



ROSINOX RX94813811

3221196 LAMP CAP CLEAR
ø 12 mm



3221197 GREY CAP ø 12 mm



3221195 LAMP CAP GREEN ø 12 mm
ø 12 mm





Suitable for:

3221192 LAMP SUPPORT



ROSINOX RX94813812

3319219 SUPPORT FOR DARK GREY PUSH-BUTTON
mounting hole 16x16 mm - for push-button \varnothing 12 mm



ROSINOX

Suitable for:

3221193 ORANGE LAMP CAP
 \varnothing 12 mm



3221097 INDICATOR LIGHT NEUTRAL 220V
head \varnothing 8 mm - 120°C



ROSINOX RX94801073

ROSINOX RX94809845

3221025 INDICATOR LIGHT ORANGE 230V
head \varnothing 15 mm - hole \varnothing 13 mm - 120°C
faston M 6.3x0.8 mm
universal application



ROSINOX RX94801529

ROSINOX RX94801537

3221095 INDICATOR LIGHT ORANGE 230V
head \varnothing 13.5 mm - hole \varnothing 10 mm - 120°C
universal application



ROSINOX RX94812468

3221165 INDICATOR LIGHT ORANGE 400V
 \varnothing head 14 mm - \varnothing hole 11.5 mm - 120°C
universal application



ROSINOX RX94806353

3221166 INDICATOR LIGHT GREEN 400V
 \varnothing head 14 mm - \varnothing hole 11.5 mm - 120°C
universal application



ROSINOX RX94806346

3221543 INDICATOR LIGHT ORANGE 400V
 head \varnothing 14 mm - hole \varnothing 12 mm
 wire connection length 190 mm
 nichel plated brass case
 for Glass-ceramic plate (ROSINOX) RCM3F



ROSINOX RX94005857

3221024 INDICATOR LIGHT RED 230V
 head \varnothing 15 mm - hole \varnothing 13 mm - 120°C
 faston M 6.3x0.8 mm
 universal application



ROSINOX RX94801511

3221101 INDICATOR LIGHT GREEN 230V
 head \varnothing 15 mm - \varnothing hole 13 mm - 120°C
 M faston 6.3x0.8 mm
 universal application



3221025 INDICATOR LIGHT ORANGE 230V
 head \varnothing 15 mm - hole \varnothing 13 mm - 120°C
 faston M 6.3x0.8 mm
 universal application




3221026 INDICATOR LIGHT WHITE 230V
 \varnothing head 15 mm - \varnothing hole 13 mm - 120°C
 faston M 6.3x0.8 mm
 universal application



ROSINOX RX94801529

ROSINOX RX94801537

3221167 RED LAMP RECEPTACLE
 head \varnothing 15 mm - hole \varnothing 10 mm



ROSINOX RX94810215

3221162 GREEN LAMP RECEPTACLE
 head \varnothing 14.5 mm - hole \varnothing 10 mm



ROSINOX RX94810956

3221163 ORANGE LAMP RECEPTACLE
 head \varnothing 15 mm - hole \varnothing 10 mm



3221168 TRANSPARENT LAMP RECEPTACLE
 head \varnothing 15 mm - hole \varnothing 10 mm





Suitable for:

ROSINOX

Suitable for:



Interference suppression filters

3160479 INTERFERENCE SUP. FILTER D.E.M.FC701Y2FL
0.47μF



ROSINOX RX94808409

Ironmongery (screws,nuts,washers)

1528031 COUNTERSUNK FLAT HEAD SCREWS M5x12
slotted - stainless steel
UNI 6109 - DIN 963 - ISO 2009
for Bratt pan (ROSINOX) ROSICHEF SEM50G 30/10



ROSINOX RX94009677

1184012 CYLINDER HEAD SCREW M5x10
stainless steel - with hexagon socket
UNI 9327 - DIN 7984



ROSINOX RX94803210

9742005 FEATHER STEEL C40 8x7x30 mm
UNI 6604/A - DIN 6685/A



ROSINOX RX94810964

1186192 FLAT WASHER M5
internal/external ø 5.3/10 mm - thickness 1 mm
stainless steel - UNI 6592 - DIN 125 A - ISO 7089



ROSINOX RX94813766

3528010 FLAT WASHER M6
ø internal/external 6.4/12 mm - thickness 1.6 mm
st./steel - UNI 6592 - DIN 125 A - ISO 7089



ROSINOX RX94801651

7100207 HEADLESS SCREW HEXAGONAL M5x8
stainless steel - conical top
UNI 5927 - DIN 914 - ISO 4027



ROSINOX RX94814482

5022074 HEXAGON HEAD SCREW M8x40
stainless steel - UNI 5739 - DIN 933 - ISO 4017



ROSINOX RX94016375

3528216 HEXAGONAL NUT LOW M5
st./steel - UNI 5589 - DIN 936 - ISO 4035



ROSINOX RX94813765

Suitable for:

3060069 HEXAGONAL NUT M8 MEDIUM
stainless steel - UNI 5588 - DIN 934 - ISO 4032



ROSINOX

Suitable for:

5043101 SCREWS NO HEAD WITH HEXAGON SOCKET M4x5
stainless steel - flat edge
UNI 5923 - DIN 913 - ISO 4026
for Bratt pan (ROSINOX) ROSICHEF SEM50G 30/10



ROSINOX RX94027281

Knobs

3241081 BLACK KNOB ϕ 65 mm SILK-SCREEN PRINTED
D-shaped hole 8x6.5 mm



ROSINOX RX94806189

3241157 KNOB BLUE STICKER



5046749 CAP YELLOW FOR KNOB



3241082 KNOB EXTENSION



3241573 BLACK KNOB ϕ 65 mm 0-295°C
D-shaped hole 6x4.6 mm



ROSINOX RX94812578

3241157 KNOB BLUE STICKER



5046749 CAP YELLOW FOR KNOB



5035322 BUSHING BLACK FOR KNOB ϕ 72 mm



ROSINOX RX94812686

3241707 GREY KNOB ϕ 30 mm ON-OFF-PILOT
for USA MARKET



ROSINOX RX26645069



Suitable for:

ROSINOX



Suitable for:

3241909 KNOB CAP FOR GAS TAP WHITE
 square cap 16x16 mm
 D-shaped hole 6x4.6 mm
 for Bratt pan electric (ROSINOX) MBM80E - SBM50E
 for Bratt pan gas (ROSINOX) MBM80G
 for Fry top electric (ROSINOX) GR20E
 for Fry top gas (ROSINOX) GR20G
 for Bratt pan (ROSINOX) ROSICHEF SEM50G 30/10



ROSINOX RX94006830

3241916 KNOB CAP RING NUT ø 46 mm
 for Bratt pan gas (ROSINOX) MBM80G
 for Bratt pan gas (ROSINOX) MBM100G-RCS



ROSINOX RX94030277

3241910 TAP KNOB CHROME-PLATED ø 39 mm
 square hole 16x16 mm
 for Bratt pan electric (ROSINOX) MBM80E - SBM50E
 for Bratt pan gas (ROSINOX) MBM80G - SBM50G
 for Fry top gas (ROSINOX) GR20G
 for Bratt pan (ROSINOX) ROSICHEF SEM50G 30/10



ROSINOX RX94030939

ROSINOX RX94030939+...

3241909 KNOB CAP FOR GAS TAP WHITE
 square cap 16x16 mm
 D-shaped hole 6x4.6 mm
 for Bratt pan electric (ROSINOX) MBM80E - SBM50E
 for Bratt pan gas (ROSINOX) MBM80G
 for Fry top electric (ROSINOX) GR20E
 for Fry top gas (ROSINOX) GR20G
 for Bratt pan (ROSINOX) ROSICHEF SEM50G 30/10



ROSINOX RX94006830


3241916 KNOB CAP RING NUT ø 46 mm
 for Bratt pan gas (ROSINOX) MBM80G
 for Bratt pan gas (ROSINOX) MBM100G-RCS



ROSINOX RX94030277

Labels for control panels

7108579 ADHESIVE CONTROL PLATE 148x55 mm
 for Bratt pan (ROSINOX) SBM60G - SBM80G



ROSINOX RX94053212

7101453 ADHESIVE CONTROL PLATE 148x91 mm
 for Bratt pan (ROSINOX) RCSSBM50G IONISATION
 RCS SBM80G
 for Fryer (ROSINOX)
 for Fryer electric (ROSINOX) FR30EHP



ROSINOX RX94034345



Lamp receptacles and spare parts

3786614 GASKET FOR OVEN LAMP RECEPTACLE
dimensions 48x41x3 mm



ROSINOX RX24390700

3221052 GLASS FOR OVEN LAMP RECEPTACLE \varnothing 57 mm
thread \varnothing 33.5 mm - overall height 34 mm




ROSINOX RX27610112

3221350 LAMP RECEPTACLE WITH LAMP E14 15W 230V
lamp glass \varnothing 42 mm
mounting hole \varnothing 38 mm
max temperature 300°C




ROSINOX RX27610104

3186522 GASKET FOR OVEN LAMP RECEPTACLE
dimensions \varnothing 40x30x2 mm



3221053 GASKET FOR OVEN LAMP RECEPTACLE
dimensions \varnothing 48x38x5 mm
for OVEN




3786614 GASKET FOR OVEN LAMP RECEPTACLE
dimensions 48x41x3 mm



ROSINOX RX24390700


3221392 GASKET KIT FOR OVEN LAMP RECEPTACLE
dimensions \varnothing 53x44x3 mm



3221233 GLASS FOR OVEN LAMP RECEPTACLE \varnothing 42 mm
thread \varnothing 33 mm - overall height 26 mm



3221041 LAMP E14 15W 230V
max temperature 300°C - \varnothing 22x50 mm



ROSINOX RX27610120


3221061 LAMP E14 25W 230V
max temperature 300°C - \varnothing 26x57 mm





Suitable for:

2101372 LAMP RECEPTACLE FOR LAMP E14 15-25W 230V
mounting hole \varnothing 38 mm
max temperature 300°C



ROSINOX



Suitable for:

D421015 OVEN LAMP DR FISCHER E14 15W 230V
 \varnothing 22x49 mm - max temperature 300°C



D421016 OVEN LAMP DR FISCHER E14 25W 230V
 \varnothing 25x57 mm - max temperature 300°C



5035079 LAMP RECEPTACLE WITH LAMP G9 40W 230V
external dimensions 96x80 mm
max temperature 300°C



3221172 FRAME FOR OVEN LAMP RECEPTACLE
external dimensions 96x80 mm



ROSINOX RX94814234


3186173 GASKET FOR OVEN LAMP RECEPTACLE
external dimensions 93x79 mm



3221173 GLASS FOR OVEN LAMP RECEPTACLE
external dimensions 73x58 mm



D221004 HALOGEN LAMP OSRAM G9 40W 230V SMEG
OSRAM
max. temperature 200°C



3621005 LAMP CAP FOR HALOGEN G9 40W 230V
external dimensions 74x59 mm
max. temperature 300°C





Level gauges

3201001 WATER LEVEL GAUGE HCX127 162x32 mm
 distance between holes 130 mm
 for PANS



ROSINOX RX94800216

Level probes

3397192 LEVEL PROBE \varnothing 1/4"M-270 mm
 overall length 330 mm
 for Bratt pan electric (ROSINOX) MBM80E
 for Bratt pan gas (ROSINOX) MBM80G



ROSINOX RX94023512

3341068 LEVEL PROBE \varnothing 1/4"M-350 mm



ROSINOX RX94812665

Level regulators

3341000 LEVEL REGULATOR RL30/3ES/F/G
 230V 50/60Hz



ROSINOX RX94812666

3341003 LEVEL PROBE \varnothing 1/4"M-110 mm



3341002 LEVEL PROBE \varnothing 1/4"M-114.5 mm



3341001 LEVEL PROBE \varnothing 1/4"M-155 mm



3391037 LEVEL PROBE SPACER
 external \varnothing 8 mm
 internal \varnothing 2.5 mm
 overall length 11.5 mm



3391038 LEVEL PROBE SPACER
 external \varnothing 8 mm - 7.5 mm height





Suitable for:

ROSINOX

Suitable for:



Magnet groups

3182010 MAGNETIC UNIT PEL
head \varnothing 24 mm - end piece \varnothing 18 mm - length 59 mm
thermocouple coupling M10x1
for PEL tap model 23



ROSINOX 244761276

3182009 MAGNETIC UNIT PEL BIG HEAD
head \varnothing 15.5 mm - end piece \varnothing 14 mm - length 44 mm
for PEL tap model 22-24



ROSINOX 244761275

3182003 MAGNETIC UNIT SIT
head \varnothing 25 mm - end piece \varnothing 17 mm - length 56 mm
for valve SIT AC2 - VR8-MINISIT



ROSINOX

Microswitches, mechanical

3240189 MICRO SWITCH M1DX20 10A 250V



ROSINOX RX94806130

3240234 LIMIT SWITCH PIN



3250071 MICROSWITCH SPRING \varnothing 13x25 mm




3240235 RING NUT M16x1.5 mm



5003350 ROD MICROSWITCH 48x30 mm




3240054 MICROSWITCH CROUZET 83731
5A 250V - with cable length 2000 mm



ROSINOX RX94050119

3240820 MICROSWITCH ELECTRICA NR48W 5
1NO + 1NC 16A 250V




ROSINOX RX94812476

3240473 GASKET FOR BUSHING



3240166 MOUNTING PLATE FOR MICROSWITCH
external dimensions 46x26 mm



3240154 SPRING FOR MICROSWITCH ROD



3240407 MICROSWITCH KIT 16A 250V
2 locking positions
the kit includes 5 levers:
lever 75 mm - lever 27 mm - lever 15 mm
lever 15 mm with wheel - lever 27 mm with wheel



ROSINOX RX94810935

3240152 BUSHING FOR MICROSWITCH



5035454 MICRO SUPPORT
for WASHING MACHINE LF25



3240153 ROD FOR MICROSWITCH



3240568 MICROSWITCH CROUZET EF83161.3
1NO+NC 16A 250V
complete with roll lever 28 mm





Suitable for:

ROSINOX



Suitable for:

Nozzles

3500190 CONICAL GAS JET M17x1 ϕ 1.70 mm



ROSINOX RX94033818

3500194 CONICAL GAS JET M17x1 ϕ 2.10 mm



ROSINOX RX94033859

3500159 GAS JET ϕ 1.40 mm



ROSINOX 94033750

5063664 GAS JET M10x1 ϕ 0.90 mm



ROSINOX RX94806882

3500024 GAS JET M10x1 ϕ 1.15 mm



ROSINOX RX94806874

5015403 GAS JET M10x1 ϕ 1.40 mm



ROSINOX RX94812697

3500061 GAS JET M7x1 ϕ 0.80 mm



ROSINOX RX94812640

3500063 GAS JET M7x1 ϕ 0.95 mm



ROSINOX RX94806668

O-Ring and ORM gaskets

3243069 O-RING OR 02068 EPDM
ring thickness 1.78 mm - internal ϕ 17.17 mm



ROSINOX RX94801214

3243009 O-RING 0106 EPDM
ring thickness 1.78 mm - internal ϕ 6.75 mm



ROSINOX RX94800778

1186422 O-RING 0108 EPDM
ring thickness 1.78 mm - internal ϕ 8.73 mm



ROSINOX RX94814266

1186626 O-RING 0114 EPDM
ring thickness 1.78 mm - internal ϕ 11.11 mm



ROSINOX RX94801156

Suitable for:

3186606 O-RING 0144 EPDM
ring thickness 3.53 mm - internal \varnothing 39.69 mm



ROSINOX RX94803020

ROSINOX RX94809670

Suitable for:

3186238 O-RING 0146 EPDM
ring thickness 3.53 mm - internal \varnothing 41.28 mm



ROSINOX RX9480703

3186697 O-RING 0159 EPDM
ring thickness 3.53 mm - internal \varnothing 55.56 mm



ROSINOX RX94806155

1186421 O-RING 02018 EPDM
ring thickness 1.78 mm - internal \varnothing 4.48 mm



ROSINOX RX94809555

1186411 O-RING 02031 EPDM
ring thickness 1.78 mm - internal \varnothing 7.66 mm



ROSINOX RX94809761

1186803 O-RING 02037 EPDM
ring thickness 1.78 mm - internal \varnothing 9.25 mm



ROSINOX RX94813741

ROSINOX RX94813762

1186352 O-RING 02050 EPDM
ring thickness 1.78 mm - internal \varnothing 12.42 mm



ROSINOX RX94809639

ROSINOX RX94813757

3243266 O-RING 02081 EPDM
ring thickness 1.78 mm - internal \varnothing 20.35 mm



ROSINOX RX94807450

3243382 O-RING 02087 EPDM
ring thickness 1.78 mm - internal \varnothing 21.95 mm




ROSINOX RX94807550

3186754 O-RING 02112 EPDM
ring thickness 1.78 mm - internal \varnothing 28.30 mm



ROSINOX RX94801727

3122121 O-RING 02375 EPDM
ring thickness 1.78 mm - internal \varnothing 94.97 mm



ROSINOX RX94813788

3186239 O-RING 02525 EPDM
ring thickness 1.78 mm - internal \varnothing 133.07 mm



ROSINOX RX94809035



Suitable for:

3186340 O-RING 03037 EPDM
ring thickness 2.62 mm - internal \varnothing 9.19 mm



ROSINOX RX94807765

ROSINOX RX94812680

ROSINOX RX94813760

Suitable for:

3186247 O-RING 03112 EPDM
ring thickness 2.62 mm - internal \varnothing 28.25 mm



ROSINOX RX94801487

3186244 O-RING 03125 EPDM
ring thickness 2.62 mm - internal \varnothing 31.42 mm



ROSINOX RX94807440

3243250 O-RING 03137 EPDM
ring thickness 2.62 mm - internal \varnothing 34.60 mm
for motor mixer flange



ROSINOX RX94807773

3243389 O-RING 03162 EPDM
ring thickness 2.62 mm - internal \varnothing 40.95 mm



ROSINOX RX94809191

1186466 O-RING 03181 EPDM
ring thickness 2.62 mm - internal \varnothing 45.69 mm
for group flange



ROSINOX RX94813771

ROSINOX RX94813849

1186672 O-RING 03193 EPDM
ring thickness 2.62 mm - internal \varnothing 48.89 mm
for brew group



ROSINOX RX94814051

3186245 O-RING 03200 EPDM
ring thickness 2.62 mm - internal \varnothing 50.47 mm



ROSINOX RX94814259

1186238 O-RING 04081 EPDM
ring thickness 3.53 mm - internal \varnothing 20.22 mm



ROSINOX RX94801172

3186143 O-RING 04093 EPDM
ring thickness 3.53 mm - internal \varnothing 23.40 mm



ROSINOX RX94807351



Suitable for:

Suitable for:

3186580 O-RING 04131 VITON
ring thickness 3.53 mm - internal \varnothing 32.93 mm



ROSINOX RX94803079

ROSINOX RX94803616

ROSINOX RX94812605

3061040 O-RING 04137 EPDM
ring thickness 3.53 mm - internal \varnothing 34.52 mm



ROSINOX RX94813951

3067198 O-RING 04162 EPDM
ring thickness 3.53 mm - internal \varnothing 40.86 mm



ROSINOX RX94810256

3186601 O-RING 04200 EPDM
ring thickness 3.53 mm - internal \varnothing 50.39 mm



ROSINOX RX94806924

ROSINOX RX94812565

3786459 O-RING 04200 VITON
ring thickness 3.53 mm - internal \varnothing 50.39 mm



ROSINOX RX94812518

3186001 O-RING 06150 EPDM
ring thickness 5.34 mm - internal \varnothing 37.47 mm



ROSINOX RX94810959

3186013 O-RING 06187 EPDM \varnothing 58 mm
ring thickness 5.34 mm - internal \varnothing 47.00 mm



ROSINOX RX94807781

3186014 O-RING 06225 EPDM \varnothing 67 mm
ring thickness 5.34 mm - internal \varnothing 56.52 mm



ROSINOX RX94807294


Pilot burners and accessories

3020085 FITTING FOR SPARKING PLUG FIXING M10x1mm



ROSINOX RX94805082

3020200 FITTING FOR THERMOCOUPLE \varnothing 6.5 mm
thread M10x1



ROSINOX RX94805090



Suitable for:

ROSINOX



3020285 GASKET FOR TARGET PILOT



ROSINOX RX94806510

Suitable for:

3020082 OLIVE FOR PIPE \varnothing 12 mm
for model PEL 22-24-25



ROSINOX RX94810978

3020001 ONE-FLAME PILOT BURNER SIT
multigas with jet \varnothing 0.20 mm
with 2 positions bracket



ROSINOX LF-3020434

3020101 BRACKET CLAMP 2 POSITIONS



3020092 BRACKET PILOT BURNER SUPP. LH 92x55x45mm
for mounting of pilot assembly



3020292 BRACKET PILOT BURNER SUPPORT 47x40x15 mm
for burner \varnothing 90 mm



3020293 BRACKET PILOT BURNER SUPPORT 65x50x45 mm
for burner \varnothing 115 mm



3020291 BRACKET PILOT BURNER SUPPORT 85x45x55 mm
for burner \varnothing 135 mm




3020100 BRACKET 2 POSITIONS




3020108 DEFLECTOR 1 FLAME



3020083 FITTING AND OLIVE \varnothing 4 mm



3020084 FITTING AND OLIVE \varnothing 6 mm





Suitable for:

3020102 HEXAGON HEAD SCREW 3/16"x18 mm



ROSINOX



Suitable for:

3001003 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M4x1 mm
overall length 65 mm



3020060 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M 4x1 mm
overall length 82 mm
model CB505/021 Junkers
for model P502F



ROSINOX RX94034642

ROSINOX 94805207

3020124 IGNITION PLUG ROUND \varnothing 7x44 mm
connection \varnothing 2.4 mm
overall length 58 mm



ROSINOX RX94805066

ROSINOX RX94805306

ROSINOX RX94805686

3020294 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M4x1 mm
overall length 67 mm



ROSINOX RX94027729

ROSINOX 94027729

3020365 IGNITION PLUG ROUND \varnothing 7x44 mm
connection \varnothing 2.4 mm
overall length 52 mm



3020082 OLIVE FOR PIPE \varnothing 12 mm
for model PEL 22-24-25



3348036 OLIVE FOR PIPE \varnothing 4 mm
for model PEL 21-22-24-25



ROSINOX RX94810978

3020081 OLIVE FOR PIPE \varnothing 6 mm



ROSINOX RX94812588

3020097 PILOT AERATION REGULATOR
internal \varnothing 7 mm - external \varnothing 9 mm
height 10 mm






Suitable for:

3020115 PILOT CAP 1 FLAME



3020156 PILOT JET \varnothing 0.25 mm



ROSINOX RX94812644

3020055 PILOT JET \varnothing 0.35 mm



3500269 PILOT JET \varnothing 0.45 mm



3020308 PILOT WITH NOZZLE \varnothing 0.40 mm



3020106 PILOT WITH 0.25 mm \varnothing JET



3020079 PIPE FITTING \varnothing 12 mm
thread \varnothing 3/8" M



ROSINOX

Suitable for:

3020054 PILOT JET \varnothing 0.20 mm



4058525 PILOT JET \varnothing 0.30 mm



5015516 PILOT JET \varnothing 0.40 mm



5075989 PILOT JET \varnothing 0.70 mm



3020105 PILOT WITH 0.20 mm \varnothing JET



3020107 PILOT WITH 0.35 mm \varnothing JET



3020077 PIPE FITTING \varnothing 4 mm
thread M10x1



ROSINOX RX94812587





Suitable for:

3020078 PIPE FITTING \varnothing 6 mm
thread M10x1



ROSINOX



Suitable for:

5014757 PIPE FITTING \varnothing 6 mm
thread M10x1 mm



3020419 PILOT BURNER LPG 1 FLAME
with bracket



ROSINOX RX94044476

3020117 PILOT DEFLECTOR 3 FLAMES 53x40 mm




ROSINOX RX94034634

3020042 PILOT JET \varnothing 0.19 mm



ROSINOX 822140380

3020156 PILOT JET \varnothing 0.25 mm



ROSINOX RX94812644

3020202 PILOT JET \varnothing 0.27 mm



ROSINOX RX94806072

3500385 PILOT JET \varnothing 0.30 mm
for Pot stove gas (ROSINOX)
since 1/02/03



ROSINOX RX94814110

3500386 PILOT JET \varnothing 0.40 mm
for Pot stove gas (ROSINOX)
since 1/02/03



ROSINOX RX94814111

3020449 PILOT JET \varnothing 0.54 mm



ROSINOX RX94034519

3020077 PIPE FITTING \varnothing 4 mm
thread M10x1



ROSINOX RX94812587



Suitable for:

ROSINOX




3020010 TARGET PILOT BURNER SIT 2 FLAMES
supplied without sparking plug, nozzle and gasket
with thermocouple fitting



ROSINOX RX94805041

3020200 FITTING FOR THERMOCOUPLE \varnothing 6.5 mm
thread M10x1



ROSINOX RX94805090

3020060 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M 4x1 mm
overall length 82 mm
model CB505/021 Junkers
for model P502F



ROSINOX RX94805066

ROSINOX RX94805306

ROSINOX RX94805686

3020294 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M4x1 mm
overall length 67 mm



3020085 FITTING FOR SPARKING PLUG FIXING M10x1m m



ROSINOX RX94805082

3001003 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M4x1 mm
overall length 65 mm



ROSINOX RX94034642

ROSINOX 94805207

3020124 IGNITION PLUG ROUND \varnothing 7x44 mm
connection \varnothing 2.4 mm
overall length 58 mm



ROSINOX RX94027729

ROSINOX 94027729

3020365 IGNITION PLUG ROUND \varnothing 7x44 mm
connection \varnothing 2.4 mm
overall length 52 mm



3020113 OLIVE FOR PIPE \varnothing 4 mm



3348036 OLIVE FOR PIPE \varnothing 4 mm
for model PEL 21-22-24-25



ROSINOX RX94812588



Suitable for:

3020114 OLIVE FOR PIPE \varnothing 6 mm



3020201 PILOT JET \varnothing 0.14 mm



3020542 PILOT JET \varnothing 0.20 mm



3020202 PILOT JET \varnothing 0.27 mm



ROSINOX RX94806072

3020043 PILOT JET \varnothing 0.36 mm



5022050 PILOT JET \varnothing 0.50 mm



ROSINOX

Suitable for:

3020086 PILOT GASKET



3020042 PILOT JET \varnothing 0.19 mm




ROSINOX 822140380

5047578 PILOT JET \varnothing 0.24 mm



2102405 PILOT JET \varnothing 0.35 mm



3020543 PILOT JET \varnothing 0.38 mm



3020077 PIPE FITTING \varnothing 4 mm
thread M10x1



ROSINOX RX94812587





Suitable for:

3348029 PIPE FITTING \varnothing 4 mm
thread M10x1 mm
for model PEL 21-22-24-25



5014757 PIPE FITTING \varnothing 6 mm
thread M10x1 mm



ROSINOX




Suitable for:

3020078 PIPE FITTING \varnothing 6 mm
thread M10x1




3020289 THREE-FLAME PILOT BURNER
supplied without sparking plug, nozzle
with pipe fitting and pipe pilot olive
with thermocouple fitting
with sparking plug fitting



ROSINOX RX94034485

3020200 FITTING FOR THERMOCOUPLE \varnothing 6.5 mm
thread M10x1



ROSINOX RX94805090

3020060 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M 4x1 mm
overall length 82 mm
model CB505/021 Junkers
for model P502F



ROSINOX RX94805066

ROSINOX RX94805306

ROSINOX RX94805686

3020085 FITTING FOR SPARKING PLUG FIXING M10x1mm



ROSINOX RX94805082

3001003 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M4x1 mm
overall length 65 mm



ROSINOX RX94034642

ROSINOX 94805207

3020124 IGNITION PLUG ROUND \varnothing 7x44 mm
connection \varnothing 2.4 mm
overall length 58 mm



ROSINOX RX94027729

ROSINOX 94027729



Suitable for:

3020294 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M4x1 mm
overall length 67 mm



ROSINOX



Suitable for:

3020365 IGNITION PLUG ROUND \varnothing 7x44 mm
connection \varnothing 2.4 mm
overall length 52 mm



3020111 OLIVE FOR PIPE \varnothing 4 mm



3020112 OLIVE FOR PIPE \varnothing 6 mm



3020044 PILOT JET \varnothing 0.20 mm



5071220 PILOT JET \varnothing 0.22 mm



3020452 PILOT JET \varnothing 0.32 mm



3020045 PILOT JET \varnothing 0.50 mm



3020449 PILOT JET \varnothing 0.54 mm



3020464 PILOT JET \varnothing 0.64 mm



ROSINOX RX94034519

3020077 PIPE FITTING \varnothing 4 mm
thread M10x1



3020078 PIPE FITTING \varnothing 6 mm
thread M10x1



ROSINOX RX94812587



Suitable for:

5014757 PIPE FITTING \varnothing 6 mm
thread M10x1 mm



ROSINOX

Suitable for:



3020006 **THREE-FLAME PILOT BURNER SIT**
multigas with jet \varnothing 0.20 mm
with 3 positions bracket
for Boiling pan (ROSINOX) EBA CHEF.3DH.50E
for Bratt pan gas (ROSINOX) MBM100G-RCS



ROSINOX RX9402741
ROSINOX 94034659

ROSINOX RX9402741

ROSINOX RX94034659

3020104 **BRACKET CLAMP 3 POSITIONS**



3020103 **BRACKET 3 POSITIONS**



3020109 **DEFLECTOR 2 FLAMES**




3020110 **DEFLECTOR 3 FLAMES**




5048713 **DEFLECTOR 3 FLAMES**



3020083 **FITTING AND OLIVE \varnothing 4 mm**



3020084 **FITTING AND OLIVE \varnothing 6 mm**



3020102 **HEXAGON HEAD SCREW 3/16"x18 mm**



3001003 **IGNITION PLUG ROUND \varnothing 7x44 mm**
M faston M4x1 mm
overall length 65 mm



ROSINOX RX94034642

ROSINOX 94805207



Suitable for:

3020060 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M 4x1 mm
overall length 82 mm
model CB505/021 Junkers
for model P502F



ROSINOX



Suitable for:

3020124 IGNITION PLUG ROUND \varnothing 7x44 mm
connection \varnothing 2.4 mm
overall length 58 mm



ROSINOX RX94805066

ROSINOX RX94805306

ROSINOX RX94805686

3020294 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M4x1 mm
overall length 67 mm



ROSINOX RX94027729

ROSINOX 94027729

3020365 IGNITION PLUG ROUND \varnothing 7x44 mm
connection \varnothing 2.4 mm
overall length 52 mm



3020082 OLIVE FOR PIPE \varnothing 12 mm
for model PEL 22-24-25



3348036 OLIVE FOR PIPE \varnothing 4 mm
for model PEL 21-22-24-25



ROSINOX RX94810978

5027953 OLIVE FOR PIPE \varnothing 4 mm
for COPRECI CAL3200



ROSINOX RX94812588

3020081 OLIVE FOR PIPE \varnothing 6 mm



3020097 PILOT AERATION REGULATOR
internal \varnothing 7 mm - external \varnothing 9 mm
height 10 mm




3020054 PILOT JET \varnothing 0.20 mm





Suitable for:

3020156 PILOT JET \varnothing 0.25 mm



ROSINOX RX94812644

3020055 PILOT JET \varnothing 0.35 mm



3500269 PILOT JET \varnothing 0.45 mm



3020308 PILOT WITH NOZZLE \varnothing 0.40 mm



3020106 PILOT WITH 0.25 mm \varnothing JET



3020079 PIPE FITTING \varnothing 12 mm
thread \varnothing 3/8" M



ROSINOX

Suitable for:

4058525 PILOT JET \varnothing 0.30 mm



5015516 PILOT JET \varnothing 0.40 mm



5075989 PILOT JET \varnothing 0.70 mm



3020105 PILOT WITH 0.20 mm \varnothing JET



3020107 PILOT WITH 0.35 mm \varnothing JET



3020077 PIPE FITTING \varnothing 4 mm
thread M10x1



ROSINOX RX94812587





Suitable for:

5033138 PIPE FITTING \varnothing 4 mm
thread \varnothing 1/8" M



5014757 PIPE FITTING \varnothing 6 mm
thread M10x1 mm



ROSINOX

Suitable for:

3020078 PIPE FITTING \varnothing 6 mm
thread M10x1



3020002 TWO-FLAME PILOT BURNER SIT
multigas with jet \varnothing 0.20 mm
with 2 positions bracket



ROSINOX

3020100 BRACKET 2 POSITIONS




3020101 BRACKET CLAMP 2 POSITIONS




3020109 DEFLECTOR 2 FLAMES



3020083 FITTING AND OLIVE \varnothing 4 mm



3020084 FITTING AND OLIVE \varnothing 6 mm



3020102 HEXAGON HEAD SCREW 3/16"x18 mm



3001003 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M4x1 mm
overall length 65 mm



ROSINOX RX94034642

ROSINOX 94805207



Suitable for:

3020060 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M 4x1 mm
overall length 82 mm
model CB505/021 Junkers
for model P502F



ROSINOX



Suitable for:

3020124 IGNITION PLUG ROUND \varnothing 7x44 mm
connection \varnothing 2.4 mm
overall length 58 mm



ROSINOX RX94805066

ROSINOX RX94805306

ROSINOX RX94805686

3020294 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M4x1 mm
overall length 67 mm



ROSINOX RX94027729

ROSINOX 94027729

3020365 IGNITION PLUG ROUND \varnothing 7x44 mm
connection \varnothing 2.4 mm
overall length 52 mm



3020082 OLIVE FOR PIPE \varnothing 12 mm
for model PEL 22-24-25



3348036 OLIVE FOR PIPE \varnothing 4 mm
for model PEL 21-22-24-25



ROSINOX RX94810978

5027953 OLIVE FOR PIPE \varnothing 4 mm
for COPRECI CAL3200



ROSINOX RX94812588

3020081 OLIVE FOR PIPE \varnothing 6 mm



3020097 PILOT AERATION REGULATOR
internal \varnothing 7 mm - external \varnothing 9 mm
height 10 mm




3020054 PILOT JET \varnothing 0.20 mm





Suitable for:

3020156 PILOT JET \varnothing 0.25 mm



ROSINOX RX94812644

3020055 PILOT JET \varnothing 0.35 mm



3500269 PILOT JET \varnothing 0.45 mm



3020308 PILOT WITH NOZZLE \varnothing 0.40 mm



3020106 PILOT WITH 0.25 mm \varnothing JET



3020079 PIPE FITTING \varnothing 12 mm
thread \varnothing 3/8" M



ROSINOX

Suitable for:

4058525 PILOT JET \varnothing 0.30 mm



5015516 PILOT JET \varnothing 0.40 mm



5075989 PILOT JET \varnothing 0.70 mm



3020105 PILOT WITH 0.20 mm \varnothing JET



3020107 PILOT WITH 0.35 mm \varnothing JET



3020077 PIPE FITTING \varnothing 4 mm
thread M10x1



ROSINOX RX94812587





Suitable for:

5033138 PIPE FITTING \varnothing 4 mm
thread \varnothing 1/8" M



ROSINOX



Suitable for:

3020078 PIPE FITTING \varnothing 6 mm
thread M10x1



5014757 PIPE FITTING \varnothing 6 mm
thread M10x1 mm



Position switches

3240198 LIMIT MICROSWITCH PIZZATO FR501
3A 400V



ROSINOX RX94807872

Pressure gauges

3054034 PRESSURE GAUGE \varnothing 62 mm
coupling \varnothing 1/8" M
range 0-1 bar



ROSINOX RX94812660

Probes

3445959 SILICONE PTC PROBE 5000 mm
temperature range $-55+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ROSINOX RX94807179

3397193 TEMPERATURE PROBE \varnothing 3x470 mm
2 wires - cable length 600 mm
for Fryer gas (ROSINOX) FR25G
for Fryer electric (ROSINOX) FR15EHP



ROSINOX RX94035813

ROSINOX RX94950060



Radiant heating elements

3311168 RADIANT HEATING ELEM. ø 165mm 1200W 230V
 faston electric connections
 complete with energy adjuster
 for glass-ceramic cooking top




ROSINOX RX94806171

3311169 RADIANT HEATING ELEM. ø 200mm 1700W 230V
 faston electric connections
 complete with energy adjuster
 for glass-ceramic cooking top



ROSINOX RX94806163

7105767 RADIANT HEATING ELEMENT 4000W 400V
 dimensions 300x300 mm
 radiant size 270x270 mm
 terminal block electric connections
 for glass-ceramic cooking hob
 NO PAN DETECTION SENSOR
 for Kitchen electric (ROSINOX)
 for Glass-ceramic plate (ROSINOX) RCM3F
 R/C MODULAIRE PLAQUE VITRO
 for Kitchen electric (ROSINOX)



ROSINOX RX94090024

Relays

5026284 POWER RELAY FINDER 40.52.8.024.0000
 24Vac 50/60Hz - 2 exchange contacts 8A



ROSINOX RX94807070

3351901 POWER RELAY FINDER 60.62.8.230.0000
 230V 50/60Hz
 2 exchange contacts 10A



ROSINOX RX94804291

3351021 POWER RELAY FINDER 62.82.8.230.0000
 230V 50/60Hz
 2 exchange contacts 16A



ROSINOX RX94807054

ROSINOX RX94813866

3351008 POWER RELAY FINDER 62.83.8.230.0000
 230V 50/60Hz
 3 exchange contacts 16A



ROSINOX RX94813867



Suitable for:

3351097 RELAY POWER FINDER 62.82.8.230.0309
230V 50/60Hz
2 NO contacts 16A



ROSINOX RX94814289

Suitable for:

3351102 TIME LIMIT RELAY 80.11 16A 240V 50/60Hz
1 switching contact
slow release on excitation



ROSINOX RX27470236

Safety groups for pans and spare parts

3184011 DEPRESSION VALVE \varnothing 1/4" M
in chrome plated brass
for safety group \varnothing 3/4"
for safety group \varnothing 1" 1/4



ROSINOX RX94806056

3184018 SAFETY VALVE \varnothing 1" 1/4 M
max pressure 0.5 atm
for safety group 1" 1/4
ISPESL approved



ROSINOX RX94812663

3184017 SAFETY VALVE \varnothing 3/4" M
max pressure 0.5 atm
for safety group \varnothing 3/4"



ROSINOX RX94812619

3184019 TAP WITH FUNNEL \varnothing 1/2" M
with cover



ROSINOX RX94812552


Selector switches

3057050 CONNECTING BRACKET 28x21x16 mm
distance between hooking brackets 27 mm
f/connection between selector switch and thermost.
for Bain-marie (ROSINOX) BHE2/1



ROSINOX RX94002813


40G3278 KIT SELECTOR SWITCH 0-1 POSITIONS
complete with potentiometer
contact capacity 16A 250V - max 150°C
D-shaped pin \varnothing 6x4.6 mm



ROSINOX RX94814321

Suitable for:


3057014 SELECTOR SWITCH 0-1 POSITIONS
 contact capacity 16A 250V - max 150°C
 D-shaped pin \varnothing 6x4.6 mm
 back connection for thermostat



ROSINOX RX94805892


Suitable for:

3057082 SELECTOR SWITCH 0-1 POSITIONS
 contact capacity 16A 250V - max 150°C
 D-shaped pin 6x4.6 mm




ROSINOX RX94805405

3057176 SELECTOR SWITCH 0-1 POSITIONS
 contact capacity 32A 250V - max 150°C
 D-shaped pin \varnothing 6x4.6 mm




ROSINOX RX94804994

3057177 SELECTOR SWITCH 0-1 POSITIONS
 contact capacity 16A 250V - max 150°C
 D-shaped pin \varnothing 6x4.6 mm




ROSINOX RX94806098

3057255 SELECTOR SWITCH 0-1 POSITIONS
 contact capacity 16A 250V - max 150°C
 D-shaped pin \varnothing 6x4.6 mm
 for Bain-marie (ROSINOX) BHE2/1




ROSINOX RX94015070

3057094 SELECTOR SWITCH 0-1 0-1 POSITIONS
 contact capacity 32A 250V - max 150°C
 D-shaped pin \varnothing 6x4.6 mm




ROSINOX RX94014842

3057015 SELECTOR SWITCH 0-1-0-1 POSITIONS
 contact capacity 16A 250V - max 150°C
 D-shaped pin \varnothing 6x4.6 mm




ROSINOX RX94805256

3057001 SELECTOR SWITCH 0-3 POSITIONS
 contact capacity 32A 250V - max 150°C
 D-shaped pin \varnothing 6x4.6 mm



ROSINOX RX273349196


3057002 SELECTOR SWITCH 0-3 POSITIONS
 contact capacity 32A 250V - max 150°C
 D-shaped pin \varnothing 6x4.6 mm



ROSINOX RX27334937

ROSINOX RX94015088

3057180 SELECTOR SWITCH 0-3 POSITIONS
 contact capacity 16A 250V - max 150°C
 D-shaped pin \varnothing 6x4.6 mm



ROSINOX RX94806478




Suitable for:

ROSINOX




3057023 SELECTOR SWITCH 0-6 POSITIONS
contact capacity 32A 250V - max 150°C
D shaft ø 6x4.6 mm



ROSINOX RX94015021

Suitable for:

3057024 SELECTOR SWITCH 0-6 POSITIONS
contact capacity 16A 250V - max 150°C
D-shaped pin ø 6x4.6 mm
for Bratt pan (ROSINOX) SBM60G



ROSINOX RX94015013

ROSINOX RX94806010

Solenoid valves

3120004 SOLEN. VALVE ELBI TYPE 319 1 WAY 90°
220/240V 50/60Hz - max. temperature 90°C
inlet 3/4" - outlet ø 10.5 mm



ROSINOX RX94805520

3120019 ADJUSTER FOR INLET ELBI BLACK
flow rate 5.5 L/min - tolerance +/- 15%



3120021 ADJUSTER FOR INLET ELBI BLACK
flow rate 12 L/min - tolerance +/- 15%



3120022 ADJUSTER FOR INLET ELBI BLACK
flow rate 16 L/min - tolerance +/- 15%



3120037 ADJUSTER FOR OUTLET ELBI GREEN
flow rate 0.25 L/min - tolerance +/- 25%



3120201 ADJUSTER FOR OUTLET ELBI GREY
flow rate 4.7 L/min - tolerance +/- 25%



3120016 ADJUSTER FOR OUTLET ELBI NEUTRAL
flow rate 1.2 L/min - tolerance +/- 25%



3120017 ADJUSTER FOR OUTLET ELBI ORANGE
flow rate 2.5 L/min - tolerance +/- 25%





Suitable for:

3120015 ADJUSTER FOR OUTLET ELBI RED
flow rate 0.5 L/min - tolerance +/- 25%



3120202 ADJUSTER FOR OUTLET ELBI YELLOW
flow rate 0.35 L/min / tolerance +/- 25%



3120204 OUTLET ADJUSTER ELBI BLACK
flow rate 5.5 L/min - tolerance +/- 25%



3120007 SOLEN. VALVE ELBI TYPE 349 2 WAY 180°
220/240V 50/60Hz - max. temperature 90°C
inlet 3/4" - two outlets ø 10.5 mm



ROSINOX RX94050168

3120021 ADJUSTER FOR INLET ELBI BLACK
flow rate 12 L/min - tolerance +/- 15%



3120037 ADJUSTER FOR OUTLET ELBI GREEN
flow rate 0.25 L/min - tolerance +/- 25%



ROSINOX



Suitable for:

3120203 ADJUSTER FOR OUTLET ELBI WHITE
flow rate 2 L/min - tolerance +/- 25%



3120000 FILTER FOR INLET SOLENOID VALVE ELBI



3120019 ADJUSTER FOR INLET ELBI BLACK
flow rate 5.5 L/min - tolerance +/- 15%



3120022 ADJUSTER FOR INLET ELBI BLACK
flow rate 16 L/min - tolerance +/- 15%



3120201 ADJUSTER FOR OUTLET ELBI GREY
flow rate 4.7 L/min - tolerance +/- 25%





Suitable for:

3120016 ADJUSTER FOR OUTLET ELBI NEUTRAL
flow rate 1.2 L/min - tolerance +/- 25%



3120015 ADJUSTER FOR OUTLET ELBI RED
flow rate 0.5 L/min - tolerance +/- 25%



3120202 ADJUSTER FOR OUTLET ELBI YELLOW
flow rate 0.35 L/min / tolerance +/- 25%



3120204 OUTLET ADJUSTER ELBI BLACK
flow rate 5.5 L/min - tolerance +/- 25%



3120507 SOLEN. VALVE ELBI TYPE 349 2 WAY 180°
24V 50/60Hz - max. temperature 90°C
inlet 3/4" - two outlets ø 10.5 mm



ROSINOX RX94804671

3120021 ADJUSTER FOR INLET ELBI BLACK
flow rate 12 L/min - tolerance +/- 15%



ROSINOX



Suitable for:

3120017 ADJUSTER FOR OUTLET ELBI ORANGE
flow rate 2.5 L/min - tolerance +/- 25%



3120203 ADJUSTER FOR OUTLET ELBI WHITE
flow rate 2 L/min - tolerance +/- 25%



3120000 FILTER FOR INLET SOLENOID VALVE ELBI



3120019 ADJUSTER FOR INLET ELBI BLACK
flow rate 5.5 L/min - tolerance +/- 15%



3120022 ADJUSTER FOR INLET ELBI BLACK
flow rate 16 L/min - tolerance +/- 15%





Suitable for:

3120037 ADJUSTER FOR OUTLET ELBI GREEN
flow rate 0.25 L/min - tolerance +/- 25%



3120016 ADJUSTER FOR OUTLET ELBI NEUTRAL
flow rate 1.2 L/min - tolerance +/- 25%



3120015 ADJUSTER FOR OUTLET ELBI RED
flow rate 0.5 L/min - tolerance +/- 25%




3120202 ADJUSTER FOR OUTLET ELBI YELLOW
flow rate 0.35 L/min / tolerance +/- 25%



3120204 OUTLET ADJUSTER ELBI BLACK
flow rate 5.5 L/min - tolerance +/- 25%



3120009 SOLEN. VALVE ELBI TYPE 351 1 WAY 180°
220/240V 50/60Hz - max. temperature 90°C
inlet 3/4" - outlet ø 13.5 mm



ROSINOX



Suitable for:

3120201 ADJUSTER FOR OUTLET ELBI GREY
flow rate 4.7 L/min - tolerance +/- 25%



3120017 ADJUSTER FOR OUTLET ELBI ORANGE
flow rate 2.5 L/min - tolerance +/- 25%



3120203 ADJUSTER FOR OUTLET ELBI WHITE
flow rate 2 L/min - tolerance +/- 25%



3120000 FILTER FOR INLET SOLENOID VALVE ELBI



3120019 ADJUSTER FOR INLET ELBI BLACK
flow rate 5.5 L/min - tolerance +/- 15%





Suitable for:

3120021 ADJUSTER FOR INLET ELBI BLACK
flow rate 12 L/min - tolerance +/- 15%



3120037 ADJUSTER FOR OUTLET ELBI GREEN
flow rate 0.25 L/min - tolerance +/- 25%



3120016 ADJUSTER FOR OUTLET ELBI NEUTRAL
flow rate 1.2 L/min - tolerance +/- 25%



3120015 ADJUSTER FOR OUTLET ELBI RED
flow rate 0.5 L/min - tolerance +/- 25%



3120202 ADJUSTER FOR OUTLET ELBI YELLOW
flow rate 0.35 L/min / tolerance +/- 25%



3120204 OUTLET ADJUSTER ELBI BLACK
flow rate 5.5 L/min - tolerance +/- 25%



ROSINOX

Suitable for:

3120022 ADJUSTER FOR INLET ELBI BLACK
flow rate 16 L/min - tolerance +/- 15%



3120201 ADJUSTER FOR OUTLET ELBI GREY
flow rate 4.7 L/min - tolerance +/- 25%



3120017 ADJUSTER FOR OUTLET ELBI ORANGE
flow rate 2.5 L/min - tolerance +/- 25%



3120203 ADJUSTER FOR OUTLET ELBI WHITE
flow rate 2 L/min - tolerance +/- 25%



3120000 FILTER FOR INLET SOLENOID VALVE ELBI



3120010 SOLEN. VALVE ELBI TYPE 352 2 WAY 90°
 220/240V 50/60Hz - max. temperature 90°C
 inlet 3/4" - two outlets ø 13.5 mm



ROSINOX RX94809795

3120021 ADJUSTER FOR INLET ELBI BLACK
 flow rate 12 L/min - tolerance +/- 15%



3120019 ADJUSTER FOR INLET ELBI BLACK
 flow rate 5.5 L/min - tolerance +/- 15%



3120022 ADJUSTER FOR INLET ELBI BLACK
 flow rate 16 L/min - tolerance +/- 15%



3120037 ADJUSTER FOR OUTLET ELBI GREEN
 flow rate 0.25 L/min - tolerance +/- 25%



3120201 ADJUSTER FOR OUTLET ELBI GREY
 flow rate 4.7 L/min - tolerance +/- 25%



3120016 ADJUSTER FOR OUTLET ELBI NEUTRAL
 flow rate 1.2 L/min - tolerance +/- 25%



3120017 ADJUSTER FOR OUTLET ELBI ORANGE
 flow rate 2.5 L/min - tolerance +/- 25%



3120015 ADJUSTER FOR OUTLET ELBI RED
 flow rate 0.5 L/min - tolerance +/- 25%



3120203 ADJUSTER FOR OUTLET ELBI WHITE
 flow rate 2 L/min - tolerance +/- 25%



3120202 ADJUSTER FOR OUTLET ELBI YELLOW
 flow rate 0.35 L/min / tolerance +/- 25%



3120000 FILTER FOR INLET SOLENOID VALVE ELBI





Suitable for:

3120204 **OUTLET ADJUSTER ELBI BLACK**
flow rate 5.5 L/min - tolerance +/- 25%




ROSINOX



Suitable for:

3120407 **SOLEN. VALVE T&P 2 WAY 180°**
230V 50/60Hz - max. temperature 90°C
inlet 3/4" - two outlets ø 10.5 mm



3120421 **ADJUSTER FOR OUTLET T&P BLACK**
flow rate 5 L/min - tolerance +/- 20%



ROSINOX RX94807480

3120608 **ADJUSTER FOR OUTLET T&P DARK BROWN**
flow rate 1.2 L/min - tolerance +/- 25%



3120568 **ADJUSTER FOR OUTLET T&P GREEN**
flow rate 3 L/min - tolerance +/- 25%



3120391 **ADJUSTER FOR OUTLET T&P LIGHT BLUE**
flow rate 1 L/min - tolerance +/- 25%



3120387 **ADJUSTER FOR OUTLET T&P LIGHT BROWN**
flow rate 1.5 L/min - tolerance +/- 25%



3120423 **ADJUSTER FOR OUTLET T&P ORANGE**
flow rate 0.5 L/min - tolerance +/- 25%



3120424 **ADJUSTER FOR OUTLET T&P RED**
flow rate 0.25 L/min - tolerance +/- 25%



3120386 **ADJUSTER FOR OUTLET T&P WHITE**
flow rate 0.8 L/min - tolerance +/- 25%



3120422 **ADJUSTER FOR OUTLET T&P YELLOW**
flow rate 2.5 L/min - tolerance +/- 25%





Suitable for:

D120056 ADJUSTER INLET T&P BRONZE
flowrate 12 L/min



D120057 ADJUSTER INLET T&P LIGHT BROWN
flowrate 16 L/min



D120052 ADJUSTER INLET T&P RED
flowrate 3 L/min



D120053 ADJUSTER INLET T&P YELLOW
flowrate 5.5 L/min



3120431 COIL T&P 12Vac 50/60Hz
for solenoid valves T&P



D120090 COIL T&P 120V 60Hz 8VA
for solenoid valves T&P



ROSINOX



Suitable for:

D120054 ADJUSTER INLET T&P GREY
flowrate 6 L/min



D120058 ADJUSTER INLET T&P ORANGE
flowrate 20 L/min



D120055 ADJUSTER INLET T&P WHITE
flowrate 10 L/min



D120059 ADJUSTER OUTLET T&P BLUE
flow rate 8 L/min - tolerance +/-25%



D120092 COIL T&P 12Vdc
for solenoid valves T&P




3120433 COIL T&P 220V 50/60Hz
for solenoid valves T&P





Suitable for:

3120432 COIL T&P 24Vac 50/60Hz
for solenoid valves T&P



ROSINOX



Suitable for:


D120093 COIL T&P 24Vdc
for solenoid valves T&P



3120398 SOLENOID VALVE INVENSYS 2 WAY 180°
220/240V 50/60Hz - max temperature 90°C
inlet 3/4" - two outlets ø 10.5 mm
with cable length 2000 mm



3120473 ADJUSTER FOR INLET ROBERTSHAW BROWN
flow rate 5 L/min - tolerance +/- 15%



ROSINOX RX24720054

3120474 ADJUSTER FOR INLET ROBERTSHAW DARK BLUE
flow rate 6 L/min - tolerance +/- 15%



3120478 ADJUSTER FOR INLET ROBERTSHAW GREEN
flow rate 11 L/min - tolerance +/- 15%



3120479 ADJUSTER FOR INLET ROBERTSHAW GREY
flow rate 12 L/min - tolerance +/- 15%



3120476 ADJUSTER FOR INLET ROBERTSHAW LIGHT BLUE
flow rate 9 L/min - tolerance +/- 15%



3120475 ADJUSTER FOR INLET ROBERTSHAW ORANGE
flow rate 8 L/min - tolerance +/- 15%



3120472 ADJUSTER FOR INLET ROBERTSHAW PURPLE
flow rate 4 L/min - tolerance +/- 15%



3120477 ADJUSTER FOR INLET ROBERTSHAW WHITE
flow rate 10 L/min - tolerance +/- 15%



3120481 ADJUSTER FOR INLET ROBERTSHAW YELLOW
flow rate 14.5 L/min - tolerance +/- 15%





Suitable for:

3120499 ADJUSTER FOR OUTLET ROBERTSHAW BLU
flow rate 1.2 L/min - tolerance +/- 25%



3120488 ADJUSTER FOR OUTLET ROBERTSHAW PINK
flow rate 3.3 L/min - tolerance +/- 20%



3120483 ADJUSTER FOR OUTLET ROBERTSHAW YELLOW
flow rate 0.5 L/min - tolerance +/- 15%



3120485 OUTLET ADJUSTER ROBERTSHAW LIGHT BROWN
flow rate 1.3 L/min - tolerance +/- 25%



3120625 OUTLET REDUCER ROBERTSHAW GRIGIO
flow rate 0.35 L/min - tolerance +/- 10%



3120261 SOLENOID VALVE MÜLLER 1 WAY 180°
220/240V 50/60Hz - max. temperature 90°C
inlet 3/4" - outlet ø 10.5 mm



ROSINOX



Suitable for:

3120484 ADJUSTER FOR OUTLET ROBERTSHAW GREEN
flow rate 0.8 L/min - tolerance +/- 25%



3120482 ADJUSTER FOR OUTLET ROBERTSHAW WHITE
flow rate 0.25 L/min - tolerance +/- 10%



3120487 OUTLET ADJUSTER ROBERTSHAW DARK BROWN
flow rate 2.5 L/min - tolerance +/- 20%



3120486 OUTLET ADJUSTER ROBERTSHAW LIGHT GREEN
flow rate 2 L/min - tolerance +/- 25%



3120271 COIL MÜLLER 220/240V 50/60Hz
max temperature 90°C





Suitable for:

3120274 COIL MÜLLER 220/240V 50/60Hz
max. temperature 90°C
with cable length 2000 mm



3120325 COIL MÜLLER 24Vac 50/60Hz
max temperature 90°C



ROSINOX



Suitable for:

3120273 COIL MÜLLER 230V 60Hz
temperature 90°C - for dispenser



5023165 FILTER INLET FOR SOLENOID VALVE MÜLLER
ø 19 mm



3120404 SOLENOID VALVE T&P 1 WAY 90°
230V 50/60Hz - max. temperature 90°C
inlet 3/4" con riduttore di portata 10 L/min
outlet ø 10.5 mm



3120421 ADJUSTER FOR OUTLET T&P BLACK
flow rate 5 L/min - tolerance +/- 20%



ROSINOX RX94813749

3120608 ADJUSTER FOR OUTLET T&P DARK BROWN
flow rate 1.2 L/min - tolerance +/- 25%



3120568 ADJUSTER FOR OUTLET T&P GREEN
flow rate 3 L/min - tolerance +/- 25%



3120391 ADJUSTER FOR OUTLET T&P LIGHT BLUE
flow rate 1 L/min - tolerance +/- 25%



3120387 ADJUSTER FOR OUTLET T&P LIGHT BROWN
flow rate 1.5 L/min - tolerance +/- 25%



3120423 ADJUSTER FOR OUTLET T&P ORANGE
flow rate 0.5 L/min - tolerance +/- 25%



3120424 ADJUSTER FOR OUTLET T&P RED
flow rate 0.25 L/min - tolerance +/- 25%





Suitable for:

3120386 ADJUSTER FOR OUTLET T&P WHITE
flow rate 0.8 L/min - tolerance +/- 25%



D120056 ADJUSTER INLET T&P BRONZE
flowrate 12 L/min



D120057 ADJUSTER INLET T&P LIGHT BROWN
flowrate 16 L/min



D120052 ADJUSTER INLET T&P RED
flowrate 3 L/min



D120053 ADJUSTER INLET T&P YELLOW
flowrate 5.5 L/min



3120431 COIL T&P 12Vac 50/60Hz
for solenoid valves T&P



ROSINOX

Suitable for:

3120422 ADJUSTER FOR OUTLET T&P YELLOW
flow rate 2.5 L/min - tolerance +/- 25%



D120054 ADJUSTER INLET T&P GREY
flowrate 6 L/min



D120058 ADJUSTER INLET T&P ORANGE
flowrate 20 L/min



D120055 ADJUSTER INLET T&P WHITE
flowrate 10 L/min



D120059 ADJUSTER OUTLET T&P BLUE
flow rate 8 L/min - tolerance +/- 25%



D120092 COIL T&P 12Vdc
for solenoid valves T&P





Suitable for:

D120090 COIL T&P 120V 60Hz 8VA
for solenoid valves T&P



3120432 COIL T&P 24Vac 50/60Hz
for solenoid valves T&P



ROSINOX

Suitable for:

3120433 COIL T&P 220V 50/60Hz
for solenoid valves T&P



D120093 COIL T&P 24Vdc
for solenoid valves T&P



Spark generators

3181002 SPARK GENERATOR 2 OUTLETS
220/240V 50/60Hz
for Boiling pan (ROSINOX) BM RCS MBM250GBE



ROSINOX RX94027802

ROSINOX RX94805108

3181003 SPARK GENERATOR 4 OUTLETS
220/240V 50/60Hz



ROSINOX RX94039229

ROSINOX RX94805116


3181004 SPARK GENERATOR 6 OUTLETS
220/240V - 50/60Hz



ROSINOX RX94805124

Sparking and detection plugs

3806021 DETECTOR ELECTRODE ROUND \varnothing 8x20 mm
totale length 100 mm
flange 48x22 mm
for Bratt pan gas (ROSINOX) RCSSBM60G



ROSINOX RX94051521

3001003 IGNITION PLUG ROUND \varnothing 7x44 mm
M faston M4x1 mm
overall length 65 mm



ROSINOX RX94034642

ROSINOX 94805207

Suitable for:

3020060 IGNITION PLUG ROUND \varnothing 7x44 mm
 M faston M 4x1 mm
 overall length 82 mm
 model CB505/021 Junkers
 for model P502F



ROSINOX RX94805066

ROSINOX RX94805306

ROSINOX RX94805686

Suitable for:

3020124 IGNITION PLUG ROUND \varnothing 7x44 mm
 connection \varnothing 2.4 mm
 overall length 58 mm



ROSINOX RX94027729

ROSINOX 94027729

3020126 ROUND IGNITION PLUG \varnothing 6.5x55 mm
 connection \varnothing 2.4 mm
 with silicone lead 1760 mm
 overall length with cable 1830 mm



ROSINOX RX94805157

3020127 ROUND IGNITION PLUG \varnothing 6.5x55 mm
 connection \varnothing 2.4 mm
 with silicone lead 625 mm
 overall length with cable 680 mm



ROSINOX RX94805132

3020138 ROUND IGNITION PLUG \varnothing 6.5x55 mm
 connection \varnothing 2.4 mm
 with silicone lead 970 mm
 overall length with cable 1030 mm



ROSINOX RX94805140

3020073 ROUND IGNITION PLUG \varnothing 7/10x52 mm
 model 1/B
 connection F 2.8x0.8 mm - complete with spring
 overall length 54 mm



ROSINOX RX94805033

3806020 ROUND IGNITION PLUG \varnothing 7x50 mm
 overall length 67 mm



ROSINOX RX94044214

3020230 ROUND IGNITION PLUG \varnothing 7x54 mm
 male faston M4x1 mm
 overall length 63 mm
 for COOKING HOB series 700 PROTAGONISTA NUOVA
 for COOKING HOB series 900 PROTAGONISTA NUOVA
 for COOKING HOB series 1100 PROTAGONISTA NUOVA



ROSINOX RX94034493



Suitable for:

ROSINOX



Suitable for:

3806003 ROUND IGNITION PLUG \varnothing 9.5x48 mm
 total length 97 mm
 for HONEYWELL BURNER
 for Bratt pan (ROSINOX) RCS SBM80GSS



ROSINOX RX94051513

Springs

3250233 LID SPRING \varnothing 24x240 mm
 length without hooks 195 mm
 for BRATT PAN SBM50G-SBM35E
 for BOILING PAN MBM80G-MBM80E



ROSINOX RX94024791

Switches

3319150 BIPOLAR PUSH-BUTTON 16A 250V BLACK
 mounting hole \varnothing 25 mm



ROSINOX RX94805173

3319151 SWITCH PROTECTION CAP
 \varnothing external 34 mm
 for push-buttons with mounting hole \varnothing 25 mm



3319090 BIPOLAR SWITCH GREEN 16A 250V
 16(4)A 250V - max. temperature 120°C
 with indicator light and push-button cap
 mounting hole 22x30 mm



ROSINOX RX94809514

3319780 BLOCK CONNECTION WHITE 22x30 mm



3319779 BLOCK CONNECTIONS BLACK 22x30 mm



3319782 FRAME SAFETY 2 SIDES BLACK 22x30 mm





Suitable for:

3319783 FRAME SAFETY 4 SIDES BLACK 22x30 mm



ROSINOX



Suitable for:

3319501 PUSH-BUTTON PROTECTION CAP
external dimensions 29x36 mm
for switches with mounting hole 22x30 mm



3319944 BIPOLAR SWITCH GREEN 16A 250V
16(4)A 250V - max. temperature 120°C
with indicator light - silk screen printing 0 - I
mounting hole 22x30 mm



3319780 BLOCK CONNECTION WHITE 22x30 mm



ROSINOX RX94805496

3319779 BLOCK CONNECTIONS BLACK 22x30 mm



3319782 FRAME SAFETY 2 SIDES BLACK 22x30 mm



3319783 FRAME SAFETY 4 SIDES BLACK 22x30 mm



3319501 PUSH-BUTTON PROTECTION CAP
external dimensions 29x36 mm
for switches with mounting hole 22x30 mm



3319091 CHANGEOVER SWITCH 2 POLE GREEN 16A 250V
16(4)A 250V - max. temperature 120°C
with indicator light and push-button cap
mounting hole 22x30 mm



3319780 BLOCK CONNECTION WHITE 22x30 mm



ROSINOX RX94809506

3319779 BLOCK CONNECTIONS BLACK 22x30 mm



3319782 FRAME SAFETY 2 SIDES BLACK 22x30 mm





Suitable for:

3319783 FRAME SAFETY 4 SIDES BLACK 22x30 mm



ROSINOX




Suitable for:

3319501 PUSH-BUTTON PROTECTION CAP
external dimensions 29x36 mm
for switches with mounting hole 22x30 mm



3319714 TWO-POLE LEVER SWITCH 16A 250V
threaded coupling M12x1 mm
ON-OFF function
for Bain-marie electric (ROSINOX) BME1/1



ROSINOX RX94026036

3319686 START-STOP STRIP
for lever switches-reversers



3319685 SWITCH PROTECTION CAP
for lever switches-reversers



Taps for tank refilling

3359129 WATER INLET TAP \varnothing 1/2"FF



ROSINOX RX94806338

Telethermometers

3441011 TELE-THERMOMETER BLACK 56x25 mm 0-120°C
plastic case
capillary length 1500 mm
bulb \varnothing 6x15 mm



ROSINOX RX94807252

3441007 TELE-THERMOMETER WHITE \varnothing 60 mm 0-120°C
metal case
PVC covered capillary 3000 mm
spring bulb \varnothing 8x32 mm
bulb fitting M10x1



ROSINOX RX94803038



Terminal blocks

7105702 CONNECTOR F 2-POLE
 dimensions 25.5x16x8 mm
 for Fryer (ROSINOX)




ROSINOX 94036027

3247007 TERMINAL BLOCK 3-POLES OF CERAMIC
 for cable 1.5-4 mm²
 operating temperature 300°C
 nominal voltage 250V
 dimensions 38x25x20 mm



ROSINOX RX94018090

3247009 TERMINAL BLOCK 6-POLES FV122/B 40A 600V
 for cable max 6 mm²
 operating temperature 150°C
 nominal voltage 450 V



ROSINOX RX94810223

Thermocouples and accessories

3440055 THERMOCOUPLE SIT M8x1 100 cm THREAD M8x1



ROSINOX 94028529

3440064 NUT FOR THERMOCOUPLE M8x1



3440855 THERMOCOUPLE SIT M8x1 100 cm - 10 PCS
 CONNECTOR M8x1



3440837 THERMOCOUPLE SIT M9x1 100 cm - 10 PCS



ROSINOX RX94015112



Suitable for:

3440037 THERMOCOUPLE SIT M9x1 100 cm.



ROSINOX RX94015112

Suitable for:

3440837 THERMOCOUPLE SIT M9x1 100 cm - 10 PCS



ROSINOX RX94015112

**3440859 THERMOCOUPLE SIT M9x1 60 cm - 10 PCS
CONNECTOR M8x1**



ROSINOX RX94805025

3440059 THERMOCOUPLE SIT M9x1 60 cm THREAD M8x1



ROSINOX RX94805025

3440064 NUT FOR THERMOCOUPLE M8x1



**3440859 THERMOCOUPLE SIT M9x1 60 cm - 10 PCS
CONNECTOR M8x1**



ROSINOX RX94805025

3440836 THERMOCOUPLE SIT M9x1 85 cm - 10 PCS



ROSINOX RX94024973

**3440036 THERMOCOUPLE SIT M9x1 85 cm.
for Bratt pan (ROSINOX) ROSICHEF SEM50G 30/10**



ROSINOX RX94024973

3440836 THERMOCOUPLE SIT M9x1 85 cm - 10 PCS



ROSINOX RX94024973

Suitable for:

Suitable for:

3440165 THERMOCOUPLE 11/32 P.ASA 60 cm COUPLING
with fitting M11x1

3440064 NUT FOR THERMOCOUPLE M8x1



ROSINOX

Thermostatic gas valves


3348170 THERMOSTATIC TAP ROBERTSHAW BJW
adjustment temperature 93-287°C
inlet fitting \varnothing 10 mm
outlet pipe fitting \varnothing 3/8" NPT
bulb \varnothing 5x290 mm
capillary length 1200 mm



ROSINOX

3345006 THERMOSTATIC TAP 24ST
adjustment temperature 120-320°C
connections M20x1.5 mm
thermocouple connection M9x1
bulb \varnothing 6x100 mm
capillary length 1200 mm
D-shaped pin \varnothing 10x8 mm

3348038 OLIVE FOR PIPE \varnothing 10 mm
for model PEL 22-24-25



ROSINOX RX94806536

3348044 OLIVE FOR PIPE \varnothing 10 mm
for model PEL 20-21-24-25

3020082 OLIVE FOR PIPE \varnothing 12 mm
for model PEL 22-24-25



ROSINOX RX94810978



Suitable for:

3348036 OLIVE FOR PIPE \varnothing 4 mm
for model PEL 21-22-24-25



ROSINOX RX94812588

3348031 PIPE FITTING \varnothing 10 mm
thread M20x1.5 mm
for model PEL 22-24-25



3348032 PIPE FITTING \varnothing 12 mm
thread M20x1.5 mm
for model PEL 22-24-25



3020078 PIPE FITTING \varnothing 6 mm
thread M10x1



ROSINOX RX94800935

ROSINOX




Suitable for:

3348037 OLIVE FOR PIPE \varnothing 6 mm
for model PEL 21-22-24-25



3348043 PIPE FITTING \varnothing 10 mm
thread M16x1.5 mm
for model PEL 20-21-24-25



3348029 PIPE FITTING \varnothing 4 mm
thread M10x1 mm
for model PEL 21-22-24-25



5014757 PIPE FITTING \varnothing 6 mm
thread M10x1 mm



Thermostats

3444012 KNOB BLACK \varnothing 41 mm SILK-SCREEN PRINTED
D-shaped hole 6x4.6 mm
for thermostat IMIT



3444008 KNOB BLACK \varnothing 41 mm 0-90°C
D-shaped hole 6x4.6 mm
for thermostat IMIT



ROSINOX RX94813937

Suitable for:

Suitable for:

3444974 SINGLE-PHASE THERMOSTAT 100-615°C
complete with switch
D-shaped pin \varnothing 6x4.6 mm
covered capillary length 1100 mm - 16A 250V
bulb \varnothing 4x230 mm

3444372 SINGLE-PHASE THERMOSTAT 245°C
with manual reset
covered capillary length 1170 mm - 16A 250V
bulb \varnothing 6x133 mm




ROSINOX RX94090032

ROSINOX RX94804986

3444346 SINGLE-PHASE THERMOSTAT 30-90°C
D-shaped pin \varnothing 6x4.6 mm
covered capillary length 900 mm - 16A 250V
bulb \varnothing 6x130 mm - with stuffing gland fitting M9x1

3444312 SINGLE-PHASE THERMOSTAT 360°C
with manual reset
capillary length covered 1500 mm - 16A 250V
bulb \varnothing 4x110 mm





ROSINOX RX94805249

ROSINOX RX94800158

ROSINOX RX94812622

3444774 SINGLE-PHASE THERMOSTAT 45-295°C
D-shaped pin \varnothing 6x4.6 mm
covered capillary length 900 mm - 16A 230V
bulb \varnothing 4x95 mm

3444467 SINGLE-PHASE THERMOSTAT 55-180°C
complete with selector switch
D-shaped pin \varnothing 6x4.6 mm
covered capillary length 870 mm - 16A 250V
bulb \varnothing 4x120 mm




ROSINOX RX94812577

ROSINOX RX94812560

3744068 SINGLE-PHASE THERMOSTAT 60-200°C
D-shaped pin \varnothing 6x4.6 mm
capillary length 900 mm
bulb \varnothing 6x80 mm - with adapter nipple band M9x1
with complete tank coupling M12x1

3444376 SINGLE-PHASE THERMOSTAT 95-190°C
D-shaped pin \varnothing 6x4.6 mm
covered capillary length 1010 mm - 16A 250V
bulb \varnothing 6x100 mm - with adapter nipple band M10x1



ROSINOX RX94016680

ROSINOX RX94805371



Suitable for:

ROSINOX



5009025 STUFFING GLAND THERMOSTAT M10x1
hole \varnothing 4.5 mm



ROSINOX RX94812566


Suitable for:

7101637 THERMOSTAT SINGLE PHASE 130-550°C
D-shaped pin \varnothing 6x4.6 mm
bulb \varnothing 4x120 mm
for Fry top (ROSINOX) PLAQUE25E RCM
for Fry top electric (ROSINOX) ROSICHEF 200E



ROSINOX RX94016565

3444239 THERMOSTAT SINGLE-PHASE 240°C
with manual reset
covered capillary length 860 mm - 16A 250V
bulb \varnothing 6x77 mm - with stuffing gland fitting M10x1
with M9x1 thermocouple interruption fitting




ROSINOX RX94805702

2101871 THERMOSTAT SINGLE-PHASE 50-320°C
D-shaped pin \varnothing 6x4,6 mm
capillary length 840 mm - 16A 250V
bulb \varnothing 3x178 mm




ROSINOX RX94804655

3444356 THERMOSTAT THREE-PHASE 365°C
with manual reset
covered capillary length 1300 mm - 10A 400V
bulb \varnothing 4x120 mm




ROSINOX RX24848111

3444479 THREE-PHASE THERMOSTAT 120°C
with manual reset
covered capillary length 900 mm - 10A 400V
bulb \varnothing 6x100 mm




ROSINOX RX94800505

3444769 THREE-PHASE THERMOSTAT 132°C
with automatic reset
capillary length 900 mm - 16A 230V
bulb \varnothing 6x80 mm - with adapter nipple band M10x1



ROSINOX RX94812642

3444770 THREE-PHASE THERMOSTAT 157°C
with manual reset
covered capillary length 900 mm - 16A 230V
bulb \varnothing 6x80 mm




ROSINOX RX94805413



Suitable for:


3444775 THREE-PHASE THERMOSTAT 159°C
with manual reset
capillary length 1100 mm - 16A 230V
bulb \varnothing 3.1x185 mm



ROSINOX RX94812646


Suitable for:

3444375 THREE-PHASE THERMOSTAT 225°C
with manual reset
covered capillary length 900 mm - 10A 400V
bulb \varnothing 6x90 mm - with adapter nipple band M10x1




ROSINOX RX94812594

3444307 THREE-PHASE THERMOSTAT 230°C
with manual reset
covered capillary length 900 mm - 10A 400V
bulb \varnothing 6x100 mm - with adapter nipple band M10x1



ROSINOX RX94016599

3744113 THREE-PHASE THERMOSTAT 230°C
with manual reset
covered capillary length 600 mm - 10A 400V
bulb \varnothing 4x122 mm



ROSINOX RX94812559

3444088 THREE-PHASE THERMOSTAT 30-110°C
D-shaped pin \varnothing 6x4.6 mm
capillary length 900 mm - 10A 400V
bulb \varnothing 6x140 mm - with stuffing gland fitting M9x1




ROSINOX

3444620 THREE-PHASE THERMOSTAT 45-120°C
D-shaped pin \varnothing 6x4.6 mm
covered capillary length 870 mm - 16A 380V
bulb \varnothing 6x140 mm



ROSINOX RX94805421

3444561 THREE-PHASE THERMOSTAT 50-300°C
D-shaped pin \varnothing 6x4.6 mm
covered capillary length 1740 mm - 16A 230V
bulb \varnothing 6x80 mm



ROSINOX RX94032588

3444694 THREE-PHASE THERMOSTAT 50-300°C
D-shaped pin \varnothing 6x4.6 mm
capillary length 880 mm
bulb \varnothing 6x77 mm



ROSINOX

3444052 THREE-PHASE THERMOSTAT 50-320°C
D-shaped pin \varnothing 6x4.6 mm
capillary length 900 mm - 10A 400V
bulb \varnothing 3x230 mm



ROSINOX RX94805645

3444594 THREE-PHASE THERMOSTAT 65-200°C
D-shaped pin \varnothing 6x4.6 mm
capillary length 880 mm
bulb \varnothing 6x77 mm - with adapter nipple bland M9x1
with complete tank coupling M12x1



ROSINOX RX24845588




Suitable for:

ROSINOX




3444371 THREE-PHASE THERMOSTAT 70-195°C
 D-shaped pin \varnothing 6x4.6 mm
 covered capillary length 1500 mm - 10A 400V
 bulb \varnothing 6x135 mm



ROSINOX RX94804978

Suitable for:

3444779 THREE-PHASE THERMOSTAT 75-295°C
 D-shaped pin \varnothing 6x4.6 mm
 covered capillary length 900 mm - 16A 230V
 bulb \varnothing 4x92 mm



ROSINOX RX94812621

Timers

3446159 TIMER 120 MINUTES C53
 manually set mechanical timer
 manually set cycle 120 minutes
 contact capacity 16A 250V
 max temperature 125°C
 2 normally closed contacts
 2 normally closed contacts
 complete with silkscreen printed plate and knob
 dimensions 49.5x58 mm depth 52 mm



ROSINOX RX94027836

3446155 TIMER 120 MINUTES S43V
 mechanical timer with sound alarm
 manual winding cycle 120 minutes
 complete with screenprinted plate and knob
 size \varnothing 60x27 mm



ROSINOX

3446157 TIMER 30 MINUTES C53
 manually set mechanical timer
 manually set cycle 30 minutes
 contact capacity 16A 250V
 max temperature 125°C
 2 normally closed contacts
 2 normally closed contacts
 complete with silkscreen printed plate and knob
 dimensions 49.5x58 mm depth 52 mm



ROSINOX RX94027869

3446150 TIMER 30 MINUTES S43V
 mechanical timer with sound alarm
 manual winding cycle 30 minutes
 complete with screenprinted plate and knob
 size \varnothing 60x27 mm



ROSINOX


Tools

3394406 SCRAPER FRY TOP AND BRATT PAN
 with 1 blade 102 mm



ROSINOX RX94806502

3394408 SCRAPER BLADE 102 mm - 10 PCS





Tubing and hoses

- 3450124 DRAIN PIPE 720 mm**
external \varnothing 40 mm - internal \varnothing 30 mm



ROSINOX RX94812302

Wheels and accessories

- 7102729 HANDWHEEL \varnothing 150 mm**
central hole \varnothing 14 mm - with pin groove 24x6 mm
complete with folding handle



ROSINOX RX94806020

- 5012756 SCREW NUT FOR BRATT PAN \varnothing 40x40 mm**



ROSINOX RX94806569

- 5012754 TILTING SCREW**
total length 543 mm



- 5056124 TILTING SCREW \varnothing 20 mm**
overall length 363 mm



- 40C3800 HANDWHEEL \varnothing 23x65 mm**
thread M6



- 5004961 SUPPORT FLANGE WITH BEARING UCF204**
flange external dimensions 86x86 mm



ROSINOX RX94806544

- 5012755 TILTING SCREW**
total length 350 mm



ROSINOX RX94806551



Suitable for:

3522045 HANDWHEEL \varnothing 200 mm
hole \varnothing 16 mm – with key slot 5 mm
complete with folding handle



ROSINOX RX94030871

Suitable for:

5012756 SCREW NUT FOR BRATT PAN \varnothing 40x40 mm



ROSINOX RX94806569

5004961 SUPPORT FLANGE WITH BEARING UCF204
flange external dimensions 86x86 mm



ROSINOX RX94806544


5012755 TILTING SCREW
total length 350 mm



ROSINOX RX94806551

Wire pan supports

3354001 REDUCER FOR MOKA POT 265x265 mm
in stainless steel



ROSINOX RX94806759

The data herewith contained may change without notice and LF SpA cannot be held responsible for possible errors stated or resulting by the use of this document. All rights reserved. No part of this publication may be reproduced without written permission by LF SpA.



Distributing Components, Spare Parts & Accessories in original quality worldwide

-
- LF SpA HEADQUARTERS**
via Voltri, 80 - 47522 Cesena (FC) ITALY
Tel. +39 0547 34 11 11 - Fax +39 0547 34 11 10
www.lfircambi724.it - info@lfircambi.it
Export Dept. Tel. +39 0547 34 11 50 - Fax +39 0547 34 11 55
www.lfspareparts724.com - export@lfspareparts.com
- LF SpA HOUSEHOLD COMPONENTS DIVISION**
Via Padriciano, 99 - AREA Science Park - 34149 Trieste (TS) ITALY
Tel. +39 0547 34 12 42 - Fax +39 0547 34 12 48
www.lfspareparts724.com - info@lfspareparts.com
- EPGC Sas FRANCE**
13, Rue des Forts - 59960 Neuville en Ferrain
Tel. +33 (0)3 20 25 06 21 - Fax +33 (0)3 20 25 34 12
www.epgc.com - epgc@epgc.com
- LF GmbH GERMANY**
Junkersstrasse, 3 - D-82178 Puchheim - München
Tel. +49 89 89 45 78 66 - Fax +49 89 89 45 78 88
www.lfersatzteile724.de - info@lfersatzteile.de
- LF China REPUBLIC OF CHINA**
Room 403, No.2, Huadu Mansion, Lane 422, Huanghua Rd.
Minhang Dist. - 201103 Shanghai
Tel. +86 (0)21 33 53 66 31 - Fax +86 (0)21 33 53 66 32
www.lfspareparts724.com - china@lfspareparts.com
- OOO LF RUSSIAN FEDERATION**
Ul. Anatoliya Zhivova, 8 - office 1 - 123100 Moscow
Tel./Fax +7 495 725 26 53
www.lfspareparts724.ru - info@lfspareparts.ru
- LF Repuestos Horeca S.L.U. SPAIN**
Poligono Industrial Carpetania - C/Miguel Faraday, 8 - 28906 Getafe
Tel. +34 91 477 91 00 - Fax +34 91 477 90 81
www.lfrepuestos-horeca724.es - info@lfrepuestos.es
- LF Scandinavia Aps - LF Spareparts S.p.A. DENMARK**
Nupark, 51 - 7500 Holstebro
Tel. +45 70 70 77 33
www.lfspareparts724.dk - denmark@lfspareparts.dk
- LF SpA Cesena (IT) Swiss Branch Steinhausen SWITZERLAND**
Sennweidstrasse, 45 - CH-6312 Steinhausen
Tel. +41 (0)41 760 15 80/1 - Fax +41 (0)41 760 15 85
www.lfersatzteile724.ch - info@lfersatzteile.ch
- LF Spare Parts Ltd. UNITED KINGDOM**
A10a Lakeside Business Park, Broadway Lane
South Cerney, Gloucestershire GL7 5XL
Tel. +44 (0)1285 86 16 25 - Fax +44 (0)1285 86 39 49
www.lfspareparts724.co.uk - info@lfspareparts.co.uk
- LF Central Est Europe S.r.o. CZECH REPUBLIC**
Antala Staska 1859/34
14000 Praha 4 - KRC
Tel. +420 730 156 910
www.lfspareparts724.cz - info@lfspareparts.cz
- LF SPARE PARTS INC. USA**
Legal address:
155 Office Plaza Dr - Suite A - Tallahassee, FL 32301
Business/Mailing address:
1100 South Tower, 225 Peachtree St., N.E. - Atlanta, GA 30303, USA
Tel. +1-404-525-2600 - Fax +1-404-586-3528
www.lfspareparts724.us - info@lfspareparts.us
Tel. West Coast and Midwest: 206-349-1525 Sauro
Tel. East Coast and the Caribbean: 786-817-1764 Luis
-
- AUSTRALIA AND NEW ZEALAND**
www.lfspareparts724.com
andrea.calvio@lfspareparts.com
- AUSTRIA**
www.lfersatzteile724.at
info@lfersatzteile.at
- BALKAN COUNTRIES**
www.lfspareparts724.com
matija.ramov@lfspareparts.com
- BALTIC COUNTRIES**
www.lfspareparts724.com
inara.silina@lfspareparts.com
- LATIN AMERICA AND THE CARRIBEANS**
www.lfrepuestos-horeca724.es
export@lfrepuestos.es
- POLAND**
www.lfspareparts724.pl
info@lfspareparts.pl
- SOUTH KOREA**
www.lfspareparts724.com
fabio.doni@lfspareparts.com
- TURKEY**
www.lfyedekparca724.com
export@lfspareparts.com