



Spare parts for the professional sector:  
**Cooking equipment**



Suitable for:

**THIRODE**



This catalogue is automatically generated.  
Therefore, the sequence of the items might  
not be always shown at best.  
Updates will be issued in case of additions  
and/or amendments.

*Suitable **universal spare parts** may not be included*





Suitable for:

# THIRODE



Suitable for:

## Axial motor fans

**3240501 AXIAL FAN SUNON 120x120x38 mm**  
ball bearings  
230V 50/60Hz 22W 2850rpm  
DP200A 2123XBT.GN



THIRODE 304194

THIRODE 906107

**3805037 CABLE FOR AXIAL MOTOR FAN**  
cable length 2000 mm



## Bulb sheathes

**3394326 THERMOSTAT SHEATH  $\varnothing$  1/4"**  
complete with fixing nut and washer  
bulb length 85 mm



THIRODE 901019

## Burners, flame spreaders and accessories

**3025595 BURNER  $\varnothing$  83 mm**



THIRODE

**3025802 BURNER ASSEMBLY**  
4000-5500 kcal/h  
height 160 mm -  $\varnothing$  130 mm



THIRODE 322390

**3025797 BURNER ASSEMBLY MOUNTING DISTANCE 110 mm**  
with vertical flame  
4000-7000 Kcal/h  
height 90 mm -  $\varnothing$  80 mm - pipe  $\varnothing$  27 mm



THIRODE 308404

**3025595 BURNER  $\varnothing$  83 mm**



THIRODE



Suitable for:

**3025596 FLAME SPREADER  $\varnothing$  80 mm**



THIRODE 303001

**3500185 GAS JET CONICAL M17x1  $\varnothing$  1.20 mm**



# THIRODE

Suitable for:

**3025679 GAS BURNER SUPPORT GR5  $\varnothing$  27 mm**



**3500193 GAS JET CONICAL M17x1  $\varnothing$  2.00 mm**



**3025756 BURNER ASSEMBLY MOUNTING DISTANCE 165 mm**  
with vertical flame  
4000-7000 Kcal/h  
height 90 mm -  $\varnothing$  80 mm - pipe  $\varnothing$  27 mm



**3025595 BURNER  $\varnothing$  83 mm**



THIRODE

**3025596 FLAME SPREADER  $\varnothing$  80 mm**



THIRODE

**3025679 GAS BURNER SUPPORT GR5  $\varnothing$  27 mm**



THIRODE 303001

**3500185 GAS JET CONICAL M17x1  $\varnothing$  1.20 mm**



**3500193 GAS JET CONICAL M17x1  $\varnothing$  2.00 mm**



**3025656 FLAME SPREADER  $\varnothing$  100 mm**



**3025658 FLAME SPREADER  $\varnothing$  110 mm**



THIRODE 311039

THIRODE 130625

THIRODE 141952



Suitable for:

# THIRODE



**3025635 FLAME SPREADER ø 76 mm**

Suitable for:

**3025596 FLAME SPREADER ø 80 mm**




THIRODE 311038

THIRODE 303001

## Buzzers

**3397302 ALARM BELL 220V**



THIRODE 305106

## Cables for piezo igniters

**3001002 IGNITION LEAD 1000 mm**  
with faston 6.35x0.8 mm for ignition  
with faston ø 4 mm for ignition plug

**3001016 IGNITION LEAD 1000 mm**  
with faston ø 2.4 mm for ignition  
with faston ø 4 mm for electrode



THIRODE

THIRODE 307997

## Castors, rollers and accessories

**3738001 SWIVELLING WHEEL**  
with STAINLESS STEEL supports  
polypropylene nucleus - TPE ring  
dimension ø 125x30 mm - load capacity 100 Kg  
pin hole ø 13 mm



THIRODE 983080



## Clamps

**3449402 DOUBLE-WIRE CLAMP 7.8-8.3 - 100 PCS**  
for hoses  $\varnothing$  7.8÷8.3 mm



THIRODE 2001114H

**3449452 HOSE CLAMP 16-25**  
for pipes  $\varnothing$  16÷25 mm  
made of stainless steel AISI 304  
height 9 mm and screw E7  
suitable for food industry



THIRODE 15181K

**3449464 HOSE CLAMP 20-32**  
for pipes  $\varnothing$  20÷32 mm  
made of stainless steel AISI 304  
height 9 mm and screw E7  
suitable for food industry



THIRODE 917110

**3449472 HOSE CLAMP 40-60**  
for pipes  $\varnothing$  40÷60 mm  
made of stainless steel AISI 304  
height 12 mm and screw E7  
suitable for food industry



THIRODE 2001113H

THIRODE 2002537H

## Contact thermostats


**3444609 CONTACT THERMOSTAT KSD301-R 95°C**  
manual reset - 10A 250V



THIRODE 2001681H

THIRODE 2001855H

**3444607 CONTACT THERMOSTAT 110°C**  
with manual reset



THIRODE 2001685H

**3443081 CONTACT THERMOSTAT 125°C M4**



THIRODE 2001682H

**3444341 CONTACT THERMOSTAT 215°C 16A 250V**  
with manual reset - pin M4



THIRODE 2001683H

**5039001 CONTACT THERMOSTAT 50°C**  
with automatic reset



THIRODE 301045

**3443076 CONTACT THERMOSTAT 60°C**  
with automatic reset  
connection M4



THIRODE 301065



Suitable for:

**3444608 CONTACT THERMOSTAT 60°C**  
automatic reset - for wash tank



THIRODE 2001680H

# THIRODE



Suitable for:

**3444606 CONTACT THERMOSTAT 80°C**  
safety thermostat - for boiler



THIRODE 2001684H


## Contactors

**3454060 CONTACTOR SCHNEIDER LC1D09B7**  
9A 400V 4Kw - coil 24V 50/60Hz  
3 normally open contacts  
1 normally open auxiliary contact  
1 normally closed auxiliary contact



THIRODE 1700468

**3454015 CONTACTOR SCHNEIDER LC1D18P7**  
18A 400V 7.5Kw - coil 230V 50/60Hz  
3 normally open contacts  
1 normally open auxiliary contact  
1 normally closed auxiliary contact



THIRODE 1700732

THIRODE 300698

**3454066 CONTACTOR SCHNEIDER LC1D25P7**  
25A 400V 11Kw - coil 230V 50/60Hz  
3 normally open contacts  
1 normally open auxiliary contact  
1 normally closed auxiliary contact



THIRODE 300697  
THIRODE 5875E  
THIRODE 905241  
THIRODE 910566

THIRODE 300699  
THIRODE 900130  
THIRODE 905686

THIRODE 300760  
THIRODE 905239  
THIRODE 906759

**3351049 CONTACTOR SIEMENS 3RT2016-1AP01**  
9A 400V 4Kw - coil 230V 50/60Hz  
3 normally open contacts  
1 normally open auxiliary contact



THIRODE 2001923H

**3454072 CONTACTOR SIEMENS 3RT2017-1AB01**  
12A 400V 5.5Kw - coil 24V 50/60Hz  
3 contacts NO  
1 NO auxiliary contact



THIRODE 2001138H

THIRODE 2001140H

THIRODE 5875E



## Drain taps and accessories

- 3356116 DRAIN TAP  $\varnothing$  1"1/2F**  
fixed connection  $\varnothing$  1"1/2"F - folding handle  
for Boiling pan (THIRODE)



THIRODE 313001

- 1180001 GREASE KLUBERSYNTH UH1 14-151 45 g**  
food safe grease for lubrication  
of all friction points  
ideal for water and steam taps  
operating temperature  $-45^{\circ}/+120^{\circ}$   
beige color - NSF H1 certified  
hot and cold water resistant  
high anti-corrosion power  
can replace vaseline



- 3180039 VASELINE WUERTH 750 g**  
for lubrication of food processing machines  
it protects chromed and rubber parts from  
weather factors, moisture resistant,  
operating temperature from  $-10^{\circ}\text{C}$  up to  $+120^{\circ}\text{C}$   
from  $+50^{\circ}\text{C}$  to  $+120^{\circ}\text{C}$  the grease becomes oily



- 3356149 DRAIN TAP  $\varnothing$  2" F TECNO**  
BRASS CAP - with swivel nut  $\varnothing$  2" F



THIRODE 904916

- 3179010 FITTINGS SEALING TAPE LOCTITE 55 - 50 m**  
length 50 mt  
suitable to hot and cold drinking water, gas  
replaces pastes, hemp and sealing tapes  
it allows the repositioning of couplings  
in compliance with the latest regulations  
Drinking water (Italian certification by C.S.A.,  
according to standard KTW and WRC approved)  
gas - water IMQ-UNICIG.  
compliant with UNI EN 51-2 class Arp  
approved by DVGW and DIN 30660



- 3180061 TAPE F. COUPLING SEALING LOCTITE 55-150m**  
length 150 metri  
suitable for hot / cold drinking water. gas  
replaces pastes, hemp and sealing tapes  
it allows the correct replacement of fittings  
compliant with the latest regulatory requirements  
Drinking water (C.S.A. italian certified.  
in line with KTW standard and WRC approved )  
IMQ-UNICIG gas-water,  
compliant with UNI EN 51-2 class Arp  
DVGW and DIN 30660 approved



- 3186242 ASBESTOS FREE FLAT GASKET  $\varnothing$  61x46x2 mm**  
for drain tap  $\varnothing$  2" old model





Suitable for:

**3356101 CAP FOR DRAIN TAP**  
for DRAIN TAP  $\varnothing$  2" OLD MODEL



**3242190 DRAIN TAP HANDGRIP**  
for DRAIN TAP  $\varnothing$  2" OLD MODEL  
AND FOR TECNO NEW MODEL



**3179010 FITTINGS SEALING TAPE LOCTITE 55 - 50 m**  
length 50 mt  
suitable to hot and cold drinking water, gas  
replaces pastes, hemp and sealing tapes  
it allows the repositioning of couplings  
in compliance with the latest regulations  
Drinking water (Italian certification by C.S.A.,  
according to standard KTW and WRC approved)  
gas - water IMQ-UNICIG.  
compliant with UNI EN 51-2 class Arp  
approved by DVGW and DIN 30660



**1180001 GREASE KLUBERSYNTH UH1 14-151 45 g**  
food safe grease for lubrication  
of all friction points  
ideal for water and steam taps  
operating temperature  $-45^{\circ}/+120^{\circ}$   
beige color - NSF H1 certified  
hot and cold water resistant  
high anti-corrosion power  
can replace vaseline



## THIRODE

Suitable for:

**3356016 DRAIN NIPPLE  $\varnothing$  2"x80 mm**  
in brass



**3356012 ESCUTCHEON FOR DRAIN TAP  $\varnothing$  2"**



**5015573 GASKET FLAT ASBE. FREE  $\varnothing$  61x48x2 mm**  
for drain tap  $\varnothing$  2"



**3186241 O-RING 06212 VITON**  
ring thickness 5.34 mm - internal  $\varnothing$  53.34 mm  
for DRAIN TAP  $\varnothing$  2" OLD MODEL AND  
TECNO NEW MODEL







Suitable for:

**3356128 PIN  $\varnothing$  5x30 mm**  
complete with blind nut



**3180039 VASELINE WUERTH 750 g**  
for lubrication of food processing machines  
it protects chromed and rubber parts from  
weather factors, moisture resistant,  
operating temperature from  $-10^{\circ}\text{C}$  up to  $+120^{\circ}\text{C}$   
from  $+50^{\circ}\text{C}$  to  $+120^{\circ}\text{C}$  the grease becomes oily



# THIRODE




Suitable for:

**3180061 TAPE F. COUPLING SEALING LOCTITE 55-150m**  
length 150 metri  
suitable for hot / cold drinking water. gas  
replaces pastes, hemp and sealing tapes  
it allows the correct replacement of fittings  
compliant with the latest regulatory requirements  
Drinking water (C.S.A. italian certified.  
in line with KTW standard and WRC approved )  
IMQ-UNICIG gas-water,  
compliant with UNI EN 51-2 class Arp  
DVGW and DIN 30660 approved




## Electric hot plates

**3311096 ELECTRIC HOT PLATE  $\varnothing$  180 mm 2000W 230V**  
terminal block electric connections  
with STAINLESS steel edge 8 mm  
for electric cooking top



THIRODE 905304

**3311097 ELECTRIC HOT PLATE  $\varnothing$  180 mm 2000W 400V**  
terminal block electric connections  
with STAINLESS steel edge  
for electric cooking top



THIRODE 905303

**3311100 ELECTRIC HOT PLATE  $\varnothing$  220 mm 2600W 230V**  
terminal block electric connections  
with STAINLESS steel edge  
for electric cooking top



THIRODE 303003

THIRODE 7450384

**3311101 ELECTRIC HOT PLATE  $\varnothing$  220 mm 2600W 400V**  
terminal block electric connections  
with STAINLESS steel edge  
for electric cooking top



THIRODE 303004

THIRODE 7450385



Suitable for:

# THIRODE



## 3311089 ELECTRIC HOT PLATE ø 300 mm 3500W 230V

screw electric connections  
with STAINLESS steel edge  
for electric cooking top




THIRODE 303009

Suitable for:

## 3311078 ELECTRIC HOT PLATE ø 300 mm 3500W 400V

terminal block electric connections  
with STAINLESS steel edge  
for electric cooking top  
for Hot plate (THIRODE) B10.PEC500 125020



THIRODE 303008

THIRODE 7450387

## 3311070 ELECTRIC HOT PLATE 2500W 230V

dimensions 300x300 mm  
tilting plate  
electric screw couplings  
for electric cooking top



THIRODE 7450075

## 3311173 ELECTRIC HOT PLATE 2500W 400V

dimensions 300x300 mm  
overturning plate  
screw electric connections  
for electrical cooking top



THIRODE 7450080

## 3311054 ELECTRIC HOT PLATE 2600W 400V

dimensions 220x220 mm  
terminal block electric connections  
with STAINLESS steel edge  
for electric cooking top



THIRODE 303002

## 3311062 ELECTRIC HOT PLATE 3000W 230V

dimensions 300x300 mm  
terminal block electric connections  
with STAINLESS steel edge  
for electric cooking top



THIRODE 904877

## 3311063 ELECTRIC HOT PLATE 3000W 400V

dimensions 300x300 mm  
terminal block electric connections  
with STAINLESS steel edge  
for electric cooking top



THIRODE 303561

## 3311064 ELECTRIC HOT PLATE 4000W 230V

dimensions 300x300 mm  
terminal block electric connections  
with STAINLESS steel edge  
for electric cooking top



THIRODE 904879



Suitable for:

Suitable for:

**3311065 ELECTRIC HOT PLATE 4000W 400V**  
 dimensions 300x300 mm  
 terminal block electric connections  
 with STAINLESS steel edge  
 for electric cooking top



THIRODE 303562

## Electrical cables

**3050096 NICKEL-PLATED CABLE 1.5 mm<sup>2</sup> BLACK - 5m**  
 temperature -60°+400°C  
 for 10 m coils see 3050139  
 for 100 m coils see 3050601



THIRODE 306447

**3050097 NICKEL-PLATED CABLE 2.5 mm<sup>2</sup> BLACK - 5m**  
 temperature -60°+400°C  
 for 10 m coils see 3050140  
 for 100 m coils see 3050602



THIRODE 306431

**3050098 NICKEL-PLATED CABLE 4 mm<sup>2</sup> BLACK - 5 m**  
 temperature -60°+400°C  
 for 10 m coils see 3050071  
 for 100 m coils see 3050603



THIRODE 306435

**3050099 NICKEL-PLATED CABLE 6 mm<sup>2</sup> BLACK - 5 m**  
 temperature -60°+400°C  
 for 10 m coils see 3050074  
 for 100 m coils see 3050604



THIRODE 306437

## Electrical capacitors

**3068016 CAPACITOR DUCATI ENERGIA 10µF**  
 450V 50/60Hz  
 operating temperature -25 +85°C  
 lead connector 6.35x0.8 mm  
 ø 36xh58 mm



THIRODE 5843E

THIRODE 904191

**3068024 CAPACITOR DUCATI ENERGIA 16µF**  
 450V 50/60Hz  
 operating temperature -25 +85°C  
 lead connector 6.35x0.8 mm  
 ø 36xh70 mm



THIRODE 2001118H

THIRODE 2002168H

THIRODE 304259



Suitable for:

# THIRODE



**3068027 CAPACITOR DUCATI ENERGIA 20µF**  
 450V 50/60Hz  
 operating temperature -25 +85°C  
 lead connector 6.35x0.8 mm  
 ø 40xh70 mm



THIRODE 2001119H

THIRODE 2002417H

Suitable for:

**3068008 CAPACITOR DUCATI ENERGIA 5µF**  
 450V 50/60Hz  
 operating temperature -25 +85°C  
 lead connection 6.35x0.8 mm  
 ø 28xh55 mm



THIRODE 2000001

THIRODE 2001120H

**3068010 CAPACITOR DUCATI ENERGIA 6,3µF**  
 450V 50/60Hz  
 operating temperature -25 +85°C  
 lead connection 6.35x0.8 mm  
 ø 32xh55 mm



THIRODE 2000059

THIRODE 2001121H

**3068014 CAPACITOR DUCATI ENERGIA 8µF**  
 450V 50/60Hz  
 operating temperature -25 +85°C  
 lead connection 6.35x0.8 mm  
 ø 32xh55 mm



THIRODE 3709E

**3068080 CAPACITOR ELECTRICAL 10µF**  
 450V 50/60Hz - ø 30xh71 mm



THIRODE 5843E

THIRODE 904191

**3068083 CAPACITOR ELECTRICAL 16µF**  
 450V 50/60Hz - ø 35xh71 mm



THIRODE 2001118H

THIRODE 2002168H

THIRODE 304259

**3068084 CAPACITOR ELECTRICAL 20µF**  
 450V 50/60Hz - ø 40xh71 mm



THIRODE 2001119H

THIRODE 2002417H

**3068096 CAPACITOR ELECTRICAL 5µF**  
 450V 50/60Hz - ø 30xh51 mm



THIRODE 2000001

THIRODE 2001120H

**3068097 CAPACITOR ELECTRICAL 6.3µF**  
 450V 50/60Hz - ø 30xh51 mm



THIRODE 2000059

THIRODE 2001121H

**3068079 CAPACITOR ELECTRICAL 8µF**  
 450V 50/60Hz - ø 30xh71 mm



THIRODE 3709E



## Electrical gas valves and accessories

**3526098 COIL 220V**  
for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA



THIRODE 2020037

**3523073 GAS VALVE UNITROL U7000ER-240-S7CL/S**  
inlet  $\varnothing$  3/4" F - outlet  $\varnothing$  3/4" F  
thermocouple connection 11/32"  
NATURAL GAS pressure switch 6.7" W.C.  
power supply 220/240Vac 50/60Hz



THIRODE 7473017

**3526236 COIL 240V**  
with pressure regulator - for NATURAL GAS  
for GAS VALVE UNITROL 7000



**3523080 COIL 24V**  
for LPG GAS  
for GAS VALVE UNITROL 7000



**3241707 GREY KNOB  $\varnothing$  30 mm ON-OFF-PILOT**  
for USA MARKET



**3241929 GREY KNOB  $\varnothing$  30 mm SILK-SCREEN PRINTED**  
for EUROPEAN MARKET



**3526235 LPG BLIND PLATE**  
for GAS VALVE UNITROL 7000



**3120360 MAGNETIC UNIT UNITROL**  
head  $\varnothing$  23 mm - length 59 mm  
thermocouple connection 11/32"  
for GAS VALVE UNITROL 7000 BMSER/BMSGOR




**3526238 PRESSURE REGULATOR FOR GAS VALVE**  
for NATURAL GAS 3.5" W.C.  
for GAS VALVE UNITROL 7000





Suitable for:

**3526287 PRESSURE REGULATOR FOR GAS VALVE**  
for NATURAL GAS 6.7"W.C.  
for VALVOLA GAS UNITROL 7000



# THIRODE

Suitable for:

**3440125 VALVE MICROSWITCH**  
length 300 mm  
for GAS VALVE UNITROL



**3523082 VALVE MICROSWITCH**  
length 415 mm  
for GAS VALVE UNITROL 7000 BER



**3526283 VALVE MICROSWITCH**  
length 450 mm  
for GAS VALVE UNITROL



THIRODE

**3523079 GAS VALVE UNITROL 7000BGO-S7B**  
inlet  $\varnothing$  3/4"F - outlet  $\varnothing$  3/4"F  
thermocouple connection 11/32"  
without pressure regulator



**3241707 GREY KNOB  $\varnothing$  30 mm ON-OFF-PILOT**  
for USA MARKET



THIRODE 7473020

**3241929 GREY KNOB  $\varnothing$  30 mm SILK-SCREEN PRINTED**  
for EUROPEAN MARKET



**3526235 LPG BLIND PLATE**  
for GAS VALVE UNITROL 7000



**3120360 MAGNETIC UNIT UNITROL**  
head  $\varnothing$  23 mm - length 59 mm  
thermocouple connection 11/32"  
for GAS VALVE UNITROL 7000 BMSER/BMSGOR



**3440160 THERMOPILE  $\varnothing$  10x54 mm**  
cable length 900 mm  
for GAS VALVE UNITROL 7000





Suitable for:

**3440125 VALVE MICROSWITCH**  
length 300 mm  
for GAS VALVE UNITROL



## THIRODE

Suitable for:

**3523082 VALVE MICROSWITCH**  
length 415 mm  
for GAS VALVE UNITROL 7000 BER



**3526283 VALVE MICROSWITCH**  
length 450 mm  
for GAS VALVE UNITROL



THIRODE

**3523082 VALVE MICROSWITCH**  
length 415 mm  
for GAS VALVE UNITROL 7000 BER



THIRODE

**3526090 VALVE 810 ELETROSIT  $\varnothing$  3/4"FF**  
inlet  $\varnothing$  3/4" F - outlet  $\varnothing$  3/4" F  
thermocouple connection M9x1  
maximum gas inlet pressure 50 mbar  
pressure adjustment range  
3 ÷ 18 mbar  
ambient temperature 0 ÷ 60°C  
power supply 230V 50Hz  
long buttons  
pilot connection and LATERAL thermocouple



**3526137 BUTTON FOR ELETROSIT VALVE 46 mm**



THIRODE 7472025

**3526100 COIL 220V**  
for VALVE ELETROSIT



**3526108 ELBOW FLANGE  $\varnothing$  1/2" F**  
with screws and OR  
for ELETROSIT VALVE





Suitable for:

**3526093 EXTENSION FOR ELETTROSIT BUTTON 34 mm**  
for switching on/off buttons



**3526107 FLANGE STRAIGHT  $\varnothing$  3/4" F**  
with screws and OR  
for ELETTROSIT VALVE



**3526136 SPRING FOR PUSH-BUTTON**



**3526176 VALVE 820 NOVA  $\varnothing$  1/2" FF**  
inlet  $\varnothing$  1/2" F - outlet  $\varnothing$  1/2" F  
thermocouple connection M9x1  
maximum gas inlet pressure 60 mbar  
outlet pressure adjustment range  
3÷30 mbar  
ambient temperature 0÷70°C  
power supply 230V 50Hz



THIRODE 1040532

**2100054 COIL 220V 60Hz**  
for VALVE 820 NOVA-822 NOVA-828 NOVA



# THIRODE



Suitable for:

**3526106 FLANGE STRAIGHT  $\varnothing$  1/2"**  
with screws and OR  
for ELETTROSIT VALVE



**3001008 PIEZO IGNITER**  
a  $\varnothing$  14 mm hole is required for the assembly  
faston M  $\varnothing$  2.4 mm



**3526096 VALVE MICROSWITCH**  
maximum load 0.2 A  
for VALVE ELETTROSIT-820 NOVA-824 NOVASIT



**3526098 COIL 220V**  
for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA



THIRODE 2020037

**3526099 COIL 24V**  
for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA







Suitable for:


**3526077 ELBOW FLANGE  $\varnothing$  1/2" F**  
with screws and OR  
for valves SIT 820-Honeywell V4400-V4600-VR4605P



**3526102 ELECTRIC COUPLING WITH CABLE**  
cable length 1000 mm - 3 wires  
for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA



**3020083 FITTING AND OLIVE  $\varnothing$  4 mm**



**3526075 FLANGE STRAIGHT  $\varnothing$  1/2"**  
with screws and OR  
for valves SIT 820-Honeywell V4400-V4600-VR4605P



**3526124 KNOB EXTENSION LENGTH 67 mm**  
for VALVE 820 NOVA-824 NOVASIT



**3348041 OLIVE FOR PIPE  $\varnothing$  16 mm**  
for model PEL 23



# THIRODE



Suitable for:


**3526078 ELBOW FLANGE  $\varnothing$  3/4" F**  
with screws and OR  
for valves SIT 820-Honeywell V4400-V4600-VR4605P



**5047586 EXTENSION FOR VALVE 820 NOVA**  
D-shaped pin  $\varnothing$  10x8 mm



**3020084 FITTING AND OLIVE  $\varnothing$  6 mm**




THIRODE 317104

**3526076 FLANGE STRAIGHT  $\varnothing$  3/4"**  
with screws and OR  
for valves SIT 820-Honeywell V4400-V4600-VR4605P



**3182008 MAGNETIC UNIT SIT**  
head  $\varnothing$  35 mm - end piece  $\varnothing$  20 mm - length 47 mm  
for valve SIT NOVASIT 820



**3348036 OLIVE FOR PIPE  $\varnothing$  4 mm**  
for model PEL 21-22-24-25






Suitable for:

**3001008 PIEZO IGNITER**


a  $\varnothing$  14 mm hole is required for the assembly  
faston M  $\varnothing$  2.4 mm



**3020077 PIPE FITTING  $\varnothing$  4 mm**  
thread M10x1



**5053766 PROTECTION RUBBER VALVE 820 NOVA**  
 $\varnothing$  external 46 mm -  $\varnothing$  internal 20 mm  
depth 5,5 mm



**3526096 VALVE MICROSWITCH**  
maximum load 0.2 A  
for VALVE ELETTROSIT-820 NOVA-824 NOVASIT



**3526141 VALVE 830 TANDEM  $\varnothing$  1/2"FF**  
inlet  $\varnothing$  1/2" F - outlet  $\varnothing$  1/2" F  
thermocouple fitting M10x1  
maximum gas inlet pressure 60 mbar  
outlet gas pressure setting range 3÷50 mbar  
room temperature 0÷60°C  
power supply 230V 50Hz



# THIRODE

Suitable for:

**3348034 PIPE FITTING  $\varnothing$  16 mm**  
thread M24x1.5  
for model PEL 23



**3526103 PROTECTING COVER**  
for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA



**5012595 VALVE EXTENSION 820 NOVA**  
D-shaped pin  $\varnothing$  6x4.6 mm



**2100724 COIL 24V**  
for valve 830 TANDEM-836 TANDEM





Suitable for:


**2100757 CONNECTION FOR OLIVE  $\varnothing$  16 mm**  
thread  $\varnothing$  1/2" M



**3526292 ELECTRIC COUPLING WITH CABLE**  
cable length 1000 mm - 3 wires  
for sit valve 830-836 TANDEM



**3020084 FITTING AND OLIVE  $\varnothing$  6 mm**



THIRODE 317104


## THIRODE

Suitable for:

**3526142 DOUBLE COIL FOR VALVE**  
220V 50Hz  
for VALVE 830 TANDEM-836 TANDEM



**3020083 FITTING AND OLIVE  $\varnothing$  4 mm**




**3348041 OLIVE FOR PIPE  $\varnothing$  16 mm**  
for model PEL 23



## Electronic boards

**7104261 CIRCUIT BOARD LEVEL 90x77 mm**



THIRODE 170975

THIRODE 309588

**3390340 REGULATING ELECTRONIC BOARD 110x85 mm**  
for Fryer gas (THIRODE) FR25G  
for Fryer (THIRODE) FR18 B906.FR18.E4 128210



THIRODE 170743

**3390341 POTENTIOMETER COMPLETE WITH CABLE**  
with cable length 640 mm  
D-shaped pin  $\varnothing$  6x4.6 mm  
for Fryer gas (THIRODE) FR25G



THIRODE 170744





Suitable for:

# THIRODE



Suitable for:

## Electronic boxes

**3091040 CONTROL BOX 503 EFD FOR TANDEM**  
model SIT - 220/240V 50/60Hz 7VA



THIRODE 310197

## Electronic controllers

**3445081 THERMOSTAT EVK411 PTC**  
power supply 12-24Vac/dc  
thermostat setting range -50+150°C  
ON-OFF control with one actuation point only  
1 changeover relay output 8(3)A 250V  
PTC type probe (not included)  
room temperature 0+55°C  
buzzer included  
access to configuration parameters through  
password-serial port for data exchange  
connections by screw terminal block  
front dimensions 74x32x65 mm  
mounting hole 71x29 mm



THIRODE 2504048

**3445070 PTC PVC PROBE 1500 mm**  
2-wire probe temperature range -30+80°C  
bulb ø 6x40 mm



**3445107 PTC PVC PROBE 3000 mm**  
2-wire probe temperature range -30+80°C  
bulb ø 6x40 mm



**3445183 SILICONE PTC PROBE 3000 mm**  
2-wire probe temperature range -55+150°C  
bulb ø 6x40 mm



**3445959 SILICONE PTC PROBE 5000 mm**  
temperature range -55+150°C  
bulb ø 6x40 mm



**3445110 TRANSFORMER 230V/12V 3VA**  
primary tension 230Vca 50/60Hz  
secondary tension 12Vca 3VA  
room temperature 0+60°C  
screw terminal block  
IMQ approved



THIRODE 2504043



Suitable for:

**3445111 TRANSFORMER 24V/12V 3VA**  
 primary tension 24Vca 50/60Hz  
 secondary tension 12Vca 3VA  
 room temperature 0÷60°C  
 screw terminal block  
 IMQ approved



# THIRODE

Suitable for:



**3445076 THERMOSTAT EVK411 PTC/NTC/PT100/PT1000**  
 power supply 12Vca/dc 1.5VA  
 thermostat setting range 99+600°C  
 ON-OFF control with one actuation point  
 1 exchange relay output 6(3)A 250V  
 inbuilt alarm buzzer  
 access to configuration parameters through password  
 serial port for data exchange  
 room temperature 0+60°C  
 PTC/NTC/PT100/PT1000 type probe (not included)  
 connections by screwed terminal block  
 front dimensions 74x32x65 mm  
 mounting hole 71x29 mm



THIRODE S225P20

THIRODE 651225

**3445156 PROBE NTC PVC 3000 mm**  
 temperature range -30+80°C  
 bulb ø 6x40 mm



**3445157 PROBE NTC PVC 1500 mm**  
 probe 2 wires - temperature range -30°+80°C  
 bulb ø 6x40 mm



**3445028 PROBE NTC PVC 4000 mm**  
 temperature field -30+80°C  
 bulb ø 6x20 mm



**3445167 PROBE NTC TPE IP68 1500 mm**  
 temperature range -50+110°C  
 bulb ø 5x20 mm watertight



**3445335 PROBE NTC TPE IP68 3000 mm**  
 temperature range -50+110°C  
 bulb ø 5x20 mm watertight





Suitable for:

**3445184 PROBE NTC TPE STEEL IP68 1500 mm**  
temperature range -40+110°C  
bulb ø 6x40 mm watertight



# THIRODE



Suitable for:

**3445154 PROBE NTC TPE STEEL IP68 3000 mm**  
temperature range -40+110°C  
bulb ø 6x40 mm watertight



**3445117 PROBE PT100 VETROTEX 3000 mm**  
3-wire probe temperature range 0+350°C  
bulb ø 6x100 mm



**3445379 PROBE PT1000 IP68 1500 mm**  
temperature range -50+110°C  
bulb ø 6x20 mm watertight



**3445380 PROBE PT1000 IP68 3000 mm**  
temperature range -50+110°C  
bulb ø 6x20 mm watertight



**3445070 PTC PVC PROBE 1500 mm**  
2-wire probe temperature range -30+80°C  
bulb ø 6x40 mm



**3445107 PTC PVC PROBE 3000 mm**  
2-wire probe temperature range -30+80°C  
bulb ø 6x40 mm



**3445913 SILICONE PROBE NTC 1500 mm**  
temperature range -50+110°C  
bulb ø 6x40 mm



**3445155 SILICONE PROBE NTC 3000 mm**  
temperature range -50+110°C  
bulb ø 6x40 mm



THIRODE S184P20

THIRODE 651184

**3445183 SILICONE PTC PROBE 3000 mm**  
2-wire probe temperature range -55+150°C  
bulb ø 6x40 mm





Suitable for:

**3445959 SILICONE PTC PROBE 5000 mm**  
temperature range -55+150°C  
bulb ø 6x40 mm



THIRODE 25040403

**3445111 TRANSFORMER 24V/12V 3VA**  
primary tension 24Vca 50/60Hz  
secondary tension 12Vca 3VA  
room temperature 0±60°C  
screw terminal block  
IMQ approved



# THIRODE




Suitable for:

**3445110 TRANSFORMER 230V/12V 3VA**  
primary tension 230Vca 50/60Hz  
secondary tension 12Vca 3VA  
room temperature 0+60°C  
screw terminal block  
IMQ approved



## Energy regulators

**3350026 ENERGY REGULATOR**  
contact capacity 230V 13A - max temperature 125°C  
D-shaped pin ø 6x4.6 mm  
double rotation direction  
for PYROCERAM. TOPS-SALAMANDERS-POTATO WARMERS  
for Boiling pan (THIRODE)  
for Bratt pan (THIRODE)  
for Grill (THIRODE)  
for Bratt pan (THIRODE) 125371




THIRODE 1800602

THIRODE 301200

THIRODE 72113E

**3350031 ENERGY REGULATOR**  
contact capacity 400V 7A  
max temperature 125°C  
D-shaped pin ø 6x4.6 mm  
for Boiling pan (THIRODE)  
for Bratt pan (THIRODE)



THIRODE 301201

**3350065 ENERGY REGULATOR**  
contact capacity 230V 12A  
D-shaped pin ø 6x4.6 mm



THIRODE 904982

**3350066 ENERGY REGULATOR**  
contact capacity 400V 7A  
D-shaped pin ø 6x4.6 mm



THIRODE 7492053




Suitable for:

# THIRODE



Suitable for:

**3350067 ENERGY REGULATOR**  
contact capacity 24V 16A  
D-shaped pin  $\varnothing$  6x4.6 mm



THIRODE 7492054

## Feet

**3313074 ADJUSTABLE PLASTIC FOOT  $\varnothing$  18 mm**  
for tubular 30x30 mm  
adjustable height 24÷56 mm  
max capacity 90 Kg



THIRODE 634147

**3313122 ADJUSTABLE PLASTIC FOOT  $\varnothing$  32 mm**  
for tubular  $\varnothing$  45 mm  
adjustable height 28÷78 mm



THIRODE 381165

**3313005 ADJUSTABLE S/STEEL FOOT  $\varnothing$  2" x h 135 mm**  
with fixed screw M12x40 mm  
adjustable height 135÷200 mm



THIRODE 2001489H

THIRODE 2001871H

## Filters

**3160462 WATER FILTER  $\varnothing$  1/2"FF**



THIRODE 91297387

## Fittings

**3349347 NICHEL-PL.HOSE-END FITTING  $\varnothing$  3/8" M  $\varnothing$  12**



THIRODE 27221





## Fryer baskets and accessories

**3055553 FRYER BASKET 400x240x150 mm**  
made of chrome-plated iron



THIRODE 325454

## Fuses

**3049041 QUICK ACTING FUSE  $\varnothing$  5x20 mm - 10 PCS**  
250V 315mA



THIRODE 309316

**3049045 QUICK ACTING FUSE  $\varnothing$  5x20 mm - 10 PCS**  
250V 800mA



THIRODE 2001921H

**3049052 QUICK ACTING FUSE  $\varnothing$  5x20 mm - 10 PCS**  
250V 4A



THIRODE 2001981H

THIRODE 2002146H

**3049034 QUICK ACTING FUSE  $\varnothing$  6.3x32 mm - 10 PCS**  
500V 10A



THIRODE 3090506


## Gas burners

**3023336 BURNER  $\varnothing$  50x490 mm**  
total length 555 mm  
stainless steel  
for Kitchen gas (THIRODE) B9FV800FG




THIRODE 141613

**3025806 NOZZLE HOLDER FOR BURNER 50x40 mm**  
for Kitchen gas (THIRODE) B9FV800FG



THIRODE 381335

**3025806 NOZZLE HOLDER FOR BURNER 50x40 mm**  
for Kitchen gas (THIRODE) B9FV800FG



THIRODE 381335



Suitable for:

# THIRODE



Suitable for:

## Gas taps and accessories

**5046716 BY-PASS SCREW  $\varnothing$  0.60 mm FOR MOD. 20/21**  
thread M5x0.5



THIRODE 310173

**3348150 GAS TAP COPRECI CAL5200**  
without pilot flame  
flange inlet fitting  $\varnothing$  21 mm  
outlet fitting  $\varnothing$  M16x1.25 mm  
thermocouple fitting M8x1  
pin length 26 mm  
for Kitchen (THIRODE) - Series 1000 - Series 750  
Series 900



**3182022 MAGNETIC GROUP PEL SMALL HEAD**  
head  $\varnothing$  15.5 mm - end piece  $\varnothing$  11.5 mm - length 44mm



THIRODE 310069

**3182011 MAGNETIC UNIT PEL SMALL HEAD**  
head  $\varnothing$  15 mm - end piece  $\varnothing$  11 mm - length 44 mm  
for PEL tap models 20-21  
for EGA tap model 25213  
for JUNKERS tap model CH110



**3186789 TAP GASKET  $\varnothing$  11x7x3 mm**




THIRODE 7473048

**3348136 GAS TAP STN3R**  
with pilot flame  
flange pipe connection  $\varnothing$  20 mm  
outlet fitting  $\varnothing$  1/2" F  
thermocouple connection M9x1  
pin length 25 mm  
square pin 7x7 mm



**3182019 MAGNETIC UNIT**  
head  $\varnothing$  19 mm - end piece  $\varnothing$  18 mm - length 50 mm  
for gas tap



THIRODE 7462038

THIRODE 310578

THIRODE 7462039



Suitable for:

**3348037 OLIVE FOR PIPE  $\varnothing$  6 mm**  
for model PEL 21-22-24-25



**5014757 PIPE FITTING  $\varnothing$  6 mm**  
thread M10x1 mm



# THIRODE

Suitable for:

**3020078 PIPE FITTING  $\varnothing$  6 mm**  
thread M10x1



**3348016 GAS TAP 21/S**  
with pilot flame  
fittings  $\varnothing$  M16x1.5mm  
with flow regulator  
thermocouple connection M9x1  
D-shaped pin  $\varnothing$  8x6.5 mm  
for Kitchen (THIRODE) B906.FV.CF.ALKP 128172




THIRODE 310139

**3348085 BUSH FOR TAP**




**3348220 CAP WITH PIN  $\varnothing$  6x4.6 mm**  
pin length 30/23 mm upper/lower  
for model PEL 21




**7102841 BODY FITTING TAP**  
 $\varnothing$  pipe 10 mm  
thread  $\varnothing$  3/8" F - M16x1 mm  
for taps PEL 20S-21S



**3348219 CAP WITH PIN  $\varnothing$  6x4.6 mm**  
pin length 45/20 mm upper/lower  
for model PEL 21



**3348221 CAP WITH PIN  $\varnothing$  6x4.6 mm**  
pin length 30/17,5 mm upper/lower  
for model PEL 21





Suitable for:

**3348021 CAP WITH PIN  $\varnothing$  8x6.5 mm**  
pin length 22 mm  
for model PEL 21S



**3348243 CAP WITH PIN  $\varnothing$  8x6.5 mm**  
pin length 22/15 mm right/lef  
for model PEL 21S



**3348058 MAGNET PROTECTION NUT M8x1**  
thread M18x1 mm  
for model PEL 20-21-22



**3182022 MAGNETIC GROUP PEL SMALL HEAD**  
head  $\varnothing$  15.5 mm - end piece  $\varnothing$  11.5 mm - length 44mm




**3348044 OLIVE FOR PIPE  $\varnothing$  10 mm**  
for model PEL 20-21-24-25



# THIRODE

Suitable for:

**3348238 CAP WITH PIN  $\varnothing$  8x6.5 mm**  
pin 35/15 mm upper/lower  
for model PEL 21S



**3348236 FLANGIA WITH PRESSURE FITTING  $\varnothing$  16/10 mm**  
thread M16x1,5 mm - M10x1,25 mm  
for model PEL 21S



**3348059 MAGNET PROTECTION NUT M9x1**  
thread M18x1mm  
for model PEL 20-21-22



**3182011 MAGNETIC UNIT PEL SMALL HEAD**  
head  $\varnothing$  15 mm - end piece  $\varnothing$  11 mm - length 44 mm  
for PEL tap models 20-21  
for EGA tap model 25213  
for JUNKERS tap model CH110



THIRODE 7473048

**3348036 OLIVE FOR PIPE  $\varnothing$  4 mm**  
for model PEL 21-22-24-25





Suitable for:

**3348037 OLIVE FOR PIPE  $\varnothing$  6 mm**  
for model PEL 21-22-24-25



**3348029 PIPE FITTING  $\varnothing$  4 mm**  
thread M10x1 mm  
for model PEL 21-22-24-25



**5014757 PIPE FITTING  $\varnothing$  6 mm**  
thread M10x1 mm




## THIRODE

Suitable for:


**3348043 PIPE FITTING  $\varnothing$  10 mm**  
thread M16x1.5 mm  
for model PEL 20-21-24-25



**3020078 PIPE FITTING  $\varnothing$  6 mm**  
thread M10x1



**3348010 GAS TAP 22N/O**  
with pilot flame  
with horizontal flange  
fittings  $\varnothing$  M20x1.5mm  
with flow regulator  
D-shaped pin  $\varnothing$  10x8 mm



THIRODE 904883


**3348017 CAP WITH PIN  $\varnothing$  10x8 mm**  
pin length 26 mm  
for model PEL 22



**3348229 CAP WITH PIN  $\varnothing$  10 mm**  
pin length 31 mm  
for model PEL 22S/O




**3348019 CAP WITH PIN  $\varnothing$  10x9 mm**  
pin length 26 mm  
for model PEL 22






Suitable for:

**3348231 CAP WITH PIN  $\varnothing$  6x4.6 mm**  
pin length 35/21 mm upper/lower  
for model PEL 22




**3348213 FLANGE  $\varnothing$  12/10 mm**  
without adjustment  
thread M20x1.5 mm  
for model PEL 22S



**3348025 FLANGE HORIZONTAL CONICAL  $\varnothing$  12/10 mm**  
thread M20x1.5  
for model PEL 22



**3348214 FLANGIA WITH PRESSURE FITTING  $\varnothing$  12/10 mm**  
thread M20x1.5 mm  
for model PEL 22S



**3348059 MAGNET PROTECTION NUT M9x1**  
thread M18x1mm  
for model PEL 20-21-22



# THIRODE

Suitable for:

**3348232 CAP WITH PIN  $\varnothing$  8x6.5 mm**  
pin length 39/7 mm upper/lower  
for model PEL 22



**3348023 FLANGE HORIZONTAL  $\varnothing$  12/10 mm**  
thread M20x1.5  
for model PEL 22



**3348024 FLANGE VERTICAL  $\varnothing$  12/10 mm**  
thread M20x1.5  
for model PEL 22



**3348058 MAGNET PROTECTION NUT M8x1**  
thread M18x1 mm  
for model PEL 20-21-22



**3182009 MAGNETIC UNIT PEL BIG HEAD**  
head  $\varnothing$  15.5 mm - end piece  $\varnothing$  14 mm - length 44 mm  
for PEL tap model 22-24



THIRODE 71001E





Suitable for:

**3182021 MAGNETIC UNIT PEL LARGE HEAD**  
head  $\varnothing$  15.5 mm - end piece  $\varnothing$  14 mm - length 44 mm




**3020082 OLIVE FOR PIPE  $\varnothing$  12 mm**  
for model PEL 22-24-25



**3348037 OLIVE FOR PIPE  $\varnothing$  6 mm**  
for model PEL 21-22-24-25



**3348031 PIPE FITTING  $\varnothing$  10 mm**  
thread M20x1.5 mm  
for model PEL 22-24-25



**3348029 PIPE FITTING  $\varnothing$  4 mm**  
thread M10x1 mm  
for model PEL 21-22-24-25



**5014757 PIPE FITTING  $\varnothing$  6 mm**  
thread M10x1 mm



# THIRODE

Suitable for:

**3348038 OLIVE FOR PIPE  $\varnothing$  10 mm**  
for model PEL 22-24-25



**3348036 OLIVE FOR PIPE  $\varnothing$  4 mm**  
for model PEL 21-22-24-25



**3348230 PIN FOT GAS TAP  $\varnothing$  6x4.6 mm**  
pin length 45/20 mm rh/lh  
for model PEL 22



**3348032 PIPE FITTING  $\varnothing$  12 mm**  
thread M20x1.5 mm  
for model PEL 22-24-25



**3020078 PIPE FITTING  $\varnothing$  6 mm**  
thread M10x1





Suitable for:

# THIRODE



Suitable for:

**3348002 GAS TAP 22S/O**  
 with pilot flame  
 with horizontal flange  
 fittings  $\varnothing$  M20x1.5mm  
 with flow regulator  
 thermocouple connection M9x1  
 D-shaped pin  $\varnothing$  10x8 mm  
 for Bratt pan (THIRODE) SA41.BM.FI.G 122901



**3348229 CAP WITH PIN  $\varnothing$  10 mm**  
 pin length 31 mm  
 for model PEL 22S/O



THIRODE 310140

THIRODE 904882


**3348017 CAP WITH PIN  $\varnothing$  10x8 mm**  
 pin length 26 mm  
 for model PEL 22



**3348245 CAP WITH PIN  $\varnothing$  10x8 mm**  
 pin length 34/26 mm upper/lower  
 for model PEL 22S



**3348019 CAP WITH PIN  $\varnothing$  10x9 mm**  
 pin length 26 mm  
 for model PEL 22



**3348231 CAP WITH PIN  $\varnothing$  6x4.6 mm**  
 pin length 35/21 mm upper/lower  
 for model PEL 22




**3348232 CAP WITH PIN  $\varnothing$  8x6.5 mm**  
 pin length 39/7 mm upper/lower  
 for model PEL 22



**3348213 FLANGE  $\varnothing$  12/10 mm**  
 without adjustment  
 thread M20x1.5 mm  
 for model PEL 22S



**3348023 FLANGE HORIZONTAL  $\varnothing$  12/10 mm**  
 thread M20x1.5  
 for model PEL 22



**3348025 FLANGE HORIZONTAL CONICAL  $\varnothing$  12/10 mm**  
 thread M20x1.5  
 for model PEL 22








Suitable for:

**3348024** FLANGE VERTICAL  $\varnothing$  12/10 mm  
thread M20x1.5  
for model PEL 22



**3348058** MAGNET PROTECTION NUT M8x1  
thread M18x1 mm  
for model PEL 20-21-22



**3182009** MAGNETIC UNIT PEL BIG HEAD  
head  $\varnothing$  15.5 mm - end piece  $\varnothing$  14 mm - length 44 mm  
for PEL tap model 22-24



THIRODE 71001E

**3348038** OLIVE FOR PIPE  $\varnothing$  10 mm  
for model PEL 22-24-25



**3348036** OLIVE FOR PIPE  $\varnothing$  4 mm  
for model PEL 21-22-24-25



**3348230** PIN FOT GAS TAP  $\varnothing$  6x4.6 mm  
pin length 45/20 mm rh/lh  
for model PEL 22



## THIRODE

Suitable for:

**3348214** FLANGIA WITH PRESSURE FITTING  $\varnothing$  12/10 mm  
thread M20x1.5 mm  
for model PEL 22S



**3348059** MAGNET PROTECTION NUT M9x1  
thread M18x1mm  
for model PEL 20-21-22



**3182021** MAGNETIC UNIT PEL LARGE HEAD  
head  $\varnothing$  15.5 mm - end piece  $\varnothing$  14 mm - length 44 mm




**3020082** OLIVE FOR PIPE  $\varnothing$  12 mm  
for model PEL 22-24-25



**3348037** OLIVE FOR PIPE  $\varnothing$  6 mm  
for model PEL 21-22-24-25



**3348031** PIPE FITTING  $\varnothing$  10 mm  
thread M20x1.5 mm  
for model PEL 22-24-25





Suitable for:

**3348032** PIPE FITTING  $\varnothing$  12 mm  
thread M20x1.5 mm  
for model PEL 22-24-25



**3020078** PIPE FITTING  $\varnothing$  6 mm  
thread M10x1



**3348233** GAS TAP 22S/O  
with pilot flame  
with horizontal flange  
fittings M20x1.5 mm  
with flow regulator  
thermocouple connection M8x1  
D-shaped pin  $\varnothing$  10x8 mm




THIRODE

**3348017** CAP WITH PIN  $\varnothing$  10x8 mm  
pin length 26 mm  
for model PEL 22



**3348019** CAP WITH PIN  $\varnothing$  10x9 mm  
pin length 26 mm  
for model PEL 22



# THIRODE

Suitable for:

**3348029** PIPE FITTING  $\varnothing$  4 mm  
thread M10x1 mm  
for model PEL 21-22-24-25



**5014757** PIPE FITTING  $\varnothing$  6 mm  
thread M10x1 mm




**3348229** CAP WITH PIN  $\varnothing$  10 mm  
pin length 31 mm  
for model PEL 22S/O



**3348245** CAP WITH PIN  $\varnothing$  10x8 mm  
pin length 34/26 mm upper/lower  
for model PEL 22S




**3348231** CAP WITH PIN  $\varnothing$  6x4.6 mm  
pin length 35/21 mm upper/lower  
for model PEL 22





Suitable for:


**3348232** CAP WITH PIN  $\varnothing$  8x6.5 mm  
pin length 39/7 mm upper/lower  
for model PEL 22



**3348023** FLANGE HORIZONTAL  $\varnothing$  12/10 mm  
thread M20x1.5  
for model PEL 22



**3348024** FLANGE VERTICAL  $\varnothing$  12/10 mm  
thread M20x1.5  
for model PEL 22



**3348058** MAGNET PROTECTION NUT M8x1  
thread M18x1 mm  
for model PEL 20-21-22




**3182009** MAGNETIC UNIT PEL BIG HEAD  
head  $\varnothing$  15.5 mm - end piece  $\varnothing$  14 mm - length 44 mm  
for PEL tap model 22-24



# THIRODE

Suitable for:

**3348213** FLANGE  $\varnothing$  12/10 mm  
without adjustment  
thread M20x1.5 mm  
for model PEL 22S



**3348025** FLANGE HORIZONTAL CONICAL  $\varnothing$  12/10 mm  
thread M20x1.5  
for model PEL 22



**3348214** FLANGIA WITH PRESSURE FITTING  $\varnothing$  12/10 mm  
thread M20x1.5 mm  
for model PEL 22S



**3348059** MAGNET PROTECTION NUT M9x1  
thread M18x1mm  
for model PEL 20-21-22



**3182021** MAGNETIC UNIT PEL LARGE HEAD  
head  $\varnothing$  15.5 mm - end piece  $\varnothing$  14 mm - length 44 mm





Suitable for:

**3348038 OLIVE FOR PIPE  $\varnothing$  10 mm**  
for model PEL 22-24-25



**3348036 OLIVE FOR PIPE  $\varnothing$  4 mm**  
for model PEL 21-22-24-25



**3348230 PIN FOT GASTAP  $\varnothing$  6x4.6 mm**  
pin length 45/20 mm rh/lh  
for model PEL 22



**3348032 PIPE FITTING  $\varnothing$  12 mm**  
thread M20x1.5 mm  
for model PEL 22-24-25



**3020078 PIPE FITTING  $\varnothing$  6 mm**  
thread M10x1



# THIRODE

Suitable for:


**3020082 OLIVE FOR PIPE  $\varnothing$  12 mm**  
for model PEL 22-24-25



**3348037 OLIVE FOR PIPE  $\varnothing$  6 mm**  
for model PEL 21-22-24-25



**3348031 PIPE FITTING  $\varnothing$  10 mm**  
thread M20x1.5 mm  
for model PEL 22-24-25




**3348029 PIPE FITTING  $\varnothing$  4 mm**  
thread M10x1 mm  
for model PEL 21-22-24-25



**5014757 PIPE FITTING  $\varnothing$  6 mm**  
thread M10x1 mm



**3348011 GAS TAP 23S/O**  
 with pilot flame  
 with horizontal flange  
 inlet fitting M28x1.5mm  
 outlet fitting M24x1.5mm  
 with flow regulator  
 thermocouple connection M9x1  
 D-shaped pin  $\varnothing$  10x8 mm  
 for Boiling pan (THIRODE)  
 for Bratt pan gas (THIRODE) SA65 - SA85  
 for Boiling pan (THIRODE) B9P.MACD250G




**3348060 CAP WITH PIN  $\varnothing$  10x8 mm**  
 pin length 25 mm  
 for model PEL 23



THIRODE 310141


**3348062 CAP WITH PIN  $\varnothing$  10x8 mm**  
 pin length 35 mm  
 for model PEL 23




**3348027 FLANGE HORIZONTAL  $\varnothing$  12/16 mm**  
 thread M24x1.5 mm  
 for model PEL 23



**3348237 FLANGE HORIZONTAL  $\varnothing$  12/16 mm**  
 without adjustment  
 thread M24x1.5 mm  
 for model PEL 23



**3348028 FLANGE VERTICAL  $\varnothing$  12/16 mm**  
 thread M24x1.5  
 for model PEL 23



**3348040 OLIVE FOR PIPE  $\varnothing$  12 mm**  
 for model PEL 23



**3348041 OLIVE FOR PIPE  $\varnothing$  16 mm**  
 for model PEL 23



**3348042 OLIVE FOR PIPE  $\varnothing$  20 mm**  
 for model PEL 23



**3348036 OLIVE FOR PIPE  $\varnothing$  4 mm**  
 for model PEL 21-22-24-25





Suitable for:

**3348037 OLIVE FOR PIPE  $\varnothing$  6 mm**  
for model PEL 21-22-24-25



**3348033 PIPE FITTING  $\varnothing$  12 mm**  
thread M24x1.5  
for model PEL 23




**3348035 PIPE FITTING  $\varnothing$  20 mm**  
thread M28x1.5  
for model PEL 23



**3020078 PIPE FITTING  $\varnothing$  6 mm**  
thread M10x1



**3348013 GAS TAP 23S/V**  
with pilot flame  
with vertical flange  
inlet fitting M28x1.5mm  
outlet connection M24x1.5mm  
with flow regulator  
thermocouple connection M10x1  
D-shaped pin  $\varnothing$  10x8 mm



THIRODE 905992

# THIRODE

Suitable for:

**3182020 PEL MAGNETIC GROUP**  
head  $\varnothing$  24 mm - end  $\varnothing$  18 mm - length 59 mm  
thermocouple fitting M9x1  
for tap PEL model 23S



THIRODE 71027E

**3348034 PIPE FITTING  $\varnothing$  16 mm**  
thread M24x1.5  
for model PEL 23



**3348029 PIPE FITTING  $\varnothing$  4 mm**  
thread M10x1 mm  
for model PEL 21-22-24-25



**5014757 PIPE FITTING  $\varnothing$  6 mm**  
thread M10x1 mm



**3348060 CAP WITH PIN  $\varnothing$  10x8 mm**  
pin length 25 mm  
for model PEL 23






Suitable for:

**3348062 CAP WITH PIN  $\varnothing$  10x8 mm**  
pin length 35 mm  
for model PEL 23



**3348237 FLANGE HORIZONTAL  $\varnothing$  12/16 mm**  
without adjustment  
thread M24x1.5 mm  
for model PEL 23



**3182010 MAGNETIC UNIT PEL**  
head  $\varnothing$  24 mm - end piece  $\varnothing$  18 mm - length 59 mm  
thermocouple coupling M10x1  
for PEL tap model 23



**3348041 OLIVE FOR PIPE  $\varnothing$  16 mm**  
for model PEL 23



**3348036 OLIVE FOR PIPE  $\varnothing$  4 mm**  
for model PEL 21-22-24-25



**3348033 PIPE FITTING  $\varnothing$  12 mm**  
thread M24x1.5  
for model PEL 23




## THIRODE

Suitable for:

**3348027 FLANGE HORIZONTAL  $\varnothing$  12/16 mm**  
thread M24x1.5 mm  
for model PEL 23



**3348028 FLANGE VERTICAL  $\varnothing$  12/16 mm**  
thread M24x1.5  
for model PEL 23



**3348040 OLIVE FOR PIPE  $\varnothing$  12 mm**  
for model PEL 23



**3348042 OLIVE FOR PIPE  $\varnothing$  20 mm**  
for model PEL 23



**3348037 OLIVE FOR PIPE  $\varnothing$  6 mm**  
for model PEL 21-22-24-25



**3348034 PIPE FITTING  $\varnothing$  16 mm**  
thread M24x1.5  
for model PEL 23





Suitable for:

**3348035** PIPE FITTING  $\varnothing$  20 mm  
thread M28x1.5  
for model PEL 23



**3020078** PIPE FITTING  $\varnothing$  6 mm  
thread M10x1



# THIRODE

Suitable for:

**3348029** PIPE FITTING  $\varnothing$  4 mm  
thread M10x1 mm  
for model PEL 21-22-24-25



**5014757** PIPE FITTING  $\varnothing$  6 mm  
thread M10x1 mm



## Gas valves and accessories

**3523038** ELBOW FLANGE MINISIT  $\varnothing$  1/2" F  
with screws and OR



THIRODE 7430180


**3523035** KNOB MINISIT BLACK  $\varnothing$  37 mm



THIRODE 2020055

THIRODE 7479041

**3523047** LID MINISIT



THIRODE 7472037

**3523092** MINISIT VALVE FOR FOOD-WARMER 40÷110°C  
inlet  $\varnothing$  1/2" F - outlet  $\varnothing$  3/8" F  
thermocouple connection M9x1  
maximum gas inlet pressure 50 mbar  
ambient temperature 0÷80°C  
capillary length 1050 mm  
bulb  $\varnothing$  5x125 mm



THIRODE 7472022

**2100757** CONNECTION FOR OLIVE  $\varnothing$  16 mm  
thread  $\varnothing$  1/2" M







Suitable for:

**3523038 ELBOW FLANGE MINISIT  $\varnothing$  1/2" F**  
with screws and OR



THIRODE 7430180

**3523035 KNOB MINISIT BLACK  $\varnothing$  37 mm**



THIRODE 2020055


THIRODE 7479041

**3182003 MAGNETIC UNIT SIT**  
head  $\varnothing$  25 mm - end piece  $\varnothing$  17 mm - length 56 mm  
for valve SIT AC2 - VR8-MINISIT



THIRODE 7473051

**3523060 OIL SEAL FITTING  $\varnothing$  6.5 mm**  
internal thread M10x0.75 - external thread M14x1.5



**3020082 OLIVE FOR PIPE  $\varnothing$  12 mm**  
for model PEL 22-24-25



**3001070 PIEZO IGNITER MINISIT**  
a  $\varnothing$  22 mm hole is required for the assembly  
faston M  $\varnothing$  2.4 mm




## THIRODE

Suitable for:

**3523037 ELBOW FLANGE MINISIT  $\varnothing$  3/8"**  
with screws and OR



**3523047 LID MINISIT**



THIRODE 7472037

**3523061 NUT  $\varnothing$  1/4"x6 mm**



**3348044 OLIVE FOR PIPE  $\varnothing$  10 mm**  
for model PEL 20-21-24-25



**3348041 OLIVE FOR PIPE  $\varnothing$  16 mm**  
for model PEL 23



**3001071 PIEZO IGNITER MINISIT WITH COVER**  
M faston 2.4 mm






Suitable for:


**3020079** PIPE FITTING  $\varnothing$  12 mm  
thread  $\varnothing$  3/8" M



**3523039** SENSING ELEMENT MINISIT 30÷100°C  
capillary length 1050 mm  
bulb  $\varnothing$  5x125 mm



**3523093** MINISIT VALVE FOR FRYER 70÷210°C  
inlet  $\varnothing$  1/2" F - outlet  $\varnothing$  3/8" F  
thermocouple connection M9x1  
maximum gas inlet pressure 50 mbar  
ambient temperature 0÷60°C  
length capillary 1300 mm  
bulb  $\varnothing$  4x122 mm  
without cover. knob and flanges



THIRODE 7472030

**3523038** ELBOW FLANGE MINISIT  $\varnothing$  1/2" F  
with screws and OR



THIRODE 7430180

**3523035** KNOB MINISIT BLACK  $\varnothing$  37 mm



THIRODE 2020055

THIRODE 7479041

# THIRODE



Suitable for:

**3523036** REDUCTION STRAIGHT  $\varnothing$  3/8" F -  $\varnothing$  1/2" F  
in brass with internal and external thread  
internal thread  $\varnothing$  3/8" F - external thread  $\varnothing$  1/2" F  
for MINISIT flange



**5058320** TUBE NUT FITTING  $\varnothing$  10 mm  
thread M14x1,5 mm




**2100757** CONNECTION FOR OLIVE  $\varnothing$  16 mm  
thread  $\varnothing$  1/2" M



**3523037** ELBOW FLANGE MINISIT  $\varnothing$  3/8" F  
with screws and OR



**3523047** LID MINISIT



THIRODE 7472037




Suitable for:

**3182003 MAGNETIC UNIT SIT**  
head  $\varnothing$  25 mm - end piece  $\varnothing$  17 mm - length 56 mm  
for valve SIT AC2 - VR8-MINISIT



THIRODE 7473051

**3523060 OIL SEAL FITTING  $\varnothing$  6.5 mm**  
internal thread M10x0.75 - external thread M14x1.5



**3020082 OLIVE FOR PIPE  $\varnothing$  12 mm**  
for model PEL 22-24-25




**3001070 PIEZO IGNITER MINISIT**  
a  $\varnothing$  22 mm hole is required for the assembly  
faston M  $\varnothing$  2.4 mm



**3020079 PIPE FITTING  $\varnothing$  12 mm**  
thread  $\varnothing$  3/8" M



**3523096 SENSING ELEMENT MINISIT 50÷190°C**  
stainless steel capillary length 1200 mm  
bulb  $\varnothing$  4x120 mm



## THIRODE

Suitable for:

**3523061 NUT  $\varnothing$  1/4"x6 mm**




**3348044 OLIVE FOR PIPE  $\varnothing$  10 mm**  
for model PEL 20-21-24-25



**3348041 OLIVE FOR PIPE  $\varnothing$  16 mm**  
for model PEL 23



**3001071 PIEZO IGNITER MINISIT WITH COVER**  
M faston 2.4 mm



**3523036 REDUCTION STRAIGHT  $\varnothing$  3/8" F -  $\varnothing$  1/2" F**  
in brass with internal and external thread  
internal thread  $\varnothing$  3/8" F - external thread  $\varnothing$  1/2" F  
for MINISIT flange



**5058320 TUBE NUT FITTING  $\varnothing$  10 mm**  
thread M14x1,5 mm





Suitable for:

# THIRODE



**3523011 VALVE 440 D3  $\varnothing$  3/4"FF**  
 inlet  $\varnothing$  3/4" F - outlet  $\varnothing$  3/4" F  
 thermocouple connection M9x1  
 maximum gas inlet pressure 50 mbar  
 room temperature 0÷80°C  
 with thread for ring nut under the push-button



THIRODE 7473027

Suitable for:

**3020083 FITTING AND OLIVE  $\varnothing$  4 mm**



**3523091 VALVE 710 MINISIT OVEN 70÷310°C**  
 inlet  $\varnothing$  1/2" F - outlet  $\varnothing$  3/8" F  
 thermocouple connection M9x1  
 maximum gas inlet pressure 50 mbar  
 ambient temperature 0÷60°C  
 capillary length 1300 mm  
 bulb  $\varnothing$  4x75 mm  
 without cover. knob and flanges



THIRODE 7472031

**2100757 CONNECTION FOR OLIVE  $\varnothing$  16 mm**  
 thread  $\varnothing$  1/2" M



**3523038 ELBOW FLANGE MINISIT  $\varnothing$  1/2" F**  
 with screws and OR



THIRODE 7430180

**3523037 ELBOW FLANGE MINISIT  $\varnothing$  3/8"**  
 with screws and OR



**3523035 KNOB MINISIT BLACK  $\varnothing$  37 mm**



THIRODE 2020055


THIRODE 7479041

**3182003 MAGNETIC UNIT SIT**  
 head  $\varnothing$  25 mm - end piece  $\varnothing$  17 mm - length 56 mm  
 for valve SIT AC2 - VR8-MINISIT



THIRODE 7473051

**3523047 LID MINISIT**



THIRODE 7472037


**3523061 NUT  $\varnothing$  1/4"x6 mm**





Suitable for:

**3523060 OIL SEAL FITTING  $\phi$  6.5 mm**  
internal thread M10x0.75 - external thread M14x1.5



**3020082 OLIVE FOR PIPE  $\phi$  12 mm**  
for model PEL 22-24-25



**3001070 PIEZO IGNITER MINISIT**  
a  $\phi$  22 mm hole is required for the assembly  
faston M  $\phi$  2.4 mm



**3020079 PIPE FITTING  $\phi$  12 mm**  
thread  $\phi$  3/8" M



**5058320 TUBE NUT FITTING  $\phi$  10 mm**  
thread M14x1,5 mm



# THIRODE



Suitable for:


**3348044 OLIVE FOR PIPE  $\phi$  10 mm**  
for model PEL 20-21-24-25



**3348041 OLIVE FOR PIPE  $\phi$  16 mm**  
for model PEL 23



**3001071 PIEZO IGNITER MINISIT WITH COVER**  
M faston 2.4 mm



**3523036 REDUCTION STRAIGHT  $\phi$  3/8" F -  $\phi$  1/2" F**  
in brass with internal and external thread  
internal thread  $\phi$  3/8" F - external thread  $\phi$  1/2" F  
for MINISIT flange



## Gaskets and seals

**3786346 GASKET FLAT ASB. FREE  $\phi$  14x9x2 mm - 100**



THIRODE 966067

**5010462 GASKET FLAT ASBESTOS FREE  $\phi$  24x17x2 mm**



THIRODE 2002079H



Suitable for:

# THIRODE



Suitable for:


## Gaskets for oven door

**3786310 OVEN DOOR GASKET**  
 made of silicone elastomer  
 profile dimensions 22x11.5 mm  
 COLOUR BLACK  
 SOLD PER METRE  
 for Oven under cooktop (THIRODE) - Series 700  
 Series 900



THIRODE 366386

**3786311 OVEN DOOR GASKET KIT**  
 made of silicone elastomer  
 composed of 3 pcs:  
 2 pcs 290 mm - 1 piece 690 mm  
 profile dimensions 21.5x16.8 mm  
 COLOUR BLACK



THIRODE 366371

## Grids for oven

**3185053 STAINLESS STEEL GRID GN 2/1 650x530 mm**



THIRODE 635022

## Handles


**3242221 CHROME-PLATED ADJUSTABLE DOOR STRIKE**  
 base length 38x18x31 mm  
 fixing distance 26 mm  
 RAHRBACH



THIRODE S486P51

THIRODE 679486

**3242948 LH-RH CATCH WITH LOCK 795 CR**  
 straight handgrip  
 base length 150x30x40.5h mm  
 mounting distance 133 mm  
 adjustable catch between 9 and 22 mm



THIRODE 74441

**3242042 STRIKE FOR DOOR HANDLE**  
 distance between holes 45 mm



Suitable for:

**3242583 LH-RH CATCH WITH LOCK 885 CR**  
 straight handgrip  
 base length 122x28x35h mm  
 mounting distance 104 mm  
 adjustable catch mounting distance 31 mm



THIRODE 906392

Suitable for:

**3242042 STRIKE FOR DOOR HANDLE**  
 distance between holes 45 mm



**3242579 LH-RH CATCH WITHOUT LOCK 570 CR**  
 straight handgrip  
 base length 150x23x30h mm  
 mounting distance 110 mm  
 catch height 16.5 mm



THIRODE 621002

**3242922 STRIKE FOR DOOR CATCH**  
 fitting height 16.5 mm



**3242735 OVEN DOOR HANDLE**  
 distance between mounting holes 180 mm



THIRODE A15018

## Heating elements

**3455152 HEATING ELEMENT 1300W 230V**  
 length 363 mm width 88 mm  
 overall height 138 mm



THIRODE 302196

**7103632 HEATING ELEMENT 1500W 230V**  
 length 270 mm - width 215 mm  
 fittings M14x1.5 mm



THIRODE D02162



Suitable for:

# THIRODE




**3455079 HEATING ELEMENT 1800W 230V**  
length 506 mm - width 70 mm  
height 106 mm  
operating ambient: dry



THIRODE 311739


Suitable for:

**3455153 HEATING ELEMENT 1800W 230V**  
length 553 mm - width 88 mm  
overall height 140 mm  
for BRATTPAN PL.SN900  
for Bratt pan electric (THIRODE) PL.SN900



THIRODE 302197

**3455173 HEATING ELEMENT 1800W 230V**  
length 520 mm - width 55 mm  
height 80 mm



THIRODE 310128

**3455155 HEATING ELEMENT 2000W 230V**  
length 302 mm width 32 mm  
height 205 mm - fittings M12x1 mm  
for Fryer electric (THIRODE) FR10



THIRODE 302214

**7102455 HEATING ELEMENT 2000W 230V**  
length 233 mm - width 215 mm  
couplings M14x1.5 mm



THIRODE D02149

THIRODE 984781

**3455161 HEATING ELEMENT 2500W 230V**  
length 465 mm - height 80 mm  
for Boiling pan electric (THIRODE)




THIRODE 302195

**3455156 HEATING ELEMENT 2700W 230V**  
length 300 mm - width 55 mm  
height 205 mm - fittings M12x1 mm  
for Fryer electric (THIRODE) FR10  
for Fryer (THIRODE) D706.FR15




THIRODE 302215

**3455298 HEATING ELEMENT 3300W 400V**  
length 530 mm - width 450 mm  
flange 70x70 mm  
for Oven under cooktop electric (THIRODE)  
Series 1000 - Series 700 - Series 750 - Series 900



THIRODE 302191

**3455080 HEATING ELEMENT 4500W 230V**  
length 508 mm - width 590 mm  
flange 195x45 mm



THIRODE 322496

**3455157 HEATING ELEMENT 5000W 230V**  
length 288 mm - width 80 mm  
height 295 mm - fittings M12x1 mm  
for Fryer electric (THIRODE) FR18



THIRODE 302221





Suitable for:

Suitable for:

**3455159 HEATING ELEMENT 6000W 230V**  
 immersed depth 380 mm  
 flange  $\varnothing$  external 72 mm  
 complete with O-ring  
 operating ambient: immersion  
 for Bain-marie electric (THIRODE)

**3186014 O-RING 06225 EPDM  $\varnothing$  67 mm**  
 ring thickness 5.34 mm - internal  $\varnothing$  56.52 mm



THIRODE 303123

THIRODE 318044

THIRODE 966001

**3455175 HEATING ELEMENT 6000W 230V**  
 immersed depth 495 mm  
 flange  $\varnothing$  external 63 mm  
 with bulb sheath  
 complete with O-ring  
 operating ambient: immersion

**3186013 O-RING 06187 EPDM  $\varnothing$  58 mm**  
 ring thickness 5.34 mm - internal  $\varnothing$  47.00 mm




THIRODE 1030210

THIRODE 103210

THIRODE 2001827H

**3755617 HEATING ELEMENT 700W 245V**  
 overall length 470 mm - fitting M14x1.25 mm

**3455158 HEATING ELEMENT 7500W 400V**  
 length 495 mm - width 55 mm  
 height 300 mm - couplings  $\varnothing$  1/4"  
 for Fryer electric (THIRODE) FR25



THIRODE 402077

THIRODE 302222

**3755611 QUARTZ PIPE  $\varnothing$  10x460 mm**

**3455376 STRIKE FOR HEATING ELEMENT**  
 $\varnothing$  external 12.5 mm - for screw  $\varnothing$  4 mm  
 total length 28 mm



THIRODE 404007

THIRODE 109003

**3755620 WIRE HEATING ELEMENT 700W 110V**  
 total length 385 mm

**3755611 QUARTZ PIPE  $\varnothing$  10x460 mm**



THIRODE 401032R

THIRODE 404007



Suitable for:

**3455376 STRIKE FOR HEATING ELEMENT**  
ø external 12.5 mm - for screw ø 4 mm  
total length 28 mm



THIRODE 109003


# THIRODE



Suitable for:

## Hinges, catches and accessories

**3053391 CHROME-PLATED HINGE 361**  
length 140 mm - mounting distance 30-35 mm  
for door thickness from 37 mm, gasket included



THIRODE 71258E

## Hydraulic piping

**3450152 HOSE RUBBER REINFORCED ø 13/19 mm**  
internal ø 13 mm - external ø 19 mm  
temperature -40+100°C  
sold per meter



THIRODE 44210

THIRODE 916206

## Incandescent lamps and neon lamps

**3221041 LAMP E14 15W 230V**  
max temperature 300°C - ø 22x50 mm



THIRODE 70597E

**3221061 LAMP E14 25W 230V**  
max temperature 300°C - ø 26x57 mm



THIRODE 70598E

**3221059 LAMP E27 40W 230V**  
max temperature 300°C



THIRODE 308463

**3221105 NEUTRAL HALOGEN LAMP G4 20W 12V**  
max. temperature 250°C



THIRODE 308477

Suitable for:

Suitable for:

**3221270 OVEN NEON LAMP E10 1,2mA 380/400V**  
dimensions  $\varnothing$  10x28 mm



THIRODE 74540009


## Indicator lights

**3221547 INDICATOR LIGHT GREEN 24V**  
head  $\varnothing$  14 mm - hole  $\varnothing$  12 mm  
wire connection length 190 mm  
nichel plated brass case



THIRODE

**3221539 INDICATOR LIGHT GREEN 240V**  
 $\varnothing$  head 13.5 mm -  $\varnothing$  hole 10 mm - 120°C  
wire connection length 200 mm



THIRODE 308334

**3221499 INDICATOR LIGHT GREEN 250V**  
head  $\varnothing$  14 mm - hole  $\varnothing$  13 mm



THIRODE S297P15

**3221544 INDICATOR LIGHT GREEN 400V**  
head  $\varnothing$  14 mm - hole  $\varnothing$  12 mm  
wire connection length 190 mm  
nichel plated brass case



THIRODE

**5045040 INDICATOR LIGHT LED GREEN 5Vdc**  
head  $\varnothing$  7 mm - hole  $\varnothing$  6 mm  
with cable length 220 mm



THIRODE 2001678H

**3221025 INDICATOR LIGHT ORANGE 230V**  
head  $\varnothing$  15 mm - hole  $\varnothing$  13 mm - 120°C  
faston M 6.3x0.8 mm  
universal application



THIRODE 904360

**3221096 INDICATOR LIGHT ORANGE 230V**  
head  $\varnothing$  7 mm - hole  $\varnothing$  6 mm  
wire connection length 200 mm



THIRODE 2002147H

**3221546 INDICATOR LIGHT ORANGE 24V**  
head  $\varnothing$  14 mm - hole  $\varnothing$  12 mm  
wire connection length 190 mm  
nichel plated brass case



THIRODE




Suitable for:

# THIRODE



Suitable for:

**3221515** INDICATOR LIGHT ORANGE 250V  
head  $\varnothing$  14 mm - hole  $\varnothing$  13 mm



THIRODE S298P15

THIRODE 645298

**5047239** INDICATOR LIGHT ORANGE 250V  
hole  $\varnothing$  6 mm - 120°C



THIRODE 907534

**3221686** LAMP CAP FLAT GREEN SU2/C  
mounting hole  $\varnothing$  6 mm - head  $\varnothing$  7 mm



**3221519** INDICATOR LIGHT ORANGE 400V  
head  $\varnothing$  7 mm - hole  $\varnothing$  6 mm  
connection by PVC wires length 250 mm



THIRODE 905445

**3221543** INDICATOR LIGHT ORANGE 400V  
head  $\varnothing$  14 mm - hole  $\varnothing$  12 mm  
wire connection length 190 mm  
nichel plated brass case



**6216029** INDICATOR LIGHT ORANGE 5Vdc  
head  $\varnothing$  7 mm - hole  $\varnothing$  6 mm  
with cable length 200 mm



THIRODE 2001677H

THIRODE

**3221548** INDICATOR LIGHT RED 24V  
head  $\varnothing$  14 mm - hole  $\varnothing$  12 mm  
wire connection length 190 mm  
nichel plated brass case



**3221498** INDICATOR LIGHT RED 250V  
head  $\varnothing$  14 mm - hole  $\varnothing$  13 mm



THIRODE S298P15

THIRODE 645296

THIRODE

**3221514** INDICATOR LIGHT RED 250V  
head  $\varnothing$  14 mm - hole  $\varnothing$  12 mm  
wire connection length 190 mm  
nichel plated brass case



THIRODE

Suitable for:

**3221617 INDICATOR LIGHT RED 380V**  
 head  $\varnothing$  14 mm - hole  $\varnothing$  10 mm  
 wire connection length 700 mm  
 for Bratt pan gas (THIRODE) B9PSA50G



THIRODE 308010

**3221021 RED LAMP RECEPTACLE**  
 head  $\varnothing$  14.5 mm - hole  $\varnothing$  12 mm



THIRODE 904359

**3221126 INDICATOR LIGHT NEUTRAL 24V**  
 head  $\varnothing$  8 mm - 120°C



Suitable for:

**3221545 INDICATOR LIGHT RED 400V**  
 head  $\varnothing$  14 mm - hole  $\varnothing$  12 mm  
 wire connection length 190 mm  
 nichel plated brass case



THIRODE

**3221097 INDICATOR LIGHT NEUTRAL 220V**  
 head  $\varnothing$  8 mm - 120°C



## Ironmongery (screws,nuts,washers)

**3528028 HEXAGON HEAD SCREW M10x20**  
 stainless steel - UNI 5739 - DIN 933 - ISO 4017



THIRODE 24011036

THIRODE 917002

THIRODE 989043

**3528106 HEXAGONAL HEAD SCREW M5x16**  
 st./steel - UNI 5739 - DIN 933 - ISO 4017



THIRODE 16055K

THIRODE 989018

**3528112 HEXAGONAL HEAD SCREW M6x16**  
 st./steel - UNI 5739 - DIN 933 - ISO 4017



THIRODE 388106

**3528216 HEXAGONAL NUT LOW M5**  
 st./steel - UNI 5589 - DIN 936 - ISO 4035



THIRODE 989100



Suitable for:

# THIRODE



Suitable for:

## Knobs

**3241750 BLACK KNOB  $\varnothing$  49 mm**  
D-shaped hole 6x4,6 mm  
for Fryer (THIRODE)  
for Grill (THIRODE)  
for Hot plate (THIRODE)



THIRODE 132742

THIRODE 132843

THIRODE 381224

**3241745 BLACK KNOB  $\varnothing$  50 mm**  
D-shaped hole 10x8 mm  
for GAS TAP



THIRODE 310997

**3241896 BLACK KNOB  $\varnothing$  50 mm**  
with cap - square hole 7x7 mm  
for water tap



THIRODE 138184

**3241897 BLACK KNOB  $\varnothing$  50 mm**  
with cap - D-shaped hole 10x8 mm  
for gas tap



THIRODE 132845

**3241898 BLACK KNOB  $\varnothing$  50 mm**  
with index - D-shaped hole 8x6.5 mm  
for gas tap



THIRODE 132844

THIRODE 311115

**3241566 BLACK KNOB  $\varnothing$  50 mm 0-1-2-3**  
D-shaped hole 6x4.6 mm  
for EGO energy regulator



THIRODE 308091

**3241741 BLACK KNOB  $\varnothing$  50 mm 100-350°C**  
D-shaped hole 6x4.6 mm  
for EGO thermostat



THIRODE 308078

**3241870 BEZEL RING NUT  $\varnothing$  52 mm**  
chrome plated metal Bezel  
for EGO thermostate knob



**3444126 BLACK KNOB  $\varnothing$  50 mm 30-110°C**  
D-shaped pin  $\varnothing$  6x4.6 mm  
for EGO thermostat



THIRODE 163248

THIRODE 308067

**3241637 BLACK KNOB  $\varnothing$  50 mm 60°-200°C**  
D-shaped hole 6x4.6 mm  
for EGO thermostat



THIRODE 308066


Suitable for:

Suitable for:

**3241401 BLACK KNOB  $\varnothing$  70 mm UNIVERSAL**  
D-shaped hole 8x6.5 mm



**3241464 SELF-STICK DISK MIN/MAX**  
external  $\varnothing$  63 mm



THIRODE 171475


**3241463 SELF-STICK DISK WITH ARROW SYMBOL**  
external  $\varnothing$  63 mm




**3241451 SELF-STICK DISK WITHOUT PILOT SYMBOL**  
external  $\varnothing$  63 mm  
for gas taps without pilot




**3241465 SELF-STICK DISK 0-1-0-1**  
external  $\varnothing$  63 mm




**3241466 SELF-STICK DISK 0-1-2-3**  
external  $\varnothing$  63 mm



**3241467 SELF-STICK DISK 0-1-2-3-4-5-6**  
external  $\varnothing$  63 mm




**3241452 SELF-STICK DISK 1-2-3-4-5-6-7-8**  
external  $\varnothing$  63 mm  
for thermostatic gas taps PEL




**3241453 SELF-STICK DISK 1-2-3-4-5-6-7-8**  
external  $\varnothing$  63 mm  
for thermostatic gas taps EGA




**3241458 SELF-STICK DISK 100-180°C**  
external  $\varnothing$  63 mm



**3241456 SELF-STICK DISK 30-110°C**  
external  $\varnothing$  63 mm




**3241457 SELF-STICK DISK 30-110°C**  
external  $\varnothing$  63 mm






Suitable for:

**3241454 SELF-STICK DISK 30-90°C**  
external ø 63 mm




**3241459 SELF-STICK DISK 50-250°C**  
external ø 63 mm



**3241461 SELF-STICK DISK 50-300°C**  
external ø 63 mm



**5053595 SELF-STICKING DISK RED PILOT SYMBOL**  
ø external 64 mm



**3241883 FIXING KNOB CAP WHITE ø 40 mm**  
D-shaped hole 6x4.6 mm  
for Bratt pan (THIRODE) B9PSA50G



THIRODE 381285

**3241749 KNOB BLACK ø 49 mm**  
D-shaped hole 10x8 mm  
for gas tap PEL 22-23  
for Boiling pan (THIRODE)




THIRODE 132744

# THIRODE




Suitable for:


**3241455 SELF-STICK DISK 30-90°C**  
external ø 63 mm



**3241460 SELF-STICK DISK 50-300°C**  
external ø 63 mm



**3241462 SELF-STICK DISK 50-320°C**  
external ø 63 mm



**3241450 SELF-STICKING DISK WITH PILOT SYMBOL**  
external ø 63 mm  
for gas taps with pilot



**3241735 KNOB BLACK ø 34 mm 2-3-4-5-6-7-8**  
D-shaped hole 6x4.6 mm  
for GAS VALVE GC1300



THIRODE 7479045

**3241828 KNOB BLACK ø 50 mm SILKSCREEN PRINTED**  
round hole ø 10 mm  
pin fastening with screw  
for GAS TAP JUNKERS



THIRODE 310291

THIRODE 310292





Suitable for:

**3241319 KNOB BLACK  $\varnothing$  50 mm 30°-85°C**  
D-shaped hole 6x4.6 mm  
for THERMOSTAT EGO



THIRODE 308064

Suitable for:

**3241734 RED KNOB  $\varnothing$  34 mm STOP**  
threaded hole M4  
for GAS VALVE GC1300



THIRODE 7492056

**3241886 SELECTOR SWITCH KNOB  $\varnothing$  52 mm**  
D-shaped hole 6x4.6 mm  
for Bratt pan gas (THIRODE) B9PSA50G  
for Pot stove (THIRODE) D9FR  
for Glass-ceramic plate (THIRODE) D9.FR 122617



THIRODE 134938

**3241883 FIXING KNOB CAP WHITE  $\varnothing$  40 mm**  
D-shaped hole 6x4.6 mm  
for Bratt pan (THIRODE) B9PSA50G



THIRODE 381285

**3241884 WATER TAP KNOB CHROME-PLATED  $\varnothing$  33 mm**  
height 37 mm -  $\varnothing$  knob 10 mm  
knob length 50 mm  
for Bratt pan gas (THIRODE) B9PSA50G



THIRODE 313062

## Lamp receptacles and spare parts

**3221615 HALOGEN LAMP RECEPTACLE G4 20W 12/24V**  
wire connection length 110 mm



THIRODE 147328

**3186525 GASKET FOR LAMP RECEPTACLE**  
external  $\varnothing$  49 mm  
internal  $\varnothing$  32 mm  
thickness 2.8 mm



**3221638 HALOGEN LAMP NEUT. OSRAM G4 20W 12V**  
max. temperature 300°C



**3221105 NEUTRAL HALOGEN LAMP G4 20W 12V**  
max. temperature 250°C



THIRODE 308477



Suitable for:

**3221616 NEUTRAL HALOGEN LAMP G4 20W 24V**  
max. temperature 250°C




# THIRODE



Suitable for:

## Magnet groups


**3182019 MAGNETIC UNIT**  
head  $\varnothing$  19 mm - end piece  $\varnothing$  18 mm - length 50 mm  
for gas tap



THIRODE 310578

THIRODE 7462039

**3182009 MAGNETIC UNIT PEL BIG HEAD**  
head  $\varnothing$  15.5 mm - end piece  $\varnothing$  14 mm - length 44 mm  
for PEL tap model 22-24



THIRODE 71001E

**3182011 MAGNETIC UNIT PEL SMALL HEAD**  
head  $\varnothing$  15 mm - end piece  $\varnothing$  11 mm - length 44 mm  
for PEL tap models 20-21  
for EGA tap model 25213  
for JUNKERS tap model CH110



THIRODE 7473048

**3182003 MAGNETIC UNIT SIT**  
head  $\varnothing$  25 mm - end piece  $\varnothing$  17 mm - length 56 mm  
for valve SIT AC2 - VR8-MINISIT



THIRODE 7473051

**3182020 PEL MAGNETIC GROUP**  
head  $\varnothing$  24 mm - end  $\varnothing$  18 mm - length 59 mm  
thermocouple fitting M9x1  
for tap PEL model 23S



THIRODE 71027E

## Magnets

**3242588 DOOR LOCK MAGNET**  
distance between magnetic part holes 40 mm  
distance between holes of strike plate 42 mm



THIRODE 7403095



## Microswitches, mechanical

3240189 MICRO SWITCH M1DX20 10A 250V



THIRODE 1700340


THIRODE 300682

THIRODE 900502

3250071 MICROSWITCH SPRING  $\varnothing$  13x25 mm



5003350 ROD MICROSWITCH 48x30 mm



3240407 MICROSWITCH KIT 16A 250V


2 locking positions  
the kit includes 5 levers:  
lever 75 mm - lever 27 mm - lever 15 mm  
lever 15 mm with wheel - lever 27 mm with wheel



THIRODE 300688

3240934 MICROSWITCH PANASONIC ABV16146131

0.1A 250V - lever length 32 mm  
with cable length 290 mm  
for Bratt pan (THIRODE) SA41.BE.G 122904



THIRODE 300668

THIRODE 300678

3240234 LIMIT SWITCH PIN



3240235 RING NUT M16x1.5 mm



3240568 MICROSWITCH CROUZET EF83161.3

1NO+NC 16A 250V  
complete with roll lever 28 mm





Suitable for:

# THIRODE



**3240410 MICROSWITCH 16(4)A 250V**



THIRODE 303621

**3240236 LIMIT SWITCH CONTROL**



Suitable for:

**3240203 BUSHING DOOR MICROSWITCH**  
external  $\varnothing$  10x15 mm



**3240234 LIMIT SWITCH PIN**



**3240233 MICROSWITCH FITTING M16x1.5 mm**



**3250071 MICROSWITCH SPRING  $\varnothing$  13x25 mm**



**3240235 RING NUT M16x1.5 mm**



## Motors

**3240493 MOTOR WITH FAN 32W 230V 50Hz 0.27A**  
TYPE R2K150/0020A9-4218bc  
fan  $\varnothing$  150 mm - pin length 50 mm



THIRODE 645457

## Nozzles

**3500252 CONICAL GAS JET M10x1  $\varnothing$  1.05 mm**



THIRODE 7433049

**3500239 CONICAL GAS JET M10x1  $\varnothing$  1.20 mm**



THIRODE 7433008

THIRODE 7433181

Suitable for:

Suitable for:

**3500254 CONICAL GAS JET M10x1  $\varnothing$  1.80 mm**

**3500243 CONICAL GAS JET M10x1  $\varnothing$  1.85 mm**



THIRODE 7433020

THIRODE 7433039

**3500244 CONICAL GAS JET M10x1  $\varnothing$  2.00 mm**

**3500245 CONICAL GAS JET M10x1  $\varnothing$  2.10 mm**




THIRODE 7433123

THIRODE 7433013

**3500246 CONICAL GAS JET M10x1  $\varnothing$  2.20 mm**

**3500248 CONICAL GAS JET M10x1  $\varnothing$  2.35 mm**



THIRODE 7433399

THIRODE 1250160

THIRODE 7433055

**3500249 CONICAL GAS JET M10x1  $\varnothing$  2.60 mm**

**3500250 CONICAL GAS JET M10x1  $\varnothing$  2.80 mm**



THIRODE 7433014

THIRODE 7433054

**3500251 CONICAL GAS JET M10x1  $\varnothing$  3.10 mm**

**3500163 GAS JET  $\varnothing$  1.60 mm**



THIRODE 7433121

THIRODE 311166

THIRODE 680948

## O-Ring and ORM gaskets

**3786454 O-RING GASKET 0153 EPDM**  
ring thickness 3.53 mm - internal  $\varnothing$  49.21 mm

**3060608 O-RING 03050 EPDM**  
ring thickness 2.62 mm - internal  $\varnothing$  12.37 mm



THIRODE 2001373H

THIRODE 2001376H



# THIRODE



Suitable for:

Suitable for:

**3243009 O-RING 0106 EPDM**  
ring thickness 1.78 mm - internal  $\varnothing$  6.75 mm



THIRODE 2001978H  
THIRODE 966010

THIRODE 2001978HK

THIRODE 5814E

**1186304 O-RING 0112 EPDM**  
ring thickness 2.62 mm - internal  $\varnothing$  9.92 mm



THIRODE 2001371H

**3186606 O-RING 0144 EPDM**  
ring thickness 3.53 mm - internal  $\varnothing$  39.69 mm



THIRODE 2001372H

**3160615 O-RING 0201 EPDM**  
ring thickness 5.34 mm - internal  $\varnothing$  120.70 mm



THIRODE 2001851H

THIRODE 5830E

**3243139 O-RING 02025 EPDM**  
ring thickness 1.78 mm - internal  $\varnothing$  6.07 mm



THIRODE 5091E

**1186612 O-RING 02025 VITON**  
ring thickness 1.78 mm - internal  $\varnothing$  6.07 mm



THIRODE 2001374H

**1186411 O-RING 02031 EPDM**  
ring thickness 1.78 mm - internal  $\varnothing$  7.66 mm



THIRODE 5814E

**1186803 O-RING 02037 EPDM**  
ring thickness 1.78 mm - internal  $\varnothing$  9.25 mm



THIRODE 2001375H

THIRODE 5090E

**1186352 O-RING 02050 EPDM**  
ring thickness 1.78 mm - internal  $\varnothing$  12.42 mm



THIRODE 966011

**6456074 O-RING 02325 EPDM**  
ring thickness 1.78 mm - internal  $\varnothing$  82.27 mm  
for pump housing




THIRODE 2001378H

Suitable for:

Suitable for:

**3122365 O-RING 02475 EPDM**  
ring thickness 1.78 mm - internal  $\varnothing$  120.37 mm



THIRODE 1255E  
THIRODE 2001837H  
THIRODE 5620E

THIRODE 2001345H  
THIRODE 2002422H

THIRODE 2001351H  
THIRODE 3710E

**1186318 O-RING 03043 EPDM**  
ring thickness 2.62 mm - internal  $\varnothing$  10.78 mm



THIRODE 2001912H

THIRODE 366381

**1186238 O-RING 04081 EPDM**  
ring thickness 3.53 mm - internal  $\varnothing$  20.22 mm



THIRODE 15173K

THIRODE 966085

**1186655 O-RING 04131 EPDM**  
ring thickness 3.53 mm - internal  $\varnothing$  32.93 mm



THIRODE 15138K

THIRODE 2001917H

THIRODE 2002353H

**3186290 O-RING 04187 EPDM**  
ring thickness 3.53 mm - internal  $\varnothing$  47.22 mm



THIRODE

**5022973 O-RING 04275 EPDM**  
ring thickness 3.53 mm - internal  $\varnothing$  69.44 mm



THIRODE 2001911H

**3186271 O-RING 04312 EPDM**  
ring thickness 3.53 mm - internal  $\varnothing$  78.97 mm



THIRODE 2000004

**3160607 O-RING 04400 EPDM**  
ring thickness 3.53 mm - internal  $\varnothing$  101.20 mm



THIRODE 5584E

**3186001 O-RING 06150 EPDM**  
ring thickness 5.34 mm - internal  $\varnothing$  37.47 mm



THIRODE 2001370H

**3186339 O-RING 06175 EPDM**  
ring thickness 5.34 mm - internal  $\varnothing$  43.82 mm



THIRODE 15118K

THIRODE 99013717



Suitable for:

**3186013 O-RING 06187 EPDM  $\varnothing$  58 mm**  
ring thickness 5.34 mm - internal  $\varnothing$  47.00 mm



THIRODE 2001827H

Suitable for:

**3186333 O-RING 06200 EPDM**  
ring thickness 5.34 mm - internal  $\varnothing$  50.16 mm



THIRODE 15082K

THIRODE 966084

**3186014 O-RING 06225 EPDM  $\varnothing$  67 mm**  
ring thickness 5.34 mm - internal  $\varnothing$  56.52 mm




THIRODE 318044

THIRODE 966001

## Pilot burners and accessories

**3020084 FITTING AND OLIVE  $\varnothing$  6 mm**




THIRODE 317104

**3020085 FITTING FOR SPARKING PLUG FIXING M10x1mm**



THIRODE 317980

**3020200 FITTING FOR THERMOCOUPLE  $\varnothing$  6.5 mm**  
thread M10x1



THIRODE 317979

**3020112 OLIVE FOR PIPE  $\varnothing$  6 mm**



THIRODE 310275

**3020001 ONE-FLAME PILOT BURNER SIT**  
multigas with jet  $\varnothing$  0.20 mm  
with 2 positions bracket



THIRODE 2020122

THIRODE 905107

**3020101 BRACKET CLAMP 2 POSITIONS**







Suitable for:

**3020092 BRACKET PILOT BURNER SUPP. LH 92x55x45mm**  
for mounting of pilot assembly




**3020293 BRACKET PILOT BURNER SUPPORT 65x50x45 mm**  
for burner ø 115 mm



**3020100 BRACKET 2 POSITIONS**



**3020083 FITTING AND OLIVE ø 4 mm**



**3020102 HEXAGON HEAD SCREW 3/16"x18 mm**



**3020060 IGNITION PLUG ROUND ø 7x44 mm**  
M faston M 4x1 mm  
overall length 82 mm  
model CB505/021 Junkers  
for model P502F




THIRODE 308480

# THIRODE



Suitable for:

**3020292 BRACKET PILOT BURNER SUPPORT 47x40x15 mm**  
for burner ø 90 mm




**3020291 BRACKET PILOT BURNER SUPPORT 85x45x55 mm**  
for burner ø 135 mm



**3020108 DEFLECTOR 1 FLAME**



**3020084 FITTING AND OLIVE ø 6 mm**



THIRODE 317104

**3001003 IGNITION PLUG ROUND ø 7x44 mm**  
M faston M4x1 mm  
overall length 65 mm



**3020124 IGNITION PLUG ROUND ø 7x44 mm**  
connection ø 2.4 mm  
overall length 58 mm



THIRODE 7455048



Suitable for:

**3020294 IGNITION PLUG ROUND  $\varnothing$  7x44 mm**  
M faston M4x1 mm  
overall length 67 mm



# THIRODE



Suitable for:

**3020365 IGNITION PLUG ROUND  $\varnothing$  7x44 mm**  
connection  $\varnothing$  2.4 mm  
overall length 52 mm



**3020082 OLIVE FOR PIPE  $\varnothing$  12 mm**  
for model PEL 22-24-25



**3348036 OLIVE FOR PIPE  $\varnothing$  4 mm**  
for model PEL 21-22-24-25



**3020081 OLIVE FOR PIPE  $\varnothing$  6 mm**



**3020097 PILOT AERATION REGULATOR**  
internal  $\varnothing$  7 mm - external  $\varnothing$  9 mm  
height 10 mm




**3020115 PILOT CAP 1 FLAME**



**3020054 PILOT JET  $\varnothing$  0.20 mm**



**3020156 PILOT JET  $\varnothing$  0.25 mm**



**4058525 PILOT JET  $\varnothing$  0.30 mm**



**3020055 PILOT JET  $\varnothing$  0.35 mm**



**5015516 PILOT JET  $\varnothing$  0.40 mm**





Suitable for:

3500269 PILOT JET  $\varnothing$  0.45 mm



# THIRODE

Suitable for:

5075989 PILOT JET  $\varnothing$  0.70 mm



THIRODE 7433158

3020308 PILOT WITH NOZZLE  $\varnothing$  0.40 mm



3020105 PILOT WITH 0.20 mm  $\varnothing$  JET



3020106 PILOT WITH 0.25 mm  $\varnothing$  JET



3020107 PILOT WITH 0.35 mm  $\varnothing$  JET



3020079 PIPE FITTING  $\varnothing$  12 mm  
thread  $\varnothing$  3/8" M



3020077 PIPE FITTING  $\varnothing$  4 mm  
thread M10x1



3020078 PIPE FITTING  $\varnothing$  6 mm  
thread M10x1



5014757 PIPE FITTING  $\varnothing$  6 mm  
thread M10x1 mm



3020457 PILOT BURNER BASE  
thread  $\varnothing$  10 mm



THIRODE 368146



Suitable for:

# THIRODE



**3020459 PILOT BURNER CAP  $\varnothing$  1/8" F**  
for Kitchen gas (THIRODE) B9FV800FG



THIRODE 368234

**3020458 PILOT BURNER SUPPORT**  
for Kitchen gas (THIRODE) B9FV800FG



THIRODE 165527

**3020557 PILOT JET  $\varnothing$  0.20 mm**



**3020040 PILOT JET  $\varnothing$  0.30 mm**



THIRODE 311171

**3020041 PILOT JET  $\varnothing$  0.41 mm**



THIRODE 310273

**3020187 PILOT JET  $\varnothing$  0.51 mm**



Suitable for:

**3020457 PILOT BURNER BASE**  
thread  $\varnothing$  10 mm



THIRODE 368146

**5035324 PILOT JET  $\varnothing$  0.18 mm**



**3020157 PILOT JET  $\varnothing$  0.25 mm**



THIRODE 310274

**3020541 PILOT JET  $\varnothing$  0.35 mm**



**2106308 PILOT JET  $\varnothing$  0.45 mm**



**4053669 PILOT JET  $\varnothing$  0.75 mm**





Suitable for:

**3020018 PILOT BURNER GPL CB 503.003**  
with LPG jet and pilot olive  
with pilot pipe connection



THIRODE 7434013

**5026012 OLIVE FOR PIPE  $\varnothing$  4 mm**  
for pilot burner series CB 502-CB 503



Suitable for:

**3020051 FITTING FOR PILOT  $\varnothing$  4 mm**  
thread M10x1  
for pilot burner JUNKERS/ORKLI



**3020112 OLIVE FOR PIPE  $\varnothing$  6 mm**



THIRODE 310275

**3020048 PILOT JET  $\varnothing$  0.21 mm**  
for pilot burner series CB 503-CB 50203.




**3020049 PILOT JET  $\varnothing$  0.28 mm**  
for pilot burner series CB 503



**3348029 PIPE FITTING  $\varnothing$  4 mm**  
thread M10x1 mm  
for model PEL 21-22-24-25



**3020078 PIPE FITTING  $\varnothing$  6 mm**  
thread M10x1



**5014757 PIPE FITTING  $\varnothing$  6 mm**  
thread M10x1 mm





Suitable for:

# THIRODE



**3020421 PILOT BURNER HONEYWELL Q327**  
with NG jet  
for Bratt pan (THIRODE) B9P.SA50.G



THIRODE 310092

**3500331 PILOT JET**  
for LPG - pilot Honeywell Q327



THIRODE 310091

**3020422 PILOT BURNER HONEYWELL Q349**  
supplied without sparking plug, nozzle  
with pilot pipe fitting  $\varnothing$  6 mm



THIRODE 310148

**3500328 PILOT JET**  
for LPG - pilot Honeywell Q349



THIRODE 310150

**3020458 PILOT BURNER SUPPORT**  
for Kitchen gas (THIRODE) B9FV800FG



THIRODE 165527

Suitable for:

**3806001 IGNITION PLUG ROUND  $\varnothing$  6x44 mm**  
fitting M8x10 mm - complete with fastening nut  
overall length 75 mm  
for pilot burner Honeywell serie Q327-Q349



THIRODE 310215

**3806001 IGNITION PLUG ROUND  $\varnothing$  6x44 mm**  
fitting M8x10 mm - complete with fastening nut  
overall length 75 mm  
for pilot burner Honeywell serie Q327-Q349



THIRODE 310215

**3500329 PILOT JET**  
for NATURAL GAS - pilot Honeywell Q349



THIRODE 310152

**3500328 PILOT JET**  
for LPG - pilot Honeywell Q349



THIRODE 310150



Suitable for:

**3500329 PILOT JET**  
for NATURAL GAS - pilot Honeywell Q349



THIRODE 310152

Suitable for:

**3500331 PILOT JET**  
for LPG - pilot Honeywell Q327



THIRODE 310091

**3020157 PILOT JET  $\varnothing$  0.25 mm**



THIRODE 310274

**3020040 PILOT JET  $\varnothing$  0.30 mm**



THIRODE 311171

**5015516 PILOT JET  $\varnothing$  0.40 mm**



THIRODE 1040182

**3020041 PILOT JET  $\varnothing$  0.41 mm**



THIRODE 310273

**3500269 PILOT JET  $\varnothing$  0.45 mm**



THIRODE 7433158

**3020414 PILOT JET LPG**  
thread M7x1 mm



THIRODE 312126

**3020415 PILOT JET NATURAL GAS**  
thread M7x1 mm



THIRODE 312127

**3020460 SIT THREE-FLAME PILOT BURNER**  
supplied without sparking plug, nozzle and gasket  
for Boiling pan gas (THIRODE) SA41BEG LX  
for Kitchen gas (THIRODE) B9FV800FG



THIRODE 310272

**3020085 FITTING FOR SPARKING PLUG FIXING M10x1mm**




THIRODE 317980



Suitable for:

**3020200 FITTING FOR THERMOCOUPLE  $\varnothing$  6.5 mm  
thread M10x1**



THIRODE 317979

**3020060 IGNITION PLUG ROUND  $\varnothing$  7x44 mm  
M faston M 4x1 mm  
overall length 82 mm  
model CB505/021 Junkers  
for model P502F**



THIRODE 308480

**3020294 IGNITION PLUG ROUND  $\varnothing$  7x44 mm  
M faston M4x1 mm  
overall length 67 mm**



**3020111 OLIVE FOR PIPE  $\varnothing$  4 mm**



**3020112 OLIVE FOR PIPE  $\varnothing$  6 mm**



THIRODE 310275

**5035324 PILOT JET  $\varnothing$  0.18 mm**



# THIRODE

Suitable for:

**3001003 IGNITION PLUG ROUND  $\varnothing$  7x44 mm  
M faston M4x1 mm  
overall length 65 mm**



**3020124 IGNITION PLUG ROUND  $\varnothing$  7x44 mm  
connection  $\varnothing$  2.4 mm  
overall length 58 mm**



THIRODE 7455048

**3020365 IGNITION PLUG ROUND  $\varnothing$  7x44 mm  
connection  $\varnothing$  2.4 mm  
overall length 52 mm**



**3348036 OLIVE FOR PIPE  $\varnothing$  4 mm  
for model PEL 21-22-24-25**



**3020086 PILOT GASKET**



**3020557 PILOT JET  $\varnothing$  0.20 mm**







Suitable for:

3020157 PILOT JET  $\varnothing$  0.25 mm



THIRODE 310274

3020541 PILOT JET  $\varnothing$  0.35 mm




2106308 PILOT JET  $\varnothing$  0.45 mm



4053669 PILOT JET  $\varnothing$  0.75 mm



3348029 PIPE FITTING  $\varnothing$  4 mm  
thread M10x1 mm  
for model PEL 21-22-24-25



5014757 PIPE FITTING  $\varnothing$  6 mm  
thread M10x1 mm



# THIRODE

Suitable for:

3020040 PILOT JET  $\varnothing$  0.30 mm



THIRODE 311171

3020041 PILOT JET  $\varnothing$  0.41 mm



THIRODE 310273

3020187 PILOT JET  $\varnothing$  0.51 mm



3020077 PIPE FITTING  $\varnothing$  4 mm  
thread M10x1



3020078 PIPE FITTING  $\varnothing$  6 mm  
thread M10x1





Suitable for:

# THIRODE



**3020006 THREE-FLAME PILOT BURNER SIT**  
multigas with jet  $\varnothing$  0.20 mm  
with 3 positions bracket



THIRODE 2020124  
THIRODE 7434003

THIRODE 311022

THIRODE 71517E

**3020103 BRACKET 3 POSITIONS**



**3020110 DEFLECTOR 3 FLAMES**



**3020083 FITTING AND OLIVE  $\varnothing$  4 mm**



**3020102 HEXAGON HEAD SCREW 3/16"x18 mm**



**3020060 IGNITION PLUG ROUND  $\varnothing$  7x44 mm**  
M faston M 4x1 mm  
overall length 82 mm  
model CB505/021 Junkers  
for model P502F



THIRODE 308480

Suitable for:

**3020104 BRACKET CLAMP 3 POSITIONS**




**3020109 DEFLECTOR 2 FLAMES**



**5048713 DEFLECTOR 3 FLAMES**



**3020084 FITTING AND OLIVE  $\varnothing$  6 mm**



THIRODE 317104

**3001003 IGNITION PLUG ROUND  $\varnothing$  7x44 mm**  
M faston M4x1 mm  
overall length 65 mm



**3020124 IGNITION PLUG ROUND  $\varnothing$  7x44 mm**  
connection  $\varnothing$  2.4 mm  
overall length 58 mm



THIRODE 7455048



Suitable for:

**3020294 IGNITION PLUG ROUND  $\varnothing$  7x44 mm**  
M faston M4x1 mm  
overall length 67 mm



**3020082 OLIVE FOR PIPE  $\varnothing$  12 mm**  
for model PEL 22-24-25



**5027953 OLIVE FOR PIPE  $\varnothing$  4 mm**  
for COPRECI CAL3200



**3020097 PILOT AERATION REGULATOR**  
internal  $\varnothing$  7 mm - external  $\varnothing$  9 mm  
height 10 mm



**3020156 PILOT JET  $\varnothing$  0.25 mm**



**3020055 PILOT JET  $\varnothing$  0.35 mm**



## THIRODE

Suitable for:

**3020365 IGNITION PLUG ROUND  $\varnothing$  7x44 mm**  
connection  $\varnothing$  2.4 mm  
overall length 52 mm



**3348036 OLIVE FOR PIPE  $\varnothing$  4 mm**  
for model PEL 21-22-24-25



**3020081 OLIVE FOR PIPE  $\varnothing$  6 mm**



**3020054 PILOT JET  $\varnothing$  0.20 mm**



**4058525 PILOT JET  $\varnothing$  0.30 mm**



**5015516 PILOT JET  $\varnothing$  0.40 mm**





Suitable for:

3500269 PILOT JET  $\varnothing$  0.45 mm



# THIRODE

Suitable for:

5075989 PILOT JET  $\varnothing$  0.70 mm



THIRODE 7433158

3020308 PILOT WITH NOZZLE  $\varnothing$  0.40 mm



3020105 PILOT WITH 0.20 mm  $\varnothing$  JET



3020106 PILOT WITH 0.25 mm  $\varnothing$  JET



3020107 PILOT WITH 0.35 mm  $\varnothing$  JET



3020079 PIPE FITTING  $\varnothing$  12 mm  
thread  $\varnothing$  3/8" M



3020077 PIPE FITTING  $\varnothing$  4 mm  
thread M10x1



5033138 PIPE FITTING  $\varnothing$  4 mm  
thread  $\varnothing$  1/8" M



3020078 PIPE FITTING  $\varnothing$  6 mm  
thread M10x1



5014757 PIPE FITTING  $\varnothing$  6 mm  
thread M10x1 mm



Suitable for:

**3020002 TWO-FLAME PILOT BURNER SIT**  
multigas with jet  $\varnothing$  0.20 mm  
with 2 positions bracket




THIRODE

**3020100 BRACKET 2 POSITIONS**



**3020083 FITTING AND OLIVE  $\varnothing$  4 mm**



**3020102 HEXAGON HEAD SCREW 3/16"x18 mm**



**3020060 IGNITION PLUG ROUND  $\varnothing$  7x44 mm**  
M faston M 4x1 mm  
overall length 82 mm  
model CB505/021 Junkers  
for model P502F



THIRODE 308480

Suitable for:


**3020101 BRACKET CLAMP 2 POSITIONS**



**3020109 DEFLECTOR 2 FLAMES**



**3020084 FITTING AND OLIVE  $\varnothing$  6 mm**



THIRODE 317104

**3001003 IGNITION PLUG ROUND  $\varnothing$  7x44 mm**  
M faston M4x1 mm  
overall length 65 mm



**3020124 IGNITION PLUG ROUND  $\varnothing$  7x44 mm**  
connection  $\varnothing$  2.4 mm  
overall length 58 mm



THIRODE 7455048



Suitable for:

**3020294 IGNITION PLUG ROUND  $\varnothing$  7x44 mm**  
M faston M4x1 mm  
overall length 67 mm



# THIRODE



Suitable for:

**3020365 IGNITION PLUG ROUND  $\varnothing$  7x44 mm**  
connection  $\varnothing$  2.4 mm  
overall length 52 mm



**3020082 OLIVE FOR PIPE  $\varnothing$  12 mm**  
for model PEL 22-24-25



**3348036 OLIVE FOR PIPE  $\varnothing$  4 mm**  
for model PEL 21-22-24-25



**5027953 OLIVE FOR PIPE  $\varnothing$  4 mm**  
for COPRECI CAL3200



**3020081 OLIVE FOR PIPE  $\varnothing$  6 mm**



**3020097 PILOT AERATION REGULATOR**  
internal  $\varnothing$  7 mm - external  $\varnothing$  9 mm  
height 10 mm



**3020054 PILOT JET  $\varnothing$  0.20 mm**



**3020156 PILOT JET  $\varnothing$  0.25 mm**



**4058525 PILOT JET  $\varnothing$  0.30 mm**



**3020055 PILOT JET  $\varnothing$  0.35 mm**



**5015516 PILOT JET  $\varnothing$  0.40 mm**





Suitable for:

3500269 PILOT JET  $\varnothing$  0.45 mm



# THIRODE

Suitable for:

5075989 PILOT JET  $\varnothing$  0.70 mm



THIRODE 7433158

3020308 PILOT WITH NOZZLE  $\varnothing$  0.40 mm



3020105 PILOT WITH 0.20 mm  $\varnothing$  JET



3020106 PILOT WITH 0.25 mm  $\varnothing$  JET



3020107 PILOT WITH 0.35 mm  $\varnothing$  JET



3020079 PIPE FITTING  $\varnothing$  12 mm  
thread  $\varnothing$  3/8" M




3020077 PIPE FITTING  $\varnothing$  4 mm  
thread M10x1



5033138 PIPE FITTING  $\varnothing$  4 mm  
thread  $\varnothing$  1/8" M



3020078 PIPE FITTING  $\varnothing$  6 mm  
thread M10x1



5014757 PIPE FITTING  $\varnothing$  6 mm  
thread M10x1 mm





Suitable for:

# THIRODE



Suitable for:

## Potentiometers

### 3390341 POTENTIOMETER COMPLETE WITH CABLE

with cable length 640 mm  
D-shaped pin  $\varnothing$  6x4.6 mm  
for Fryer gas (THIRODE) FR25G



THIRODE 170744

## Probes

**3445913 SILICONE PROBE NTC 1500 mm**  
temperature range  $-50+110^{\circ}\text{C}$   
bulb  $\varnothing$  6x40 mm



THIRODE S184P20

THIRODE 651184

**3445959 SILICONE PTC PROBE 5000 mm**  
temperature range  $-55+150^{\circ}\text{C}$   
bulb  $\varnothing$  6x40 mm



THIRODE 25040403

**3397184 TEMPERATURE PROBE PT100 640 mm**  
2-wire probe  
bulb  $\varnothing$  3x12 mm  
with fixing connection M8x1.25 mm



THIRODE 301452

## Radiant heating elements

**2105893 RADIANT HEATING ELEMENT 4000W 400V**  
dimensions 300x300 mm  
radiant size 270x270 mm  
electric connections with cables length 1600 mm  
for glass-ceramic cooking hob  
WITHOUT PAN DETECTION SENSOR  
for Glass-ceramic plate (THIRODE) 128514 T-D709:FR



THIRODE 140300


THIRODE 650406





## Relays

**3351154 BASE OCTAL ES8 10A 400V**  
8 poles



THIRODE 5937E

**3351085 POWER RELAY FINDER 40.31.7.048.0000**  
48Vdc - 1 exchange contact 10A  
for Bratt pan gas (THIRODE) B9PSA50G



THIRODE 309491

**3351901 POWER RELAY FINDER 60.62.8.230.0000**  
230V 50/60Hz  
2 exchange contacts 10A



THIRODE 2001867H

**3351021 POWER RELAY FINDER 62.82.8.230.0000**  
230V 50/60Hz  
2 exchange contacts 16A



THIRODE 2001873H

**3351029 POWER RELAY FINDER 62.82.8.230.0300**  
230V 50/60Hz  
2 contacts NO 16A



THIRODE 2002044H

**3351008 POWER RELAY FINDER 62.83.8.230.0000**  
230V 50/60Hz  
3 exchange contacts 16A



THIRODE 2001258H

THIRODE 900073

**3351602 POWER RELAY FINDER 65.31.8.230.0300**  
230V 50/60Hz  
1 contact NO 30A



THIRODE 2001929H

THIRODE 300283

**3351605 RELAY POWER FINDER 60.63.8.230.0000**  
230V 50/60Hz  
3 exchange contacts 10A



THIRODE 2001887H

## Selector switches


**3057050 CONNECTING BRACKET 28x21x16 mm**  
distance between hooking brackets 27 mm  
f/connection between selector switch and thermostat.



THIRODE 300177

THIRODE 905109

**3057027 SELECTOR SWITCH 0-1 POSITIONS**  
contact capacity 16A 250V - max 150°C  
D-shaped pin  $\varnothing$  6x4.6 mm  
rear hole for thermostat  
for Kitchen (THIRODE) - Series 700 - Series 900



THIRODE 300176




Suitable for:

# THIRODE




**3057255** **SELECTOR SWITCH 0-1 POSITIONS**  
contact capacity 16A 250V - max 150°C  
D-shaped pin  $\varnothing$  6x4.6 mm




THIRODE 905108

**5036256** **SELECTOR SWITCH 0-1 POSITIONS**  
contact capacity 16A 250V - max 150°C  
D-shaped pin  $\varnothing$  6x4.6 mm




THIRODE 300175

**3057015** **SELECTOR SWITCH 0-1-0-1 POSITIONS**  
contact capacity 16A 250V - max 150°C  
D-shaped pin  $\varnothing$  6x4.6 mm




THIRODE 300002

**3057087** **SELECTOR SWITCH 0-3 POSITIONS**  
contact capacity 16A 250V - max 150°C  
D-shaped pin  $\varnothing$  6x4.6 mm




THIRODE 002736

**3057306** **SELECTOR SWITCH 0-3 POSITIONS**  
contact capacity 32A 250V - max 150°C  
D-shaped pin  $\varnothing$  6x4.6 mm  
for Oven under cooktop electric (THIRODE)  
Series 1000 - Series 700 - Series 900




THIRODE 300051

**7104056** **SELECTOR SWITCH 0-3 POSITIONS**  
contact capacity 16A 250V - max 150°C  
D-shaped pin  $\varnothing$  6x4.6 mm




THIRODE 300770

**3057270** **SELECTOR SWITCH 0-4 POSITIONS**  
contact capacity 16A 250V - max 150°C  
D-shaped pin  $\varnothing$  6x4.6 mm




THIRODE 300178

**3057023** **SELECTOR SWITCH 0-6 POSITIONS**  
contact capacity 32A 250V - max 150°C  
D shaft  $\varnothing$  6x4.6 mm



THIRODE 300010

**3057024** **SELECTOR SWITCH 0-6 POSITIONS**  
contact capacity 16A 250V - max 150°C  
D-shaped pin  $\varnothing$  6x4.6 mm




THIRODE 300011



## Sleeving for cables

**3050764 GLASS SLEEVING  $\varnothing$  12 mm - 10 m**  
max temperature +350°C  
for 100 m roll see 3050164



THIRODE 307293

**3050761 GLASS SLEEVING  $\varnothing$  6 mm - 10 m**  
max temperature +350°C  
for 100 m roll see 3050161



THIRODE 307292

**3050762 GLASS SLEEVING  $\varnothing$  8 mm - 10 m**  
max temperature +350°C  
for 100 m roll see 3050162



THIRODE 307291

**3050752 SILICONE SEALING BRAIDING  $\varnothing$  6 mm - 10 m**  
temperature -60°+280°C  
for 100 m rolls see 3050152



THIRODE 7452036

## Solenoid valves

**3120005 SOLEN. VALVE ELBI TYPE 329 1 WAY 180°**  
220/240V 50/60Hz - max. temperature 90°C  
inlet 3/4" - outlet  $\varnothing$  10.5 mm



THIRODE 144937

THIRODE 2001650H

THIRODE 2001651H

THIRODE 314334

**3120019 ADJUSTER FOR INLET ELBI BLACK**  
flow rate 5.5 L/min - tolerance +/- 15%



**3120021 ADJUSTER FOR INLET ELBI BLACK**  
flow rate 12 L/min - tolerance +/- 15%



**3120022 ADJUSTER FOR INLET ELBI BLACK**  
flow rate 16 L/min - tolerance +/- 15%



**3120037 ADJUSTER FOR OUTLET ELBI GREEN**  
flow rate 0.25 L/min - tolerance +/- 25%



**3120201 ADJUSTER FOR OUTLET ELBI GREY**  
flow rate 4.7 L/min - tolerance +/- 25%





Suitable for:

**3120016 ADJUSTER FOR OUTLET ELBI NEUTRAL**  
flow rate 1.2 L/min - tolerance +/- 25%



**3120015 ADJUSTER FOR OUTLET ELBI RED**  
flow rate 0.5 L/min - tolerance +/- 25%



**3120202 ADJUSTER FOR OUTLET ELBI YELLOW**  
flow rate 0.35 L/min / tolerance +/- 25%



**3120204 OUTLET ADJUSTER ELBI BLACK**  
flow rate 5.5 L/min - tolerance +/- 25%



**3120010 SOLEN. VALVE ELBI TYPE 352 2 WAY 90°**  
220/240V 50/60Hz - max. temperature 90°C  
inlet 3/4" - two outlets ø 13.5 mm



THIRODE 241447

THIRODE 241754

**3120021 ADJUSTER FOR INLET ELBI BLACK**  
flow rate 12 L/min - tolerance +/- 15%



# THIRODE

Suitable for:

**3120017 ADJUSTER FOR OUTLET ELBI ORANGE**  
flow rate 2.5 L/min - tolerance +/- 25%



**3120203 ADJUSTER FOR OUTLET ELBI WHITE**  
flow rate 2 L/min - tolerance +/- 25%



**3120000 FILTER FOR INLET SOLENOID VALVE ELBI**



**3120019 ADJUSTER FOR INLET ELBI BLACK**  
flow rate 5.5 L/min - tolerance +/- 15%



**3120022 ADJUSTER FOR INLET ELBI BLACK**  
flow rate 16 L/min - tolerance +/- 15%





Suitable for:

**3120037 ADJUSTER FOR OUTLET ELBI GREEN**  
flow rate 0.25 L/min - tolerance +/- 25%



**3120016 ADJUSTER FOR OUTLET ELBI NEUTRAL**  
flow rate 1.2 L/min - tolerance +/- 25%



**3120015 ADJUSTER FOR OUTLET ELBI RED**  
flow rate 0.5 L/min - tolerance +/- 25%



**3120202 ADJUSTER FOR OUTLET ELBI YELLOW**  
flow rate 0.35 L/min / tolerance +/- 25%



**3120204 OUTLET ADJUSTER ELBI BLACK**  
flow rate 5.5 L/min - tolerance +/- 25%



**3120405 SOLEN. VALVE T&P 1 WAY 180°**  
230V 50/60Hz - max. temperature 90°C  
inlet 3/4" - outlet ø 10.5 mm



# THIRODE

Suitable for:

**3120201 ADJUSTER FOR OUTLET ELBI GREY**  
flow rate 4.7 L/min - tolerance +/- 25%



**3120017 ADJUSTER FOR OUTLET ELBI ORANGE**  
flow rate 2.5 L/min - tolerance +/- 25%



**3120203 ADJUSTER FOR OUTLET ELBI WHITE**  
flow rate 2 L/min - tolerance +/- 25%



**3120000 FILTER FOR INLET SOLENOID VALVE ELBI**



**3120421 ADJUSTER FOR OUTLET T&P BLACK**  
flow rate 5 L/min - tolerance +/- 20%





Suitable for:

**3120608 ADJUSTER FOR OUTLET T&P DARK BROWN**  
flow rate 1.2 L/min - tolerance +/- 25%



**3120391 ADJUSTER FOR OUTLET T&P LIGHT BLUE**  
flow rate 1 L/min - tolerance +/- 25%



**3120423 ADJUSTER FOR OUTLET T&P ORANGE**  
flow rate 0.5 L/min - tolerance +/- 25%



**3120386 ADJUSTER FOR OUTLET T&P WHITE**  
flow rate 0.8 L/min - tolerance +/- 25%



**D120056 ADJUSTER INLET T&P BRONZE**  
flowrate 12 L/min



**D120057 ADJUSTER INLET T&P LIGHT BROWN**  
flowrate 16 L/min



# THIRODE

Suitable for:

**3120568 ADJUSTER FOR OUTLET T&P GREEN**  
flow rate 3 L/min - tolerance +/- 25%



**3120387 ADJUSTER FOR OUTLET T&P LIGHT BROWN**  
flow rate 1.5 L/min - tolerance +/- 25%



**3120424 ADJUSTER FOR OUTLET T&P RED**  
flow rate 0.25 L/min - tolerance +/- 25%



**3120422 ADJUSTER FOR OUTLET T&P YELLOW**  
flow rate 2.5 L/min - tolerance +/- 25%



**D120054 ADJUSTER INLET T&P GREY**  
flowrate 6 L/min



**D120058 ADJUSTER INLET T&P ORANGE**  
flowrate 20 L/min





Suitable for:

**D120052 ADJUSTER INLET T&P RED**  
flowrate 3 L/min



**D120053 ADJUSTER INLET T&P YELLOW**  
flowrate 5.5 L/min



**3120431 COIL T&P 12Vac 50/60Hz**  
for solenoid valves T&P



**D120090 COIL T&P 120V 60Hz 8VA**  
for solenoid valves T&P



**3120432 COIL T&P 24Vac 50/60Hz**  
for solenoid valves T&P



**3120409 SOLEN. VALVE T&P 1 WAY 180°**  
230V 50/60Hz - max. temperature 90°C  
inlet 3/4" - outlet ø 13.5 mm



# THIRODE



Suitable for:

**D120055 ADJUSTER INLET T&P WHITE**  
flowrate 10 L/min



**D120059 ADJUSTER OUTLET T&P BLUE**  
flow rate 8 L/min - tolerance +/-25%



**D120092 COIL T&P 12Vdc**  
for solenoid valves T&P



**3120433 COIL T&P 220V 50/60Hz**  
for solenoid valves T&P



**D120093 COIL T&P 24Vdc**  
for solenoid valves T&P



**3120421 ADJUSTER FOR OUTLET T&P BLACK**  
flow rate 5 L/min - tolerance +/- 20%





Suitable for:

**3120608 ADJUSTER FOR OUTLET T&P DARK BROWN**  
flow rate 1.2 L/min - tolerance +/- 25%



**3120391 ADJUSTER FOR OUTLET T&P LIGHT BLUE**  
flow rate 1 L/min - tolerance +/- 25%



**3120423 ADJUSTER FOR OUTLET T&P ORANGE**  
flow rate 0.5 L/min - tolerance +/- 25%



**3120386 ADJUSTER FOR OUTLET T&P WHITE**  
flow rate 0.8 L/min - tolerance +/- 25%



**D120056 ADJUSTER INLET T&P BRONZE**  
flowrate 12 L/min



**D120057 ADJUSTER INLET T&P LIGHT BROWN**  
flowrate 16 L/min



# THIRODE

Suitable for:

**3120568 ADJUSTER FOR OUTLET T&P GREEN**  
flow rate 3 L/min - tolerance +/- 25%



**3120387 ADJUSTER FOR OUTLET T&P LIGHT BROWN**  
flow rate 1.5 L/min - tolerance +/- 25%



**3120424 ADJUSTER FOR OUTLET T&P RED**  
flow rate 0.25 L/min - tolerance +/- 25%



**3120422 ADJUSTER FOR OUTLET T&P YELLOW**  
flow rate 2.5 L/min - tolerance +/- 25%



**D120054 ADJUSTER INLET T&P GREY**  
flowrate 6 L/min



**D120058 ADJUSTER INLET T&P ORANGE**  
flowrate 20 L/min







Suitable for:

**D120052 ADJUSTER INLET T&P RED**  
flowrate 3 L/min



**D120053 ADJUSTER INLET T&P YELLOW**  
flowrate 5.5 L/min



**3120431 COIL T&P 12Vac 50/60Hz**  
for solenoid valves T&P



**D120090 COIL T&P 120V 60Hz 8VA**  
for solenoid valves T&P



**3120432 COIL T&P 24Vac 50/60Hz**  
for solenoid valves T&P



**3120408 SOLEN. VALVE T&P 1 WAY 90°**  
230V 50/60Hz - max. temperature 90°C  
inlet 3/4" - outlet ø 13.5 mm



THIRODE 23458

THIRODE 914100

# THIRODE

Suitable for:

**D120055 ADJUSTER INLET T&P WHITE**  
flowrate 10 L/min



**D120059 ADJUSTER OUTLET T&P BLUE**  
flow rate 8 L/min - tolerance +/-25%



**D120092 COIL T&P 12Vdc**  
for solenoid valves T&P



**3120433 COIL T&P 220V 50/60Hz**  
for solenoid valves T&P



**D120093 COIL T&P 24Vdc**  
for solenoid valves T&P



**3120421 ADJUSTER FOR OUTLET T&P BLACK**  
flow rate 5 L/min - tolerance +/- 20%





Suitable for:

**3120608 ADJUSTER FOR OUTLET T&P DARK BROWN**  
flow rate 1.2 L/min - tolerance +/- 25%



**3120391 ADJUSTER FOR OUTLET T&P LIGHT BLUE**  
flow rate 1 L/min - tolerance +/- 25%



**3120423 ADJUSTER FOR OUTLET T&P ORANGE**  
flow rate 0.5 L/min - tolerance +/- 25%



**3120386 ADJUSTER FOR OUTLET T&P WHITE**  
flow rate 0.8 L/min - tolerance +/- 25%



**D120056 ADJUSTER INLET T&P BRONZE**  
flowrate 12 L/min



**D120057 ADJUSTER INLET T&P LIGHT BROWN**  
flowrate 16 L/min



# THIRODE

Suitable for:

**3120568 ADJUSTER FOR OUTLET T&P GREEN**  
flow rate 3 L/min - tolerance +/- 25%



**3120387 ADJUSTER FOR OUTLET T&P LIGHT BROWN**  
flow rate 1.5 L/min - tolerance +/- 25%



**3120424 ADJUSTER FOR OUTLET T&P RED**  
flow rate 0.25 L/min - tolerance +/- 25%



**3120422 ADJUSTER FOR OUTLET T&P YELLOW**  
flow rate 2.5 L/min - tolerance +/- 25%



**D120054 ADJUSTER INLET T&P GREY**  
flowrate 6 L/min



**D120058 ADJUSTER INLET T&P ORANGE**  
flowrate 20 L/min





Suitable for:

**D120052 ADJUSTER INLET T&P RED**  
flowrate 3 L/min



**D120053 ADJUSTER INLET T&P YELLOW**  
flowrate 5.5 L/min




**3120431 COIL T&P 12Vac 50/60Hz**  
for solenoid valves T&P




**D120090 COIL T&P 120V 60Hz 8VA**  
for solenoid valves T&P



**3120432 COIL T&P 24Vac 50/60Hz**  
for solenoid valves T&P



**3120407 SOLEN. VALVE T&P 2 WAY 180°**  
230V 50/60Hz - max. temperature 90°C  
inlet 3/4" - two outlets ø 10.5 mm



THIRODE 147152  
THIRODE 634086

THIRODE 1700434

THIRODE 3697E

# THIRODE

Suitable for:

**D120055 ADJUSTER INLET T&P WHITE**  
flowrate 10 L/min




**D120059 ADJUSTER OUTLET T&P BLUE**  
flow rate 8 L/min - tolerance +/-25%



**D120092 COIL T&P 12Vdc**  
for solenoid valves T&P



**3120433 COIL T&P 220V 50/60Hz**  
for solenoid valves T&P



**D120093 COIL T&P 24Vdc**  
for solenoid valves T&P



**3120421 ADJUSTER FOR OUTLET T&P BLACK**  
flow rate 5 L/min - tolerance +/- 20%





Suitable for:

**3120608 ADJUSTER FOR OUTLET T&P DARK BROWN**  
flow rate 1.2 L/min - tolerance +/- 25%



**3120391 ADJUSTER FOR OUTLET T&P LIGHT BLUE**  
flow rate 1 L/min - tolerance +/- 25%



**3120423 ADJUSTER FOR OUTLET T&P ORANGE**  
flow rate 0.5 L/min - tolerance +/- 25%



**3120386 ADJUSTER FOR OUTLET T&P WHITE**  
flow rate 0.8 L/min - tolerance +/- 25%



**D120056 ADJUSTER INLET T&P BRONZE**  
flowrate 12 L/min



**D120057 ADJUSTER INLET T&P LIGHT BROWN**  
flowrate 16 L/min



# THIRODE

Suitable for:

**3120568 ADJUSTER FOR OUTLET T&P GREEN**  
flow rate 3 L/min - tolerance +/- 25%



**3120387 ADJUSTER FOR OUTLET T&P LIGHT BROWN**  
flow rate 1.5 L/min - tolerance +/- 25%



**3120424 ADJUSTER FOR OUTLET T&P RED**  
flow rate 0.25 L/min - tolerance +/- 25%



**3120422 ADJUSTER FOR OUTLET T&P YELLOW**  
flow rate 2.5 L/min - tolerance +/- 25%



**D120054 ADJUSTER INLET T&P GREY**  
flowrate 6 L/min



**D120058 ADJUSTER INLET T&P ORANGE**  
flowrate 20 L/min





Suitable for:

**D120052 ADJUSTER INLET T&P RED**  
flowrate 3 L/min



**D120053 ADJUSTER INLET T&P YELLOW**  
flowrate 5.5 L/min



**3120431 COIL T&P 12Vac 50/60Hz**  
for solenoid valves T&P



**D120090 COIL T&P 120V 60Hz 8VA**  
for solenoid valves T&P



**3120432 COIL T&P 24Vac 50/60Hz**  
for solenoid valves T&P



**3120410 SOLEN. VALVE T&P 2 WAY 90°**  
230V 50/60Hz - max. temperature 90°C  
inlet 3/4" - two outlets ø 13.5 mm



# THIRODE



Suitable for:

**D120055 ADJUSTER INLET T&P WHITE**  
flowrate 10 L/min




**D120059 ADJUSTER OUTLET T&P BLUE**  
flow rate 8 L/min - tolerance +/-25%



**D120092 COIL T&P 12Vdc**  
for solenoid valves T&P



**3120433 COIL T&P 220V 50/60Hz**  
for solenoid valves T&P



**D120093 COIL T&P 24Vdc**  
for solenoid valves T&P



**3120421 ADJUSTER FOR OUTLET T&P BLACK**  
flow rate 5 L/min - tolerance +/- 20%





Suitable for:

**3120608 ADJUSTER FOR OUTLET T&P DARK BROWN**  
flow rate 1.2 L/min - tolerance +/- 25%



**3120391 ADJUSTER FOR OUTLET T&P LIGHT BLUE**  
flow rate 1 L/min - tolerance +/- 25%



**3120423 ADJUSTER FOR OUTLET T&P ORANGE**  
flow rate 0.5 L/min - tolerance +/- 25%



**3120386 ADJUSTER FOR OUTLET T&P WHITE**  
flow rate 0.8 L/min - tolerance +/- 25%



**D120056 ADJUSTER INLET T&P BRONZE**  
flowrate 12 L/min



**D120057 ADJUSTER INLET T&P LIGHT BROWN**  
flowrate 16 L/min



# THIRODE

Suitable for:

**3120568 ADJUSTER FOR OUTLET T&P GREEN**  
flow rate 3 L/min - tolerance +/- 25%



**3120387 ADJUSTER FOR OUTLET T&P LIGHT BROWN**  
flow rate 1.5 L/min - tolerance +/- 25%



**3120424 ADJUSTER FOR OUTLET T&P RED**  
flow rate 0.25 L/min - tolerance +/- 25%



**3120422 ADJUSTER FOR OUTLET T&P YELLOW**  
flow rate 2.5 L/min - tolerance +/- 25%



**D120054 ADJUSTER INLET T&P GREY**  
flowrate 6 L/min



**D120058 ADJUSTER INLET T&P ORANGE**  
flowrate 20 L/min





Suitable for:

**D120052 ADJUSTER INLET T&P RED**  
flowrate 3 L/min



**D120053 ADJUSTER INLET T&P YELLOW**  
flowrate 5.5 L/min




**3120431 COIL T&P 12Vac 50/60Hz**  
for solenoid valves T&P



**D120090 COIL T&P 120V 60Hz 8VA**  
for solenoid valves T&P



**3120432 COIL T&P 24Vac 50/60Hz**  
for solenoid valves T&P



**3120013 SOLENOID VALVE ELBI TYPE 359 3-WAY 90°**  
220/240V 50/60Hz - max. temperature 90°C  
inlet 3/4" - three outlets ø 10.5 mm



# THIRODE



Suitable for:

**D120055 ADJUSTER INLET T&P WHITE**  
flowrate 10 L/min



**D120059 ADJUSTER OUTLET T&P BLUE**  
flow rate 8 L/min - tolerance +/-25%



**D120092 COIL T&P 12Vdc**  
for solenoid valves T&P



**3120433 COIL T&P 220V 50/60Hz**  
for solenoid valves T&P



**D120093 COIL T&P 24Vdc**  
for solenoid valves T&P



**3120019 ADJUSTER FOR INLET ELBI BLACK**  
flow rate 5.5 L/min - tolerance +/- 15%





Suitable for:

**3120021 ADJUSTER FOR INLET ELBI BLACK**  
flow rate 12 L/min - tolerance +/- 15%



**3120037 ADJUSTER FOR OUTLET ELBI GREEN**  
flow rate 0.25 L/min - tolerance +/- 25%



**3120016 ADJUSTER FOR OUTLET ELBI NEUTRAL**  
flow rate 1.2 L/min - tolerance +/- 25%



**3120015 ADJUSTER FOR OUTLET ELBI RED**  
flow rate 0.5 L/min - tolerance +/- 25%



**3120202 ADJUSTER FOR OUTLET ELBI YELLOW**  
flow rate 0.35 L/min / tolerance +/- 25%



**3120204 OUTLET ADJUSTER ELBI BLACK**  
flow rate 5.5 L/min - tolerance +/- 25%



# THIRODE

Suitable for:

**3120022 ADJUSTER FOR INLET ELBI BLACK**  
flow rate 16 L/min - tolerance +/- 15%



**3120201 ADJUSTER FOR OUTLET ELBI GREY**  
flow rate 4.7 L/min - tolerance +/- 25%



**3120017 ADJUSTER FOR OUTLET ELBI ORANGE**  
flow rate 2.5 L/min - tolerance +/- 25%



**3120203 ADJUSTER FOR OUTLET ELBI WHITE**  
flow rate 2 L/min - tolerance +/- 25%




**3120000 FILTER FOR INLET SOLENOID VALVE ELBI**





Suitable for:

**3120014 SOLENOID VALVE ELBI TYPE 369 3-WAY 180°**  
 220/240V 50/60Hz - max temperature 90°C  
 inlet 3/4" - three outlets ø 10.5 mm



THIRODE 147723

**3120021 ADJUSTER FOR INLET ELBI BLACK**  
 flow rate 12 L/min - tolerance +/- 15%



Suitable for:

**3120019 ADJUSTER FOR INLET ELBI BLACK**  
 flow rate 5.5 L/min - tolerance +/- 15%



**3120022 ADJUSTER FOR INLET ELBI BLACK**  
 flow rate 16 L/min - tolerance +/- 15%



**3120037 ADJUSTER FOR OUTLET ELBI GREEN**  
 flow rate 0.25 L/min - tolerance +/- 25%



**3120201 ADJUSTER FOR OUTLET ELBI GREY**  
 flow rate 4.7 L/min - tolerance +/- 25%



**3120016 ADJUSTER FOR OUTLET ELBI NEUTRAL**  
 flow rate 1.2 L/min - tolerance +/- 25%



**3120017 ADJUSTER FOR OUTLET ELBI ORANGE**  
 flow rate 2.5 L/min - tolerance +/- 25%



**3120015 ADJUSTER FOR OUTLET ELBI RED**  
 flow rate 0.5 L/min - tolerance +/- 25%



**3120203 ADJUSTER FOR OUTLET ELBI WHITE**  
 flow rate 2 L/min - tolerance +/- 25%



**3120202 ADJUSTER FOR OUTLET ELBI YELLOW**  
 flow rate 0.35 L/min / tolerance +/- 25%



**3120000 FILTER FOR INLET SOLENOID VALVE ELBI**





Suitable for:

**3120204 OUTLET ADJUSTER ELBI BLACK**  
flow rate 5.5 L/min - tolerance +/- 25%



# THIRODE




Suitable for:

**3120426 SOLENOID VALVE ROBERTSHAW 4 WAY 180°**  
230V 50/60Hz - max temperature 90°C  
inlet 3/4" - four outlets ø 10.5 mm  
operating pressure from 0.2 to 10 bar



**3120473 ADJUSTER FOR INLET ROBERTSHAW BROWN**  
flow rate 5 L/min - tolerance +/- 15%



THIRODE 147793

**3120474 ADJUSTER FOR INLET ROBERTSHAW DARK BLUE**  
flow rate 6 L/min - tolerance +/- 15%



**3120478 ADJUSTER FOR INLET ROBERTSHAW GREEN**  
flow rate 11 L/min - tolerance +/- 15%



**3120479 ADJUSTER FOR INLET ROBERTSHAW GREY**  
flow rate 12 L/min - tolerance +/- 15%



**3120476 ADJUSTER FOR INLET ROBERTSHAW LIGHT BLUE**  
flow rate 9 L/min - tolerance +/- 15%



**3120475 ADJUSTER FOR INLET ROBERTSHAW ORANGE**  
flow rate 8 L/min - tolerance +/- 15%



**3120472 ADJUSTER FOR INLET ROBERTSHAW PURPLE**  
flow rate 4 L/min - tolerance +/- 15%



**3120477 ADJUSTER FOR INLET ROBERTSHAW WHITE**  
flow rate 10 L/min - tolerance +/- 15%



**3120481 ADJUSTER FOR INLET ROBERTSHAW YELLOW**  
flow rate 14.5 L/min - tolerance +/- 15%





Suitable for:

**3120499 ADJUSTER FOR OUTLET ROBERTSHAW BLU**  
flow rate 1.2 L/min - tolerance +/- 25%



**3120488 ADJUSTER FOR OUTLET ROBERTSHAW PINK**  
flow rate 3.3 L/min - tolerance +/- 20%



**3120483 ADJUSTER FOR OUTLET ROBERTSHAW YELLOW**  
flow rate 0.5 L/min - tolerance +/- 15%



**3120485 OUTLET ADJUSTER ROBERTSHAW LIGHT BROWN**  
flow rate 1.3 L/min - tolerance +/- 25%



**3120625 OUTLET REDUCER ROBERTSHAW GRIGIO**  
flow rate 0.35 L/min - tolerance +/- 10%



**3120404 SOLENOID VALVE T&P 1 WAY 90°**  
230V 50/60Hz - max. temperature 90°C  
inlet 3/4" con riduttore di portata 10 L/min  
outlet ø 10.5 mm



# THIRODE

Suitable for:

**3120484 ADJUSTER FOR OUTLET ROBERTSHAW GREEN**  
flow rate 0.8 L/min - tolerance +/- 25%



**3120482 ADJUSTER FOR OUTLET ROBERTSHAW WHITE**  
flow rate 0.25 L/min - tolerance +/- 10%



**3120487 OUTLET ADJUSTER ROBERTSHAW DARK BROWN**  
flow rate 2.5 L/min - tolerance +/- 20%



**3120486 OUTLET ADJUSTER ROBERTSHAW LIGHT GREEN**  
flow rate 2 L/min - tolerance +/- 25%



**3120421 ADJUSTER FOR OUTLET T&P BLACK**  
flow rate 5 L/min - tolerance +/- 20%





Suitable for:

**3120608 ADJUSTER FOR OUTLET T&P DARK BROWN**  
flow rate 1.2 L/min - tolerance +/- 25%



**3120391 ADJUSTER FOR OUTLET T&P LIGHT BLUE**  
flow rate 1 L/min - tolerance +/- 25%



**3120423 ADJUSTER FOR OUTLET T&P ORANGE**  
flow rate 0.5 L/min - tolerance +/- 25%



**3120386 ADJUSTER FOR OUTLET T&P WHITE**  
flow rate 0.8 L/min - tolerance +/- 25%



**D120056 ADJUSTER INLET T&P BRONZE**  
flowrate 12 L/min



**D120057 ADJUSTER INLET T&P LIGHT BROWN**  
flowrate 16 L/min



# THIRODE

Suitable for:

**3120568 ADJUSTER FOR OUTLET T&P GREEN**  
flow rate 3 L/min - tolerance +/- 25%



**3120387 ADJUSTER FOR OUTLET T&P LIGHT BROWN**  
flow rate 1.5 L/min - tolerance +/- 25%



**3120424 ADJUSTER FOR OUTLET T&P RED**  
flow rate 0.25 L/min - tolerance +/- 25%



**3120422 ADJUSTER FOR OUTLET T&P YELLOW**  
flow rate 2.5 L/min - tolerance +/- 25%



**D120054 ADJUSTER INLET T&P GREY**  
flowrate 6 L/min



**D120058 ADJUSTER INLET T&P ORANGE**  
flowrate 20 L/min





Suitable for:

**D120052 ADJUSTER INLET T&P RED**  
flowrate 3 L/min



**D120053 ADJUSTER INLET T&P YELLOW**  
flowrate 5.5 L/min



**3120431 COIL T&P 12Vac 50/60Hz**  
for solenoid valves T&P



**D120090 COIL T&P 120V 60Hz 8VA**  
for solenoid valves T&P



**3120432 COIL T&P 24Vac 50/60Hz**  
for solenoid valves T&P



**3120414 SOLENOID VALVE T&P 3-WAY 180°**  
230V 50/60Hz - max. temperature 90°C  
inlet 3/4" with flowrate adjuster 10 L/min  
three ø 10.5 mm outlets



THIRODE 314345

THIRODE 3664E

# THIRODE



Suitable for:

**D120055 ADJUSTER INLET T&P WHITE**  
flowrate 10 L/min




**D120059 ADJUSTER OUTLET T&P BLUE**  
flow rate 8 L/min - tolerance +/-25%



**D120092 COIL T&P 12Vdc**  
for solenoid valves T&P



**3120433 COIL T&P 220V 50/60Hz**  
for solenoid valves T&P



**D120093 COIL T&P 24Vdc**  
for solenoid valves T&P



**3120421 ADJUSTER FOR OUTLET T&P BLACK**  
flow rate 5 L/min - tolerance +/- 20%





Suitable for:

**3120608 ADJUSTER FOR OUTLET T&P DARK BROWN**  
flow rate 1.2 L/min - tolerance +/- 25%



**3120391 ADJUSTER FOR OUTLET T&P LIGHT BLUE**  
flow rate 1 L/min - tolerance +/- 25%



**3120423 ADJUSTER FOR OUTLET T&P ORANGE**  
flow rate 0.5 L/min - tolerance +/- 25%



**3120386 ADJUSTER FOR OUTLET T&P WHITE**  
flow rate 0.8 L/min - tolerance +/- 25%



**D120056 ADJUSTER INLET T&P BRONZE**  
flowrate 12 L/min



**D120057 ADJUSTER INLET T&P LIGHT BROWN**  
flowrate 16 L/min



# THIRODE

Suitable for:

**3120568 ADJUSTER FOR OUTLET T&P GREEN**  
flow rate 3 L/min - tolerance +/- 25%



**3120387 ADJUSTER FOR OUTLET T&P LIGHT BROWN**  
flow rate 1.5 L/min - tolerance +/- 25%



**3120424 ADJUSTER FOR OUTLET T&P RED**  
flow rate 0.25 L/min - tolerance +/- 25%



**3120422 ADJUSTER FOR OUTLET T&P YELLOW**  
flow rate 2.5 L/min - tolerance +/- 25%



**D120054 ADJUSTER INLET T&P GREY**  
flowrate 6 L/min



**D120058 ADJUSTER INLET T&P ORANGE**  
flowrate 20 L/min





Suitable for:

**D120052 ADJUSTER INLET T&P RED**  
flowrate 3 L/min



**D120053 ADJUSTER INLET T&P YELLOW**  
flowrate 5.5 L/min




**3120431 COIL T&P 12Vac 50/60Hz**  
for solenoid valves T&P



**D120090 COIL T&P 120V 60Hz 8VA**  
for solenoid valves T&P



**3120432 COIL T&P 24Vac 50/60Hz**  
for solenoid valves T&P



**D120087 SOLENOID VALVE T&P 3-WAY 90°**  
220/240V 50/60Hz - max. temperature 90°C  
inlet 3/4" - three outlets ø 13.5 mm - universal



# THIRODE



Suitable for:

**D120055 ADJUSTER INLET T&P WHITE**  
flowrate 10 L/min



**D120059 ADJUSTER OUTLET T&P BLUE**  
flow rate 8 L/min - tolerance +/-25%



**D120092 COIL T&P 12Vdc**  
for solenoid valves T&P



**3120433 COIL T&P 220V 50/60Hz**  
for solenoid valves T&P



**D120093 COIL T&P 24Vdc**  
for solenoid valves T&P



**3120421 ADJUSTER FOR OUTLET T&P BLACK**  
flow rate 5 L/min - tolerance +/- 20%





Suitable for:

**3120608 ADJUSTER FOR OUTLET T&P DARK BROWN**  
flow rate 1.2 L/min - tolerance +/- 25%



**3120391 ADJUSTER FOR OUTLET T&P LIGHT BLUE**  
flow rate 1 L/min - tolerance +/- 25%



**3120423 ADJUSTER FOR OUTLET T&P ORANGE**  
flow rate 0.5 L/min - tolerance +/- 25%



**3120386 ADJUSTER FOR OUTLET T&P WHITE**  
flow rate 0.8 L/min - tolerance +/- 25%



**D120056 ADJUSTER INLET T&P BRONZE**  
flowrate 12 L/min



**D120057 ADJUSTER INLET T&P LIGHT BROWN**  
flowrate 16 L/min



# THIRODE

Suitable for:

**3120568 ADJUSTER FOR OUTLET T&P GREEN**  
flow rate 3 L/min - tolerance +/- 25%



**3120387 ADJUSTER FOR OUTLET T&P LIGHT BROWN**  
flow rate 1.5 L/min - tolerance +/- 25%



**3120424 ADJUSTER FOR OUTLET T&P RED**  
flow rate 0.25 L/min - tolerance +/- 25%



**3120422 ADJUSTER FOR OUTLET T&P YELLOW**  
flow rate 2.5 L/min - tolerance +/- 25%



**D120054 ADJUSTER INLET T&P GREY**  
flowrate 6 L/min



**D120058 ADJUSTER INLET T&P ORANGE**  
flowrate 20 L/min







Suitable for:

**D120052 ADJUSTER INLET T&P RED**  
flowrate 3 L/min



**D120053 ADJUSTER INLET T&P YELLOW**  
flowrate 5.5 L/min



**3120431 COIL T&P 12Vac 50/60Hz**  
for solenoid valves T&P



**D120090 COIL T&P 120V 60Hz 8VA**  
for solenoid valves T&P



**3120432 COIL T&P 24Vac 50/60Hz**  
for solenoid valves T&P



# THIRODE



Suitable for:

**D120055 ADJUSTER INLET T&P WHITE**  
flowrate 10 L/min



**D120059 ADJUSTER OUTLET T&P BLUE**  
flow rate 8 L/min - tolerance +/-25%



**D120092 COIL T&P 12Vdc**  
for solenoid valves T&P



**3120433 COIL T&P 220V 50/60Hz**  
for solenoid valves T&P



**D120093 COIL T&P 24Vdc**  
for solenoid valves T&P



## Spark generators

**3181002 SPARK GENERATOR 2 OUTLETS**  
220/240V 50/60Hz  
for Kitchen (THIRODE) B7.FV.CF.FG



THIRODE 308465

**3181003 SPARK GENERATOR 4 OUTLETS**  
220/240V 50/60Hz  
for Kitchen (THIRODE) B7.FV.CF.FG



THIRODE 308466

THIRODE 308467



Suitable for:

# THIRODE



Suitable for:

## Sparking and detection plugs

**3806001 IGNITION PLUG ROUND  $\varnothing$  6x44 mm**  
fitting M8x10 mm - complete with fastening nut  
overall length 75 mm  
for pilot burner Honeywell serie Q327-Q349



THIRODE 310215

**3020060 IGNITION PLUG ROUND  $\varnothing$  7x44 mm**  
M faston M 4x1 mm  
overall length 82 mm  
model CB505/021 Junkers  
for model P502F



THIRODE 308480

**3020124 IGNITION PLUG ROUND  $\varnothing$  7x44 mm**  
connection  $\varnothing$  2.4 mm  
overall length 58 mm



THIRODE 7455048

**3806002 ROUND IGNITION PLUG  $\varnothing$  7x45 mm**  
faston F 3.2 mm  
fitting  $\varnothing$  1/8"  
with cable length 1300 mm  
overall length with cable 1366 mm  
for Bratt pan gas (THIRODE) SA41BMFIG  
for Fryer electric (THIRODE) FR18 - FR25



THIRODE 308468

THIRODE 308469

## Springs

**3250230 LID SPRING  $\varnothing$  30x200 mm**



THIRODE 385051

**3027001 THREADED ROD  $\varnothing$  8x330 mm**  
for BRATT PAN B9PSA50G



THIRODE 368358

**3250231 OVEN DOOR SPRING  $\varnothing$  24x81 mm**  
for OVEN B9FV800FG



THIRODE 385420

**3027001 THREADED ROD  $\varnothing$  8x330 mm**  
for BRATT PAN B9PSA50G



THIRODE 368358



## Switches

**3319529 BIPOLAR SWITCH BLACK 10A 250V**  
 16(4)A 250V - max. temperature 120°C  
 mounting hole 22x30 mm - silk screen printing 0 -



THIRODE 905914

**3319779 BLOCK CONNECTIONS BLACK 22x30 mm**



**3319783 FRAME SAFETY 4 SIDES BLACK 22x30 mm**



**3319780 BLOCK CONNECTION WHITE 22x30 mm**



**3319782 FRAME SAFETY 2 SIDES BLACK 22x30 mm**



**3319501 PUSH-BUTTON PROTECTION CAP**  
 external dimensions 29x36 mm  
 for switches with mounting hole 22x30 mm



**3319371 BIPOLAR SWITCH BLACK 16A 250V**  
 16(4)A 250V  
 silk screen printing 0 - I  
 max. temperature 120°C  
 mounting hole 22x30 mm



THIRODE 905913

**3319779 BLOCK CONNECTIONS BLACK 22x30 mm**



**3319780 BLOCK CONNECTION WHITE 22x30 mm**



**3319782 FRAME SAFETY 2 SIDES BLACK 22x30 mm**





Suitable for:

**3319783 FRAME SAFETY 4 SIDES BLACK 22x30 mm**



# THIRODE



Suitable for:

**3319501 PUSH-BUTTON PROTECTION CAP**  
external dimensions 29x36 mm  
for switches with mounting hole 22x30 mm



**3319733 BLACK UNIPOLAR PUSH-BUTTON**  
mounting hole 14x17 mm  
for Kitchen (THIRODE) B7.FV.CF.FG  
for Kitchen (THIRODE) B7.FV.CF.FG



THIRODE 300157

THIRODE 302556

## Tangential and radial motor fans

**3526170 TANGENTIAL FAN 180 mm RH**  
230V 50Hz -  $\varnothing$  60 mm  
with wire heating element 2000W 230V  
operating temperature  $-30+135^{\circ}\text{C}$   
for Warm table (THIRODE) ETV1500 124146  
SE.EBM1500 124560




THIRODE 135557

THIRODE 304237

**3355363 HEATING ELEMENT 2000W 230V**  
length 200 mm - width 35 mm  
for 180 mm tangential fan



**3526153 TANGENTIAL FAN 180 mm RH**  
25W 230V 50/60Hz -  $\varnothing$  60 mm  
operating temperature  $-30^{\circ}+100^{\circ}\text{C}$



**3526160 TANGENTIAL FAN 180x180 mm**  
28W - 230V 50/60Hz -  $\varnothing$  60 mm DOUBLE  
 $T^{\circ}\text{max } 60^{\circ}\text{C}$



THIRODE 504365


**7103628 HEATING ELEMENT 2000W 230V**  
length 195 mm - width 38 mm  
for tangential ventilator 180 mm  
with cable length 230 mm





## Taps for tank refilling

- 3359330 TAP WATER INLET  $\varnothing$  1/2"MM-1/8"FF**  
 fittings  $\varnothing$  1/2"MM -  $\varnothing$  1/8"FF  
 for Boiling pan (THIRODE)



THIRODE 313054

## Terminal blocks

- 3247009 TERMINAL BLOCK 6-POLES FV122/B 40A 600V**  
 for cable max 6 mm<sup>2</sup>  
 operating temperature 150°C  
 nominal voltage 450 V



THIRODE 306090

## Thermocouples and accessories

- 3440019 EXTENSION FOR THERMOCOUPLE M9x1 60 cm.**  
 female nut M9x1



THIRODE 7492000

- 3440015 INTERRUPTION CONNECTOR M9x1**



THIRODE 905680

- 3440074 THERMOCOUPLE LF 90 cm**  
 7 slotted elements kit



THIRODE 634321

- 3440154 THERMOCOUPLE M9x1 90 cm**  
 bulb  $\varnothing$  10x54 mm - with fixing connection M11x1  
 for PILOT HONEYWELL Q349-Q327  
 for Bratt pan (THIRODE) 125505



THIRODE 310144

- 3440057 THERMOCOUPLE SIT M8x1 150 cm THREAD M8x1**



THIRODE 310193


- 3440064 NUT FOR THERMOCOUPLE M8x1**





Suitable for:

**3440857 THERMOCOUPLE SIT M8x1 150 cm - 10 PCS  
CONNECTOR M8x1**



# THIRODE

Suitable for:



**2101036 THERMOCOUPLE SIT M9x1 120 cm  
ALUMINIZED HEAD**



THIRODE 310277

THIRODE 7473029

**3440038 THERMOCOUPLE SIT M9x1 120 cm**



**3440838 THERMOCOUPLE SIT M9x1 120 cm - 10 PCS**



THIRODE 310277

**3440039 THERMOCOUPLE SIT M9x1 150 cm**



**3440839 THERMOCOUPLE SIT M9x1 150 cm - 10 PCS**



THIRODE 7473034

**2111641 THERMOCOUPLE SIT M9x1 85 cm  
ALUMINIUM HEAD**



**3440899 THERMOCOUPLE SIT M9x1 85 cm - 10 PCS  
ALUMINIZED HEAD**



THIRODE 310276

**3440036 THERMOCOUPLE SIT M9x1 85 cm.**



**3440836 THERMOCOUPLE SIT M9x1 85 cm - 10 PCS**




THIRODE 7473056

Suitable for:

Suitable for:

**3440165 THERMOCOUPLE 11/32 P.ASA 60 cm COUPLING**  
with fitting M11x1

**3440064 NUT FOR THERMOCOUPLE M8x1**



THIRODE

**3440099 UNIVERSAL THERMOCOUPLE 120 cm**  
10 slotted elements kit




THIRODE 7473055

## Thermostatic gas valves

**3345018 THERMOSTATIC TAP 25ST**  
operating temperature 100-300°C  
connections M16x1.5 mm  
thermocouple connection M9x1  
bulb  $\varnothing$  6x75 mm  
capillary length 1200 mm  
D-shaped pin  $\varnothing$  8x6.5 mm

**3348038 OLIVE FOR PIPE  $\varnothing$  10 mm**  
for model PEL 22-24-25



THIRODE 310137

**3348044 OLIVE FOR PIPE  $\varnothing$  10 mm**  
for model PEL 20-21-24-25

**3020082 OLIVE FOR PIPE  $\varnothing$  12 mm**  
for model PEL 22-24-25



**3348036 OLIVE FOR PIPE  $\varnothing$  4 mm**  
for model PEL 21-22-24-25

**3348037 OLIVE FOR PIPE  $\varnothing$  6 mm**  
for model PEL 21-22-24-25





Suitable for:

**3348031** PIPE FITTING  $\varnothing$  10 mm  
thread M20x1.5 mm  
for model PEL 22-24-25



**3348032** PIPE FITTING  $\varnothing$  12 mm  
thread M20x1.5 mm  
for model PEL 22-24-25



**3348029** PIPE FITTING  $\varnothing$  4 mm  
thread M10x1 mm  
for model PEL 21-22-24-25



**5014757** PIPE FITTING  $\varnothing$  6 mm  
thread M10x1 mm



## THIRODE

Suitable for:


**3348043** PIPE FITTING  $\varnothing$  10 mm  
thread M16x1.5 mm  
for model PEL 20-21-24-25



**3020077** PIPE FITTING  $\varnothing$  4 mm  
thread M10x1



**3020078** PIPE FITTING  $\varnothing$  6 mm  
thread M10x1



## Thermostats

**3444616** BULB CONNECTION M12 HOLE  $\varnothing$  6 mm  
stuffing gland M9x1 - washer  $\varnothing$  7.7 mm  
gasket  $\varnothing$  7.8 mm - thickness 5 mm



THIRODE 91373062

**3744008** SINGLE-PHASE THERMOSTAT 100-180°C  
D-shaped pin  $\varnothing$  6x4.6 mm  
capillary length 900 mm  
bulb  $\varnothing$  6x130 mm - with adapter nipple bland M9x1  
with complete tank coupling M12x1



THIRODE 7471024





Suitable for:

**3444974 SINGLE-PHASE THERMOSTAT 100-615°C**  
 complete with switch  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 covered capillary length 1100 mm - 16A 250V  
 bulb  $\varnothing$  4x230 mm  
 for Glass-ceramic plate (THIRODE) D9.FR 122617



THIRODE 301034

**3444908 SINGLE-PHASE THERMOSTAT 210°C**  
 with manual reset  
 capillary length 900 mm  
 bulb  $\varnothing$  6x80 mm - with adapter nipple bland M9x1  
 for Fryer (THIRODE)



THIRODE 301027

**3744012 SINGLE-PHASE THERMOSTAT 225°C**  
 with automatic reset  
 capillary length 900 mm - 16A 250V  
 bulb  $\varnothing$  6x55 mm  
 for Fryer (THIRODE) FR25MC



THIRODE 301063

**3744010 SINGLE-PHASE THERMOSTAT 30-110°C**  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 capillary length 1800 mm  
 bulb  $\varnothing$  6x135 mm - with stuffing gland coupling M9x  
 with tank sealing coupling complete M12x1  
 for Bain-marie (THIRODE) - Series 700 - Series 900  
 for Boiling pan (THIRODE) - Series 700  
 Series 900



THIRODE 301001

Suitable for:

**3444929 SINGLE-PHASE THERMOSTAT 140°C**  
 with manual reset  
 capillary length 900 mm  
 bulb  $\varnothing$  6x90 mm  
 for Bain-marie (THIRODE)  
 for Boiling pan (THIRODE)  
 for Fryer electric (THIRODE) FR18 - FR25




THIRODE 301054

**3444903 SINGLE-PHASE THERMOSTAT 220°C**  
 with manual reset  
 capillary length 900 mm  
 bulb  $\varnothing$  6x80 mm - with stuffing gland fitting M9x1



THIRODE 2020060

**3444732 SINGLE-PHASE THERMOSTAT 246°C**  
 with manual reset  
 capillary length 900 mm - 16A 230V  
 bulb  $\varnothing$  6x80 mm - with stuffing gland fitting M9x1  
 with tank sealing fitting complete M12x1



THIRODE 905973

**3444913 SINGLE-PHASE THERMOSTAT 30-85°C**  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 capillary length 900 mm  
 bulb  $\varnothing$  6x100 mm - with stuffing gland fitting M9x1  
 for Oven under cooktop (THIRODE) - Series 700  
 Series 900



THIRODE 301048




Suitable for:

# THIRODE



**3444062 SINGLE-PHASE THERMOSTAT 50-320°C**  
 complete with auxiliary selector switch  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 capillary length 900 mm - 16A 250V  
 bulb  $\varnothing$  3x220 mm



THIRODE 7471032

Suitable for:

**3444174 SINGLE-PHASE THERMOSTAT 50-320°C**  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 capillary length 900 mm - 16A 250V  
 bulb  $\varnothing$  3x220 mm




THIRODE 7471032

**3444635 SINGLE-PHASE THERMOSTAT 50-320°C**  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 covered capillary length 1200 mm  
 double bulb  $\varnothing$  3x120 mm



THIRODE 2050031

**3744068 SINGLE-PHASE THERMOSTAT 60-200°C**  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 capillary length 900 mm  
 bulb  $\varnothing$  6x80 mm - with adapter nipple band M9x1  
 with complete tank coupling M12x1



THIRODE 2020062

**3744011 SINGLE-PHASE THERMOSTAT 60-287°C**  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 capillary length 1470 mm  
 bulb  $\varnothing$  3.1x226 mm



THIRODE 301031

**3444004 THERMOSTAT SINGLE-PHASE TR2 0-90°C**  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 capillary length 1500 mm - 15A 250V  
 bulb  $\varnothing$  6.5x95 mm



THIRODE 901017

**3444899 THERMOSTAT SINGLE-PHASE 135°C**  
 manual reset  
 capillary length 1500 mm  
 bulb  $\varnothing$  6x80 mm



THIRODE 1244727

THIRODE 303641

THIRODE 904843

**3444510 THERMOSTAT SINGLE-PHASE 30-110°C**  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 capillary length 850 mm - 16A 250V  
 bulb  $\varnothing$  6x138 mm - w/ stuffing gland fitting M9x1  
 with complete tank sealing fitting M12x1



THIRODE 24650



Suitable for:

Suitable for:

**1444012 THERMOSTAT SINGLE-PHASE 30-95°C**  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 capillary length 850 mm - 16A 250V  
 bulb  $\varnothing$  6x140 mm - with stuffing gland fitting M9x1

**3444198 THREE-PHASE THERMOSTAT 100-180°C**  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 covered capillary length 2000 mm - 10A 400V  
 bulb  $\varnothing$  6x130 mm





THIRODE 1244788

THIRODE 905838

THIRODE 301062

**3444562 THREE-PHASE THERMOSTAT 100-350°C**  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 covered capillary length 1800 mm - 16A 230V  
 bulb  $\varnothing$  6x80 mm

**3744062 THREE-PHASE THERMOSTAT 100-350°C**  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 capillary length 1470 mm - 16A 400V  
 bulb  $\varnothing$  6x75 mm



THIRODE 301006

THIRODE 7471044

**3444925 THREE-PHASE THERMOSTAT 140°C**  
 with automatic reset  
 capillary length 900 mm  
 bulb  $\varnothing$  6x80 mm - with stuffing gland fitting M9x1  
 with complete tank sealing fitting M12x1

**3444959 THREE-PHASE THERMOSTAT 220°C**  
 with manual reset  
 capillary length 1000 mm  
 bulb  $\varnothing$  6x90 mm  
 for Fryer electric (THIRODE) FR10





THIRODE 301055

THIRODE 301061

**3444088 THREE-PHASE THERMOSTAT 30-110°C**  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 capillary length 900 mm - 10A 400V  
 bulb  $\varnothing$  6x140 mm - with stuffing gland fitting M9x1

**3444592 THREE-PHASE THERMOSTAT 340°C**  
 with manual reset  
 capillary length 1190 mm  
 bulb  $\varnothing$  4x128 mm



THIRODE 301003


THIRODE 7492058

THIRODE 901007

THIRODE 301053

**7107650 THREE-PHASE THERMOSTAT 350°C**  
 D shaped pin  $\varnothing$  6x4.6 mm  
 capillary length covered 1180 mm  
 bulb  $\varnothing$  4x228 mm

**3444904 THREE-PHASE THERMOSTAT 370°C**  
 with manual reset  
 covered capillary length 1500 mm  
 bulb  $\varnothing$  6x77 mm



THIRODE 301073

THIRODE 1040069



Suitable for:

# THIRODE



## 2105402 THREE-PHASE THERMOSTAT 50-270°C

D shaped pin  $\varnothing$  6x4.6 mm  
capillary length 880 mm  
bulbo  $\varnothing$  3,1x263 mm




THIRODE 301051

Suitable for:

## 3444561 THREE-PHASE THERMOSTAT 50-300°C

D-shaped pin  $\varnothing$  6x4.6 mm  
covered capillary length 1740 mm - 16A 230V  
bulb  $\varnothing$  6x80 mm



THIRODE 301005

## 3444594 THREE-PHASE THERMOSTAT 65-200°C

D-shaped pin  $\varnothing$  6x4.6 mm  
capillary length 880 mm  
bulb  $\varnothing$  6x77 mm - with adapter nipple bland M9x1  
with complete tank coupling M12x1



THIRODE 2020061

THIRODE 301004

## Timers

### 3446161 TIMER 12 HOURS C53

manually set mechanical timer  
manually set cycle 12 hours  
contact capacity 16A 250V  
max temperature 125°C  
2 normally closed contacts  
2 normally closed contacts  
complete with silkscreen printed plate and knob  
dimensions 49.5x58 mm depth 52 mm



THIRODE

### 3446162 TIMER 24 HOURS C53

manually set mechanical timer  
manually set cycle 24 hours  
contact capacity 16A 250V  
max temperature 125°C  
2 normally closed contacts  
2 normally closed contacts  
complete with silkscreen printed plate and knob  
dimensions 49.5x58 mm depth 52 mm



THIRODE

### 3446160 TIMER 6 HOURS C53

manually set mechanical timer  
manually set cycle 6 hours  
contact capacity 16A 250V  
max temperature 125°C  
2 normally closed contacts  
2 normally closed contacts  
complete with silkscreen printed plate and knob  
dimensions 49.5x58 mm depth 52 mm



THIRODE

### 3446158 TIMER 60 MINUTES C53

manually set mechanical timer  
manually set cycle 60 minutes  
contact capacity 16A 250V  
max temperature 125°C  
2 normally closed contacts  
2 normally closed contacts  
complete with silkscreen printed plate and knob  
dimensions 49.5x58 mm depth 52 mm



THIRODE



---

## Washing showers

---

**3359610 BLACK SHOWER HEAD ECO  $\varnothing$  1/2" M**  
with coupling 3/8" M x 1/2" M



THIRODE 313063

---

## Wheels and accessories

---

**3522043 HANDWHEEL**  
hole for pin  $\varnothing$  14 mm - length 162 mm  
with handle in BACHELITE



THIRODE 104066

THIRODE 301970

**5043353 HANDWHEEL**  
pin hole  $\varnothing$  12 mm - length 128 mm  
with BAKELITE handle  
for Bratt pan (THIRODE)



THIRODE 132713

THIRODE 132723

The data herewith contained may change without notice and LF SpA cannot be held responsible for possible errors stated or resulting by the use of this document. All rights reserved. No part of this publication may be reproduced without written permission by LF SpA.



## Distributing Components, Spare Parts & Accessories in original quality worldwide

- 
- LF SpA HEADQUARTERS**  
via Voltri, 80 - 47522 Cesena (FC) ITALY  
Tel. +39 0547 34 11 11 - Fax +39 0547 34 11 10  
[www.lfricambi724.it](http://www.lfricambi724.it) - [info@lfricambi.it](mailto:info@lfricambi.it)  
Export Dept. Tel. +39 0547 34 11 50 - Fax +39 0547 34 11 55  
[www.lfspareparts724.com](http://www.lfspareparts724.com) - [export@lfspareparts.com](mailto:export@lfspareparts.com)
- LF SpA HOUSEHOLD COMPONENTS DIVISION**  
Via Padriciano, 99 - AREA Science Park - 34149 Trieste (TS) ITALY  
Tel. +39 0547 34 12 42 - Fax +39 0547 34 12 48  
[www.lfspareparts724.com](http://www.lfspareparts724.com) - [info@lfspareparts.com](mailto:info@lfspareparts.com)
- EPGC Sas FRANCE**  
13, Rue des Forts - 59960 Neuville en Ferrain  
Tel. +33 (0)3 20 25 06 21 - Fax +33 (0)3 20 25 34 12  
[www.epgc.com](http://www.epgc.com) - [epgc@epgc.com](mailto:epgc@epgc.com)
- LF GmbH GERMANY**  
Junkersstrasse, 3 - D-82178 Puchheim - München  
Tel. +49 89 89 45 78 66 - Fax +49 89 89 45 78 88  
[www.lfersatzteile724.de](http://www.lfersatzteile724.de) - [info@lfersatzteile.de](mailto:info@lfersatzteile.de)
- LF China REPUBLIC OF CHINA**  
Room 403, No.2, Huadu Mansion, Lane 422, Huanghua Rd.  
Minhang Dist. - 201103 Shanghai  
Tel. +86 (0)21 33 53 66 31 - Fax +86 (0)21 33 53 66 32  
[www.lfspareparts724.com](http://www.lfspareparts724.com) - [china@lfspareparts.com](mailto:china@lfspareparts.com)
- OOO LF RUSSIAN FEDERATION**  
Ul. Anatoliya Zhivova, 8 - office 1 - 123100 Moscow  
Tel./Fax +7 495 725 26 53  
[www.lfspareparts724.ru](http://www.lfspareparts724.ru) - [info@lfspareparts.ru](mailto:info@lfspareparts.ru)
- LF Repuestos Horeca S.L.U. SPAIN**  
Poligono Industrial Carpetania - C/Miguel Faraday, 8 - 28906 Getafe  
Tel. +34 91 477 91 00 - Fax +34 91 477 90 81  
[www.lfrepuestos-horeca724.es](http://www.lfrepuestos-horeca724.es) - [info@lfrepuestos.es](mailto:info@lfrepuestos.es)
- LF Scandinavia Aps - LF Spareparts S.p.A. DENMARK**  
Nupark, 51 - 7500 Holstebro  
Tel. +45 70 70 77 33  
[www.lfspareparts724.dk](http://www.lfspareparts724.dk) - [denmark@lfspareparts.dk](mailto:denmark@lfspareparts.dk)
- LF SpA Cesena (IT) Swiss Branch Steinhausen SWITZERLAND**  
Sennweidstrasse, 45 - CH-6312 Steinhausen  
Tel. +41 (0)41 760 15 80/1 - Fax +41 (0)41 760 15 85  
[www.lfersatzteile724.ch](http://www.lfersatzteile724.ch) - [info@lfersatzteile.ch](mailto:info@lfersatzteile.ch)
- LF Spare Parts Ltd. UNITED KINGDOM**  
A10a Lakeside Business Park, Broadway Lane  
South Cerney, Gloucestershire GL7 5XL  
Tel. +44 (0)1285 86 16 25 - Fax +44 (0)1285 86 39 49  
[www.lfspareparts724.co.uk](http://www.lfspareparts724.co.uk) - [info@lfspareparts.co.uk](mailto:info@lfspareparts.co.uk)
- LF Central Est Europe S.r.o. CZECH REPUBLIC**  
Antala Staska 1859/34  
14000 Praha 4 - KRC  
Tel. +420 730 156 910  
[www.lfspareparts724.cz](http://www.lfspareparts724.cz) - [info@lfspareparts.cz](mailto:info@lfspareparts.cz)
- LF SPARE PARTS INC. USA**  
Legal address:  
155 Office Plaza Dr - Suite A - Tallahassee, FL 32301  
Business/Mailing address:  
1100 South Tower, 225 Peachtree St., N.E. - Atlanta, GA 30303, USA  
Tel. +1-404-525-2600 - Fax +1-404-586-3528  
[www.lfspareparts724.us](http://www.lfspareparts724.us) - [info@lfspareparts.us](mailto:info@lfspareparts.us)  
Tel. West Coast and Midwest: 206-349-1525 Sauro  
Tel. East Coast and the Caribbean: 786-817-1764 Luis
- 
- AUSTRALIA AND NEW ZEALAND**  
[www.lfspareparts724.com](http://www.lfspareparts724.com)  
[andrea.calvio@lfspareparts.com](mailto:andrea.calvio@lfspareparts.com)
- AUSTRIA**  
[www.lfersatzteile724.at](http://www.lfersatzteile724.at)  
[info@lfersatzteile.at](mailto:info@lfersatzteile.at)
- BALKAN COUNTRIES**  
[www.lfspareparts724.com](http://www.lfspareparts724.com)  
[matija.ramov@lfspareparts.com](mailto:matija.ramov@lfspareparts.com)
- BALTIC COUNTRIES**  
[www.lfspareparts724.com](http://www.lfspareparts724.com)  
[inara.silina@lfspareparts.com](mailto:inara.silina@lfspareparts.com)
- LATIN AMERICA AND THE CARRIBEANS**  
[www.lfrepuestos-horeca724.es](http://www.lfrepuestos-horeca724.es)  
[export@lfrepuestos.es](mailto:export@lfrepuestos.es)
- POLAND**  
[www.lfspareparts724.pl](http://www.lfspareparts724.pl)  
[info@lfspareparts.pl](mailto:info@lfspareparts.pl)
- SOUTH KOREA**  
[www.lfspareparts724.com](http://www.lfspareparts724.com)  
[fabio.doni@lfspareparts.com](mailto:fabio.doni@lfspareparts.com)
- TURKEY**  
[www.lfyedekparca724.com](http://www.lfyedekparca724.com)  
[export@lfspareparts.com](mailto:export@lfspareparts.com)