



Spare parts for:

## Commercial refrigeration



Suitable for:

# CUBIGEL



This catalogue is automatically generated.  
Therefore, the sequence of the items might  
not be always shown at best.  
Updates will be issued in case of additions  
and/or amendments.  
*Suitable universal spare parts may not be included*

Rel. 2014-04151633





# CUBIGEL



## COMPRESSOR CUBIGEL R134a HMBP



LF Code	Model	Motor power HP	Displacement cm <sup>3</sup>	Electric diagram	LRA	Watt	Ampere	Refrigeration power Watt				Power Volt/Ph/Hz	
								Evaporating temperature °C					
								-10	-5	0	+5		
3070157	GD30MB-d	1/10	3.0	CSIR	4.6	160	0.9	116	150	188	233	220-240/1/50	
3070160	GD36MB-d	1/10	3.6	CSIR	5.2	180	1.1	127	165	210	261	220-240/1/50	
3070062	GD40MB-d	1/8	4.0	CSIR	5.6	200	1.2	153	196	245	301	220-240/1/50	
3070011	GL45TB	1/6	4.5	CSIR	6.5	220	1.2	175	223	278	342	220-240/1/50	
3070012	GL60TB	1/5	5.7	CSIR	8.3	250	1.5	222	284	356	437	220-240/1/50	
3070013	GL80TB	1/4L	7.6	CSIR	9.8	315	1.8	280	360	451	554	220-240/1/50	
3070014	GL90TB	1/4	8.8	CSIR	12.0	360	2.1	339	432	539	661	220-240/1/50	
3070015	GP12TB	1/3	12.0	CSIR	13.5	520	2.9	450	580	727	893	220-240/1/50	
3070051	GP14TB	3/8	14.0	CSIR	18.0	590	3.4	497	643	810	999	220-240/1/50	
3070156	GP16TB	3/8	16.0	CSIR	20.0	666	3.9	619	788	983	1205	220-240/1/50	
3070016	GX18TB	1/2	18.4	CSIR	24.0	755	4.6	709	907	1134	1390	220-240/1/50	
3070084	GX21TB	5/8	20.7	CSIR	26.0	850	5.3	792	1012	1265	1550	220-240/1/50	
3070083	GX23TB	5/8	23.2	CSIR	26.0	950	5.8	887	1132	1413	1730	220-240/1/50	
3070085	GS26TB	3/4	25.9	CSR	32.0	1030	6.3	984	1306	1668	2071	220-240/1/50	
3070086	GS34TB	1	34.4	CSR	32.0	1300	6.6	1439	1860	2331	2852	220-240/1/50	

Condensation temperature +54.4°C

## COMPRESSOR CUBIGEL R134a LBP



LF Code	Model	Motor power HP	Displacement cm <sup>3</sup>	Electric diagram	LRA	Watt	Ampere	Refrigeration power Watt				Power Volt/Ph/Hz	
								Evaporating temperature °C					
								-30	-25	-20	-10		
3070236	GD24AA	1/20	2.4	RSIR	5.5	67	0.63	22	34	49	85	220-240/1/50	
3070196	GL60AA	1/6	6.0	RSIR	9	126	0.85	75	107	145	239	220-240/1/50	
3070197	GL80AA	1/5	8.1	RSIR	11.5	162	1.1	102	144	196	326	220-240/1/50	
3070201	GL90AA	1/4	9.1	RSIR	12.8	184	1.2	119	165	219	351	220-240/1/50	
3070198	GL99AA	1/3	10.0	RSIR	14	189	1.3	125	175	233	377	220-240/1/50	


Condensation temperature +54.4°C



# CUBIGEL



## COMPRESSOR CUBIGEL R404a-R507 HMBP



LF Code	Model	Motor power HP	Displacement cm <sup>3</sup>	Electric diagram	LRA	Watt	Ampere	Refrigeration power Watt				Power Volt/Ph/Hz	
								Evaporating temperature °C					
								-10	-5	0	+5		
3070161	ML40TB	1/6	4.0	CSIR	8.4	340	1.9	266	327	396	473	220-240/1/50	
3070021	ML45TB	1/5	4.5	CSIR	9.7	365	2.1	296	364	441	528	220-240/1/50	
3070022	ML60TB	1/4	5.7	CSIR	10.6	440	2.5	352	438	536	647	220-240/1/50	
3070023	ML80TB	1/3	7.6	CSIR	12.8	555	3.1	487	604	735	880	220-240/1/50	
3070024	ML90TB	3/8	8.5	CSIR	16.0	669	3.8	583	721	879	1055	220-240/1/50	
3070088	MP12TB	1/2	12.0	CSR	17.0	775	3.7	804	998	1218	1463	220-240/1/50	
3070089	MP14TB	5/8	14.2	CSR	19.0	978	4.7	954	1169	1409	1674	220-240/1/50	
3070036	MX18TB	3/4	18.4	CSR	29.5	1245	6.5	1185	1472	1796	2157	220-240/1/50	
3070063	MX21TB	1	20.7	CSR	33.0	1415	7.1	1331	1653	2018	2425	220-240/1/50	
3070064	MS26TB	1.2	25.9	CSR	38.0	1629	8.1	1687	2133	2632	3185	220-240/1/50	
3070065	MS34TB	1.5	34.4	CSR	41.0	2300	11.5	2370	2935	3556	4231	220-240/1/50	

Condensation temperature +54.4°C

## COMPRESSOR CUBIGEL R404a-R507 LBP



LF Code	Model	Motor power HP	Displacement cm <sup>3</sup>	Electric diagram	LRA	Watt	Ampere	Refrigeration power Watt				Power Volt/Ph/Hz	
								Evaporating temperature °C					
								-30	-25	-20	-10		
3070087	ML45FB	1/6	4.6	CSIR	8.5	210	1.4	100	134	174	275	220-240/1/50	
3070041	ML60FB	1/5	6.0	CSIR	9.0	260	1.6	134	178	229	352	220-240/1/50	
3070042	ML80FB	1/4L	8.1	CSIR	12.2	340	2.1	190	253	326	507	220-240/1/50	
3070043	ML90FB	1/4	8.8	CSIR	12.2	350	2.3	208	276	356	550	220-240/1/50	
3070031	MP12FB	1/3	12.0	CSIR	14.8	450	2.7	252	351	467	747	220-240/1/50	
3070213	MPT12LA	3/8	12.1	CSR	13.9	467	2.2	348	453	601	876	220-240/1/50	
3070032	MP14FB	1/2	14.0	CSIR	17.5	560	3.4	304	422	558	881	220-240/1/50	
3070228	MPT14LA	1/2	14.3	CSR	16.0	565	2.8	420	535	669	988	220-240/1/50	
3070033	MX18FBa	5/8	18.4	CSR	18.0	600	3.0	397	548	724	1151	220-240/1/50	
3070034	MX21FBa	3/4	20.7	CSR	24.0	695	3.5	464	632	828	1301	220-240/1/50	
3070072	MX23FB	1	23.2	CSR	24.0	790	4.0	536	720	937	1410	220-240/1/50	
3070035	MS26FB	1.2	25.9	CSR	30.0	890	4.5	572	816	1094	1744	220-240/1/50	
3070066	MS34FB	1.5	34.4	CSR	39.0	1205	6.4	764	1089	1457	2319	220-240/1/50	

Condensation temperature +54.4°C