



Spare parts for:

Cooking equipment



Suitable for:

ATA



This catalogue is automatically generated.
Therefore, the sequence of the items might
not be always shown at best.

Updates will be issued in case of additions
and/or amendments.

Suitable universal spare parts may not be included

Rel. 2013-11151616





Suitable for:

ATA



Suitable for:

Bearings

9063010 BEARING 6204 DDU

external \varnothing 47 mm -internal \varnothing 20 mm-thickness 14 mm
 for BAKERMIX KNEADER MIX203.B
 for OEM KNEADER F201/1-F501/2
 for OEM POTATO PEELER PLP10-PLP15-PLP23-PLP32
 for OEM POTATO PEELER PC6-PC8-PL10-PL15-PL23-PL32
 for OEM POTATO PEELER PV10-PV15-PV23




ATA 6638

Contactors

3446557 CONTACTOR LOVATO BG0901A

coil 9A 230V 50/60Hz 4Kw
 3 normally open contacts
 1 normally closed auxiliary contact



ATA 9800

Drain hoses

3450032 DRAIN PIPE \varnothing 38x2000 mm

muffs internal \varnothing 31 and 40 mm
 max temperature 90°C



ATA 4128

Drain taps and accessories

3526671 BALL VALVE \varnothing 1/2" FF

for Bain-marie (ZANUSSI)
 for Bratt pan (ZANUSSI)
 for Food-service trolley (BLANCO) SAG2 - SAG3
 SG3 ECO-LINE
 for Pasta cooker (EMMEPI) - Series 700
 for Pasta cooker (ZANUSSI)



ATA K20029

Electric hot plates

- 3311062 ELECTRIC HOT PLATE 3000W 230V**
 dimensions 300x300 mm
 terminal block electric connections
 with STAINLESS steel edge
 for electric cooking top
 for Kitchen electric (FAGOR) CE-941
 for Oven under cooktop electric (FAGOR) CE-920
 CE-940



ATA K24011

Electrical gas valves and accessories

- 3526176 VALVE 820 NOVA \varnothing 1/2"FF**
 inlet \varnothing 1/2"F - outlet \varnothing 1/2"F
 thermocouple connection M9x1
 maximum gas inlet pressure 60 mbar
 outlet pressure adjustment range
 3÷30 mbar
 ambient temperature 0÷70°C
 power supply 230V 50Hz
 for Boiling pan gas (MARENO)
 Series 900PROTAGONISTA NUOVA
 for Bratt pan gas (MARENO)
 Series 900PROTAGONISTA NUOVA
 for Bratt pan gas (OLIS) - Series 700 - Series 900
 for Fryer (BARON) 9FRI/G420
 for Fryer gas (OLIS) - Series 900
 for Pasta cooker gas (MARENO)



ATA K00055

Gas taps and accessories

- | | |
|---|--|
| <p>3348029 FITTING FOR PIPE \varnothing 4 mm
 for model PEL 21-22</p> | <p>3348016 GAS COCK 21/SV
 with pilot flame
 fittings \varnothing M16x1.5mm
 thermocouple connection M9x1 mm
 D-shaped pin \varnothing 8x6.5 mm</p> |
|---|--|



ATA K22005



ATA K22001




Suitable for:

3348002 GAS COCK 22/0
 with pilot flame
 with horizontal flange
 fittings \varnothing M20x1.5mm
 with flow regulator
 thermocouple connection M8x1
 D-shaped pin \varnothing 10x8 mm
 for Boiling pan (THIRODE)
 for Bratt pan gas (THIRODE) SA30 - SA41
 for Grill (FAGOR) - Series 900



ATA K22011

3348043 PIPE FITTING \varnothing 10 mm
 for model PEL 20-21



ATA K22004

3348033 PIPE FITTING \varnothing 12 mm
 for model PEL 23



ATA K22040

3348038 PIPE OLIVE \varnothing 10 mm
 for model PEL 22



ATA K22013

3348040 PIPE OLIVE \varnothing 12 mm
 for model PEL 23



ATA K22037

ATA



Suitable for:

3348036 OLIVE FOR 4 mm \varnothing PIPE
 for model PEL 21-22




ATA K22003

3348032 PIPE FITTING \varnothing 12 mm
 for model PEL 22



ATA K22014

3348035 PIPE FITTING \varnothing 20 mm
 for model PEL 23



ATA K22039

3348044 PIPE OLIVE \varnothing 10 mm
 for model PEL 20 - 21



ATA K22002

3348042 PIPE OLIVE \varnothing 20 mm
 for model PEL 23



ATA K22038

Heating elements

3355046 HEATING ELEMENT 6000W 220/380V
 immersed length 490 mm
 flange external \varnothing 63 mm
 with thermostat probe receptacle
 with O-ring
 for Boiling pan electric (ZANUSSI) - Series HD900
 Series H900
 for Pasta cooker electric (ZANUSSI) - Series H900
 Series 900



ATA 6205

3186013 O-RING GASKET 06187 EPDM \varnothing 58 mm



ATA 4207

Ironmongery (screws,nuts,washers)

3316051 HEATING ELEMENT RETAINING NUT \varnothing 1"1/2



ATA 1047

ATA 4124

1349504 NUT FOR TAP \varnothing 1/2"



ATA 7139

Lamps

3221258 NEON LAMP Ba9s 1.5mA 230V
 dimensions \varnothing 10x28 mm
 for Fryer electric (COMETTO) CCE14



ATA 14657

3221097 NEUTRAL INDICATOR LAMP 220V
 head \varnothing 8 mm - 120°C



ATA 7215

3221163 ORANGE LAMP RECEPTACLE
 head \varnothing 15 mm - hole \varnothing 10 mm



ATA 7953



Suitable for:

ATA



Suitable for:

Microswitches

3240179 MAGNETIC MICROSWITCH E5301C
0.4A 250V - contact NO - head 65x20x9 mm
with cable length 500 mm



ATA 13105

3240181 PROTECTED MAGNET 62x18x10 mm



ATA 13642

3240204 MAGNETIC MICROSWITCH E5301C
0.4A 250V - contact NO - head 65x20x9 mm
with magnet 63x19x11 mm
with cable length 1900 mm



ATA 13122

3240181 PROTECTED MAGNET 62x18x10 mm



ATA 13642

3240181 PROTECTED MAGNET 62x18x10 mm



ATA 13642

OR and ORM gaskets

3186013 O-RING GASKET 06187 EPDM \varnothing 58 mm



ATA 4207

3186014 O-RING GASKET 06225 EPDM \varnothing 67 mm



ATA

1186238 O-RING 04081 EPDM



ATA 1037

3786459 O-RING 04200 VITON



ATA K20007

Piezo ignitors

- 3001020** **PIEZO IGNITER 10015**
18 mm \varnothing mounting hole
2.4 mm \varnothing male faston connector



ATA K24003

Pilot burners and accessories

- 3020085** **NUT FOR SPARKING PLUG CONNECTION**



ATA K22024

- 3020082** **OLIVE FOR 12 mm \varnothing PIPE**



ATA K22012

- 3020025** **ONE-FLAME PILOT BURNER SIT**
multigas type with nozzle \varnothing 0.25 mm
with 2 positions bracket



ATA K22015

- 3020054** **PILOT JET \varnothing 0.20 mm**



ATA K22025

- 3020055** **PILOT JET \varnothing 0.35 mm**



ATA K22026

- 3020054** **PILOT JET \varnothing 0.20 mm**



ATA K22025

- 3020040** **PILOT JET \varnothing 0.30 mm**



ATA K22022



Suitable for:

3020055 PILOT JET \varnothing 0.35 mm



ATA K22026

3020038 THREE-FLAME PRINTED PILOT BURNER SIT
without sparking plug, gas nozzle and gasket
thermocouple fitting included
for Lava rock grill gas (ANGELO PO) - Series SNACK



ATA K22019

ATA



Suitable for:

3020011 THREE-FLAME PILOT BURNER
without sparking plug, gas jet
with pipe fitting and pilot pipe olive
with thermocouple connection
with sparking plug fitting
for Bratt pan gas (ZANUSSI)
for Pasta cooker gas (ZANUSSI) - Series N900
Series PR700



ATA K22029

3020040 PILOT JET \varnothing 0.30 mm



ATA K22022

Probes

3445107 PTC PVC PROBE 3000 mm
2-wire probe temperature range $-30+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm




ATA 7710

ATA 7723

Relays

3351031 MINI RELAY 26.01 8A 230V 50Hz
1 cut-off contact



ATA 7711



Rotary switches

3057026 SELECTOR SWITCH 0-1 POSITIONS


contact capacity 16A 250V - max 150°C
 D shaft \varnothing 6x4.6 mm
 for Bain-marie (EMMEPI) - Series 650
 for Bain-marie electric (OLIS) 72/02CBE
 72/02TCBE
 for Bratt pan electric (OLIS) 74/02KBEBI
 for Bratt pan gas (OLIS) 74/02KBGMB
 for Fryer (GICO) - Series 500 - Series 700
 Series 900 - Series 920
 for Fryer electric (OLIS) 72/02FRE - 74/02FRE
 92/02FRE - 92/04FRE
 for Hot cupboard (OLIS) TAC210 - TAC211 - TAC212
 for Kitchen gas (OLIS) 76/02CGGE
 for Oven under cooktop (GICO) - Series 500
 Series 700



ATA K24034

3057023 SELECTOR SWITCH 0-6 POSITIONS

contact capacity 32A 250V - max 150°C
 D shaft \varnothing 6x4.6 mm
 for Bratt pan electric (COMETTO)
 for Hot plate electric (COMETTO)
 for Kitchen electric (EMMEPI) - Series 900
 for Pot stove electric (COMETTO)



ATA K24014

Solenoid valves

3120016 OUTLET REDUCER ELBI 1.2 L/min NEUTRAL

for solenoid valve ELBI
 rated value +/- 25%



ATA 7269

3120408 SOLENOID VALVE 230V \varnothing 13.5 mm

solenoid valve 90° - 230V 50/60Hz - max 90°C
 inlet 3/4" - 1 outlet \varnothing 13.5 mm



ATA

3120013 SOLENOID VALVE 263 220/240V \varnothing 10 mm

solenoid valve 90° - 220/240V 50/60Hz - max 90°C
 inlet 3/4" - triple outlet \varnothing 10 mm



ATA 7209

3120004 SOLENOID VALVE 319 220/240V \varnothing 10 mm

solenoid valve 90° - 220/240V 50/60Hz - max 90°C
 inlet 3/4" - outlet \varnothing 10 mm



ATA 2504

3120504 SOLENOID VALVE 319 24V \varnothing 10 mm

solenoid valve 90° - 24V 50Hz - max 90°C
 inlet 3/4" - outlet \varnothing 10 mm



ATA 13103

3120006 SOLENOID VALVE 339 220/240V \varnothing 10 mm

solenoid valve 90° - 220/240V 50/60Hz - max 90°C
 inlet 3/4" - dual outlet \varnothing 10 mm



ATA 1066



Suitable for:

ATA



3120506 SOLENOID VALVE 339 24V ø 10 mm
solenoid valve 90° - 24V 50Hz - max 90°C
inlet 3/4" - dual outlet ø 10 mm



ATA 14131

Suitable for:

3120008 SOLENOID VALVE 350 220/240V ø 14 mm
solenoid valve 90° - 220/240V 50/60Hz - max 90°C
inlet 3/4" - outlet ø 14 mm



ATA 7604

3120511 SOLENOID VALVE 350 24V ø 14 mm
solenoid valve 90° - 24V 50Hz - max 90°C
3/4" inlet - ø 14 mm outlet



ATA

Switches

3319015 RED BIPOLAR PUSH BUTTON 16A 250V
with indicator lamp
silk-screen print 0 - I
max temperature 120°C
mounting hole 22x30 mm



ATA 1085

3319018 RED CHANGE OVER SWITCH 16A 250V
with indicator lamp
max temperature 120°C
mounting hole 22x30 mm



ATA 1087

Terminal blocks

3247037 4-POLE TERMINAL BLOCK FV173 40A 600V
for cable max 6 mm²
operating temperature 150°C
nominal voltage 450 V



ATA 13162



Thermocouples and accessories

3440836 THERMOCOUPLE SIT M9x1 85 cm - 10 PCS



ATA K22176

3440036 THERMOCOUPLE SIT M9x1 85 cm.



ATA K22176

3440836 THERMOCOUPLE SIT M9x1 85 cm - 10 PCS



ATA K22176

Thermostatic gas valves

3345018 THERMOSTATIC GAS COCK PEL25ST

temperature range 100-300°C
fitting inlet/outlet M16x1.5 mm
thermocouple connection M9x1
bulb \varnothing 6x100 mm
D-shaped pin \varnothing 8x6.5 mm
for Fry top
for Oven under cooktop



ATA K22131

Thermostats

3444312 SINGLE-PHASE THERMOSTAT 360°C

with manual reset
covered capillary 1500 mm - 3 contacts 16A 250V
bulb \varnothing 4x110 mm
for Fry top gas (ANGELO PO) - Series ALPHA
Series BIFRONTI - Series DELTA - Series GAMMA
Series JUNIOR - Series OMEGA - Series SENIOR
Series SUMMIT
for Oven under cooktop (SILKO)



ATA K24041

3444031 SINGLE-PHASE THERMOSTAT 90-185°C

complete with auxiliary selector switch
D-shaped pin \varnothing 6x4.6 mm
covered capillary length 2500 mm - 16A 250V
bulb \varnothing 4x230 mm
for Fryer (ZANUSSI) - Series HD900 - Series N700
Series N900 - Series PR700



ATA K24048



Suitable for:

3444004 THERMOSTAT TR2 0-90°C
D-shaped pin \varnothing 6x4.6 mm
capillary 1500 mm - 15A 250V
bulb \varnothing 6.5x95 mm



ATA 1080

ATA 7280

ATA



Suitable for:

3444052 THREE-PHASE THERMOSTAT 50-320°C
D-shaped pin \varnothing 6x4.6 mm
capillary length 900 mm - 10A 400V
bulb \varnothing 3x230 mm
for Grill electric (ZANUSSI) MG/E1 - MG/E2 - RG/E1
RG/E2



ATA K24015