



Spare parts for:

## Cooking equipment



Suitable for:

# PALUX



This catalogue is automatically generated.  
Therefore, the sequence of the items might  
not be always shown at best.

Updates will be issued in case of additions  
and/or amendments.

*Suitable **universal spare parts** may not be included*





Suitable for:

# PALUX



Suitable for:

## Cables for piezo igniters

- 3001002 SIT IGNITION LEAD 1000 mm**  
 with faston 6.35x0.8 mm ignition  
 with faston  $\varnothing$  4 mm for electrode  
 for Oven under cooktop gas (FAGOR) HG9-10 - HG9-20



PALUX

## Electrical gas valves and accessories

- 3526090 ELETROSIT VALVE  $\varnothing$  3/4"FF**  
 inlet  $\varnothing$  3/4"F - outlet  $\varnothing$  3/4"F  
 thermocouple connection M9x1  
 maximum gas inlet pressure 50 mbar  
 pressure adjustment range  
 3÷18 mbar  
 ambient temperature 0÷60°C  
 power supply 230V 50Hz  
 long buttons  
 pilot connection and LATERAL thermocouple  
 for Bratt pan gas (BONNET)  
 for Bratt pan gas (OLIS) KBG970 - 725KBG - 94KBCM  
 94KBG  
 for Fryer gas (BONNET)



PALUX 321907

## Gas taps and accessories

- 3348014 GAS COCK 20/S**  
 without pilot flame  
 fittings  $\varnothing$  M16x1.5mm  
 thermocouple fitting M8x1  
 D-shaped pin  $\varnothing$  8x6.5mm



PALUX 32369-1

- 3182011 MAGNETIC UNIT PEL SMALL HEADED**  
 $\varnothing$  head 15 mm -  $\varnothing$  end 11 mm - length 44 mm  
 for PEL tap models 20-21  
 for EGA tap model 25213  
 for JUNKERS tap model CH110



PALUX

Suitable for:

Suitable for:

- 3348003 GAS COCK 22/V**  
 with pilot flame  
 with vertical flange  
 fittings  $\varnothing$  M20x1.5mm  
 thermocouple connection M9x1  
 D-shaped pin  $\varnothing$  10x8 mm



PALUX 32137/38/39

## Handles

- 3242718 DOOR HANDLE STRIKE**  
 for high temperatures  
 mounting distance 43 mm  
 for OVEN



PALUX LF-3242042

## Heating elements

- 3755413 HEATING ELEMENT 1500W 230V**  
 length 420 mm - width 80 mm  
 height 30 mm - fittings M14x1.5 mm  
 for Grill electric (PALUX)



PALUX 083577

PALUX 83577

- 3755422 HEATING ELEMENT 1500W 230V**  
 length 400 mm - width 40 mm  
 height 50 mm  
 for Fry top electric (PALUX)



PALUX

- 3755423 HEATING ELEMENT 1500W 230V**  
 length 340 mm - width 70 mm  
 height 30 mm - fittings M14x1.5 mm  
 for Bain-marie electric (PALUX)



PALUX 056928

- 3755417 HEATING ELEMENT 1660W 230V**  
 length 260 mm - width 60 mm  
 height 245 mm - fittings M14x1.5 mm  
 for Fryer electric (PALUX)



PALUX



Suitable for:

# PALUX



**3355048 HEATING ELEMENT 2000W 220V**  
length 570 mm - width 90 mm  
height 50 mm  
for Fry top electric (ZANUSSI) - Series R700



PALUX 26944

**3755421 HEATING ELEMENT 2250W 230V**  
length 485 mm - width 125 mm  
fittings M14x1.5 mm  
for Grill electric (PALUX)



PALUX

**3755411 HEATING ELEMENT 2500W 230V**  
length 285 mm - width 80 mm  
fittings M14x1.5 mm




PALUX 233978

**3755414 HEATING ELEMENT 3000W 230V**  
length 350 mm - width 24 mm  
for BOILER



PALUX 378585

**3755420 HEATING ELEMENT 3000W 230V**  
length 485 mm - width 190 mm  
couplings M14x1.5 mm  
for Grill electric (PALUX)



PALUX

**3755415 HEATING ELEMENT 3300W 230V**  
length 255 mm - width 70 mm  
with cables and receptacle  
for BOILER



PALUX 372749

## Lamps

**3221053 GASKET FOR OVEN LAMP RECEPTACLE**  
dimensions  $\varnothing$  48x38x5 mm  
for OVEN



PALUX

**3221381 HALOGEN LAM PR7S 300W 230V**  
length 117 mm



PALUX

**3221041 OVEN LAMP E14 15W 230V**  
max temperature 300°C  
for OVEN - PIZZA OVEN



PALUX 47635



## Magnet groups

### 3182011 MAGNETIC UNIT PEL SMALL HEADED

ø head 15 mm - ø end 11 mm - length 44 mm  
for PEL tap models 20-21  
for EGA tap model 25213  
for JUNKERS tap model CH110



PALUX

## Microswitches

### 3240406 MICROSWITCH 10A 250V



PALUX 92444

## Piezo ignitors

### 3001005 PIEZO IGNITER

a ø 18 mm hole is needed for the assembly  
male faston ø 2.4 mm  
for Bain-marie gas (SILKO) BMG40 - BMG60  
for Fry top gas (SILKO) SKT



PALUX 008893

PALUX 8893

### 3001009

### PIEZO IGNITER JUNKERS

with faston 6.35x0.8 mm



PALUX 89354

### 3001041 PIEZO IGNITER JUNKERS CP101.053

a ø 22 mm hole is needed for the assembly  
male faston ø 2.4 mm



PALUX 269174



Suitable for:

# PALUX



Suitable for:

## Pilot burners and accessories

**3020018 PILOT BURNER CB 503.003**  
with LPG jet and pilot olive  
with pilot pipe connection



PALUX

**3020159 PILOT BURNER GPL CB 503.006**  
with LPG nozzle and pilot olive



PALUX

## Rotary switches

**3057002 SELECTOR SWITCH 0-1 0-1 POSITIONS**  
contact capacity 32A 250V - max 150°C  
D shaft  $\varnothing$  6x4.6 mm



PALUX 126608

**3057094 SELECTOR SWITCH 0-1 0-1 POSITIONS**  
contact capacity 32A 250V - max 150°C  
D spindle  $\varnothing$  6x4.6 mm



PALUX 291722

**3057096 SELECTOR SWITCH 0-4 POSITIONS**  
contact capacity 16A 250V - max 150°C  
D-shaft  $\varnothing$  6x4.6 mm  
for Salamander electric (FRANKE) FR1/1E2



PALUX

**3057092 SELECTOR SWITCH 0-6 POSITIONS**  
contact capacity 16A 250V - max 150°C  
D-shaft  $\varnothing$  6x4.6 mm  
for Kitchen electric (KÜPPERSBUSCH) - Series FEH



PALUX 101703

**3057024 SELECTOR SWITCH 0-7 POSITIONS**  
contact capacity 16A 250V - max 150°C  
D shaft  $\varnothing$  6x4.6 mm  
for Kitchen electric (EMMEPI) - Series 650  
Series 700 - Series 750  
for Kitchen electric (GICO) - Series 700  
for Kitchen electric (GIGA) - Series 600  
Series 700 - Series 800 - Series 900  
for Kitchen electric (OFFCAR) - Series 700  
Series 900  
for Kitchen electric (OLIS) 72/02CEPT - 76/02CEPT  
for Pot stove electric (OLIS) 72/02TCE - 74/02CEPT  
74/02TCE - 76/02TCE - 92/04CE - 92/04TCE  
94/04CE - 94/04TCE



PALUX 246848



## Spark generators

- 3181002 SPARK GENERATOR 2 OUTLETS**  
 220/240V 50/60Hz  
 for Boiling pan gas (CHARVET)  
 for Fryer gas (CAPIC) CTI - CTIB - C10 - T1 - TIB  
 for Kitchen (THIRODE) B7.FV.CF.FG



PALUX LF-3001061

## Sparking and detection plugs

- 3020074 ROUND IGNITION ELECTRODE  $\varnothing$  5/8x52 mm**  
 model 2/B  
 total length 66 mm  
 for Pot stove gas (ZANUSSI) - Series HD700



PALUX 323713

## Thermostats

- 3444681 SINGLE-PHASE THERMOSTAT 318°C**  
 capillary length 800 mm  
 bulb  $\varnothing$  4x110 mm - with adapter nipple band M9x1  
 with complete tank joint M12x1




PALUX 242746

- 3444701 SINGLE-PHASE THERMOSTAT 55-250°C**  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 covered capillary length 1170 mm - 16A 250V  
 bulb  $\varnothing$  3.1x226 mm - with stuffing gland M9x1



PALUX 091634

- 3444702 THREE-PHASE THERMOSTAT 100-180°C**  
 complete with switch  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 covered capillary length 720 mm - 16A 230V  
 bulb  $\varnothing$  3.1x305 mm



PALUX 026611

PALUX 26611

- 3444739 THREE-PHASE THERMOSTAT 250°C**  
 with manual reset  
 covered capillary length 1470 mm - 10A 400V  
 bulb  $\varnothing$  6x100 mm - adapter nipple bland M9x1



PALUX 637726



Suitable for:

**3444706 THREE-PHASE THERMOSTAT 255°C**  
with manual reset  
covered capillary length 730 mm - 10A 400V  
bulb  $\varnothing$  3.1x307 mm



PALUX 027332

**3444504 THREE-PHASE THERMOSTAT 50-300°C**  
D-shaped pin  $\varnothing$  6x4.6 mm  
capillary length 880 mm - 10A 400V  
bulb  $\varnothing$  4x128 mm  
for Hot plate (PALUX)



PALUX 224081

# PALUX



Suitable for:

**3444076 THREE-PHASE THERMOSTAT 30-110°C**  
D-shaped pin  $\varnothing$  6x4.6 mm  
covered capillary length 1200 mm - 10A 400V  
bulb  $\varnothing$  6x130 mm



PALUX 290319

**3744055 THREE-PHASE THERMOSTAT 95-185°C**  
D-shaped pin  $\varnothing$  6x4.6 mm  
covered capillary length 1480 mm - 16A 400V  
bulb  $\varnothing$  6x120 mm  
for Fryer (PALUX)



PALUX 178144

## Timers

**3446100 MECHANICAL TIMER 15 MINUTES**  
manually set mechanical timer  
manually set cycle 15 minutes  
max temperature 125°C  
D-shaped pin  $\varnothing$  6x4.6 mm



PALUX 5356050