




Spare parts for:  
**Cooking equipment**



Suitable for:

**TESTO**



This catalogue is automatically generated.  
Therefore, the sequence of the items might  
not be always shown at best.  
Updates will be issued in case of additions  
and/or amendments.

*Suitable universal spare parts may not be included*





Suitable for:

**TESTO**

Suitable for:

## Measuring tools

**3394164 DIGITAL THERMOMETER TESTO 106**  
 for food  
 temperature -50+275°C  
 resolution 0.1°C  
 operating temperature -20°+50°C  
 dimensions 215x34x19 mm



TESTO 0563-1063

**3394168 DIGITAL THERMOMETER TESTO 810**  
 air and surface temperature with infrared in one instrument  
 surface temperature: measuring range -30°+300°C  
 air temperature: measuring range -10°+50°C  
 dimensions 119x46x25 mm



TESTO 0560-0810

**3394161 MINI IMMERSION THERMOMETER TESTO 905**  
 thermocouple sensor type K  
 measurement field -50°+350°C - -58°+660°F  
 shortly up to +500°C/930°F  
 operating temperature 0+40°C - +32°+104°F



TESTO 0560-9051

TESTO 0560-9055

**3394162 MINITHERMOMETER -50°+250°C TESTO 0526**  
 the exceeding of the measurement values max/min of the temperature is indicated with "---



TESTO 0560-1111

TESTO 0900-0526

**3394166 MINITHERMOMETER INFRARED TESTO 805**  
 measuring range -25°+250°C  
 dimensions 80x31x19 mm



TESTO 0563-8051

**3394160 TESTER FOR COOKING OIL TESTO 265**  
 capacitive sensor for oil (%TPM) - PTC (°C)  
 measurement field 0.5-40 %TPM - +40°+210°C  
 display indicating temperature exceeding max and min  
 oil temperature +40°+210°C  
 dimensions 302x35x21 mm



TESTO 0563-0265

TESTO 0563-2700

**3394169 THERMOHYGROMETER TESTO 610**  
 shows humidity and air temperature  
 temperature: measurement field -10°+50°C  
 humidity: measurement field 0-100% UR  
 measurement unit %UR, wet-bulb, dew point  
 dimensions 119x46x25 mm



TESTO 0560-0610

**3394163 THERMOMETER FOR FOOD TESTO 926**  
 probe type T (Cu-CuNi) or NTC if used  
 immersion/penetration radio probe  
 measuring range -50°+400°C  
 operating temperature -20°+50°C  
 dimensions 182x64x40 mm



TESTO 0563-9262