




Spare parts for:

Ovens



Suitable for:

AMBASSADE



This catalogue is automatically generated.
Therefore, the sequence of the items might
not be always shown at best.

Updates will be issued in case of additions
and/or amendments.

*Suitable **universal spare parts** may not be included*

Rel. 2013-11211323





Suitable for:

AMBASSADE



Suitable for:

Energy regulators

3350079 ENERGY CONTROLLER

complete with switch
contact capacity 230V 13A
D-shaped pin \varnothing 6x4.6 mm
for Convection oven electric (AMBASSADE) CFE806CV
1FRFE08CV



AMBASSADE 65225001

Fans for motors

3241894 FAN \varnothing 180 mm

thickness 62 mm
total blades 12 - \varnothing hole 12 mm
for Convection oven electric (AMBASSADE) 1FRFE08CV



AMBASSADE 65260003

Gaskets and seals

3786629 MOTOR SHAFT GASKET

external \varnothing 22 mm - internal \varnothing 11 mm
for Convection oven electric (AMBASSADE) 1FRFE08CV



AMBASSADE 65119021

Gaskets for oven door

3786628 OVEN DOOR GASKET 400x240 mm

made of silicone elastomer
with fastening clips
COLOUR BLACK
for Convection oven gas (AMBASSADE) FG301CT



AMBASSADE 6530952

3786627 OVEN DOOR GASKET 500x390 mm

made of silicone elastomer
with fastening clips
COLOUR BLACK
for Convection oven electric (AMBASSADE) CFE705CT
1FRFE07-CT



AMBASSADE 65111003



Suitable for:

Suitable for:

3786323 OVEN DOOR GASKET 580x400 mm
made of silicone elastomer
COLOUR BLACK
for Convection oven electric (AMBASSADE) SFE705CT
44FIRE



AMBASSADE 65111012

Handles

3242730 HANDLE FASTENING SCREW M16x27.5 mm
for Convection oven electric (AMBASSADE) 1FRFE08CV



AMBASSADE 65132004

Heating elements

3455138 HEATING ELEMENT 2650W 230V
external \varnothing 215 mm - total height 80 mm
flange 70x22 mm



AMBASSADE 6527752

Knobs

3241893 BLACK RING NUT \varnothing 57 mm FOR KNOB
for Convection oven electric (AMBASSADE) 1FRFE08CV



AMBASSADE 50325200



Suitable for:

AMBASSADE



Suitable for:

Lamps

3221583 GREEN INDICATOR LAMP 220V
mounting hole 27.2 x 22.2 mm
universal application



AMBASSADE 6532194

AMBASSADE 6533194

3221584 ORANGE INDICATOR LAMP 220V
mounting hole 27.2 x 22.2 mm
universal application



AMBASSADE 6532193

3221628 ORANGE INDICATOR LAMP 230V
hole \varnothing 9 mm
wire connection
for Convection oven electric (AMBASSADE) 1FRFE08CV



AMBASSADE 90000125

3221170 ORANGE INDICATOR LIGHT 230V
head \varnothing 10 mm - hole \varnothing 9 mm - 120°C



AMBASSADE 6537607

3221582 WHITE INDICATOR LAMP 220V
mounting hole 27.2 x 22.2 mm
universal application



AMBASSADE 65231002

Microswitches

3803066 MICROSWITCH EF83161.3 16A 250V
for Convection oven (AMBASSADE)



AMBASSADE 6522001



Suitable for:

AMBASSADE



Suitable for:

Motors

3241892 MOTOR FIR 1074 75W 224V
 0.55A 2800rpm 2.5μF
 distance between fixing holes 70 mm
 pin ø 11 mm - pin height 74 mm
 for Convection oven electric (AMBASSADE) CFE806CV
 1FRFE08CV



AMBASSADE 65260008

3240992 MOTOR WITH FAN R2S150AD08-39
 46W 220V 50Hz - SINGLE-PHASE
 for Convection oven (ROSINOX)
 for Convection oven (AMBASSADE) 30FRIFE0705RT



AMBASSADE 6527753

Relays

3351048 TIME LIMIT RELAY MLS2 24/240V
 timer 0.1"-100 h



AMBASSADE 6537884


Rotary switches

3057026 SELECTOR SWITCH 0-1 POSITIONS
 contact capacity 16A 250V - max 150°C
 D shaft ø 6x4.6 mm
 for Convection oven electric (INOXTREND) CRCA107E
 CRCA111E



AMBASSADE 6528979

3057315 SELECTOR SWITCH 6 POSITIONS
 contact capacity 16A 250V - max 150°C
 D-shaped pin ø 6x4.ø 6 mm
 for Convection oven electric (AMBASSADE) 1FRE08CV



AMBASSADE 65221002

Solenoid valves

3120407 SOLENOID VALVE 230V ø 10.5 mm
 solenoid valve 180° - 230V 50/60Hz - max 90°C
 inlet 3/4"- 2 outlets ø 10.5 mm



AMBASSADE 65042005

3120414 SOLENOID VALVE 230V ø 10.5 mm
 solenoid valve 180° - 230V 50/60Hz - max 90°C
 inlet 3/4"- 3 outlets ø 10.5 mm



AMBASSADE 65109013



Suitable for:

AMBASSADE



Suitable for:

Supports

3241895 FASTENING PLATE FOR MOTOR GASKET

hole \varnothing 13 mm
for Convection oven electric (AMBASSADE) 1FRFE08CV



AMBASSADE 50309500

Switches

3319295 BLACK BIPOLAR SWITCH 16A 250V

with green led lamp
temperature max 120°C
mounting hole 22x30 mm



AMBASSADE 6540129

Telethermometers

3394359 WHITE TELETHERMOMETER \varnothing 60 mm 0-400°C

metal case
capillary length 1100 mm
bulb \varnothing 8x150 mm - with coupling
for Convection oven electric (AMBASSADE) 1FRFE08CV



AMBASSADE 65224012

Thermocouples and accessories

3440139 THERMOCOUPLE M8x1 75 cm COUPLING M8x1



AMBASSADE 6539895



Suitable for:

AMBASSADE




Suitable for:

Thermostats

3443074 SINGLE-PHASE THERMOSTAT 110°C

D-shaped pin \varnothing 6x4.6 mm
covered capillary length 900 mm - 16A 250V
bulb \varnothing 6x80 mm - with stuff.gland coupling M9x1
for Convection oven electric (AMBASSADE) 1FRFE08CV



AMBASSADE 65224008

3444936 SINGLE-PHASE THERMOSTAT 365°C

with manual reset
covered capillary length 1800 mm - 16A 250V
bulb \varnothing 3x160 mm



AMBASSADE 6538562

3444935 SINGLE-PHASE THERMOSTAT 50-300°C

D-shaped pin \varnothing 6x4.6 mm
covered capillary length 870 mm - 16A 250V
bulb \varnothing 3x160 mm



AMBASSADE 6553670

3444937 3-PHASE THERMOSTAT 368°C

with manual reset
covered capillary length 1500 mm - 10A 400V
bulb \varnothing 3x160 mm



AMBASSADE 6539942

3444952 3-PHASE THERMOSTAT 70-140-200°C

with manual reset
covered capillary length 900 mm - 10A 400V
bulb \varnothing 3x260 mm
for Convection oven (AMBASSADE) - Series RT
for Convection oven (COMETTO)



AMBASSADE 65224002



Suitable for:

AMBASSADE



Suitable for:

Timers

3446182 TIMER 120 MINUTES C53

manually set mechanical timer
manually set cycle 120 minutes
single pole
1 normally open contact
1 normally closed contact
contact capacity 16(4)A 250V
max temperature 125°C
D-shaped pin \varnothing 6x4,6 mm
for Convection oven (AMBASSADE) 44FRIFR505RT
for Convection oven electric (BOURGEOIS) CP1012
CP1022 - CP2012 - CP2022
for Convection oven electric (HOBART) CSL06E
CSL10E - CSM0611E - CSM0611N - CSM1011E
CSM1011N - CSM1021E - CSM1021N - CSM2011E
CSM2011N - CSM2021E - CSM2021N



AMBASSADE 6528965

3397188 TIMER 90 MINUTES C10

manual winding cycle 90 minutes
contacts 16A 120V
1 normally open contact
1 normally closed contact
D-shaped pin \varnothing 6x4.6 mm



AMBASSADE 6532959