



Spare parts for:

## Cooking equipment



Suitable for:

# ALBA



This catalogue is automatically generated.  
Therefore, the sequence of the items might  
not be always shown at best.

Updates will be issued in case of additions  
and/or amendments.

*Suitable universal spare parts may not be included*





Suitable for:

# ALBA

Suitable for:



## Burners, flame spreaders and accessories

**3025284 FLAME SPREADER  $\varnothing$  105 mm**



ALBA 203312841005

**3025283 BURNER  $\varnothing$  105 mm**



**3025289 AERATION REGULATOR**  
internal  $\varnothing$  42 mm - external  $\varnothing$  45 mm  
height 50 mm



**3025290 JET HOLDER**  
nozzle hole M11x1



**3025285 VENTURI F/FLAME SPREADER 105 mm**



**3025281 FLAME SPREADER  $\varnothing$  80 mm**



ALBA 203312841004

**3025280 BURNER  $\varnothing$  80 mm**



**3025289 AERATION REGULATOR**  
internal  $\varnothing$  42 mm - external  $\varnothing$  45 mm  
height 50 mm



**3025290 JET HOLDER**  
nozzle hole M11x1



**3025282 VENTURI F/FLAME SPREADER 80 mm**





## Cables for piezo igniters

- 3001028 IGNITION LEAD 500 mm**  
with faston  $\varnothing$  2.4 mm for ignition  
with faston  $\varnothing$  4 mm for sparking plug



ALBA 341500024004

## Capacitors, electrical

- 3068081 CAPACITOR ELECTRICAL 12.5 $\mu$ F**  
450V 50/60Hz -  $\varnothing$  35xh71 mm



ALBA 15081

- 3068079 CAPACITOR ELECTRICAL 8 $\mu$ F**  
450V 50/60Hz -  $\varnothing$  30xh71 mm



ALBA 16043

## Clamps

- 3449452 HOSE CLAMP 16-25**  
for pipes  $\varnothing$  16÷25 mm  
made of stainless steel AISI 304  
height 9 mm and screw E7  
suitable for food industry



ALBA 11807

- 3449453 HOSE CLAMP 25-40**  
for pipes  $\varnothing$  25÷40 mm  
made of stainless steel AISI 304  
height 9 mm and screw E7  
suitable for food industry



ALBA 11806

## Contactors

- 3446214 CONTACTOR LOVATO BG09T4A**  
4KW 400V 9A - 4 normally open contacts  
coil 230V 50/60Hz



ALBA 15086

ALBA 15086/F



Suitable for:

ALBA



Suitable for:

## Drain taps and accessories

**3356173 DRAIN TAP  $\varnothing$  1"1/2F**  
 complete with food grease tube  
 GASKET SEAL  
 fixed connection  $\varnothing$  1"1/2F  
 made of STAINLESS steel  
 IN COMPLIANCE WITH EUROPEAN REGULATION 1935/2004  
 FOODSAFE



ALBA 541933101088

**1180001 GREASE KLUBERSYNTH UH1 14-151 45 g**  
 food safe grease for lubrication  
 of all friction points  
 ideal for water and steam taps  
 operating temperature  $-45^{\circ}/+120^{\circ}$   
 beige color - NSF approval H1  
 hot and cold water resistant  
 high anti-corrosion power  
 can replace vaseline



**3180039 VASELINE 750 g**  
 for lubrication of food processing machines  
 it protects chromed and rubber parts from  
 weather factors, moisture resistant,  
 operating temperature from  $-10^{\circ}\text{C}$  up to  $+120^{\circ}\text{C}$   
 from  $+50^{\circ}\text{C}$  to  $+120^{\circ}\text{C}$  the grease becomes oily



**3179010 FITTINGS SEALING TAPE LOCTITE 55 - 50 m**  
 length 50 mt  
 suitable to hot and cold drinking water, gas  
 replaces pastes, hemp and sealing tapes  
 it allows the repositioning of couplings  
 in compliance with the latest regulations  
 Drinking water (Italian certification by C.S.A.,  
 according to standard KTW and WRC approved)  
 gas - water IMQ-UNICIG.  
 compliant with UNI EN 51-2 class Arp  
 approved by DVGW and DIN 30660




**3180061 TAPE FOR JOINT SEALING LOCTITE 55 - 150m**  
 length 150 metri  
 suitable for hot / cold drinking water. gas  
 replaces pastes, hemp and sealing tapes  
 it allows the correct replacement of fittings  
 compliant with the latest regulatory requirements  
 Drinking water (C.S.A. italian certified.  
 in line with KTW standard and WRC approved )  
 IMQ-UNICIG gas-water,  
 compliant with UNI EN 51-2 class Arp  
 DVGW and DIN 30660 approved





## Electric hot plates

- 3311170 ELECTRIC HOT PLATE  $\varnothing$  230 mm 2100W 230V**  
 faston electric connections  
 complete with energy adjuster  
 for glass-ceramic cooking top



ALBA 541524210040

- 3311054 ELECTRIC HOT PLATE 2600W 400V**  
 dimensions 220x220 mm  
 terminal block electric connections  
 with STAINLESS steel edge  
 for electric cooking top



ALBA 541524400220


- 3311063 ELECTRIC HOT PLATE 3000W 400V**  
 dimensions 300x300 mm  
 terminal block electric connections  
 with STAINLESS steel edge  
 for electric cooking top



ALBA 000400000010


## Electrical gas valves and accessories

- 3526140 VALVE 836 TANDEM  $\varnothing$  1/2"FF**  
 inlet  $\varnothing$  1/2" F - outlet  $\varnothing$  1/2" F  
 maximum gas inlet pressure 60 mbar  
 max.gas outlet pressure adjustment range 7÷50 mbar  
 outlet gas pressure setting range min.2÷45 mbar  
 room temperature 0÷60°C  
 power supply 230V 30A rectified



ALBA 422700000007

- 2100724 COIL 24V**  
 for valve 830 TANDEM-836 TANDEM



- 2100757 CONNECTION FOR OLIVE  $\varnothing$  16 mm**  
 thread  $\varnothing$  1/2" M



- 3030001 COUPLING ELECTRIC WITH CABLE**  
 for valve sit 824 NOVA-826 NOVA-836 TANDEM





Suitable for:

**3526292 COUPLING ELECTRIC WITH CABLE**  
for valve sit 836 TANDEM



**3526143 MODULATOR COIL**  
220V rectified  
for VALVE 836 TANDEM



**3020084 NUT & OLIVE ø 6 mm**



ALBA 319700958031

## ALBA



Suitable for:

**3526142 DOUBLE COIL FOR VALVE**  
220V 50Hz  
for VALVE 830 TANDEM-836 TANDEM



**3020083 NUT & OLIVE ø 4 mm**



**3348041 PIPE OLIVE ø 16 mm**  
for model PEL 23



---

## Energy regulators

---

**3350026 ENERGY ADJUSTER**  
contact capacity 230V 13A - max temperature 125°C  
D-shaped pin ø 6x4.6 mm  
double rotation direction  
for PYROCERAM. TOPS-SALAMANDERS-POTATO WARMERS



ALBA 405611100089

---

## Feet

---

**3313005 ADJUSTABLE S/STEEL FOOT ø 2" x h 135 MM**  
with fixed screw M12x25 mm  
adjustable height 135÷200 mm



ALBA 15116



**Fittings**

**3349346 NICHEL-PL.HOSE-END FITTING  $\varnothing$  1/4" M  $\varnothing$  12**



ALBA 12005

**Gas valves and accessories**

**3526260 EUROSIT VALVE CAP**



ALBA 541910500631

**3526258 EUROSIT VALVE FOR FRYER 110÷190°C**  
 with new knob  
 inlet  $\varnothing$  3/8" F - outlet  $\varnothing$  3/8" F  
 thermocouple connection M9x1  
 maximum gas inlet pressure 50 mbar  
 outlet pressure adjustment range  
 3÷18 mbar  
 ambient temperature 0÷120°C  
 capillary length 1050 mm  
 bulb  $\varnothing$  4x200 mm  
 RoHS certificated



ALBA 541910500630

**3526260 EUROSIT VALVE CAP**




ALBA 541910500631

**3526127 FLANGE FOR KNOB EXTENSION**



**4056009 CAP FOR VALVE EUROSIT**



**5050400 FITTING FOR OLIVE  $\varnothing$  10 mm**  
 thread  $\varnothing$  3/8" M



**3020083 NUT & OLIVE  $\varnothing$  4 mm**





Suitable for:

**3020084 NUT & OLIVE  $\varnothing$  6 mm**



ALBA 319700958031

**3020082 OLIVE FOR 12 mm  $\varnothing$  PIPE**



**3020079 PIPE FITTING  $\varnothing$  12 mm  
thread  $\varnothing$  3/8" M**



**3526123 RUBBER PROTECTION FOR EUROSIT VALVE**



**3526130 EUROSIT VALVE FOR OVEN 100÷340°C**  
inlet  $\varnothing$  3/8" F - outlet  $\varnothing$  3/8" F  
thermocouple connection M9x1  
maximum gas inlet pressure 50 mbar  
outlet pressure adjustment range  
3÷18 mbar  
ambient temperature 0÷120°C  
capillary length 1050 mm  
bulb  $\varnothing$  4x72 mm



ALBA 541910630310


# ALBA

Suitable for:

**5050401 OLIVE FOR PIPE  $\varnothing$  10 MM**  
external  $\varnothing$  13 mm - height 8 mm




**3001111 PIEZO IGNITER EUROSIT**  
male faston  $\varnothing$  2.4 mm



**5021481 RACCORDO USCITA GAS VALVOLA**  
con manopola nuova  
entrata  $\varnothing$  3/8" F - uscita  $\varnothing$  3/8" F  
attacco termocoppia M9x1  
pressione massima di ingresso gas 50 mbar  
campo di taratura della pressione di  
uscita 3÷18 mbar  
temperatura ambiente 0÷120°C  
capillare lunghezza 1050 mm  
bulbo  $\varnothing$  4x200 mm  
certificata RoHS



**4056009 CAP FOR VALVE EUROSIT**







Suitable for:

**3526129 CLASP  $\varnothing$  3x14 mm**  
UNI 6873 - DIN 1481 - ISO 8752



**3526677 EXTENSION FOR EUROSIT VALVE**  
D-shaped pin  $\varnothing$  10x8 mm



**3526127 FLANGE FOR KNOB EXTENSION**



**3526125 KNOB EXTENSION 47 mm**  
D-shaped pin  $\varnothing$  8x6.5 mm



**3020084 NUT & OLIVE  $\varnothing$  6 mm**



ALBA 319700958031

**3020082 OLIVE FOR 12 mm  $\varnothing$  PIPE**



# ALBA

Suitable for:

**3526260 EUROSIT VALVE CAP**



ALBA 541910500631

**5050400 FITTING FOR OLIVE  $\varnothing$  10 mm**  
thread  $\varnothing$  3/8" M



**3526128 KNOB EXTENSION LENGTH 34 mm**  
D-shaft  $\varnothing$  8x6.5 mm



**3020083 NUT & OLIVE  $\varnothing$  4 mm**



**5050401 OLIVE FOR PIPE  $\varnothing$  10 MM**  
external  $\varnothing$  13 mm - height 8 mm



**3001111 PIEZO IGNITER EUROSIT**  
male faston  $\varnothing$  2.4 mm





Suitable for:

**3020079** PIPE FITTING  $\varnothing$  12 mm  
thread  $\varnothing$  3/8" M



## ALBA

Suitable for:

**5021481** RACCORDO USCITA GAS VALVOLA  
entrata  $\varnothing$  3/8" F - uscita  $\varnothing$  3/8" F  
attacco termocoppia M9x1  
pressione massima di ingresso gas 50 mbar  
campo di taratura della pressione di  
uscita 3÷18 mbar  
temperatura ambiente 0÷120°C  
capillare lunghezza 1050 mm  
bulbo  $\varnothing$  4x72 mm



**3526123** RUBBER PROTECTION FOR EUROSIT VALVE



**3523949** MINISIT VALVE FOR FRYER 110÷190°C  
inlet  $\varnothing$  1/2" F - outlet  $\varnothing$  3/8" F  
thermocouple connection M9x1  
maximum gas inlet pressure 50 mbar  
ambient temperature 0÷60°C  
capillary length 1050 mm  
bulb  $\varnothing$  6x105 mm  
supplied without lid knob and flanges



**2100757** CONNECTION FOR OLIVE  $\varnothing$  16 mm  
thread  $\varnothing$  1/2" M



ALBA 405309000710


**3523035** KNOB MINISIT BLACK  $\varnothing$  37 mm




**3182003** MAGNETIC UNIT SIT  
 $\varnothing$  head 25 mm -  $\varnothing$  end 17 mm - length 56 mm  
for valve SIT AC2 - VR8-MINISIT



**3523047** MINISIT COVER



**3523038** MINISIT ELBOW FLANGE  $\varnothing$  1/2" F  
with screws and "O" ring





Suitable for:

**3523037 MINISIT ELBOW FLANGE  $\varnothing$  3/8"**  
with screws and "O" ring



**3001071 MINISIT PIEZO IGNITER WITH COVER**  
male faston 2.4 mm



**3523061 NUT  $\varnothing$  1/4"x6 mm**



**3020082 OLIVE FOR 12 mm  $\varnothing$  PIPE**



**3348044 PIPE OLIVE  $\varnothing$  10 mm**  
for model PEL 20 - 21



## ALBA

Suitable for:

**3001070 MINISIT PIEZO IGNITER**  
a  $\varnothing$  22 mm hole is required for the assembly  
male faston  $\varnothing$  2.4 mm



**3523051 MINISIT SENSING ELEMENT 110÷190°C**  
capillary length 1050 mm  
bulb  $\varnothing$  6x105 mm



**3523060 OIL SEAL FITTING  $\varnothing$  6.5 mm**  
internal thread M10x0.75 - external thread M14x1.5



**3020079 PIPE FITTING  $\varnothing$  12 mm**  
thread  $\varnothing$  3/8"M



**3348041 PIPE OLIVE  $\varnothing$  16 mm**  
for model PEL 23





Suitable for:

**5058320 RACCORDO PER TUBO  $\varnothing$  10 mm**  
 entrata  $\varnothing$  1/2"F - uscita  $\varnothing$  3/8"F  
 attacco termocoppia M9x1  
 pressione massima di ingresso gas 50 mbar  
 temperatura ambiente 0÷60°C  
 capillare lunghezza 1050 mm  
 bulbo  $\varnothing$  6x105 mm  
 fornita senza coperchio manopola e flange



# ALBA



Suitable for:

**3523036 REDUCTION STRAIGHT  $\varnothing$  3/8"F -  $\varnothing$  1/2"F**  
 in brass with internal and external thread  
 $\varnothing$  internal thread 3/8"F -  $\varnothing$  external thread 1/2"F  
 for MINISIT flange



## Heating elements

**3755856 HEATING ELEMENT 10200W 230/400V**  
 length 300 mm - width 180 mm  
 coupling M54x1.5 mm - complete with cables  
 complete with OR gaskets



ALBA 541524700008

**3186601 O-RING 04200 EPDM**



**3186697 O-RING 0159 EPDM**



**3755652 RING NUT 1"-3/4" FOR HEATING ELEMENT**



**3755661 HEATING ELEMENT 15000W 230V**  
 length 300 mm - width 285 mm  
 connection M54x1.5 mm - complete with cables  
 complete with OR gaskets  
 with two holes per bulb



ALBA 541524000007

**3186601 O-RING 04200 EPDM**



**1186715 O-RING 0159 VITON**



**3786459 O-RING 04200 VITON**





Suitable for:

**3755652 RING NUT 1"-3/4" FOR HEATING ELEMENT**



# ALBA



Suitable for:

**3755489 HEATING ELEMENT 6800W 230V**  
length 300 mm - width 110 mm  
connection M54x1.5 mm - with cables  
with O-rings



**3186697 O-RING 0159 EPDM**



ALBA 54152400006

**3186601 O-RING 04200 EPDM**



**3755652 RING NUT 1"-3/4" FOR HEATING ELEMENT**



## Ignitors

**3001007 PIEZO IGNITER**  
a  $\varnothing$  22 mm hole is needed for the assembly  
2.4 mm  $\varnothing$  male faston connector



ALBA 541922045000

## Indicator lights

**3221132 GREEN INDICATOR LAMP 230V**  
head  $\varnothing$  13.5 mm - hole  $\varnothing$  10 mm - 120°C  
universal application



ALBA 347561183522

ALBA 347561183600

**3221095 ORANGE INDICATOR LAMP 230V**  
head  $\varnothing$  13.5 mm - hole  $\varnothing$  10 mm - 120°C  
universal application



ALBA 347561183523

ALBA 347561183610



Suitable for:

# ALBA



Suitable for:

## Injectors

**3500040** GAS JET M9x1  $\varnothing$  0.85 mm



ALBA 541910060085

**3500043** GAS JET M9x1  $\varnothing$  1.10 mm



ALBA 000007042707

ALBA 541910060110

**3500046** GAS JET M9x1  $\varnothing$  1.25 mm



ALBA 541910060130

**3500050** GAS JET M9x1  $\varnothing$  1.80 mm



ALBA 000007042750

ALBA 541910060170

**3500051** GAS JET M9x1  $\varnothing$  1.90 mm



ALBA 000007042716

## Interference suppression filters

**3160479** INTERFERENCE SUP. FILTER D.E.M.FC701Y2FL  
0.47 $\mu$ F



ALBA 15149

## Ironmongery (screws,nuts,washers)

**3060069** HEXAGONAL NUT M8 MEDIUM  
stainless steel - UNI 5588 - DIN 934 - ISO 4032



ALBA 11702

**1528030** MID HEXAGONAL NUT M6  
stainless steel - UNI 5588 - DIN 934 - ISO 4032



ALBA 11706



## Microswitches

### 3240407 MICROSWITCH KIT 16A 250V

3 locking positions  
the kit includes 5 levers:  
lever 75 mm - lever 27 mm - lever 15 mm  
lever 15 mm with wheel - lever 27 mm with wheel



ALBA 10704

### 3240568 MICROSWITCH EF83161.3 16A 250V



## OR and ORM gaskets

### 3186013 O-RING GASKET 06187 EPDM $\varnothing$ 58 mm



ALBA 13005

### 3186014 O-RING GASKET 06225 EPDM $\varnothing$ 67 mm



ALBA 13015

### 1186411 O-RING 02031 EPDM



ALBA 13002

## Pilot burners and accessories

### 3020084 NUT & OLIVE $\varnothing$ 6 mm



ALBA 319700958031

### 3020202 PILOT GAS JET $\varnothing$ 0.27 mm



ALBA 541933977270

### 3020043 PILOT GAS JET $\varnothing$ 0.36 mm



ALBA 541933977115

### 3020054 PILOT JET $\varnothing$ 0.20 mm



ALBA 541933977028



Suitable for:

# ALBA



Suitable for:

**3020055 PILOT JET  $\varnothing$  0.35 mm**



ALBA 541933977031

**3020251 TARGET ONE-FLAME PILOT BURNER SIT**  
without sparking plug, gas nozzle and gasket



**5014757 CONNECTION PIPE  $\varnothing$  6 mm**  
thread M10x1 mm



ALBA 541933290080

**3020085 FITTING FOR SPARKING PLUG FIXING M10x1mm**



**3020200 FITTING FOR THERMOCOUPLE  $\varnothing$  6.5 mm**  
thread M10x1



**5022050 NOZZLE FOR PILOT BURNER  $\varnothing$  0.50 mm**



**3020114 OLIVE FOR PIPE  $\varnothing$  6 mm**




**3348036 OLIVE FOR 4 mm  $\varnothing$  PIPE**  
for model PEL 21-22



**3020201 PILOT GAS JET  $\varnothing$  0.14 mm**



**3020042 PILOT GAS JET  $\varnothing$  0.19 mm**



**3020542 PILOT GAS JET  $\varnothing$  0.20 mm**








Suitable for:

**3020202 PILOT GAS JET  $\varnothing$  0.27 mm**



ALBA 54193397270

**3020543 PILOT GAS JET  $\varnothing$  0.38 mm**



**3020077 PIPE FITTING  $\varnothing$  4 mm  
thread M10x1**



**3020078 PIPE FITTING  $\varnothing$  6 mm  
thread M10x1**



**3001003 ROUND SPARKING PLUG  $\varnothing$  7x44 mm  
male faston M4x1 mm  
total length 65 mm**



ALBA 541910065036


**3020124 SPARKING PLUG ROUND  $\varnothing$  7x44 mm  
connection  $\varnothing$  2.4 mm  
overall length 58 mm**



# ALBA

Suitable for:

**3020043 PILOT GAS JET  $\varnothing$  0.36 mm**



ALBA 541933977115

**3020113 PILOT OLIVE FOR PIPE  $\varnothing$  4 mm**



**3348029 PIPE FITTING  $\varnothing$  4 mm  
thread M10x1  
for model PEL 21-22**



**3020294 ROUND IGNITION ELECTRODE  $\varnothing$  7x44 mm  
M faston M4x1 mm  
overall length 67 mm**



**3020060 SPARKING PLUG ROUND  $\varnothing$  7x44 mm  
faston M 4x1 mm  
overall length 82 mm  
model CB505/021 Junkers  
for model P502F**



**3020365 SPARKING PLUG ROUND  $\varnothing$  7x44 mm  
connection  $\varnothing$  2.4 mm  
overall length 52 mm**





Suitable for:

# ALBA



**3020006 THREE-FLAME PILOT BURNER SIT**  
multigas with jet  $\varnothing$  0.20 mm  
with 3 positions bracket



ALBA 541910500054

**5048713 DEFLECTOR 3 FLAMES**



**4058525 NOZZLE FOR PILOR BURNER  $\varnothing$  0.30 mm**



**3020084 NUT & OLIVE  $\varnothing$  6 mm**



ALBA 319700958031

**3348036 OLIVE FOR 4 mm  $\varnothing$  PIPE**  
for model PEL 21-22



**3020097 PILOT AERATION REGULATOR**  
internal  $\varnothing$  7 mm - external  $\varnothing$  9 mm  
height 10 mm



**5014757 CONNECTION PIPE  $\varnothing$  6 mm**  
thread M10x1 mm



**3020102 HEXAGON HEAD SCREW 3/16"x18 mm**



**3020083 NUT & OLIVE  $\varnothing$  4 mm**



**3020082 OLIVE FOR 12 mm  $\varnothing$  PIPE**



**3020081 OLIVE FOR 6 mm  $\varnothing$  PIPE**



**3020308 PILOT ASSEMBLY WITH NOZZLE  $\varnothing$  0.40 mm**





Suitable for:

3020054 PILOT JET  $\varnothing$  0.20 mm



ALBA 541933977028

3020055 PILOT JET  $\varnothing$  0.35 mm



ALBA 541933977031

3500269 PILOT NOZZLE  $\varnothing$  0.45 mm



3020106 PILOT WITH 0.25 mm  $\varnothing$  JET



3020079 PIPE FITTING  $\varnothing$  12 mm  
thread  $\varnothing$  3/8" M



5033138 PIPE FITTING  $\varnothing$  4 mm  
thread  $\varnothing$  1/8" M



# ALBA

Suitable for:

3020156 PILOT JET  $\varnothing$  0.25 mm



5015516 PILOT NOZZLE  $\varnothing$  0.40 mm



3020105 PILOT WITH 0.20 mm  $\varnothing$  JET



3020107 PILOT WITH 0.35 mm  $\varnothing$  JET



3020077 PIPE FITTING  $\varnothing$  4 mm  
thread M10x1



3020078 PIPE FITTING  $\varnothing$  6 mm  
thread M10x1





Suitable for:

**5027953 PIPE OLIVE  $\varnothing$  4 mm**  
for COPRECI CAL3200



**3001003 ROUND SPARKING PLUG  $\varnothing$  7x44 mm**  
male faston M4x1 mm  
total length 65 mm



ALBA 541910055036

**3020124 SPARKING PLUG ROUND  $\varnothing$  7x44 mm**  
connection  $\varnothing$  2.4 mm  
overall length 58 mm



**3020110 THREE-FLAME DEFLECTOR**



**3020104 THREE-POSITION BRACKET CLAMP**



# ALBA



Suitable for:

**3020294 ROUND IGNITION ELECTRODE  $\varnothing$  7x44 mm**  
M faston M4x1 mm  
overall length 67 mm



**3020060 SPARKING PLUG ROUND  $\varnothing$  7x44 mm**  
faston M 4x1 mm  
overall length 82 mm  
model CB505/021 Junkers  
for model P502F



**3020365 SPARKING PLUG ROUND  $\varnothing$  7x44 mm**  
connection  $\varnothing$  2.4 mm  
overall length 52 mm



**3020103 THREE-POSITION BRACKET**





## Relays


**3351021 POWER RELAY FINDER 62.82.8.230.0000**  
 230V 50/60Hz  
 2 exchange contacts 16A



ALBA 15620


## Rotary switches

**3057177 SELECTOR SWITCH 0-1 POSITIONS**  
 contact capacity 16A 250V - max 150°C  
 D-shaped pin  $\varnothing$  6x4.6 mm




ALBA 345355300002

**3057022 SELECTOR SWITCH 0-1 0-1 POSITIONS**  
 contact capacity 16A 250V - max 150°C  
 D-shaped pin  $\varnothing$  6x4.6 mm



ALBA 345362103751

**3057094 SELECTOR SWITCH 0-1 0-1 POSITIONS**  
 contact capacity 32A 250V - max 150°C  
 D-shaped pin  $\varnothing$  6x4.6 mm



ALBA 345355000000

## Safety groups for pans and spare parts

**3184007 PRESSURE GAUGE  $\varnothing$  60 mm**  
 in chrome plated brass  
 radial connection 1/4"  
 scale 0-1 bar  
 for safety groups



ALBA 388411221358



Suitable for:

# ALBA

Suitable for:



## Solenoid valves

**3120005 SOLEN. VALVE ELBI TYPE 329 1 WAY 180°**  
220/240V 50/60Hz - max. temperature 90°C  
inlet 3/4" - outlet ø 10.5 mm



ALBA 10703

**3120021 ADJUSTER FOR INLET ELBI BLACK**  
flow rate 12 L/min - tolerance +/- 15%



**3120019 ADJUSTER FOR INLET ELBI BLACK**  
flow rate 5.5 L/min - tolerance +/- 15%



**3120022 ADJUSTER FOR INLET ELBI BLACK**  
flow rate 16 L/min - tolerance +/- 15%



**3120204 ADJUSTER FOR OUTLET ELBI BROWN**  
flow rate 5.5 L/min - tolerance +/- 25%



**3120201 ADJUSTER FOR OUTLET ELBI GRAY**  
flow rate 4.7 L/min - tolerance +/- 25%



**3120037 ADJUSTER FOR OUTLET ELBI GREEN**  
flow rate 0.25 L/min - tolerance +/- 25%



**3120016 ADJUSTER FOR OUTLET ELBI NEUTRAL**  
flow rate 1.2 L/min - tolerance +/- 25%



**3120017 ADJUSTER FOR OUTLET ELBI ORANGE**  
flow rate 2.5 L/min - tolerance +/- 25%



**3120015 ADJUSTER FOR OUTLET ELBI RED**  
flow rate 0.5 L/min - tolerance +/- 25%



**3120203 ADJUSTER FOR OUTLET ELBI WHITE**  
flow rate 2 L/min - tolerance +/- 25%



**3120202 ADJUSTER FOR OUTLET ELBI YELLOW**  
flow rate 0.35 L/min / tolerance +/- 25%





Suitable for:

**3120000 FILTER FOR INLET SOLENOID VALVE ELBI**



# ALBA



Suitable for:

**3120009 SOLEN. VALVE ELBI TYPE 351 1 WAY 180°**  
220/240V 50/60Hz - max. temperature 90°C  
inlet 3/4" - outlet ø 13.5 mm



ALBA 30001000

**3120021 ADJUSTER FOR INLET ELBI BLACK**  
flow rate 12 L/min - tolerance +/- 15%



**3120019 ADJUSTER FOR INLET ELBI BLACK**  
flow rate 5.5 L/min - tolerance +/- 15%



**3120022 ADJUSTER FOR INLET ELBI BLACK**  
flow rate 16 L/min - tolerance +/- 15%



**3120204 ADJUSTER FOR OUTLET ELBI BROWN**  
flow rate 5.5 L/min - tolerance +/- 25%



**3120201 ADJUSTER FOR OUTLET ELBI GRAY**  
flow rate 4.7 L/min - tolerance +/- 25%



**3120037 ADJUSTER FOR OUTLET ELBI GREEN**  
flow rate 0.25 L/min - tolerance +/- 25%



**3120016 ADJUSTER FOR OUTLET ELBI NEUTRAL**  
flow rate 1.2 L/min - tolerance +/- 25%



**3120017 ADJUSTER FOR OUTLET ELBI ORANGE**  
flow rate 2.5 L/min - tolerance +/- 25%



**3120015 ADJUSTER FOR OUTLET ELBI RED**  
flow rate 0.5 L/min - tolerance +/- 25%





Suitable for:

**3120203 ADJUSTER FOR OUTLET ELBI WHITE**  
flow rate 2 L/min - tolerance +/- 25%



# ALBA



Suitable for:

**3120202 ADJUSTER FOR OUTLET ELBI YELLOW**  
flow rate 0.35 L/min / tolerance +/- 25%



**3120000 FILTER FOR INLET SOLENOID VALVE ELBI**



**3120368 SOLENOID VALVE ODE  $\varnothing$  3/4"FF 220/230V**  
for steam - NC  
max temperature 140°C  
max differential pressure 25 bar  
coil '220/230V 50Hz - flowrate 140 L/min



**1120820 coil ODE BDA08223DS 220/230V 50/60Hz**  
14.5 VA  
width 30 mm - height 39 mm - depth 42 mm



ALBA 405652000000

**3120034 FEMALE LARGE CONNECTOR**  
for coils



## Spark generators

**3181003 SPARK GENERATOR 4 OUTLETS**  
220/240V 50/60Hz



ALBA 405309772016



## Sparking and detection plugs

**3001003 ROUND SPARKING PLUG  $\varnothing$  7x44 mm**  
male faston M4x1 mm  
total length 65 mm



ALBA 541910055036

**3020068 SPARKING PLUG ROUND  $\varnothing$  7x44 mm**  
square coupling  
faston M M4x1 mm  
overall length 63 mm



ALBA 541910055709

## Taps for tank refilling

**3358009 WATER INLET TAP  $\varnothing$  1/2" FF**



ALBA 551413035030

ALBA 551413035031

**3241826 TAP KNOB**



## Telethermometers

**3441011 BLACK TELETHERMOMETER 56x25 mm 0-120°C**  
plastic case  
capillary length 1500 mm  
bulb  $\varnothing$  6x15 mm



ALBA 10500005

**3441011 BLACK TELETHERMOMETER 56x25 mm 0-120°C**  
plastic case  
capillary length 1500 mm  
bulb  $\varnothing$  6x15 mm



ALBA 10500005

## Terminal blocks

**3247016 3-POLE TERMINAL BLOCK FV273 40A 450V**  
for cable max 6 mm<sup>2</sup>  
operating temperature 150°C  
nominal voltage 450 V



ALBA 500550

**3247009 6-POLE TERMINAL BLOCK FV122/B 40A 600V**  
for cable max 6 mm<sup>2</sup>  
operating temperature 150°C  
nominal voltage 450 V



ALBA 500551



Suitable for:

ALBA



Suitable for:

## Thermocouples and accessories

**3440015 INTERRUPTION CONNECTOR M9x1**




ALBA 54191000400

**3440054 THERMOCOUPLE SIT M8x1 85 cm THREAD M8x1**



ALBA 541100427760

**3440854 THERMOCOUPLE SIT M8x1 85 cm - 10 PCS CONNECTOR M8x1**



**3440837 THERMOCOUPLE SIT M9x1 100 cm - 10 PCS**



ALBA 541933290088

ALBA 541933290091

**3440037 THERMOCOUPLE SIT M9x1 100 cm.**



ALBA 541933290088

ALBA 541933290091

**3440837 THERMOCOUPLE SIT M9x1 100 cm - 10 PCS**



ALBA 541933290088

ALBA 541933290091

**3440080 THERMOCOUPLE SIT M9x1 40 cm.**



ALBA 541933290082

ALBA 541933290231

**3440880 THERMOCOUPLE SIT M9x1 40 cm - 10 PCS**



**3440049 THERMOCOUPLE SIT M9x1 75 cm**



ALBA 541933290750


**3440849 THERMOCOUPLE SIT M9x1 75 cm - 10 PCS**






## Thermostats

**3444974 SINGLE-PHASE THERMOSTAT 100-615°C**  
 complete with switch  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 covered capillary length 1100 mm - 16A 250V  
 bulb  $\varnothing$  4x230 mm




ALBA 40561100083

**3444736 SINGLE-PHASE THERMOSTAT 130°C**  
 with manual reset  
 capillary length 850 mm - 16A 230V  
 bulb  $\varnothing$  6x130 mm




ALBA 40561100076

**3444199 SINGLE-PHASE THERMOSTAT 230°C**  
 with manual reset  
 complete with wiring  
 covered capillary length 850 mm - 16A 230V  
 bulb  $\varnothing$  4x120 mm - with adapter nipple bland M9x1



ALBA 40561100091

**3444019 SINGLE-PHASE THERMOSTAT 30-90°C**  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 capillary length 1000 mm - 16A 250V  
 bulb  $\varnothing$  6x130 mm



ALBA 40561100073

**3444663 SINGLE-PHASE THERMOSTAT 50-195°C**  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 covered capillary length 2300 mm  
 bulb  $\varnothing$  4x160 mm




ALBA 40561100088

**3444376 SINGLE-PHASE THERMOSTAT 95-190°C**  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 covered capillary length 1010 mm - 16A 250V  
 bulb  $\varnothing$  6x100 mm - with adapter nipple band M10x1



ALBA 34535300006

**3444307 THREE-PHASE THERMOSTAT 230°C**  
 with manual reset  
 covered capillary length 900 mm - 10A 400V  
 bulb  $\varnothing$  6x100 mm - with adapter nipple band M10x1



ALBA 40561100007

**3444506 THREE-PHASE THERMOSTAT 240°C**  
 with manual reset  
 covered capillary length 900 mm - 10A 400V  
 bulb  $\varnothing$  4x150 mm




ALBA 40561100087



Suitable for:

**3444592** **THREE-PHASE THERMOSTAT 340°C**  
with manual reset  
capillary length 1190 mm  
bulb  $\varnothing$  4x128 mm




ALBA 405611100084

**ALBA**



Suitable for:

**3444251** **THREE-PHASE THERMOSTAT 50-300°C**  
D-shaped pin  $\varnothing$  6x4.6 mm  
covered capillary length 1100 mm - 10A 400V  
bulb  $\varnothing$  3x220 mm






















ALBA 405611100074

ALBA 405611100082

The data herewith contained may change without notice and LF SpA cannot be held responsible for possible errors stated or resulting by the use of this document. All rights reserved. No part of this publication may be reproduced without written permission by LF SpA.



## Distributing Components, Spare Parts & Accessories in original quality worldwide

- 
-  **LF SpA HEADQUARTERS**  
via Voltri, 80 - 47522 Cesena (FC) ITALY  
Tel. +39 0547 34 11 11 - Fax +39 0547 34 11 10  
[www.lfrcambi724.it](http://www.lfrcambi724.it) - [www.lfrcambi724.mobi](http://www.lfrcambi724.mobi)  
[info@lfrcambi.it](mailto:info@lfrcambi.it)  
Export Dept.: Tel. +39 0547 34 11 50 - Fax: +39 0547 34 11 55  
[www.lfspareparts724.com](http://www.lfspareparts724.com) - [www.lfspareparts724.mobi](http://www.lfspareparts724.mobi)  
[export@lfspareparts.com](mailto:export@lfspareparts.com)
-  **LF SpA HOUSEHOLD COMPONENTS DIVISION**  
Via Padriciano, 34149 Trieste - Italia - AREA Science Park  
Tel. +39 0547 34 12 42 - Fax +39 0547 34 12 48  
[www.lfspareparts724.com](http://www.lfspareparts724.com) - [www.lfspareparts724.mobi](http://www.lfspareparts724.mobi)  
[info@lfspareparts.com](mailto:info@lfspareparts.com)
-  **EPGC Sas FRANCE**  
13, Rue des Forts - 59960 Neuville en Ferrain  
Tel. +33 (0)3 20 25 06 21  
Fax +33 (0)3 20 25 34 12  
[www.epgc.com](http://www.epgc.com)  
[www.epgc724.mobi](http://www.epgc724.mobi)  
[epgc@epgc.com](mailto:epgc@epgc.com)
-  **LF GmbH GERMANY**  
Junkersstrasse, 3 - D-82178 Puchheim - München  
Tel. +49 89 89 45 78 66  
Fax +49 89 89 45 78 88  
[www.lfersatzteile724.de](http://www.lfersatzteile724.de)  
[www.lfersatzteile724.mobi](http://www.lfersatzteile724.mobi)  
[info@lfersatzteile.de](mailto:info@lfersatzteile.de)
-  **LF China REPUBLIC OF CHINA**  
Room 403, No.2, Huadu Mansion, Lane 422, Huanghua Rd.  
Minhang Dist. - 201103 Shanghai  
Tel. +86 (0)21 33 53 66 31  
Fax +86 (0)21 33 53 66 32  
[www.lfspareparts724.com](http://www.lfspareparts724.com)  
[www.lfspareparts724.mobi](http://www.lfspareparts724.mobi)  
[china@lfspareparts.com](mailto:china@lfspareparts.com)
-  **OOO LF RUSSIAN FEDERATION**  
Ul. Anatoliya Zhivova, 8 - office 1 - 123100 Moscow  
Tel./Fax +7 495 725 26 53  
[www.lfspareparts724.ru](http://www.lfspareparts724.ru)  
[www.lfspareparts724.mobi](http://www.lfspareparts724.mobi)  
[info@lfspareparts.ru](mailto:info@lfspareparts.ru)
-  **LF Repuestos Horeca S.L.U. SPAIN**  
Poligono Industrial Carpetania - C/Miguel Faraday, 8 - 28906 Getafe  
Tel. +34 91 477 91 00  
Fax +34 91 477 90 81  
[www.lfrepuestos-horeca724.es](http://www.lfrepuestos-horeca724.es)  
[www.lfrepuestos724.mobi](http://www.lfrepuestos724.mobi)  
[info@lfrepuestos.es](mailto:info@lfrepuestos.es)
-  **LF SpA Cesena (IT) Swiss Branch Steinhausen SWITZERLAND**  
Sennweidstrasse, 45 - CH-6312 Steinhausen  
Tel. +41 (0)41 760 15 80-1  
Fax +41 (0)41 760 15 85  
[www.lfersatzteile724.ch](http://www.lfersatzteile724.ch)  
[www.lfersatzteile724.mobi](http://www.lfersatzteile724.mobi)  
[info@lfersatzteile.ch](mailto:info@lfersatzteile.ch)
-  **LF Spare Parts Ltd. UNITED KINGDOM**  
A10a Lakeside Business Park, Broadway Lane  
South Cerney, Gloucestershire GL7 5XL  
Tel. +44 (0)1285 86 16 25  
Fax +44 (0)1285 86 39 49  
[www.lfspareparts724.co.uk](http://www.lfspareparts724.co.uk)  
[www.lfspareparts724.mobi](http://www.lfspareparts724.mobi)  
[info@lfspareparts.co.uk](mailto:info@lfspareparts.co.uk)
- 
-  **AUSTRALIA AND NEW ZEALAND**  
[www.lfspareparts724.com](http://www.lfspareparts724.com)  
[andrea.calvio@lfspareparts.com](mailto:andrea.calvio@lfspareparts.com)
-  **AUSTRIA**  
[www.lfersatzteile724.at](http://www.lfersatzteile724.at)  
[info@lfersatzteile.at](mailto:info@lfersatzteile.at)
-  **BALKAN COUNTRIES**  
[www.lfspareparts724.com](http://www.lfspareparts724.com)  
[matijaramov@lfspareparts.com](mailto:matijaramov@lfspareparts.com)
-  **BALTIC COUNTRIES**  
[www.lfspareparts724.com](http://www.lfspareparts724.com)  
[inara.silina@lfspareparts.com](mailto:inara.silina@lfspareparts.com)
-  **CENTRAL AND EASTERN EUROPE**  
[www.lfspareparts724.cz](http://www.lfspareparts724.cz)  
[jiri.kremla@lfspareparts.cz](mailto:jiri.kremla@lfspareparts.cz)
-  **DENMARK**  
[www.lfspareparts724.dk](http://www.lfspareparts724.dk)  
[michael.leth@lfspareparts.com](mailto:michael.leth@lfspareparts.com)
-  **JAPAN**  
[www.lfspareparts724.jp](http://www.lfspareparts724.jp)  
[hiroshi.ukai@lfspareparts.jp](mailto:hiroshi.ukai@lfspareparts.jp)
-  **SOUTH KOREA**  
[www.lfspareparts724.com](http://www.lfspareparts724.com)  
[fabio.doni@lfspareparts.com](mailto:fabio.doni@lfspareparts.com)
-  **TURKEY**  
[www.lfyedekparca724.com](http://www.lfyedekparca724.com)  
[basar.ergun@lfyedekparca.com](mailto:basar.ergun@lfyedekparca.com)
-  **USA AND CANADA**  
[www.lfspareparts724.us](http://www.lfspareparts724.us)  
[sauro.dallaglio@lfspareparts.us](mailto:sauro.dallaglio@lfspareparts.us)  
[howard.truitt@lfspareparts.us](mailto:howard.truitt@lfspareparts.us)